

# Gene modeling and prediction

Hansheng Zhao

## Abstract

We performed a considerate prediction of intact protein-coding gene models using three independent approaches, i.e., de novo prediction, homology-based method, and RNA-Seq approach.

**Citation:** Hansheng Zhao Gene modeling and prediction. **protocols.io**

dx.doi.org/10.17504/protocols.io.rf7d3rn

**Published:** 03 Jul 2018

## Protocol

### De novo prediction

#### Step 1.

The repeat masked assembly was firstly annotated by AUGUSTUS (version 3.3) with default parameters, which was a de novopredictor based on the self-trained model.

☰ [SOFTWARE PACKAGE \(LINUX - \)](#)

#### AUGUSTUS, 3.3

### Homology-based prediction

#### Step 2.

In the homology-based prediction, we used seven species as reference datasets, i.e., *Elaeis guineensis*, *Phoenix dactylifera*, *Brachypodium distachyon*, *Oryza sativa*, *Setaria italic*, *Sorghum bicolor*, and *Zea mays* (see Availability of supporting data for individual genome version). Their protein sequences were downloaded for ENSEMBL database [30] and were aligned to the *C. simplicifolius* and *D. jenkinsiana* assembly using TBLASTN (version 2.2.26) with an E-value cutoff of 1e-5, respectively. Then, the splicing patterns were generated by GeneWise (version 2.0).

☰ [SOFTWARE PACKAGE \(LINUX - \)](#)

#### GeneWise, 2.0

### RNA-Seq analysis

#### Step 3.

In the RNA-Seq analysis, HISAT2 (version 2.0.2) was used to identify exon-intron splicing junctions and refine the alignment of the RNA-Seq reads to the genome. Then, we used Cufflinks (version 2.2.1) to define some protein-coding gene models in *C. simplicifolius* and *D. jenkinsiana*, respectively

☰ [SOFTWARE PACKAGE \(LINUX - \)](#)

#### Cufflinks, 2.2.1

### **Step 4.**

We integrated the evidences from the three above independent predictions using MARKER (version 2).

 [SOFTWARE PACKAGE \(LINUX - \)](#)

### **MAKER, 2**

---