

# Positive selection analysis

Hansheng Zhao

## Abstract

**Citation:** Hansheng Zhao Positive selection analysis. **protocols.io**

dx.doi.org/10.17504/protocols.io.phidj4e

**Published:** 16 Apr 2018

## Protocol

Protein sequences were aligned by PROBCONS (version 1.12) using the default parameters, except for the option of iterative refinement, for which we used 1,000 iterations.

### Step 1.

☰ SOFTWARE PACKAGE (Linux - )

**PROBCONS, 1.12** [↗](#)

chuongdo@cs.stanford.edu

<http://probcons.stanford.edu>

we obtain the conserved blocks from the sequence alignment using Gblocks (version 0.91b).

### Step 2.

☰ SOFTWARE PACKAGE (Linux - )

**Gblocks, 0.91b** [↗](#)

[http://molevol.cmima.csic.es/castresana/Gblocks\\_server.html](http://molevol.cmima.csic.es/castresana/Gblocks_server.html)

We use jModelTest (version 2.1.6) to find the best model according to the Bayesian Information Criterion

### Step 3.

☰ SOFTWARE PACKAGE (Linux - )

**jModelTest, 2.1.6** [↗](#)

<http://evomics.org/learning/phylogenetics/jmodeltest/>

We use PhyML (release 20141106) to reconstruct the phylogenetic tree under the best model, with bootstrapping of 1,000 replicates.

### Step 4.

☰ SOFTWARE PACKAGE (Linux - )

**PhyML, 3.0** [↗](#)

<http://www.atgc-montpellier.fr/phyml/>

Finally, certain branches selected from the phylogenetic tree were examined in a positive selection analysis using PAML (version 4.8) and a branch-site model

### Step 5.

☰ SOFTWARE PACKAGE (Linux - )

**PAML, 4.5** [↗](#)