

Jenkins

Locating server among [http://samesappd...]

ve

V104LAB_TestComplete (to start testComplete tests by KEJning)

Connect slave to Jenkins one of these ways:

- Launch agent from browser on slave
- Run from slave command line:

Error

java.lang.Exception: http://samesappd01:8080/tcpSlaveAgentListener/ is invalid: -1 null
at hudson.remoting.Engine.run(Engine.java:170)

OK

testComplete

None

ENABLE AUTO RE

Mark this node temporarily

search

Build Executor Status

Status

Build History

Load Statistics

Script Console

Log

System Information

Configure System [J...]

samesappd01

ESITTV104LAB_T...

search

This screenshot shows a Jenkins slave configuration page. The main content area displays instructions for connecting a slave to Jenkins, including two methods: launching the agent from a browser on the slave or running it from the slave's command line. A prominent error dialog box is overlaid on the page, indicating a problem with the URL 'http://samesappd01:8080/tcpSlaveAgentListener/'. The error message reads: 'java.lang.Exception: http://samesappd01:8080/tcpSlaveAgentListener/ is invalid: -1 null' and points to 'at hudson.remoting.Engine.run(Engine.java:170)'. The Jenkins interface includes standard navigation links like 'Back to Jenkins', 'Status', and 'Configure', along with system status indicators for the slave ('Jenkins slave agent') and master ('samesappd01').