

→ 136,128 sessions → 147 days → 414,070 commands → 63,283 password combos tried

I left a fake server on the internet for 147 days — dressed up as a Solana cryptocurrency node — and logged every break-in attempt. What followed was educational, chaotic, and deeply weird.

// THE GOOD STUFF

Gone in 60 seconds.

The server went live. Before the minute was up, the first automated scanner was inside running graphics-card checks. Port 22 is watched around the clock. It doesn't take days to find a new server — it takes seconds.

8,949 logins to say "ok."

One bot spent a whole night connecting, typing the word **ok**, and disconnecting. It was verifying its stolen password list still worked — like an automated receipt check — before doing anything with it.

Bots evicting other bots.

3,210 sessions broke in specifically to murder any crypto miners already running, then install their own. Cut-throat real estate for stolen server power. The internet is, at its core, a turf war.

Top password: admin123. Tried 15,938 times.

Runner-up: **support**. Someone also tried a blank password 290 times. The #2 most-targeted username was **azureuser** — attackers' lists now include Azure's default account name. They know the defaults.

Typos in the crime.

One visitor typed **solona** instead of **solana**, and **cx ..** instead of **cd ..** (the command to go up a folder). Still found the fake crypto wallet in four minutes. Determination beats spelling.

Shrinking passwords.

One visitor came back 21 times in one day: **password123** → **wer** → **n** → **f** → **(empty)** → **a**. At some point they realized the door had no lock. They tried the empty string anyway. Respect the commitment.

French backdoor. Password: Hackers666.

A beautifully engineered, multi-platform attack script. Full French-language inline comments. Proper error handling. Meticulous OS detection. Chosen secret password: **Hackers666**. They can't all be winners.

The disguise fooled almost no one.

147 days as a glittering crypto goldmine. 136,128 visitors. Five found the fake wallet. Everyone else ignored the story entirely and went straight for free server power.

✨ P.S. A friend found the in-shell terminal game on day 2 and died six times in four minutes. Their visits aren't in the numbers above.

// THE ONE THING YOU CAN DO RIGHT NOW

Turn off SSH password authentication. Use a key instead. A key is a digital lock that no wordlist can guess. Run `ssh-keygen`, add the public key to your server, set `PasswordAuthentication no` in your SSH config. That's it. Every session in this 40-page report worked because the server accepted passwords. Remove that and 99% of this goes away.