

Module 12 Lab:
SIEM and Splunk
JR Clark (002035589)
NEU DAMG7350 (Spring 2026)

Introduction

This lab demonstrates how a Security Information and Event Management (SIEM) platform supports the Detection and Analysis phase of the incident response lifecycle. Using Splunk Enterprise on a Kali Linux host, I generated authentication failures, web server activity, vulnerability scanning traffic, and firewall blocks to simulate realistic adversary behaviors to observe how these events are captured and correlated within a SIEM and interpret their significance using incident response methodology and the MITRE ATT&CK framework.

SIEM Configuration and Log Coverage

A dedicated Splunk index was created to isolate lab-generated telemetry, and multiple log sources were ingested to provide visibility across authentication, system activity, web traffic, and network boundary enforcement. This reflects a core SIEM principle: effective detection depends on broad, multi-layered logging coverage. Without telemetry from different layers of the host and network stack, meaningful correlation and efficient triage are not possible.

Authentication Events and Early Indicators of Attack

Failed SSH login attempts generated clear authentication failure entries. These represent early indicators of brute-force activity, aligning with MITRE ATT&CK technique T1110. In a real SOC, analysts would correlate these failures with subsequent successful logins, privilege escalation, or lateral movement. Even in this controlled environment, the authentication logs demonstrated how SIEM platforms surface anomalous access patterns that warrant investigation.

Web Server Activity and Reconnaissance Detection

Enabling Apache and running Nikto produced high-volume HTTP requests, missing header warnings, and /server-status probes. These events represent reconnaissance behavior consistent with MITRE ATT&CK technique T1595. Splunk's normalization and timestamp alignment made it easy to distinguish normal web access from automated probing. In practice, this type of activity would be

correlated with authentication anomalies or unexpected outbound connections to determine whether reconnaissance is part of a broader intrusion attempt.

The Nikto findings align with OWASP Top 10 categories such as Security Misconfiguration, reinforcing how SIEM telemetry can validate whether secure development practices are being upheld in deployed environments.

Firewall Enforcement and Network Boundary Monitoring

UFW firewall block events provide visibility into attempted access to ports or services that should not be exposed, which aligns with OWASP A05:2021 Security Misconfiguration. To introduce a high-value network control point, I ingested UFW firewall logs. Firewall telemetry is critical because it captures attempted access that never reaches the application layer. Once ingested, the UFW logs revealed repeated inbound TCP packets from an external IP targeting random, high-numbered non-service ports that normally should not receive external connections. Each event was tagged as a block action, indicating that the firewall successfully denied unsolicited traffic.

To quantify this activity, I used the following SPL query: `index=lab15-index sourcetype=ufr action=blocked | stats count by src_ip, dest_port`. This statistical aggregation surfaces repeated inbound attempts from the same external IP across multiple high-range ports, reinforcing the interpretation that this traffic represents scanning or probing behavior rather than legitimate communication.

For analysis, I filtered the UFW events to isolate block actions and grouped them by source IP, destination port, and protocol. This approach demonstrates how SIEM correlation reduces analyst workload by aggregating related events and highlighting anomalous patterns. In an enterprise environment, repeated blocks from a single external IP would be triaged as potential scanning or probing activity.

SIEM Value in the Incident Response Lifecycle

The lab reinforced several core principles emphasized in Module 12:

- **Detection:** SIEM platforms centralize and normalize logs, enabling analysts to identify suspicious patterns across authentication, web, and firewall activity.
- **Correlation:** Events that appear benign in isolation—failed logins, web probes, firewall blocks—form a coherent narrative when viewed together.
- **Containment:** Firewall blocks represent automated containment actions that prevent exploitation or lateral movement.
- **Post-Incident Review:** Splunk's indexed, timestamped events support timeline reconstruction and evidence preservation.
- **Preparation:** Effective detection depends on enabling and validating log sources during the preparation phase of the IR lifecycle.

While basic filtering and grouping were sufficient for this analysis, Splunk's statistical functions (such as aggregating block counts over time) could be used in a production SOC to quantify scanning intensity or identify temporal patterns.

Conclusion

This lab demonstrated how SIEM platforms operationalize the Detection and Analysis phase of incident response by centralizing and correlating host-level telemetry. Through authentication failures, web server activity, vulnerability scanning, and firewall blocks, I simulated realistic adversary behaviors and observed how Splunk surfaces these signals for investigation. The additional UFW log source provided a high-value example of network-level detection, illustrating how boundary controls contribute to early identification of unauthorized access attempts.

References

OWASP Foundation. (2021). A05:2021 – Security Misconfiguration .
https://owasp.org/Top10/2021/A05_2021-Security_Misconfiguration/

OWASP Foundation. (2021). *OWASP Top Ten Web Application Security Risks*.
<https://owasp.org/www-project-top-ten/>




Sawant, A. (2026). Incident response and SIEM [Online course]. Coursera & Northeastern University.


Methodology and Use of AI Tools

I completed all technical steps of this lab directly in the Kali Linux virtual machine. All screenshots and observations were generated from my own live capture sessions. I used Microsoft Copilot as a writing and organizational aid to help structure the report, refine transitions between sections, and ensure alignment with the assignment rubric. I wrote up the scenarios and asked CoPilot to draft the configuration file based on my specifications. All analysis, interpretations, and conclusions reflect my own understanding of the material and the concepts covered in Module 12.

APPENDIX: Documented Process

The following table documents the exact steps performed for this lab, with each left-column description corresponding to the screenshot or output shown in the right column.

Step 1: Create Kali Linux clone in Virtual Box and	
Step 2: Register on Splunk, download Splunk Enterprise via Terminal on Kali Linux	 <pre>(jenn@kali-linux)-[~] \$ wget -O splunk-10.2.2-80b90d638de6-linux-amd64.deb "https://download.splunk.com/products/splunk/releases/10.2.2/linux/splunk-10.2.2-80b90d638de6-linux-amd64.deb" --2026-04-02 14:00:52-- https://download.splunk.com/products/splunk/releases/10.2.2/linux/splunk-10.2.2-80b90d638de6-linux-amd64.deb Resolving download.splunk.com (download.splunk.com)... 3.169.183.24, 3.169.183.74, 3.169.183.124, ... Connecting to download.splunk.com (download.splunk.com)[3.169.183.24]:443 ... connected. HTTP request sent, awaiting response... 200 OK Length: 1330700064 (1.2G) [binary/octet-stream] Saving to: 'splunk-10.2.2-80b90d638de6-linux-amd64.deb' 2.2-80b90d638de6-li 8%[>] 106.42M 367KB/s eta 20m 3s</pre>
Step 3: Install the Splunk	 <pre>(jenn@kali-linux)-[~] \$ sudo dpkg -i splunk-10.2.2-80b90d638de6-linux-amd64.deb Selecting previously unselected package splunk. (Reading database ... 422235 files and directories currently installed.) Preparing to unpack splunk-10.2.2-80b90d638de6-linux-amd64.deb ... verify that this system has all the commands we will require to perform the preflight step no need to run the splunk-preinstall upgrade check Unpacking splunk (10.2.2) ...</pre>
Step 4: Set Admin & Password, set up splunk to start with system boot	 <pre>(jenn@kali-linux)-[~] \$ sudo /opt/splunk/bin/splunk enable boot-start --accept-license --answer-yes This appears to be your first time running this version of Splunk. Splunk software must create an administrator account during startup. Otherwise, you cannot log in. Create credentials for the administrator account. Characters do not appear on the screen when you type in credentials. Please enter an administrator username: Jenn Password must contain at least: * 8 total printable ASCII character(s). Please enter a new password: Please confirm new password: Copying '/opt/splunk/etc/openldap/ldap.conf.default' to '/opt/splunk/etc/openldap/ldap.conf'. writing RSA key writing RSA key Moving '/opt/splunk/share/splunk/search_mrsparkle/modules.new' to '/opt/splunk/share/splunk/search_mrsparkle/modules'. systemctl: /opt/splunk/lib/libcrypto.so.3: version 'OPENSSL_3.4.0' not found (required by /usr/lib/x86_64-linux-gnu/systemd/libsystemd-shared-259.so) Init script installed at /etc/init.d/splunk. Init script is configured to run at boot.</pre>

Step 5: Run Splunk	FYI – need to update instructions: <pre>(jenn@kali-linux)-[~] \$ sudo /opt/splunk/bin/splunk start Running Splunk Enterprise as root is deprecated and will be removed in a future release. For details, see the Release Notes. To run as root, use the --run-as-root option. (jenn@kali-linux)-[~] \$ sudo /opt/splunk/bin/splunk start --run-as-root Splunk> Now with more code! Checking prerequisites... Checking http port [8000]: open Checking mgmt port [8089]: open Checking appserver port [127.0.0.1:8065]: open Checking kvstore port [8191]: open Checking configuration ... Done. Creating: /opt/splunk/var/lib/splunk Creating: /opt/splunk/var/run/splunk/appserver/i18n Creating: /opt/splunk/var/run/splunk/appserver/modules/static /css Creating: /opt/splunk/var/run/splunk/upload Creating: /opt/splunk/var/run/splunk/search_telemetry Creating: /opt/splunk/var/run/splunk/search_log Creating: /opt/splunk/var/spool/splunk Creating: /opt/splunk/var/spool/dirmoncache</pre>
Step 6: Login to Splunk	

Step 7: Set up rsyslog on Kali Linux

```
jenn@kali-linux: ~  
Session Actions Edit View Help  
(jenn@kali-linux)-[~]  
$ sudo apt update  
Hit:1 http://http.kali.org/kali kali-rolling InRelease  
1820 packages can be upgraded. Run 'apt list --upgradable' to see them.  
Installing:  
  rsyslog  
Installing dependencies:  
  libestr0 libfastjson4 liblognorm5  
Suggested packages:  
  rsyslog-doc rsyslog-kafka rsyslog-clickhouse  
  rsyslog-mysql rsyslog-hiredis rsyslog-openssl  
  rsyslog-pgsql rsyslog-snmp | rsyslog-gnutls  
  rsyslog-mongodb rsyslog-kubernetes rsyslog-gssapi  
  rsyslog-elasticsearch rsyslog-docker rsyslog-relp  
Summary:  
Upgrading: 0, Installing: 4, Removing: 0, Not Upgrading: 1820  
Download size: 907 kB  
Space needed: 2,432 kB / 418 MB available  
Get:2 http://http.kali.org/kali kali-rolling/main amd64 libfastjson4 amd64 1.  
2304.0-2+b1 [29.1 kB]  
Get:1 http://http.kali.org/kali kali-rolling/main amd64 libestr0 amd64 0.1.11  
-2+b1 [9,608 B]  
Get:3 http://kali.download/kali kali-rolling/main amd64 liblognorm5 amd64 2.0  
.9-1 [68.6 kB]  
Get:4 http://mirrors.ocf.berkeley.edu/kali kali-rolling/main amd64 rsyslog am  
d64 8.2512.0-3 [800 kB]  
Fetched 907 kB in 1s (895 kB/s)
```

Step 8: Select Data Source for Splunk & Configure

Upload objects - S3 bucket x Add Data - Select Source x +

← → ↻ ⌂ Not Secure http://kali-linux:8000/en-US/manager 80% ☆ ⓘ ⌵ ⌵ ⌵

OffSec Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB

splunk>enterprise Apps Administrator 5 Messages Settings Activity Help Find

Add Data Select Source Set Source Type Input Settings Review Done < Back Next >

Files & Directories
Upload a file, index a local file, or monitor an entire directory.

HTTP Event Collector
Configure tokens that clients can use to send data over HTTP or HTTPS.

TCP / UDP
Configure the Splunk platform to listen on a network port.

Scripts
Get data from any API, service, or database with a script.

checkapp

Systemd Journal Input for Splunk
This is the input that gets data from journald (systemd's logging component) into Splunk.

Configure this instance to monitor files and directories for data. To monitor all objects in a directory, select the directory. The Splunk platform monitors and assigns a single source type to all objects within the directory. This might cause problems if there are different object types or data sources in the directory. To assign multiple source types to objects in the same directory, configure individual data inputs for those objects. [Learn More](#)



File or Directory ? /var/log/syslog Browse

On Windows: c:\apache\apache.error.log or \\\hostname\apache\apache.error.log. On Unix: /var/log or /mnt/www01/var/log.

Continuously Monitor Index Once

Include list ?

Exclude list ?

	
Step 10: Add a new source for /var/log/auth.log	
Step 11: create new user student1	<pre>(jenn@kali-linux)-[~] \$ sudo adduser student1 [sudo] password for jenn: New password: Retype new password: passwd: password updated successfully Changing the user information for student1 Enter the new value, or press ENTER for the default Full Name []: Room Number []: Work Phone []: Home Phone []: Other []: Is the information correct? [Y/n] y</pre>
Step 12: Enable SSH on Kali Linux	<pre>(jenn@kali-linux)-[~] \$ sudo systemctl enable --now ssh Synchronizing state of ssh.service with SysV service script with /usr/lib/systemd/systemd/systemd-sysv-install. Executing: /usr/lib/systemd/systemd-sysv-install enable ssh Created symlink '/etc/systemd/system/ssh.service' → '/usr/lib/systemd/system/ssh.service'. Created symlink '/etc/systemd/system/multi-user.target.wants/ssh.service' → '/usr/lib/systemd/system/ssh.service'.</pre>
Step 13: Ensure Hydra is installed and generate some failed logins:	<pre>(jenn@kali-linux)-[~] \$ hydra -l student1 -p WrongPass ssh://127.0.0.1 -t 4 -V -f Hydra v9.6 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is on-binding, these ** ignore laws and ethics anyway). Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-04-02 15:28:02 [DATA] max 1 task per 1 server, overall 1 task, 1 login try (l:1/p:1), ~1 try per task [DATA] attacking ssh://127.0.0.1:22/ [ATTEMPT] target 127.0.0.1 - login "student1" - pass "WrongPass" - 1 of 1 [child 0] (0/0) 1 of 1 target completed, 0 valid password found Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-04-02 15:28:05</pre>

Step 14: Return to Splunk to view failed login attempts:

The screenshot shows the Splunk interface with a search query: `source="/var/log/auth.log" host="kali-linux" index="lab15-index" sourcetype="linux_secure"`. The results show several events, including session closures and openings for user root. The interface includes a search bar, a sidebar with field lists, and a main results pane with a table of events.

Time	Event
4/2/26 3:35:01.325 PM	2026-04-02T15:35:01.325133-07:00 kali-linux CRON[117057]: pam_unix(cron:session): session closed for user root
4/2/26 3:35:01.319 PM	2026-04-02T15:33:01.319482-07:00 kali-linux CRON[117057]: pam_unix(cron:session): session opened for user root(uid=0) by root(uid=0)
4/2/26 3:32:50.697 PM	2026-04-02T15:32:50.697821-07:00 kali-linux sudo: pam_unix(sudo:session): session closed for user root
4/2/26 3:32:40.572 PM	2026-04-02T15:32:40.572127-07:00 kali-linux mongod:8.0: looking for plugins in "/home/build/build_home/opt/mongo/openssl/lib/sasl2": failed to open directory: error: No such file or directory
4/2/26 3:32:40.571 PM	2026-04-02T15:32:40.571795-07:00 kali-linux mongod:8.0: looking for plugins in "/home/build/build_home/opt/mongo/openssl/lib/sasl2": failed to open directory: error: No such file or directory

Step 15: Create a web scan security event:

```
(jenn@kali-linux)-[~]
$ sudo systemctl enable --now apache2
Synchronizing state of apache2.service with SysV service script with /usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable apache2
```

Step 16: Confirm access to the Debian Default page:

The screenshot shows the Apache2 Debian Default Page in a web browser. The page has a red header with the Debian logo and the text "It works!". Below the header, there is a paragraph of text explaining the page's purpose and providing instructions for users. A "Configuration Overview" section is also visible, detailing the configuration files and their locations.

Configuration Overview

Debian's Apache2 default configuration is different from the upstream default configuration, and split into several files optimized for interaction with Debian tools. The configuration system is **fully documented** in `/usr/share/doc/apache2/README.Debian.gz`. Refer to this for the full documentation. Documentation for the web server itself can be found by accessing the **manual** if the `apache2-doc` package was installed on this server.

The configuration layout for an Apache2 web server installation on Debian systems is as follows:

```
/etc/apache2/
|-- apache2.conf
|   |-- ports.conf
|-- mods-enabled
|   |-- *.load
|   |-- *.conf
|-- conf-enabled
|   |-- *.conf
|-- sites-enabled
```

Step 17: Install & run Nikto software

```
(jenn@kali-linux)-[~]
$ nikto -h http://127.0.0.1
- Nikto v2.6.0

+ Your Nikto installation is out of date.
+ Target IP: 127.0.0.1
+ Target Hostname: 127.0.0.1
+ Target Port: 80
+ Platform: Linux/Unix
+ Start Time: 2026-04-02 15:40:43 (GMT-7)

+ Server: Apache/2.4.65 (Debian)
+ No CGI Directories found (use '-C all' to force check all possible dirs). CGI tests skipped.
+ [999984] /: Server may leak inodes via ETags, header found with file /, inode: 29cf, size: 6498ff1efd28a, mtime: gzip. See: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1418
+ [013587] /: Suggested security header missing: referrer-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Referrer-Policy
+ [013587] /: Suggested security header missing: x-content-type-options. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Content-Type-Options
+ [013587] /: Suggested security header missing: permissions-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Permissions-Policy
+ [013587] /: Suggested security header missing: content-security-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/CSP
+ [013587] /: Suggested security header missing: strict-transport-security. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Strict-Transport-Security
+ [600050] Apache/2.4.65 appears to be outdated (current is at least 2.4.66).
+ [999990] OPTIONS: Allowed HTTP Methods: POST, OPTIONS, HEAD, GET .
+ [001406] /server-status: The mod_status module reveals Apache information. See: https://httpd.apache.org/docs/2.4/mod/mod_status.html
```

Step 18: Add Apache Logs as a data type:

Add Data

Select Source Input Settings Review Done

< Back Submit

Review

Input Type Directory Monitor
Source Path /var/log/apache2
Includelist N/A
Excludelist N/A
Source Type Automatic
App Context search
Host kali-linux
Index lab15-index

Step 19: Review results of search – you see the Nikto events

Search | Splunk 10.2.2 x Apache2 Debian Default Pag x +

Not Secure http://kali-linux:8000/en-US/app/search/search/ 67%

OffSec Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB Google Hacking DB

splunk>enterprise Apps Administrator Messages Settings Activity Help Find

Search Analytics Datasets Reports Alerts Dashboards Modules Search & Reporting

New Search Save As Create Table View Close

source="/var/log/apache2/*" host="kali-linux" index="lab15-index" Time range: All time

8,045 events (before 4/2/26 3:48:03.000 PM) No Event Sampling Job

Events (8,045) Patterns Statistics Visualization

Timeline format Zoom Out Zoom to Selection Deselect 1 minute per column

Format Show: 50 Per Page View List

< Hide Fields All Fields	i	Time	Event
SELECTED FIELDS # host 1 # source 2 # sourcetype 2	>	4/2/26 3:42:47000 PM	127.0.0.1 -- [02/Apr/2026:15:42:47 -0700] "GET /flexgateway/cfmpooling HTTP/1.1" 400 483 "-" "Mozilla/5.0 (Linux; Android 10; Pixel 3 Pro) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/142.0.6386.115 Mobile Safari/537.36" host=kali-linux source=varlogapache2access.log sourcetype=access_combined
INTERESTING FIELDS # bytes 20 # date_hour 2 # date_minute 1 # date_month 6 # date_second 21 # date_wday 1 # date_year 1 # date_zone 2 # file 100+ # ident 1 # index 1 # iserror 1 # method 13 # puid 100+ # referer 3	>	4/2/26 3:42:37000 PM	127.0.0.1 -- [02/Apr/2026:15:42:37 -0700] "GET /flexgateway/cfmpooling HTTP/1.1" 400 483 "-" "Mozilla/5.0 (Linux; Android 10; Pixel 3 Pro) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/142.0.6386.115 Mobile Safari/537.36" host=kali-linux source=varlogapache2access.log sourcetype=access_combined
	>	4/2/26 3:42:27000 PM	127.0.0.1 -- [02/Apr/2026:15:42:27 -0700] "GET /flexgateway/cfmpooling HTTP/1.1" 400 483 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 14_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/17.4 Safari/605.1.15" host=kali-linux source=varlogapache2access.log sourcetype=access_combined
	>	4/2/26 3:42:17000 PM	127.0.0.1 -- [02/Apr/2026:15:42:17 -0700] "GET /flexgateway/cfmpooling HTTP/1.1" 400 483 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 14_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/17.4 Safari/605.1.15" host=kali-linux source=varlogapache2access.log sourcetype=access_combined
	>	4/2/26 3:42:07000 PM	127.0.0.1 -- [02/Apr/2026:15:42:07 -0700] "GET /flexgateway/cfmpooling HTTP/1.1" 400 483 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 15_0) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/18.0 Safari/605.1.15" host=kali-linux source=varlogapache2access.log sourcetype=access_combined
	>	4/2/26 3:41:57000 PM	127.0.0.1 -- [02/Apr/2026:15:41:57 -0700] "GET /flexgateway/cfmpooling HTTP/1.1" 400 483 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 15_0) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/18.0 Safari/605.1.15" host=kali-linux source=varlogapache2access.log sourcetype=access_combined
	>	4/2/26	127.0.0.1 -- [02/Apr/2026:15:41:47 -0700] "GET /flexgateway/httpsecure HTTP/1.1" 400 483 "-" "Mozilla/5.0 (iPhone; CPU iPhone OS

Step 20: Add log source
for UFW for firewall
block events

Add Data

< Back

Submit >

Review

Input Type

Source Path

Continuously Monitor

Source Type

App Context

Host

Index

File Monitor

/var/log/uFW.log

Yes

UFW

search

kali-linux

lab15-index

Step 21: Review UFW
events

i	Time	Event
>	4/2/26 3:04:38.800 PM	2020-04-02T15:04:38.800989-07:00 kali-linux kernel: [UFW BLOCK] IN=eth0 OUT= MAC=08:00:27:aa:75:3b:52:55:0a:00:02:02:08:00 SRC=34.107.243.93 DST=10.0.2.15 LEN=40 TOS=0x00 PREC=0x00 TTL=64 ID=41350 PROTO=TCP SPT=443 DPT=33074 WINDOW=05535 RES=0x00 ACK FIN URGP=0 host = kali-linux source = /var/log/uFW.log sourcetype = UFW
>	4/2/26 3:04:38.800 PM	2020-04-02T15:04:38.800989-07:00 kali-linux kernel: [UFW BLOCK] IN=eth0 OUT= MAC=08:00:27:aa:75:3b:52:55:0a:00:02:02:08:00 SRC=34.107.243.93 DST=10.0.2.15 LEN=40 TOS=0x00 PREC=0x00 TTL=64 ID=41310 PROTO=TCP SPT=443 DPT=33074 WINDOW=05535 RES=0x00 ACK FIN URGP=0 host = kali-linux source = /var/log/uFW.log sourcetype = UFW
>	4/2/26 3:04:38.800 PM	2020-04-02T15:04:38.800988-07:00 kali-linux kernel: [UFW BLOCK] IN=eth0 OUT= MAC=08:00:27:aa:75:3b:52:55:0a:00:02:02:08:00 SRC=34.107.243.93 DST=10.0.2.15 LEN=40 TOS=0x00 PREC=0x00 TTL=64 ID=41304 PROTO=TCP SPT=443 DPT=33074 WINDOW=05535 RES=0x00 ACK FIN URGP=0 host = kali-linux source = /var/log/uFW.log sourcetype = UFW