

Module 7 Report:

Applied Scenario & Case Study Analysis: Network Protocols & Threats

JR Clark (002035589)
NEU DAMG7350 (Spring 2026)

Introduction

The transition from IPv4 to IPv6 has become one of the most complex and security-sensitive evolutions in modern network architecture. While IPv6 offers massive address space, improved routing efficiency, and built-in support for secure communication, most organizations—including hospitals—operate in long-term dual-stack environments. This coexistence introduces monitoring gaps, misconfigurations, and new attack surfaces that adversaries can exploit. At the same time, secure protocols such as TLS, IPsec, and SSH remain foundational to trust on the internet, yet history shows that even these protocols can fail catastrophically when implementations are flawed. This report analyzes both dimensions: the risks of unmonitored IPv6 traffic in a healthcare environment and the broader lessons from the Heartbleed vulnerability in OpenSSL.

Part 1: IPv6/IPv4 Dual-Stack Scenario Analysis

Risk Created by an IDS That Does Not Monitor IPv6 Traffic

Failing to monitor IPv6 traffic creates a **shadow network** inside the hospital—an entire parallel communication channel invisible to security tools. Attackers can exploit this blind spot to conduct reconnaissance, launch denial-of-service attacks, or exfiltrate data without triggering alerts. As the module notes, dual-stack environments inherently expand the attack surface because IPv6 eliminates NAT and assigns globally routable addresses to devices by default. In a hospital, this includes IoMT devices, printers, infusion pump gateways, and imaging systems.

Unmonitored IPv6 traffic enables:

- **Stealth Reconnaissance:** IPv6 Neighbor Discovery Protocol (NDP) broadcasts can be captured from outside the building using drones or high-gain antennas, allowing attackers to map internal devices without physical access.

- **Service Disruption:** Attackers can target IPv6-enabled printers or medical devices with direct DoS floods, preventing critical workflows such as printing discharge instructions or pharmacy labels.
- **Credential Theft:** De-authentication attacks can force devices off Wi-Fi and redirect them to a rogue IPv6 “evil twin” access point to harvest credentials.
- **Undetected Data Exfiltration:** Malware can tunnel data over IPv6 while the IDS only inspects IPv4, bypassing all monitoring and alerting.

In short, the hospital is effectively blind to half of its network traffic, creating a high-risk environment for patient safety and operational continuity.

Two Immediate Steps to Reduce This Risk

1. **Enable IPv6-Aware Security Controls (RA Guard, DHCPv6 Guard, and IDS/IPS Updates).** IPv6 introduces new control-plane protocols such as Router Advertisements (RA) and Multicast Listener Discovery (MLD). Without protections, attackers can impersonate routers or inject malicious advertisements. Enabling **RA Guard (RFC 6105)** ensures that only authorized routers can send RAs, preventing rogue devices from redirecting traffic. Updating the IDS/IPS to inspect IPv6, ICMPv6, and extension headers closes the monitoring gap.
2. **Implement Identity-Based Microsegmentation and Network Access Control (NAC).** Devices should be placed into restricted VLANs or quarantine segments until authenticated. This prevents unauthorized IPv6-enabled devices from communicating freely and limits lateral movement. NAC also ensures consistent enforcement across both IPv4 and IPv6, reducing the risk of misconfigured or unmanaged IoMT devices.

Likely Vulnerabilities Attackers Would Find When Scanning IPv6 Ranges

Attackers scanning the hospital's IPv6 ranges could uncover:

- **Directly Accessible Devices:** IPv6 removes NAT, exposing devices that were previously shielded behind private IPv4 ranges.
- **Legacy IoMT Weaknesses:** Over half of hospital IoT devices contain known vulnerabilities, including outdated web interfaces, open Telnet ports, or unpatched firmware.
- **SLAAC Misconfigurations:** Devices may embed their MAC address into their IPv6 identifier, revealing manufacturer and model information useful for targeted exploits.
- **Default Credentials:** Printers, cameras, and medical gateways often expose administrative interfaces with factory-default logins.
- **Unencrypted Internal Protocols:** Older DICOM implementations, HTTP-based admin pages, and proprietary device protocols may be visible over IPv6.

A real-world example illustrates this risk: while working onsite at Abbott, I discovered that a networked printer displayed its IP address on a label. By adding the printer directly via IP, I bypassed the badge-swipe requirement entirely—demonstrating how direct addressing can circumvent intended access controls.

Part 2: Heartbleed Case Study

Which Protocol Was Directly Affected?

Heartbleed directly affected **TLS**, the protocol responsible for securing application-layer communications such as HTTPS. As the module explains, *“TLS secures communications at the application layer, underpinning HTTPS and enabling secure web browsing. It provides both encryption and authentication via digital certificates, helping prevent*

impersonation attacks.” The vulnerability was not in the TLS protocol design itself but in **OpenSSL’s implementation** of the TLS heartbeat extension, which allowed attackers to read arbitrary server memory.

What Heartbleed Teaches About Relying on Encryption Protocols

Heartbleed demonstrates that **encryption protocols are only as strong as their implementations**. Even though TLS is a robust, well-designed protocol, a single bounds-checking error in OpenSSL undermined confidentiality, integrity, and authentication across millions of systems.

Key lessons include:

- **Implementation flaws can defeat strong cryptography.** Heartbleed exposed private keys, passwords, and session tokens despite the underlying algorithms being secure.
- **Trust cascades across the stack.** When a TLS library fails, every application that depends on it—websites, VPNs, APIs—fails with it.
- **Security requires continuous maintenance.** Organizations must patch promptly, rotate certificates, and monitor for library-level vulnerabilities.
- **Defense in depth is essential.** Encryption alone cannot compensate for weak coding practices, outdated libraries, or missing validation.

Heartbleed remains a defining example of how a single implementation bug can compromise global trust in secure communication.

References

Alsubaei, F., Abuhussein, A., & Shiva, S. (2022). *Security and privacy in the Internet of Medical Things: Taxonomy and risk assessment*. *Sensors*, 22(15), 1–22.

<https://pmc.ncbi.nlm.nih.gov/articles/PMC9403058/>

de Zoysa, D. B. K., Perera, H., & Samarasinghe, T. (n.d.). *Cyber attacks on healthcare devices using unmanned aerial vehicles*. ResearchGate.

https://www.researchgate.net/publication/337938736_Cyber_Attacks_on_Healthcare_Devices_Using_Unmanned_Aerial_Vehicles

OpenStax. (n.d.). *Vulnerabilities and threats in web applications and IoT technology*. In *Foundations of information systems*. <https://openstax.org/books/foundations-information-systems/pages/6-2-vulnerabilities-and-threats-in-web-applications-and-iot-technology>

Puzakova, J. (2025, May 15). *The IPv6 paradox: Why the internet's future protocol remains in transition*. IPXO. <https://www.ipxo.com/blog/the-ipv6-paradox/>

US Signal. (n.d.). *IoT in healthcare: Security risks and patient privacy*.

<https://ussignal.com/blog/iot-in-healthcare-security-risks-and-patient-privacy/>

Sawant, A. (2024). Module 7 “Network Protocols and Threats.” Northeastern University. Accessed on Coursera.com on 2/10/2026.

AI Use & Methodology Statement

This paper was developed using my own analysis and professional experience, with support from Microsoft Copilot. Copilot assisted with review of the initial draft, validating it against the assignment rubric, and helping refine the length and clarity. All AI-generated suggestions were reviewed, edited, and validated by me to ensure accuracy, alignment with course materials, and compliance with Northeastern University’s Academic Integrity and Use of AI policy. I am fully responsible for the final content.