Bootcamp Day 3

Overview

Establish a connection between Person and Contacts services.

Additional Features

Describes a single, uni-directional relationship between two entities

Resource Identifier

```
/v1/contact/{ownerId}/{contactId}
```

Part	Required	Туре	Example	Description
ownerld	yes	string	joe	The ID of the entity who owns the contact
contactId	yes	string	bob	The ID of the contact entity

GET Method

Gets the existence of a relation between the given two entities.

Request

Http Body

None

Response

Returns a JSON list of the entity IDs that have been stored as contacts for the requested entity

```
{
   "ownerId":"joe",
   "contactId":
   {
      "id":"bob",
      "name":"Mr Bob",
      "email":"bob@example.com",
      "self":"http://localhost:8080/v1/person/bob"
   }
}
```

Code	Description	
204	Relation exists	
404	Relation does not exist	

Http Body

None.

PUT Method

Creates a relation between the given two entities.

Request

Http Body

None

Response

Return Codes:

Code	Description	
204	Success	
404	Person does not exists	

Http Body

None.

DELETE Method

Deletes a relation between the given two entities.

Request

Http Body

None

Response

Return Codes:

Code	Description
204	Success
404	- Relationship does not exists - Contact person entity is removed

Http Body

None.

Feature

Limit the number of contacts per owner to 5

PUT Request

Http Body

Response

Return Codes:

Code	Description
204	Success
404	- Person does not exists - Contact limit exceeds 5

Http Body

None.