

API

Manual

# Riya Travel& Tours (I) Pvt Ltd

## Riya Web Services (RWS) Reference Manual Edition 2.0

This document is the Reference manual for API (Application Programming Interface) and includes the Access URL, Authentication, XML Request and Response formats.



# API Reference Manual of RWS

## Document History

The purpose of the document history is to list the changes made to each edition of the *Application Programming Interface* (API) User Guide, including the section affected and a description of the change.

Edition	Date	Changes
1.0		Document Created (First Draft)
1.1	26-03-2012	Design changes
1.2	21-06-2012	Description Changes & design changes
1.3	25-10-2012	Block PNR and Ticketing
1.4	02-02-2013	<ul style="list-style-type: none"><li>❖ Infant booking in LCC carrier</li><li>❖ GoAir Business Class</li><li>❖ Departure and Arrival Terminal Details</li><li>❖ Round trip and Connecting flights specifications in booking</li><li>❖ Static IP Patching</li><li>❖ Agent Account Balance</li></ul>
1.5	22-04-2013	<ul style="list-style-type: none"><li>❖ Sell Request</li></ul>
2.0	08-05-2014	<ul style="list-style-type: none"><li>❖ Book Reservation Version2</li><li>❖ Sell Request Version2</li><li>❖ Track Details</li><li>❖ Work Flow</li></ul>

## **Disclaimer**

This documentation is the confidential and proprietary information of Riya Travel & Tours and may be used, modified, altered, copied, reproduced, or transferred only in accordance with a written license agreement executed by Riya Travel & Tours India Pvt. Ltd.

© All rights reserved.

## **Table of Contents**

<b>1</b>	<b><u>Introduction</u></b>
<b>2</b>	<b><u>Access URL</u></b>
<b>3</b>	<b><u>Authentication</u></b>
<b>4</b>	<b><u>Availability</u></b>
4.1	<u>XML Request</u>
4.2	<u>Method</u>
4.3	<u>Description</u>
4.4	<u>Data Format and Details</u>
4.5	<u>XML Response</u>
4.5.1	<u>In case of Error</u>
4.5.2	<u>In case of Exception</u>
4.6	<u>Description</u>
4.7	<u>Data Format and Details</u>
<b>5</b>	<b><u>Sell Flight</u></b>
5.1	<u>XML Request</u>
5.2	<u>Method</u>
5.3	<u>Description</u>
5.4	<u>Data Format and Details</u>
5.5	<u>XML Response</u>

5.5.1 In case of Error

5.5.2 In case of Exception

5.6 Description

## **6 Sell Request Version2**

6.1 XML Request

6.2 Method

6.3 Description

6.4 Data Format and Details

6.5 XML Response

## **7 Book Reservation**

7.1 XML Request

7.2 Method

7.3 Description

7.4 Data Format and Details

7.5 XML Response

7.5.1 In case of Error

7.5.2 In case of Exception

7.6 Description

7.7 Data format and details

## **8 Book Reservation Version-2**

8.1 XML Request

8.2 Method

8.3 Description

8.4 Xml Response

8.5.1 In case of Error

8.5.2 In case of Exception

## **9 Cancellation**

9.1 XML Request

9.2 Method

9.3 Description

9.4 Data Format and Details

9.5 XML Response

## **10 Cancel Submit**

10.1 XML Request

10.2 Method

10.3 Description

10.4 Data Format and Details

10.5 XML Response

## **11 Reprint PNR Retrieve**

11.1 XML Request

11.2 Method

11.3 Description

11.4 Data Format and Details

11.5 XML Response

## **12 Agent Transaction**

12.1 XML Request

- 12.2 [Method](#)
- 12.3 [Description](#)
- 12.4 [Data Format and Details](#)
- 12.5 [XML Response](#)
- 12.6 [Description](#)
- 12.7 [Data Format and Details](#)

### **13     Fare Rule**

- 13.1 [XML Request](#)
- 13.2 [Method](#)
- 13.3 [Data Format and Details](#)
- 13.4 [XML Response](#)

### **14     Block PNR**

- 14.1 [XML Request](#)
- 14.2 [XML Response](#)
- 14.3 [Method](#)

### **15     Ticketing**

- 15.1 [XML Request](#)
- 15.2 [XML Response](#)
- 15.3 [Method](#)

### **16     Agent Account Balance**

- 16.1 [XML Request](#)
- 16.2 [Method](#)

16.3 Description

16.4 Data Format and Details

16.5 XML Response

## **17 Track Details**

17.1 XML Request

17.2 Method

17.3 Description

17.4 XML Response

## **18 Work Flow**

## **19 Support**



**Riya**  
*the travel expert!*

## 1. INTRODUCTION

Riya Travel & Tours India Private Limited provides Application Programming Interface (API) by integrated web services called as Riya Web Services (RWS) which offers a means of accessing and using data from its hosted services. It provides a gateway access to all Airlines Tickets booked through RIYA as product for an external plug-in. This gateway may be used to develop a separate application, or be integrated with an existing tool of users.

## 2. ACCESS URL

API URL: <http://riya.mywebcheck.in/riyaws/rws.asmx>

## 3. AUTHENTICATION

Parameters	Value
WebTerminal	Your Agent ID
WebUserName	Your Username
WebPassword	Your Password
WebIp	Your Requested static IP

Please pass the above credentials in SOAP Header class.

## 4. AVAILABILITY

### 4.1 XML Request(Sample):

```
<Availability>
  <SegmentType>(D or I)</SegmentType>
  <TripType>(O or R)</TripType>
  <Itinerary>
    <Item>
      <Origin>MAA</Origin>
      <Destination>DEL</Destination>
      <Date>04/20/2013</Date>
    </Item>

    ( If roundtrip)
    <Item>
      <Origin>DEL</Origin>
      <Destination>MAA</Destination>
      <Date>04/25/2013</Date>
    </Item>

  </Itinerary>
  <AirlineIdentification>
    <AirlineId>AI</AirlineId>
    <AirlineId>SG</AirlineId>
  </AirlineIdentification>
  <Paxreference>
    <Adults>1</Adults>
    <Childs>0</Childs>
    <Infants>0</Infants>
  </Paxreference>
  <HostAccess>Y</HostAccess>
  <ClassType>Economy</ClassType>
  <FareType>N</FareType> N - Normal fare & Y- RoundTrip Special Fare
</Availability>
```

### 4.2 Method

**FlightAvailability (clsSecurity, InputRequest)**

### 4.3 Description

This is the first step to access Riya API Web Services (RWS), by providing the proper parameters, passing shall be successful and it shall allow fetching of the flight availability from our server and it contains the following Xml content:

- **Segment Type:** Parameter to describe the kind of Travel,
  - D-Domestic
  - I-International
- **Trip Type:** Parameter to describe the kind of booking,
  - O-One Way
  - R-Round Trip

**Details:** Provide the Origin, Destination and the Date of Travel, according to the booking type request.

If it is a One-Way, then ongoing source and destination details are enclosed.

If it is a Round-Trip then along with ongoing the return journey details are also generated.

- **Origin:** Departure point.
- **Destination:** Arrival point.
- **Travel Date:** In case of one way, the departure date and in case of round trip, departure date from origin and destination.
- **Class Type:** Class the passenger chooses to travel which can be either Economy or Business which is based on the type of service the airline offers.
  - Economy
  - Business
- **FareType:** Describes the fare type as normal or special fare.
- **AirlineId:** Describes the airline the passenger chooses to travel.
- **Adult:** Number of adults travelling on the booking selection.
- **Child:** Number of Children aged between 2-12 years travelling on the booking selection.
- **Infant:** Number of Infants aged between 0-2 years travelling on the booking selection.

- **Host Access:** Indicating if it is direct access from Host or not.

#### 4.4 Data Format & Details:

Field Name	Data Type	Description
<b>SegmentType</b>	String	Segment Type shows the type of travel. It may be D-Domestic - I-International
<b>TripType</b>	String	Trip Type shows the type of booking. It may be a O-OneWay - R-RoundTrip
<b>Itinerary</b>	-	According to the booking type the details are enclosed. For One-Way it encloses a single source, destination and date of journey details.  For Round-Trip it encloses 2 source, 2 destinations and the corresponding travel dates.
<b>Origin</b>	String	Passenger's source place i.e., where they start from (airport code)
<b>Destination</b>	String	Passenger's destination place i.e., where they get off(destination Airport code)
<b>Date</b>	Date	Date field denotes the journey date. It is mandatory to give the dates in the format <b>[MM/DD/YYYY]</b>
<b>ClassType</b>	String	Class Type Identification shows the kind of class that the passenger wants to travel in.  <b>Economy</b> –for economy fare class , <b>Business</b> -for business fare class
<b>FareType</b>	String	Fare identification shows the type of fare (N - Normal fare & Y- Roundtrip Special Fare

<b>AirlineId</b>	String	Describes the airline, which the person chooses to travel.
<b>Adults</b>	Integer	Displays the number of adults chosen to travel.  NOTE : Total number of adult and child cannot exceed a maximum of 9 members in a single transaction.
<b>Child</b>	Integer	Displays the number of Children chosen to travel.  NOTE : Total number of adult and child cannot exceed a maximum of 9 members in a single transaction.
<b>Infants</b>	Integer	Displays the number of Infants chosen to travel.  NOTE: Maximum number of only 4 infants can be accepted in a single booking.
<b>HostAccess</b>	String	Host Access from the host.  N-Not Direct Access   -   Y-Direct Access

#### 4.5 XML Response (Sample):

```

<AvailabilityResponse>
<TrackId>RAC89B3DC1F7E141419AFE32431ED008D720140123202114</TrackId>
<ItineraryDetails>
<Items>
<FlightDetails>
<FlightID>1763</FlightID>
<CarrierCode>6E</CarrierCode>
<Origin>BOM</Origin>
<Destination>DEL</Destination>
<FlightNum>184</FlightNum>
<DepartureDateTime>12/05/2012 06:20</DepartureDateTime>
<ArrivalDateTime>12/05/2012 08:25</ArrivalDateTime>
<Duration>02 Hrs05 Mins</Duration>
<OrgTerminal>D</OrgTerminal>
<DesTerminal>1</DesTerminal>

```

```

<AirCraftType>320</AirCraftType>
<NumberOfStops>0</NumberOfStops>
<Via />
<ValidatingCarrier>6E</ValidatingCarrier>
<ClassCode>V0BOMDEL </ClassCode>
<ClassCodeDesc />
<FareBasisCode>V0BOMDEL</FareBasisCode>
<BreakPoint />
<CurrencyCode>INR</CurrencyCode>
</FlightDetails>
<FareDescription>
<PaxFareDetails>
<PaxType>ADT</PaxType>
<BasicAmount>1101.00</BasicAmount>
<TotalTaxAmount>2434.00</TotalTaxAmount>
<FuelSurcharge>2000.00</FuelSurcharge>
<Commission>0</Commission>
<OtherInfo>
<Item>
<TaxCode>YQ</TaxCode>
<Amount>2000.00</Amount>
</Item>
<Item>
<TaxCode>IN</TaxCode>
<Amount>50.00</Amount>
</Item>
<Item>
<TaxCode>JN</TaxCode>
<Amount>155.00</Amount>
</Item>
<Item>
<TaxCode>WO</TaxCode>
<Amount>229.00</Amount>
</Item>
<TransactionFee>0.00</TransactionFee>
<ServiceTax>0.00</ServiceTax>
<GrossAmount>3728.00</GrossAmount>
<OtherInfo>
</PaxFareDetails>
</FareDescription>
</Items>
</ItineraryDetails>
</AvailabilityResponse>

```

#### 4.5.1 In case of Error:

```

<AvailabilityResponse>
<ResultCode>
<Status></Status>
<Error>
<Description></Description>
</Error>

```

```
</ResultCode>  
</AvailabilityResponse>
```

#### 4.5.2 In case of Exception:

```
<AvailabilityResponse>  
<Exception>  
<Description></Description>  
</Exception>  
</AvailabilityResponse>
```

#### 4.6 Description:

Below will be the response received for the right request from the server. This method gets invoked once the request is initiated and is properly validated.

This response will give you the details of availability of flights, the fare and other related details. listed below, in xml tags format.

- **FlightDetails:** Includes the airline segment details and airline codes
- **FlightID:** Unique Identification Id.
- **CarrierCode:** Two letter Airline code.
- **Origin:** Place from where the passenger departs.
- **Destination:** Place where the passenger arrives at.
- **FlightNum:** Unique number allotted to a flight.
- **DepartureDateTime:** Flight departure date and time.
- **ArrivalDateTime:** Flight arrival date and time.
- **Duration:** Total number of hours taken for travel in the flight.
- **OrgTerminal:**Origin Airport Terminal ID
- **DesTerminal :** Destination Airport Terminal ID
- **Aircraft Type:** Describes the flight type.



- **NumberOfStops:** Number of places the flight lands before reaching the Final destination (with or without change of flight)
- **Via:** Describes Flight Transit point without flight change
- **ValidatingCarrier:** Ticketing Airline code
- **ClassCode:** Travelling class chosen by the passenger (Economy or business.)
- **ClassCodeDesc:** Details of the Class whether its Refundable or non-refundable
- **FareBasis:** A Specific code which includes Alpha, Numeric or Alphanumeric for a class chosen
- **BreakPoint:** Indicates connections of the fare details.
- **CurrencyCode:** Transaction currency used.
- **FareDescription:** Details of the fare selected based on passenger.
- **PaxType:** Type of Passenger(Adult/Child/Infant)
- **BasicAmount:** Basic amount for the passenger's journey which excludes the taxes and other charges
- **TotalTaxAmount:** Sum of the Total taxes excluding the base fare.
- **FuelSurCharge:** One of the Tax component levied by the Airline.
- **Commission:** Indicates agent commission amount.
- **TaxCode:** Indicates the tax code.
- **Amount:** Amount corresponding to the tax code.
- **TransactionFee:** Indicates transaction fee for the segment.
- **ServiceTax:** Indicates service tax for the segment
- **GrossAmount:** Total fare which includes the Basic fare and all taxes of each passenger.

#### 4.7 Data Format & Details:

Field Name	Data Type	Description
<b>FlightDetails</b>	---	Includes the airline segment details and airline codes
<b>FlightId</b>	String	Unique Identification Id
<b>CarrierCode</b>	String	letter Airline code
<b>Origin</b>	String	Place from where the passenger departs (Origin Airport code)
<b>Destination</b>	String	Place where the passenger arrives at. (Destination Airport code)
<b>FlightNum</b>	Integer	Unique No. allotted to a flight
<b>DepatureDateTime</b>	DateTime	Flight departure date and time
<b>ArrivalDateTime</b>	DateTime	Flight arrival date and time
<b>Duration</b>	String	Total number of hours taken for travel in the flight
<b>OrgTerminal</b>	String	Describes Origin terminal ID
<b>DesTerminal</b>	String	Describes Destination terminal ID
<b>AircraftType</b>	String	Describes the type of the Aircraft
<b>NumberOfStops</b>	Integer	Number of places the flight lands before reaching the destination
<b>Via</b>	String	Describes Flight Transit point without flight change
<b>ValidatingCarrier</b>	String	Ticketing Airline code
<b>ClassCode</b>	String	Kind of class that is chosen. It may be either economy or executive
<b>ClassCodeDesc</b>	String	Details of the Class whether its Refundable or non-refundable
<b>FareBasisCode</b>	String	A Specific code which includes Alpha, Numeric or

		Alphanumeric for a class chosen
<b>CurrencyCode</b>	String	Transaction currency that is used
<b>PaxType</b>	String	Type of Passenger(Adult/Child/Infant)
<b>BasicAmount</b>	Money	Basic amount for the passenger's journey which excludes the taxes and other charges
<b>TotalTaxAmount</b>	Money	Sum of the Total taxes excluding the base fare
<b>FuelSurcharge</b>	Money	One of the Tax component levied by the Airline
<b>Commission</b>	Money	Indicates agent commission amount
<b>TaxCode</b>	String	Indicates the tax code
<b>Amount</b>	Money	Amount corresponding to the Tax Code
<b>TransactionFee</b>	Money	Indicates Transaction fee for the segment
<b>ServiceTax</b>	Money	Indicates Service tax for the segment
<b>GrossAmount</b>	Money	Total fare which includes the Basic fare and all taxes of each passenger

## 5. SELL FLIGHT

### 5.1 XML Request (Sample):

```

<SellRequest>
  <TrackId>RAC89B3DC1F7E141419AFE32431ED008D720140123202114</TrackId>
  <TripType>O</TripType>
  <SegmentType>D</SegmentType>
  <NoofAdults>1</NoofAdults>
  <NoofChild>0</NoofChild>
  <NoofInfants>0</NoofInfants>
  <ItineraryDetails>
    <!--Repetitions for Round trip -->
    <Segments>
      <!--Repetitions for connecting Flights -->
      <item>
        <FlightID>335</FlightID>
        <CarrierId>G8</CarrierId>
        <Origin>BOM</Origin>
        <Destination>DEL</Destination>
      </item>
    </Segments>
  </ItineraryDetails>
</SellRequest>

```

```
<DepartureDateTime>17/03/2013 09:00</DepartureDateTime>  
<ArrivalDateTime>17/03/2013 10:15</ArrivalDateTime>  
<ClassCode>GoSmart</ClassCode>  
</item>  
</Segments>  
</ItineraryDetails>  
</SellRequest>
```

## 5.2 **Method:** **SellRequest (clsSecurity, InputRequest)**

## 5.3 **Description:**

- **TrackId:** Indicates the reference id of search availability
- **TripType:** Trip Type shows the type of booking. It may be a OneWay/RoundTrip
- **SegmentType:** Segment Type shows the type of travel. It may be Domestic/International
- **NoofAdults:**Adult (Type of Passenger) – Passenger who is above the age of 12yrs termed as Adult (Maximum Adult and child count is 9)
- **NoofChild:** Child (Type of Passenger) Passenger who is between 2-12 years of age.
- **NoofInfants:** Children who are below 2 years of age. (Maximum infant count is 4)
- **FlightID:** Unique flight Identification No.
- **CarrierId:** Two letter Airline Code
- **Origin:**Place from where the passenger departs (Origin Airport code)
- **Destination:** Place where the passenger arrives at. (Destination Airport code)
- **DepartureDateTime:** Flight departure date and time
- **ArrivalDateTime:** Flight arrival date and time

- **ClassCode:** Kind of class that is chosen. It may be either economy or executive

#### 5.4 Data Format & Details:

Field Name	Data Type	Description
<b>TrackId</b>	String	Indicates the reference id of search availability response.
<b>TripType</b>	String	Trip Type shows the type of booking. It may be a O-OneWay - R-RoundTrip
<b>SegmentType</b>	String	Specifies Segment type (Domestic or International)
<b>NoofAdults</b>	Integer	Displays the number of adults chosen to travel.  NOTE: Total number of adult and child cannot exceed a maximum of 9 members in a single transaction.
<b>NoofChild</b>	Integer	Displays the number of Children chosen to travel.  NOTE: Total number of adult and child cannot exceed a maximum of 9 members in a single transaction.
<b>NoofInfants</b>	Integer	Displays the number of Infants chosen to travel.  NOTE: Maximum number of only 4 infants can be accepted in a single booking.
<b>ItineraryDetails</b>		Details of flights booked
<b>Segments</b>		Details of segments booked
<b>FlightID</b>	Integer	Unique Identification Id.

<b>CarrierId</b>	String	2 letter airline code
<b>Origin</b>	String	Passenger's source place i.e., from where the journey starts (airport code)
<b>Destination</b>	String	Passenger's destination place i.e., where the journey terminates (destination Airport code)
<b>DepartureDateTime</b>	Date	Date field denotes the journey departure date. It is mandatory to give the dates in the format [DD/MM/YYYY HH:MM]
<b>ArrivalDateTime</b>	Date	Date field denotes the journey arrival date. It is mandatory to give the dates in the format [DD/MM/YYYY HH:MM]
<b>ClassCode</b>	String	Describes the choice of class by which the person chooses to travel.

### 5.5 XML Response (Sample):

```

<SellResponse>
<SellReferenceId>RA24F9522C7C56479B8E7A7961FF08B3A720140123202120</SellReferenceId>
<ResultCode>
<Status>1</Status>
</ResultCode>
<ItineraryDetails>
<Segments>
<item>
<FlightID>335</FlightID>
<CarrierId>G8</CarrierId>
<Origin>BOM</Origin>
<Destination>DEL</Destination>
<DepartureDateTime>17/03/2013 09:00</DepartureDateTime>
<ArrivalDateTime>17/03/2013 10:15</ArrivalDateTime>
<Class>GoSmart</Class>
<FareBasisCode></FareBasisCode>
<ValidatingCarrier>G8</ValidatingCarrier>
</item>
<PaxSSRList>
<AvailPaxSSR></AvailPaxSSR>
</PaxSSRList>
<FareDescription>
<PaxFareDetails>
<PaxType>ADT</PaxType>
<BasicAmount>1101.00</BasicAmount>
<TotalTaxAmount>2434.00</TotalTaxAmount>

```

```

<FuelSurcharge>2000.00</FuelSurcharge>
<Commission>0</Commission>
<OtherInfo>
<Item>
<TaxCode>YQ</TaxCode>
<Amount>2000.00</Amount>
</Item>
<Item>
<TaxCode>IN</TaxCode>
<Amount>50.00</Amount>
</Item>
<Item>
<TaxCode>JN</TaxCode>
<Amount>155.00</Amount>
</Item>
<Item>
<TaxCode>WO</TaxCode>
<Amount>229.00</Amount>
</Item>
<TransactionFee>0.00</TransactionFee>
<ServiceTax>0.00</ServiceTax>
<GrossAmount>3728.00</GrossAmount>
</OtherInfo>
</PaxFareDetails>
</FareDescription>
</Segments>
</ItineraryDetails></SellResponse>

```

#### 5.5.1 In case of Error:

```

<SellResponse>
<ResultCode>
<Status></Status>
<Error>
<Description></Description>
</Error>
</ResultCode>
</SellResponse>

```

#### 5.5.2 In case of Exception:

```

<SellResponse>
<Exception>
<Description></Description>
</Exception>
</SellResponse>

```

### 5.6 Description:

- **SellReferenceId:** reference id from sell response for booking
- **FlightID:** Indicates flight identification.

- **CarrierId:** Indicates flight carrier code.
- **Origin:** Indicates passenger departure city code.
- **Destination:** Indicates passenger arrival city code.
- **DepartureDateTime:** Indicates flight departure date and time.
- **ArrivalDateTime:** Indicates flight arrival date and time.
- **ClassCode:** Indicates type of class chosen.
- **SelectedFareBasisCode:**
- **AvailPaxSSR:**Special service request
- **PaxType:** Type of travelling passenger.
- **BasicAmount:**Booking base amount
- **TotalTaxAmount:** Total tax amount.
- **FuelSurcharge:** YQ tax amount (Fuel tax amount).
- **Commission:** Booking commission amount.
- **TaxCode:** Tax description code.
- **Amount:** Tax amount.
- **ServiceTax:** Service tax amount for agent's earnings.
- **GrossAmount:** Booking Gross amount.



## 6. SELL REQUEST VERSION-2

### 6.1 XML Request (Sample):

```
<SellRequest_V2>
<TrackId>RAB7A2DF5A57E8465ABF7DFC8BAA50FFBE20140215175448</TrackId>
<TripType>O</TripType>
<SegmentType>D</SegmentType>
<NoofAdult>1</NoofAdults>
<NoofChild>0</NoofChild>
<NoofInfant>0</NoofInfant>
<FareType>N</FareType> N - Normal fare & Y- RoundTrip Special Fare
<ItineraryDetails>
<!--Repetitions for Round trip (Domestic) -->
<Segments>
<!--Repetitions for connecting Flights -->
<item>
<FlightID>4418</FlightID>
<CarrierId>TR</CarrierId>
<Origin>MAA</Origin>
<Destination>SIN</Destination>
<DepartureDateTime>28/02/2014 07:50</DepartureDateTime>
<ArrivalDateTime>28/02/2014 11:50</ArrivalDateTime>
<ClassCode>J</ClassCode>
</item>
</Segments>
</ItineraryDetails>
</SellRequest_V2>
```

### 6.2 Method:

**SellRequestVersion2(clsSecurity, InputRequest)**

### 6.3 Description:

- **TrackId:** Indicates the reference id of search availability.
- **TripType:** Trip Type shows the type of booking. It may be a One-way/Roundtrip
- **SegmentType:** Segment Type shows the type of travel. It may be Domestic/International

- **NoofAdult:** Adult (Type of Passenger) – Passenger who is above the age of 12yrs termed as Adult (Maximum Adult and child count is 9)
- **NoofChild:** Child (Type of Passenger) Passenger who is between 2-12 years of age.
- **NoofInfant:** Children who are below 2 years of age. (Maximum infant count is 4).
- **FareType:** Indicates the Fare-type, N-Normal, Y- Roundtrip Special Fare.
- **FlightID:** Unique flight Identification No.
- **CarrierId:** 2 letter Airline Code
- **Origin:** Place from where the passenger departs (Origin Airport code)
- **Destination:** Place where the passenger arrives at. (Destination Airport code)
- **DepartureDateTime:** Flight departure date and time
- **ArrivalDateTime:** Flight arrival date and time
- **ClassCode:** Kind of class that is chosen. It may be either economy or business.

#### 6.4 Data Format & Details:

Field Name	Data Type	Description
<b>TrackId</b>	String	Indicates the reference id of search availability
<b>TripType</b>	String	Trip Type shows the type of booking. It may be a O-One-way, R-Roundtrip
<b>SegmentType</b>	String	Specifies Segment type (Domestic or International)
<b>NoofAdult</b>	Integer	Displays the number of adults chosen to travel. (Maximum 9 adults)
<b>NoofChild</b>	Integer	Displays the number of Children chosen to travel. (Maximum Adult and child count is 9)
<b>NoofInfant</b>	Integer	Displays the number of Infants chosen to travel. (Maximum infant count is 4)
<b>FareType</b>	String	Indicates Fare Type. N – Normal, Y – Roundtrip Special fare.
<b>ItineraryDetails</b>	---	Detail for Itinerary details
<b>FlightID</b>	Integer	Unique Identification Id.
<b>CarrierId</b>	String	2 letter airline code
<b>Origin</b>	String	Passenger's source place i.e., from where the journey starts (airport code)
<b>Destination</b>	String	Passenger's destination place i.e., where the journey terminates (destination Airport code)
<b>DepartureDateTime</b>	Date	Date field denotes the journey departure date. It is mandatory to give the dates in the format [DD/MM/YYYY HH:MM]
<b>ArrivalDateTime</b>	Date	Date field denotes the journey arrival date. It is mandatory to give the dates in the format [DD/MM/YYYY HH:MM]
<b>ClassCode</b>	String	Describes the choice of class by which the person chooses to travel.(economy, business, first)

## 6.5 XML Response (Sample):

```
<SellResponse>
  <SellReferenceId>RAC9F2DF5A57E8485ABF7VFC8BAA50FFBE2014022343454</SellReferenceId>
  <ResultCode>
  <Status>1</Status>
</ResultCode>
  <ItineraryDetails>
    <Segments>
      <item>
        <FlightID>4418</FlightID>
        <CarrierId>TR</CarrierId>
        <FlightNum>3013</FlightNum>
        <Origin>MAA</Origin>
        <Destination>SIN</Destination>
        <DepartureDateTime>28/02/2014 07:50</DepartureDateTime>
        <ArrivalDateTime>28/02/2014 11:50</ArrivalDateTime>
        <Class>J</Class>
        <FareBasisCode>J</FareBasisCode>
        <ValidatingCarrier>SG</ValidatingCarrier>
      </item>
      <PaxSSRList>
        <AvailPaxSSR>
          <AvailMeals>
            <item>
              <Origin>MAA</Origin>
              <Destination>SIN</Destination>
              <SegNumber>1</SegNumber> (if segnumber '0' the SSR is applicable for whole itinerary segments.
                                     if segnumber '1,2,etc' the SSR is applicable for particular sector.)
              <SSRMeal>
                <SSRCode>VGSW</SSRCode>
                <Description>Veg Sandwich</Description>
                <Amount>125.00</Amount>
              </SSRMeal>
              <SSRMeal>
                <SSRCode>NVSW</SSRCode>
                <Description>Non Veg Sandwich</Description>
                <Amount>125.00</Amount>
              </SSRMeal>
            </item>
          </AvailMeals>
          <AvailBaggages>
            <item>
              <Origin>MAA</Origin>
              <Destination>SIN</Destination>
              <SSRNumber>1</SSRNumber> (if segnumber '0' the SSR is applicable for whole itinerary segments.
                                     if segnumber '1,2,etc' the SSR is applicable for particular sector.)
              <SSRBaggage>
                <SSRCode>AC40</SSRCode>
                <Description>Baggage 40kg</Description>
                <Amount>3639.00</Amount>
              </SSRBaggage>
            </item>
          </AvailBaggages>
        </AvailPaxSSR>
      </PaxSSRList>
    </Segments>
  </ItineraryDetails>
</SellResponse>
```

<SSRBaggage>  
<SSRCode>AC35</SSRCode>  
<Description>Baggage 35kg</Description>  
<Amount>3079.00</Amount>  
</SSRBaggage>  
</item>  
</AvailBaggages>  
</AvailPaxSSR>  
</PaxSSRList>  
<FareDescription>  
<PaxFareDetails>  
<PaxType>ADT</PaxType>  
<BasicAmount>1101.00</BasicAmount>  
<TotalTaxAmount>2434.00</TotalTaxAmount>  
<FuelSurcharge>2000.00</FuelSurcharge>  
<Commission>0</Commission>  
<OtherInfo>  
<Item>  
<TaxCode>YQ</TaxCode>  
<Amount>2000.00</Amount>  
</Item>  
<Item>  
<TaxCode>IN</TaxCode>  
<Amount>50.00</Amount>  
</Item>  
<Item>  
<TaxCode>JN</TaxCode>  
<Amount>155.00</Amount>  
</Item>  
<Item>  
<TaxCode>WO</TaxCode>  
<Amount>229.00</Amount>  
</Item>  
<ServiceTax>0.00</ServiceTax>  
<GrossAmount>3728.00</GrossAmount>  
</OtherInfo>  
</PaxFareDetails>  
</FareDescription>  
</Segments>  
</ItineraryDetails>  
</SellResponse>

## 7. BOOKRESERVATION

### 7.1 XML Request (Sample):

```
<BookReservation>
<SellReferenceId>
RA24F9522C7C56479B8E7A7961FF08B3A720140123202120</SellReferenceId>
<CustomerDetails>
<Title>Mr</Title>
<Firstname>Firstname</Firstname>
<Lastname>Lastname</Lastname>
<Address1>Address1</Address1>
<Address2>Address2</Address2>
<Address3>Address3</Address3>
<City>City</City>
<State>City</State>
<Country>Country</Country>
<MailId> apitest@test.com</MailId>
<PinCode>600100</PinCode>
<ContactNo>9888888888</ContactNo>
</CustomerDetails>
<NoofAdults>1</NoofAdults>
<NoofChild>0</NoofChild>
<NoofInfants>0</NoofInfants>
<TripType>O</TripType>
<SegmentType>D</SegmentType>
<TotalAmount>3728.00</TotalAmount>
<PaymentMode>AT</PaymentMode> For prepaid account use AT and Postpaid Account CA
<Bookingdetails>
<!--Repetitions for Roundtrip -->
<Item>
<ValidatingCarrier>6E</ValidatingCarrier>
<Payment>
<item>
<CurrencyCode>INR</CurrencyCode>
<Amount>3728.00</Amount>
</item>
</Payment>
<TourCode></TourCode>
<Passengerlist>
<item>
<PaxType>ADT</PaxType>
<Title>Mr</Title>
<FirstName>Firstname</FirstName>
<LastName>Lastname</LastName>
<DateofBirth>14/04/1983</DateofBirth>
<Gender>M</Gender>
<SpecialReqcode></SpecialReqcode>
<Mealcode>VGML</Mealcode>
```

```

<PassportInfo>
<IdentityProofId>Passport</IdentityProofId>
<IdentityProofNumber>ASD11313</IdentityProofNumber>
<CountryId>IND</CountryId>
<ExpiryDate>12/03/2021</ExpiryDate>
</PassportInfo>
<Segment>
<!--More repetitions for connecting flights -->
<item>
<FlightID>1763</FlightID>
<CarrierId>6E</CarrierId>
<Origin>BOM</Origin>
<Destination>DEL</Destination>
<DepartureDateTime>12/05/2012 06:20</DepartureDateTime>
<ArrivalDateTime>12/05/2012 08:25</ArrivalDateTime>
<ClassCode>V0BOMDEL</ClassCode>
<FrequentFlyerNumber></FrequentFlyerNumber>
</item>
</Segment>
</item>
</Passengerlist>
</Item>
</Bookingdetails>
</BookReservation>

```

## 7.2 Method:

### BookReservation (clsSecurity, InputRequest)

## 7.3 Description:

- **TrackID:** Indicates the reference id of sellresponse.
- **CustomerDetails:** Describes the “Booked by” customer details.
- **Title:** Prefix added to the name.
- **FirstName:** First name of the “Booked by” customer.
- **LastName:** Last name of the “Booked by” customer.
- **Address:** Address of the “Booked by” customer.
- **City:** City of the “Booked by” customer.
- **State:** State of the “Booked by” customer.

- **Country:** Country of the “Booked by” customer.
- **MailId:** E-Mail of the “Booked by” customer.
- **Pincode:** Pincode of the “Booked by” customer.
- **ContactNo:** Contact No of the “Booked by” customer.
- **NoofAdults:** No of Adults travelling.
- **NoofChild:** No of Children travelling.
- **NoofInfants:** No of Infants travelling.
- **TripType:** Specifies Trip type, Oneway or Roundtrip.
- **SegmentType:** Specifies segment type Domestic or International.
- **TotalAmount:** Total booking amount.
- **PaymentMode:** Type of booking account Topup or credit.
- **BookingDetails:** Describes booking details.
- **ValidatingCarrier:** Indicates Ticketing carrier.
- **Payment:** Describes payment details.
- **CurrencyCode:** Specifies booking Currency code.
- **Amount:** Specifies booking amount.
- **TourCode:** Indicates tour code.
- **PassengerList:** Describes booking passenger list.
- **PaxType:** Indicates booking passenger type.
- **Title:** Indicates booking passenger title.
- **FirstName:** Indicates booking passenger first name.
- **LastName:** Indicates booking passenger last name.



- **DateofBirth:** Indicates booking passenger date of birth.
- **Gender:** Indicates booking passenger gender.
- **SpecialReqCode:** Indicates passenger special request code.
- **MealCode:** Indicates passenger meal request code (only for Full service carriers).
- **PassportInfo:** Describes passport details.
- **IdentifyProofId:** Describes passport or proof id.
- **IdentifyProofNumber:** Indicates identify proof No.
- **CountryId:** Indicates issuing country ID.
- **ExpiryDate:** Indicates proof expiry date.
- **Segment:** Describes flight segment details.
- **FlightID:** Indicates flight identification.
- **CarrierID:** Indicates flight carrier code.
- **Origin:** Indicates passenger departure city code.
- **Destination:** Indicates passenger arrival city code.
- **DepartureDatetime:** Indicates flight departure date and time.
- **ArrivalDatetime:** Indicates flight arrival date and time.
- **ClassCode:** Indicates type of class chosen.
- **FrequentFlyerNo:** Indicates Frequent flyer no.

#### 7.4 Data Format & Details:

Field Name	Data Type	Description
TrackID	String	Indicates the reference id of sellresponse

<b>CustomerDetails</b>		---	Describes the “Booked by” customer details
<b>Title</b>	String		Prefix added to the name
<b>FirstName</b>	String		First name of the “Booked by” customer
<b>LastName</b>	String		Last name of the “Booked by” customer
<b>Address</b>	String		Address of the “Booked by” customer
<b>City</b>	String		City of the “Booked by” customer
<b>State</b>	String		State of the “Booked by” customer
<b>Country</b>	String		Country of the “Booked by” customer
<b>MailId</b>	String		E-Mail of the “Booked by” customer
<b>Pincode</b>	Numeric		Pincode of the “Booked by” customer
<b>ContactNo</b>	Numeric		Indicates Booked by customer contact No.
<b>NoofAdults</b>	Integer		Indicates No of adults travelling (Maximum 9 adults)
<b>NoofChild</b>	Integer		Indicates No of child travelling (Maximum Adult and child count is 9)
<b>NoofInfants</b>	Integer		Indicates No of Infant travelling(count 4)
<b>TripType</b>	String		Specifies Trip type, One way or Roundtrip
<b>SegmentType</b>	String		Specifies Segment type (Domestic or International)
<b>TotalAmount</b>	Money		Total booking amount (Eg: Onward and Return total amount)
<b>PaymentMode</b>	String		Indicates type of Payment Mode (AT or CA)
<b>BookingDetails</b>		---	Describes booking details
<b>ValidatingCarrier</b>	String		Indicates Ticketing Carrier
<b>Payment</b>		---	Describes payment details

<b>CurrencyCode</b>	String	Specifies booking Currency code
<b>Amount</b>	Money	Specifies booking amount
<b>TourCode</b>	String	Indicates tour code
<b>PassengerList</b>	---	Describes booking passenger list
<b>PaxType</b>	String	Indicates booking passenger type (ADT/CHD/INF)
<b>Title</b>	String	Indicates booking passenger title
<b>FirstName</b>	String	Indicates booking passenger first name
<b>LastName</b>	String	Indicates booking passenger last name
<b>DateofBirth</b>	Date	Indicates booking passenger date of birth(DD/MM/YYYY)
<b>Gender</b>	String	Indicates passenger gender
<b>SpecialReqCode</b>	String	Indicates SSR codes eg: Frequent Flyer, Wheelchair
<b>MealCode</b>	String	Indicates passenger Meal req Code Eg: NVML,VGML(only for Full service carriers)
<b>PassportInfo</b>	String	Describes passport details
<b>IdentifyProofId</b>	String	Indicates Identity proof Eg: Passport, Driving License
<b>IdentifyProofNumber</b>	String	Indicates Identity proof No. Eg: Passport No
<b>CountryId</b>	String	Indicates passport issuing Country Code Eg: IND
<b>ExpiryDate</b>	Date	Indicates passport expiry date.(DD/MM/YYYY)
<b>Segment</b>	String	Describes flight segment details
<b>FlightID</b>	String	Indicates flight Identification
<b>CarrierID</b>	String	Indicates Flight Carrier code
<b>Origin</b>	String	Indicates passenger departure city code

<b>Destination</b>	String	Indicates passenger arrival city code
<b>DepartureDatetime</b>	Datetime	Indicates flight departure date and time
<b>ArrivalDatetime</b>	Datetime	Indicates flight arrival date and time
<b>ClassCode</b>	String	Indicates type of class chosen
<b>FrequentFlyerNo</b>	String	Indicates passenger frequent flyer No.

## 7.5 XML Response (Sample):

```

<Bookingresponse>
<ItineraryDetails>
<CustomerDetails>
<Title>Mr</Title>
<Firstname>Firstname</Firstname>
<Lastname>Lastname</Lastname>
<Address1>Address1</Address1>
<Address2>Address2</Address2>
<Address3>Address3</Address3>
<City>City</City>
<State>State</State>
<Country>Country</Country>
<MailId>mail@mail.com</MailId>
<PinCode>600100</PinCode>
<ContactNo>9888888888</ContactNo>
</CustomerDetails>
<TerminalContactDetails>
<TerminalName>Travel Agent</TerminalName>
<Address1>Address1</Address1>
<Address2 />
<City>City</City>
<State>State</State>
<Country>IN</Country>
<Phone>04444-444444444</Phone>
<Email>mail@gmail.com</Email>
</TerminalContactDetails>
<TotalSegments>1</TotalSegments>
<TotalAmount>3728.00</TotalAmount>
<OtherCharges>0.00</OtherCharges>
<Adults>1</Adults>
<Childs>0</Childs>
<Infants>0</Infants>
<TripType>O</TripType>
<SegmentType>D</SegmentType>
<IssuedDate>19/03/2012 20:45:43</IssuedDate>
<Item>
<Resultcode>1</Resultcode>
<BookingTrackId>RABBI0300001011932012P0002795</BookingTrackId>

```

<RiyaPNR>19AB478</RiyaPNR>  
<CRSPNR>N/A</CRSPNR>  
<BaseOrigin>BOM</BaseOrigin>  
<BaseDestination>DEL</BaseDestination>  
<TourCode />  
<PaymentDetails>  
<Item>  
<CurrencyCode>INR</CurrencyCode>  
<Amount>3728.00</Amount>  
</Item>  
</PaymentDetails>  
<TravellerInfo>  
<Item>  
<TicketNumber>19AB4781</TicketNumber>  
<PaxType>ADT</PaxType>  
<Title>Mr</Title>  
<FirstName>Firstname</FirstName>  
<LastName>Lastname</LastName>  
<DateOfBirth>N/A</DateOfBirth>  
<SegmentInformation>  
<Item>  
<AirlinePNR>KYU8AA</AirlinePNR>  
<TicketNo>19AB4781</TicketNo>  
<FlightNumber>184</FlightNumber>  
<Origin>BOM</Origin>  
<Destination>DEL</Destination>  
<DepartureDateTime>12/05/2012 06:20</DepartureDateTime>  
<ArrivalDateTime>12/05/2012 08:25</ArrivalDateTime>  
<AirCraftType>320</AirCraftType>  
<CarrierCode>6E</CarrierCode>  
<ClassCode>V0BOMDEL</ClassCode>  
<FareBasis>V0BOMDEL</FareBasis>  
<FrequentFlyerNumber>N/A</FrequentFlyerNumber>  
<SpRequest />  
<MealsPreference>N/A</MealsPreference>  
</Item>  
<MonetaryDetail>  
<BasicCurrencyCode>INR</BasicCurrencyCode>  
<CurrencyCode>INR</CurrencyCode>  
<BasicAmount>1101.00</BasicAmount>  
<TaxDetails>  
<item>  
<CurrencyCode />  
<TaxCode>YQ</TaxCode>  
<Amount>2000.00</Amount>  
</item>  
<item>  
<CurrencyCode />  
<TaxCode>IN</TaxCode>  
<Amount>50.00</Amount>  
</item>  
<item>

```

<CurrencyCode />
<TaxCode>JN</TaxCode>
<Amount>155.00</Amount>
</item>
<item>
<CurrencyCode />
<TaxCode>WO</TaxCode>
<Amount>229.00</Amount>
</item>
</TaxDetails>
<TransactionFee>TransactionFee</TransactionFee>
<TransactionFeeAmount>186.00</TransactionFeeAmount>
<ServiceTax>ServiceTax</ServiceTax>
<ServiceTaxAmount>7.00</ServiceTaxAmount>
<GrossAmount>3728.00</GrossAmount>
</MonetaryDetail>
</SegmentInformation>
</Item>
</TravellerInfo>
</Item>
</ItineraryDetails>
</Bookingresponse>

```

#### 7.5.1 In case of Error:

```

<Bookingresponse>
<ResultCode>
<Status></Status>
<Error>
<Description></Description>
</Error>
</ResultCode>
</Bookingresponse>

```

#### 7.5.2 In case of Exception:

```

<Bookingresponse>
<Exception>
<Description></Description>
</Exception>
</Bookingresponse>

```

### 7.6 Description:

- **CustomerDetails:** Describes the “Booked by” customer details.
- **Title:** Name prefix of the “Booked by” customer.
- **FirstName:** First name of the “Booked by” customer.
- **LastName:** Last name of the “Booked by” customer.

- **Address:** Address of the “Booked by” customer.
- **City:** City of the “Booked by” customer.
- **State:** State of the “Booked by” customer.
- **Country:** Country of the “Booked by” customer.
- **MailId:** Email of the “Booked by” customer.
- **Pincode:** Pincode of the “Booked by” customer.
- **ContactNo:** Contact No. of the “Booked by” customer.
- **TerminalContactDetails-** Describes the Terminal contact details.
- **TerminalName:** Name of the Agent terminal.
- **Address:** Agent Terminal Address.
- **City:** Agent Terminal City.
- **State:** Agent Terminal State.
- **Country:** Agent Terminal Country.
- **Phone:** Agent contact Phone No.
- **Email:** Agent Email-Id.
- **TotalSegments:** No of booked segments.
- **TotalAmount:** Total booked amount.
- **OtherCharges:** Other Booking charges.
- **Adults:** No of adults for booking.
- **Childs:** No of child for booking.
- **Infants:** No of infant for booking.
- **TripType:** Type of the travel (OneWay or Return).

- **SegmentType:** Type of the segment (International or Domestic).
- **IssuedDate:** Ticket Issued date.
- **Resultcode:** Booking result code.
- **BookingTrackId:** Booking track sequence id.
- **RiyaPNR:** Internal PNR No.
- **CRSPNR:** CRS PNR.
- **BaseOrigin:** Passenger base departure city code.
- **BaseDestination:** Passenger base Arrival City Code.
- **TourCode:** Booked tour code.
- **PaymentDetails** – Describes the payment details in booking.
- **CurrencyCode:** Booked currency code.
- **Amount:** Booked amount.
- **TicketNumber:** Booked Ticket No.
- **PaxType:** Passenger type code.
- **Title:** Passenger Name title.
- **FirstName:** Passenger first Name.
- **LastName:** Passenger Last Name.
- **DateOfBirth:** Passenger date of birth.
- **SegmentInformation** – Describes the details in a booking segment.
- **AirlinePNR:** Segment Airline PNR.
- **TicketNo:** Passenger Ticket No.
- **FlightNumber:** Travelling Flight No.



- **Origin:** Travelling Flight Origin.
- **Destination:** Travelling Flight Destination.
- **DepartureDateTime:** Travelling Flight Departure date and time.
- **ArrivalDateTime:** Travelling Flight Arrival date and time.
- **AirCraftType:** Travelling aircraft type.
- **CarrierCode:** Travelling flight carrier code.
- **ClassCode:** Flight Class code.
- **FareBasis:** Booking fare basis code.
- **FrequentFlyerNumber:** Passenger frequent flyer code.
- **SpRequest:** special service request.
- **MealsPreference:** Meals request.
- **MonetaryDetails** – Describes the Amount details in a booking.
- **BasicCurrencyCode:** Booking base currency code.
- **CurrencyCode:** Booking currency code.
- **BasicAmount:** Booking base fare.
- **TaxDetails:** Booking tax break up.
- **CurrencyCode:** Tax currency code.
- **TaxCode:** Tax description code.
- **Amount:** Tax amount.
- **TransactionFee:** Booking transaction fee.
- **TransactionFeeAmount:** Booking transaction fee amount.
- **ServiceTax:** Tax type.

- **ServiceTaxAmount:** Service tax amount.
- **GrossAmount:** Booking Gross amount.

### 7.7 Data Format & Details:

Field Name	Data Type	Description
<b>CustomerDetails</b>	---	Describes the Booked by customer details
<b>Title</b>	String	Indicates" Booked by" customer name title
<b>FirstName</b>	String	First name of the "Booked by" customer
<b>LastName</b>	String	Last name of the "Booked by" customer
<b>Address</b>	String	Address of the "Booked by" customer
<b>City</b>	String	City of the "Booked by" customer
<b>State</b>	String	State of the "Booked by" customer
<b>Country</b>	String	Country of the "Booked by" customer
<b>MailId</b>	String	Email id of the "Booked by" customer
<b>Pincode</b>	Numeric	Pincode of the "Booked by" customer
<b>ContactNo</b>	Numeric	Contact No. of the "Booked by" customer
<b>TerminalContactDetails</b>	String	Describes the Terminals contact details
<b>TerminalName</b>	String	Agent Terminal Name
<b>Address</b>	String	Agent Terminal Address
<b>City</b>	String	Agent terminal city
<b>State</b>	String	Agent terminal state
<b>Country</b>	String	Agent terminal country

<b>Phone</b>	String	Agent terminal contact No.
<b>Email</b>	String	Agent terminal email-id
<b>TotalSegments</b>	Integer	No Of Total flight segments
<b>TotalAmount</b>	Money	Total booked amount
<b>OtherCharges</b>	Money	Other Booking charges
<b>Adults</b>	Integer	No of adults booking
<b>Childs</b>	Integer	No of child booking
<b>Infants</b>	Integer	No of infant booking
<b>TripType</b>	String	Indicates travelling trip type
<b>SegmentType</b>	String	Indicates travelling segment type
<b>IssuedDate</b>	Datetime	Indicates Ticket issuing date
<b>Resultcode</b>	Integer	Indicates booking result code
<b>BookingTrackId</b>	String	Indicates booking track id
<b>RiyaPNR</b>	String	Indicates booking Riya PNR
<b>CRSPNR</b>	String	Indicates booking CRS PNR
<b>BaseOrigin</b>	String	Indicates passenger departure City code
<b>BaseDestination</b>	String	Indicates passenger arrival City code
<b>TourCode</b>	String	Indicates passenger tour code
<b>PaymentDetails</b>	---	Describes the payment details in booking
<b>CurrencyCode</b>	String	Indicates Booking currency code
<b>Amount</b>	Money	Indicates Booking amount
<b>TicketNumber</b>	String	Indicates booking Ticket No.

<b>PaxType</b>	String	Indicates booking passenger type
<b>Title</b>	String	Indicates booking passenger title
<b>FirstName</b>	String	Indicates booking passenger first name
<b>LastName</b>	String	Indicates booking passenger last name
<b>DateOfBirth</b>	Datetime	Indicates booking passenger date of birth
<b>SegmentInformation</b>	---	Describes the details in a booking segment
<b>AirlinePNR</b>	String	Indicates booking passenger Airline PNR
<b>TicketNo</b>	String	Indicates booking passenger Ticket No.
<b>FlightNumber</b>	Integer	Indicates booking passenger Flight No.
<b>Origin</b>	String	Indicates booking flight origin
<b>Destination</b>	String	Indicates booking flight destination
<b>DepartureDateTime</b>	Datetime	Indicates flight departure date and time
<b>ArrivalDateTime</b>	Datetime	Indicates flight arrival date and time
<b>AirCraftType</b>	String	Indicates flight aircraft type
<b>CarrierCode</b>	String	Indicates flight carrier code
<b>ClassCode</b>	String	Indicates flight booking class code
<b>FareBasis</b>	String	Indicates flight booking fare basis code
<b>FrequentFlyerNumber</b>	String	Indicates flight booking frequent flyer No.
<b>SpRequest</b>	String	Indicates passenger special service request.
<b>MealsPreference</b>	String	Indicates passenger meals request

<b>MonetaryDetail</b>		---	Describes the Amount details in a booking
<b>BasicCurrencyCode</b>	String		Indicates booking base currency code
<b>CurrencyCode</b>	String		Indicates booking currency code
<b>BasicAmount</b>	Money		Indicates booking base amount
<b>TaxDetails</b>		---	Indicates booking tax details
<b>CurrencyCode</b>	String		Indicates booking currency code
<b>TaxCode</b>	String		Indicates booking tax code
<b>Amount</b>	Money		Indicates booking tax amount
<b>TransactionFee</b>	Money		Indicates booking transaction fee
<b>TransactionFeeAmount</b>	Money		Indicates booking transaction fee amount
<b>ServiceTax</b>	Money		Indicates booking service tax
<b>ServiceTaxAmount</b>	Money		Indicates booking service tax amount
<b>GrossAmount</b>	Money		Indicates booking service gross amount

## 8. BOOK RESERVATION VERSION-2

### 8.1 XML Request (Sample):

```

<BookReservation_V2>
  <SellReferenceId>RA24F9522C7C56479B8E7A7961FF08B3A720140123202120</SellReferenceId>
  <CustomerDetails>
    <Title>MS</Title>
    <Firstname>TestA</Firstname>
    <Lastname>tsta</Lastname>
    <Address1>Chennai</Address1>
    <City />
    <State />
    <Country />
    <MailId>Test@gmail.com</MailId>
    <PinCode />
    <ContactNo>909090909090</ContactNo>
  </CustomerDetails>
</BookReservation_V2>

```

```
</CustomerDetails>
<NoofAdult>1</NoofAdult>
<NoofChild>1</NoofChild>
<NoofInfant>1</NoofInfant>
<TripType>O</TripType>
<SegmentType>D</SegmentType>
<TotalAmount>13887.00</TotalAmount>
<PaymentMode>AT</PaymentMode> For prepaid account use AT and Postpaid Account CA
<Bookingdetails>
  <!--Repetitions for Roundtrip (Domestic) -->
  <Item>
    <ValidatingCarrier>TR</ValidatingCarrier>
    <Payment>
      <item>
        <CurrencyCode>INR</CurrencyCode>
        <Amount>13887.00</Amount>
      </item>
    </Payment>
    <TourCode />
    <Passengerlist>
      <!--Repetitions for Passengers -->
      <item>
        <PaxType>ADT</PaxType>
        <Title>Mr</Title>
        <FirstName>TestA</FirstName>
        <LastName>tsta</LastName>
        <DateofBirth>19/01/1990</DateofBirth>
        <Gender>M</Gender>
        <Segment>
          <!--Repetitions for Connecting flights -->
          <item>
            <FlightID>4140</FlightID>
            <CarrierId>TR</CarrierId>
            <Origin>MAA</Origin>
            <Destination>SIN</Destination>
            <DepartureDateTime>28/02/2014 07:50</DepartureDateTime>
            <ArrivalDateTime>20/02/2014 13:05</ArrivalDateTime>
            <ClassCode>H</ClassCode>
            <Mealcode>VGSW</Mealcode>
            <MealSSRNumber>1</MealSSRNumber>
            <Baggagecode />
            <BaggageSSRNumber />
            <FrequentFlyerNumber />
          </item>
        </Segment>
      </item>
    </Passengerlist>
  </Item>
</Bookingdetails>
</BookReservation_V2>
```

## 8.2 Method:

**BookReservationVersion2(clsSecurity, InputRequest)**

## 8.3 Description:

- **SellReferenceId:** Indicates the reference id of sell response.
- **CustomerDetails:** Describes the “Booked by” customer details.
- **Title:** Prefix added to the name.
- **FirstName:** First name of the “Booked by” customer.
- **LastName:** Last name of the “Booked by” customer.
- **Address:** Address of the “Booked by” customer.
- **City:** City of the “Booked by” customer.
- **State:** State of the “Booked by” customer.
- **Country:** Country of the “Booked by” customer.
- **MailId:** E-Mail of the “Booked by” customer.
- **Pincode:** Pincode of the “Booked by” customer.
- **ContactNo:** Contact No of the “Booked by” customer.
- **NoofAdult:** No of Adults travelling.
- **NoofChild:** No of Children travelling.
- **NoofInfant:** No of Infants travelling.
- **TripType:** Specifies Trip type, One-way or Roundtrip.
- **SegmentType:** Specifies segment type, Domestic or International.
- **TotalAmount:** Total booking amount.
- **PaymentMode:** Type of booking account Top-up or Credit.

**BookingDetails:** Describes booking details.

- **ValidatingCarrier:** Indicates Ticketing carrier.

**Payment:** Describes payment details.

- **CurrencyCode:** Specifies booking Currency code.
- **Amount:** Specifies booking amount.
- **TourCode:** Indicates tour code.

**PassengerList:** Describes booking passenger list.

- **PaxType:** Indicates booking passenger type.
- **Title:** Indicates booking passenger title.
- **FirstName:** Indicates booking passenger first name.
- **LastName:** Indicates booking passenger last name.
- **DateofBirth:** Indicates booking passenger date of birth.
- **Gender:** Indicates booking passenger gender.

**PassportInfo:** Describes passport details.

- **IdentifyProofId:** Describes passport or proof id.
- **IdentifyProofNumber:** Indicates identify proof No.
- **CountryId:** Indicates issuing country ID.
- **ExpiryDate:** Indicates proof expiry date.

**Segment:** Describes flight segment details.

- **FlightID:** Indicates flight identification.
- **CarrierID:** Indicates flight carrier code.
- **Origin:** Indicates passenger departure city code.



- **Destination:** Indicates passenger arrival city code.
- **DepartureDatetime:** Indicates flight departure date and time.
- **ArrivalDatetime:** Indicates flight arrival date and time.
- **ClassCode:** Indicates type of class chosen.
- **Mealcode:** Indicates Meal code chosen by passenger.
- **MealSSRNumber:** Indicates Meal SSR number which is from Sell response.
- **Baggagecode:** Indicates Baggage code chosen by passenger.
- **BaggageSSRNumber:** Indicates Baggage SSR number.
- **FrequentFlyerNumber:** Indicates Frequent flyer no.
- **SpRequest:** special service request.
- **MealsPreference:** Meals request.
- **MonetaryDetails** – Describes the Amount details in a booking.
- **BasicCurrencyCode:** Booking base currency code.
- **CurrencyCode:** Booking currency code.
- **BasicAmount:** Booking base fare.
- **TaxDetails:** Booking tax break up.
- **CurrencyCode:** Tax currency code.
- **TaxCode:** Tax description code.
- **Amount:** Tax amount.
- **TransactionFee:** Booking transaction fee.
- **TransactionFeeAmount:** Booking transaction fee amount.
- **ServiceTax:** Tax type.

- **ServiceTaxAmount:** Service tax amount.
- **GrossAmount:** Booking Gross amount.

#### 8.4 XML Response (Sample):

```

<Bookingresponse>
<ItinearyDetails>
<CustomerDetails>
<Title>Mr</Title>
<Firstname>Firstname</Firstname>
<Lastname>Lastname</Lastname>
<Address1>Address1</Address1>
<Address2>Address2</Address2>
<Address3>Address3</Address3>
<City>City</City>
<State>State</State>
<Country>Country</Country>
<MailId>mail@mail.com</MailId>
<PinCode>600100</PinCode>
<ContactNo>9888888888</ContactNo>
</CustomerDetails>
<TerminalContactDetails>
<TerminalName>Travel Agent</TerminalName>
<Address1>Address1</Address1>
<Address2 />
<City>City</City>
<State>State</State>
<Country>IN</Country>
<Phone>04444-44444444</Phone>
<Email>mail@gmail.com</Email>
</TerminalContactDetails>
<TotalSegments>1</TotalSegments>
<TotalAmount>3728.00</TotalAmount>
<OtherCharges>0.00</OtherCharges>
<Adults>1</Adults>
<Childs>0</Childs>
<Infants>0</Infants>
<TripType>O</TripType>
<SegmentType>D</SegmentType>
<IssuedDate>19/03/2012 20:45:43</IssuedDate>
<Item>
<Resultcode>1</Resultcode>
<BookingTrackId>RABBI0300001011932012P0002795</BookingTrackId>
<RiyaPNR>19AB478</RiyaPNR>
<CRSPNR>N/A</CRSPNR>
<BaseOrigin>BOM</BaseOrigin>
<BaseDestination>DEL</BaseDestination>
<TourCode />
<PaymentDetails>
</Item>

```

<CurrencyCode>INR</CurrencyCode>  
<Amount>3728.00</Amount>  
</Item>  
</PaymentDetails>  
<TravellerInfo>  
<Item>  
<TicketNumber>19AB4781</TicketNumber>  
<PaxType>ADT</PaxType>  
<Title>Mr</Title>  
<FirstName>Firstname</FirstName>  
<LastName>Lastname</LastName>  
<DateOfBirth>N/A</DateOfBirth>  
<SegmentInformation>  
<Item>  
<AirlinePNR>KYU8AA</AirlinePNR>  
<TicketNo>19AB4781</TicketNo>  
<FlightNumber>184</FlightNumber>  
<Origin>BOM</Origin>  
<Destination>DEL</Destination>  
<DepartureDateTime>12/05/2012 06:20</DepartureDateTime>  
<ArrivalDateTime>12/05/2012 08:25</ArrivalDateTime>  
<AirCraftType>320</AirCraftType>  
<CarrierCode>6E</CarrierCode>  
<ClassCode>V0BOMDEL</ClassCode>  
<FareBasis>V0BOMDEL</FareBasis>  
<FrequentFlyerNumber>N/A</FrequentFlyerNumber>  
<BaggagePreference />  
<MealsPreference>VGSW</MealsPreference>  
</Item>  
<MonetaryDetail>  
<BasicCurrencyCode>INR</BasicCurrencyCode>  
<CurrencyCode>INR</CurrencyCode>  
<BasicAmount>1101.00</BasicAmount>  
<TaxDetails>  
<item>  
<CurrencyCode />  
<TaxCode>YQ</TaxCode>  
<Amount>2000.00</Amount>  
</item>  
<item>  
<CurrencyCode />  
<TaxCode>IN</TaxCode>  
<Amount>50.00</Amount>  
</item>  
<item>  
<CurrencyCode />  
<TaxCode>JN</TaxCode>  
<Amount>155.00</Amount>  
</item>  
<item>  
<CurrencyCode />  
<TaxCode>WO</TaxCode>

```

<Amount>229.00</Amount>
</item>
</TaxDetails>
<TransactionFee>TransactionFee</TransactionFee>
<TransactionFeeAmount>186.00</TransactionFeeAmount>
<ServiceTax>ServiceTax</ServiceTax>
<ServiceTaxAmount>7.00</ServiceTaxAmount>
<GrossAmount>3728.00</GrossAmount>
</MonetaryDetail>
</SegmentInformation>
</Item>
</TravellerInfo>
</Item>
</ItineraryDetails>
</Bookingresponse>

```

#### 8.5.1 In case of Error:

```

<ResultCode>
  <Status></Status>
  <Error>
    <Description></Description>
  </Error>
</ResultCode>
</Bookingresponse>

```

#### 8.5.2 In case of Exception:

```

<Exception>
<Description></Description>
</Exception>
</Bookingresponse>

```

## 9. CANCELLATION

### 9.1 XML Request (Sample):

```

<cancellation>
  <RiyaPNR>16AA042</RiyaPNR>
  <AirlinePNR>ABCDEF</AirlinePNR>
</cancellation>

```

### 9.2 Method:

Cancellation (clsSecurity, InputRequest)

### 9.3 Description:

- **RiyaPNR:** Describes the Specific identification code that is given to identify.
- **AirlinePNR:** Specific airline PNR.

### 9.4 Data Format & Details:

Field Name	Data Type	Description
RiyaPNR	String	It is the Specific identification code
AirlinePNR	String	Specific airline PNR.

### 9.5 XML Response (Sample):

```
<CancellationResponse>
  <Status>1</Status>
  <RiyaPNR>16AA042</RiyaPNR>
  <AilinePNR>X8PRBD</AilinePNR>
  <CRSPNR>N/A</CRSPNR>
  <PassengerDetails>
    <item>
      <PaxNo>1</PaxNo>
      <First_Name>TEST</First_Name>
      <Last_Name>TEST</Last_Name>
      <PassengerType>ADT</PassengerType>
      <TicketNo>16AA042-1</TicketNo>
      <Segmentid>1</Segmentid>
      <FlightNumber>SG 851</FlightNumber>
      <Origin>BOM</Origin>
      <Departuredatetime>24/02/2012 0550</Departuredatetime>
      <Destination>DEL</Destination>
      <Arrivaldatetime>24/02/2012 0750</Arrivaldatetime>
      <ClassCodeDesc>F</ClassCodeDesc>
      <Basic_Fare>1101</Basic_Fare>
      <TotalTax>2634</TotalTax>
      <GrossAmt>3735</GrossAmt>
      <CancelStatus>LIVE</CancelStatus>
    </item>
  </PassengerDetails>
</CancellationResponse>
```

## 10. CANCELSUBMIT

### 10.1 XML Request (Sample):

```
<CancelSubmit>
  <RiyaPNR>17AA042</RiyaPNR>
  <AirlinePNR>X8PRBD</AirlinePNR>
  <CRSPNR />
  <PassengerDetails>
    <item>
      <PaxNo>1</PaxNo>
      <TicketDetails>
        <item>
          <TicketNo>17AA042-1</TicketNo>
          <SegmentId>1</SegmentId>
          <FlightNo>SG 851</FlightNo>
          <Origin>BOM</Origin>
          <Destination>DEL</Destination>
        </item>
      </TicketDetails>
    </item>
  </PassengerDetails>
</CancelSubmit>
```

### 10.2 Method:

**CancelSubmit (clsSecurity, InputRequest)**

### 10.3 Description:

- **RiyaPNR:** Describes the Specific identification code that is given to identify.
- **AirlinePNR:** Specific airline PNR.
- **PassengerDetails:** Describes the list of passenger in the PNR
- **PaxNo:** Describes the Passenger No.
- **TicketNo:** Specifies the passenger Ticket No.
- **SegmentId:** Describes the travelling segment.
- **FlightNo:** Describes the travelling Flight No.
- **Origin:** Indicates passenger Departure Airport Code

- **Destination:** Indicates passenger Arrival Airport Code

#### 10.4 Data Format & Details:

Field Name	Data Type	Description
<b>RiyaPNR</b>	String	It is the Specific identification code
<b>AirlinePNR</b>	String	Specific airline PNR.
<b>PassengerDetails</b>	---	Describes the list of passenger in the PNR
<b>PaxNo</b>	String	Passenger No.
<b>TicketNo</b>	String	Specifies the passenger Ticket No.
<b>SegmentId</b>	String	Describes the Travelling Segment
<b>FlightNo</b>	String	Describes the Travelling Flight No.
<b>Origin</b>	String	Indicates passenger Departure Airport Code
<b>Destination</b>	String	Indicates passenger Arrival Airport Code

#### 10.5 XML Response (Sample):

```

<CancelSubmitResponse>
  <Status>1</Status>
  <Remarks>
    Your cancellation request is queued on our server. The
    request will be processed with in 8 hours of time.Your cancellation
    reference No. is 201201A007
  </Remarks>
</CancelSubmitResponse>

```

## 11. REPRINT – PNR RETRIEVE

### 11.1 XML Request (Sample):

```
<ReprintRequest>  
  <RiyaPNR>17AA042</RiyaPNR>  
</ReprintRequest>
```

### 11.2 Method:

**TicketReprint (clsSecurity, InputRequest)**

### 11.3 Description:

- **RiyaPnr:** Indicates RiyaPNR to retrieve passenger details

### 11.4 Data Format & Details:

Field Name	Data Type	Description
RiyaPNR	String	It is the Specific identification code

### 11.5 Data Format & Details:

Same as booking response

## 12. AGENT TRANSACTION

### 12.1 XML Request (Sample):

```
<AccountViewDetails>  
  <FromDate>03/09/2012</FromDate>  
  <ToDate>03/09/2012</ToDate>  
</AccountViewDetails>
```



## 12.2 Method:

**AgentTransaction (clsSecurity, InputRequest)**

## 12.3 Description:

- **FromDate:** Transaction from date.
- **ToDate:** Transaction end date.

## 12.4 Data Format & Description:

Field Name	Data Type	Description
<b>FromDate</b>	Date(MM/DD/YYYY)	Specifies from date
<b>ToDate</b>	Date(MM/DD/YYYY)	Specifies To date.

## 12.5 XML Response (Sample):

```
<AccountViewDetailsResponse>
<TravelAgentID>RSBOM0300001</TravelAgentID>
<TravelAgentname>AgencyName</TravelAgentname>
<Totalremainingamount>95842.67</Totalremainingamount>
<AmountDetails>
  <item>
    <DateTime>3/9/2012 62900 PM</DateTime>
    <Description>Airline Sales</Description>
    <TransactionId>09BC653</TransactionId>
    <Creditamount />
    <Debitamount>7990.00</Debitamount>
    <Remaining>117775.67</Remaining>
    <Remarks>APIBooking</Remarks>
    <TerminalName>RAAMD030000101</TerminalName>
    <ProductDesc>AIR</ProductDesc>
  </item>
  <item>
    <DateTime>3/9/2012 62900 PM</DateTime>
    <Description>AirlineCommission</Description>
    <TransactionId>09BC653</TransactionId>
    <Creditamount>325.00</Creditamount>
    <Debitamount />
  </item>
</AmountDetails>
</AccountViewDetailsResponse>
```

```

    <Remaining>118100.67</Remaining>
    <Remarks>APIBooking</Remarks>
    <TerminalName>RAAMD030000101</TerminalName>
    <ProductDesc>AIR</ProductDesc>
  </item>
  <item>
    <DateTime>3/9/2012 62900 PM</DateTime>
    <Description>TDSOnCommission</Description>
    <TransactionId>09BC653</TransactionId>
    <Creditamount />
    <Debitamount>32.00</Debitamount>
    <Remaining>118068.67</Remaining>
    <Remarks>APIBooking</Remarks>
    <TerminalName>RSBOM030000101</TerminalName>
    <ProductDesc>AIR</ProductDesc>
  </item>
</AmountDetails>
</AccountViewDetailsResponse>

```

## 12.6 Description:

- **TravelAgentId:** Indicates Agent Identification code.
- **TravelAgentName:** Indicates the Agent Name.
- **TotalRemainingAmount:** Indicates total balance amount in agent account.
- **AmountDetails:** Indicates agent transaction details.
- **Datetime:** Indicates Transaction date and time.
- **Description:** Indicates the details in the Transaction.
- **TransactionId:** Indicates id for each transaction.
- **CreditAmount:** Indicates the Credit amount in agent account
- **DebitAmount:** Indicates the Debitamount in agent account
- **Remaining:** Indicates balance amount after transaction.
- **Remarks:** Indicates remarks for the transaction.
- **TerminalName:** Indicates terminal name.

- **ProductDesc:** Indicates product type

## 12.7 Data Format & Details:

Field Name	Data Type	Description
<b>TravelAgentId</b>	String	Indicates the agent identification code
<b>TravelAgentName</b>	String	Indicates the agent name
<b>TotalRemainingAmount</b>	Money	Indicates total balance amount in agent account
<b>AmountDetails</b>	---	Indicates agent transaction details
<b>Datetime</b>	Date	Indicates transaction date and time
<b>Description</b>	String	Indicates the details in the Transaction
<b>TransactionId</b>	String	Indicates id for each transaction
<b>CreditAmount</b>	Money	Indicates the Credit amount in agent account
<b>DebitAmount</b>	Money	Indicates the Debit amount in Agents account
<b>Remaining</b>	Money	Indicates balance amount after transaction
<b>Remarks</b>	String	Indicates remarks for the transaction
<b>TerminalName</b>	String	Indicates Terminal name
<b>Productdesc</b>	String	Indicates the product type

## 13. FARERULE

### 13.1 XML Request (Sample):

```
<FareRuleRequest>
  <Item>
    <TrackId>RABBI0300001011932012P0002793</TrackId>
    <FlightId>1963</FlightId>
    <AirlineId>AI</AirlineId>
    <ClassCode>L</ClassCode>
  </Item>
</FareRuleRequest>
```

### 13.2 Method:

**FareRuleDescription (clsSecurity, InputRequest)**

### 13.3 Data Format & Details:

Field Name	Data Type	Description
TrackId	String	Indicates the reference id of search availability
FlightId	String	Indicates flight Identification of search availability
AirlineId	String	Indicates Flight Carrier code
ClassCode	String	Indicates class code for specific flight

### 13.4 XML Response (Sample):

```
<FareRuleResponse>
  <Status>1</Status>
  <FareRules>RU.RULE APPLICATION : APEX FARES ON DOMESTIC SECTORS
  APPLICATION
  AREA
    THESE FARES APPLY
    WITHIN INDIA.
  CLASS OF SERVICE
    THESE FARES APPLY FOR ECONOMY CLASS SERVICE.
  TYPES OF TRANSPORTATION
```

THIS RULE GOVERNS ONE-WAY FARES.  
FARES GOVERNED BY THIS RULE CAN BE USED TO CREATE  
ONE-WAY/ROUND-TRIP/CIRCLE-TRIP JOURNEYS.  
ON SPECIFIED DOMESTIC SECTORS.

MX.MAX STAY : NONE UNLESS OTHERWISE SPECIFIED

SR.SALES RESTRICT : FOR EAP14 TYPE FARES

TICKETS MUST BE ISSUED ON AI AND MAY ONLY BE SOLD IN  
INDIA/NEPAL

AP.ADVANCE RES/TKT : FOR EAP14 FARES

RESERVATIONS ARE REQUIRED FOR ALL SECTORS.  
WAITLIST NOT PERMITTED.  
TICKETING MUST BE COMPLETED AT LEAST 14 DAYS BEFORE  
DEPARTURE.

NOTE -

AP14 FARE TICKETING AND BOOKING TRANSACTIONS  
WILL BE COMPLETED SIMULTANEOUSLY AND ONLY  
CONFIRMED TICKETS TO BE ISSUED.

----

ISSUANCE OF OPEN SEATED/WAITLIST TICKET AND  
BOOKING ON TIME LIMIT IS NOT PERMITTED.

FL.FLT APPLICATION :  
THE FARE COMPONENT MUST BE ON  
ONE OR MORE OF THE FOLLOWING  
ANY AI FLIGHT.

CD.CHILD DISCOUNTS : FOR EAP14 FARES

ACCOMPANIED CHILD 2-11 - CHARGE 100 PERCENT OF THE FARE  
OR - 1ST INFANT UNDER 2 WITHOUT A SEAT - CHARGE INR 300.  
RESULTING FARE IS A ONE-WAY.

TICKETING CODE - BASE FARE CODE PLUS IN.

NOTE -

FIRST INFANT WITHOUT A SEAT CHARGE INR 300 PER  
COUPON.

SO.STOPOVERS :  
NO STOPOVERS PERMITTED.

TF.TRANSFERS/RTGS :  
NO TRANSFERS PERMITTED  
FARE BREAK AND EMBEDDED SURFACE SECTORS PERMITTED ON THE  
FARE COMPONENT.

TE.TKT ENDORSEMENT :  
THE ORIGINAL AND THE REISSUED TICKET MUST BE ANNOTATED -  
NON END/ NON REF - AND - VLD ON AI - IN THE ENDORSEMENT  
BOX.

PE.PENALTIES :

CANCELLATIONS

TICKET IS NON-REFUNDABLE.

NOTE -

IN CASE IF A NON-REFUNDABLE TICKET IS UPGRADED TO A REFUNDABLE FARE THE NEW TICKET WILL CONTINUE TO BE NON-REFUNDABLE AND THE SAME NEEDS TO BE ENDORSED ON THE TICKET.

CHANGES

BEFORE DEPARTURE

PER COUPON CHARGE INR 750 FOR REISSUE/REVALIDATION.

NOTE -

PERMITTED UP TO 1 HR BEFORE SCHEDULED DEPARTURE OF THE FLIGHT AGAINST A CHANGE FEE OF RS 750 PER COUPON.

-----

ABOVE CHANGE/ REFUND FEES OR BASIC FARE WHICHEVER IS LOWER WOULD APPLY.

-----

NO RE-VALIDATION OR CANCELLATION FEE WOULD BE APPLICABLE ON INFANT TICKETS.

-----

IN CASE OF CHANGE TO HIGHER RBD FOR TRAVEL ON THE SAME DAY/SAME FLIGHT/RE-ISSUANCE FEE WILL NOT BE APPLICABLE. ONLY DIFFERENCE IN TOTAL FARE IS TO BE COLLECTED.

AFTER DEPARTURE

PER COUPON CHARGE INR 1500 FOR NO-SHOW/REISSUE/REVALIDATION.

NOTE -

REVALIDATION OF NO-SHOW TICKET PERMITTED AGAINST A CHARGE FEE OF RS 1500 PER COUPON.

-----

ABOVE CHANGE/ REFUND FEES OR BASIC FARE WHICHEVER IS LOWER WOULD APPLY.

-----

NO RE-VALIDATION OR CANCELLATION FEE WOULD BE APPLICABLE ON INFANT TICKETS.

-----

ANY TICKET PRESENTED FOR CANCELLATION/REFUND WITHIN ONE HOUR OF SCHEDULED DEPARTURE OF THE FLIGHT WOULD BE TREATED AS NO-SHOW.

-----

IN CASE OF CHANGE TO HIGHER RBD FOR TRAVEL ON THE SAME DAY/SAME FLIGHT/RE-ISSUANCE FEE WILL NOT BE APPLICABLE. ONLY DIFFERENCE IN TOTAL FARE IS TO BE COLLECTED.

-----

CO.COMBINABILITY : DOUBLE OPEN JAWS NOT PERMITTED.

ADD-ON CONSTRUCTION IS ADDRESSED IN MISCELLANEOUS PROVISIONS - CATEGORY 23.

END-ON-END  
 END-ON-END COMBINATIONS PERMITTED WITH AI DOMESTIC  
 FARES. VALIDATE ALL FARE COMPONENTS. SIDE TRIPS  
 PERMITTED WITH NO RESTRICTIONS.  
 OPEN JAWS/ROUND TRIPS/CIRCLE TRIPS  
 FARES MAY BE COMBINED ON A HALF ROUND TRIP BASIS WITH AI  
 FARES  
 -TO FORM SINGLE OPEN JAWS  
 -TO FORM ROUND TRIPS  
 -TO FORM CIRCLE TRIPS  
 PROVIDED -  
 COMBINATIONS ARE WITH ANY FARE FOR CARRIER AI IN RULE  
 AI04/AI2H/AI42/0221/0223/4701 IN TARIFF  
 IPRTPF - WITHIN AREA 3-DOMESTIC.

MD.MISCELLANEOUS DATA :  
 THIS FARE MUST NOT BE USED AS THE HIGH OR THE LOW FARE  
 WHEN CALCULATING A DIFFERENTIAL. THIS FARE MAY BE USED AS  
 THE THROUGH FARE WHEN PRICING A FARE COMPONENT WITH OR  
 WITHOUT A DIFFERENTIAL.

</FareRules>  
 </FareRuleResponse>

## 14. BLOCK PNR

### 14.1 XML Request (Sample):

```
<BlockPnr>
<SellReferenceId>RASLV0300001022182012P0008004</SellReferenceId>
<CustomerDetails>
<Title>Mr</Title>
<Firstname>testing</Firstname>
<Lastname>testing</Lastname>
<Address1>Address</Address1>
<Address2>Address</Address2>
<Address3 />
<City>City</City>
<State>State</State>
<Country>Country</Country>
<MailId>test@test.com</MailId>
<PinCode>PinCode</PinCode>
<ContactNo>MobileNO</ContactNo>
</CustomerDetails>
<NoofAdults>1</NoofAdults>
<NoofChild>0</NoofChild>
<NoofInfants>0</NoofInfants>
<TripType>O</TripType>
<SegmentType>I</SegmentType>
<TotalAmount>27821.00</TotalAmount>
```

```
<PaymentMode>AT</PaymentMode>
<Bookingdetails>
<Item>
<ValidatingCarrier>EK</ValidatingCarrier>
<Payment>
<item>
<CurrencyCode>INR</CurrencyCode>
<Amount>27821.00</Amount>
</item>
</Payment>
<TourCode />
<Passengerlist>
<item>
<PaxType>ADT</PaxType>
<Title>Mr</Title>
<FirstName>FirstName</FirstName>
<LastName>LastName</LastName>
<DateofBirth>14/04/1983</DateofBirth>
<Gender>M</Gender>
<SpecialReqcode />
<Mealcode />
<PassportInfo>
<IdentityProofId>Passport</IdentityProofId>
<IdentityProofNumber>ProofNumber</IdentityProofNumber>
<CountryId>IND</CountryId>
<ExpiryDate>12/12/2021</ExpiryDate>
</PassportInfo>
<Segment>
<!--More repetitions for connecting flights-->
<item>
<FlightID>1342</FlightID>
<CarrierId>EK</CarrierId>
<Origin>BOM</Origin>
<Destination>DXB</Destination>
<DepartureDateTime>26/08/2012 15:15</DepartureDateTime>
<ArrivalDateTime>26/08/2012 16:45</ArrivalDateTime>
<ClassCode>R</ClassCode>
<FrequentFlyerNumber />
</item>
</Segment>
</item>
</Passengerlist>
</Item>
</Bookingdetails>
</BlockPnr>
```



## 14.2 XML Response (Sample):

```
<BlockPnrResponse>
  <ItineraryDetails>
    <CustomerDetails>
      <Title>Mr</Title>
      <Firstname>testing</Firstname>
      <Lastname>testing</Lastname>
      <Address1>Address</Address1>
      <Address2>Address</Address2>
      <Address3 />
      <City>City</City>
      <State>State</State>
      <Country>Country</Country>
      <MailId>test@test.com</MailId>
      <PinCode>PinCode</PinCode>
      <ContactNo>9988998899</ContactNo>
    </CustomerDetails>
    <TerminalContactDetails>
      <TerminalName>TerminalName</TerminalName>
      <Address1>Address</Address1>
      <Address2 />
      <City>SLV</City>
      <State>HP</State>
      <Country>IN</Country>
      <Phone>Phone</Phone>
      <Email>test@test.com</Email>
    </TerminalContactDetails>
    <TotalSegments>1</TotalSegments>
    <TotalAmount>27821.00</TotalAmount>
    <OtherCharges>0.00</OtherCharges>
    <Adults>1</Adults>
    <Childs>0</Childs>
    <Infants>0</Infants>
    <TripType>O</TripType>
    <SegmentType>I</SegmentType>
    <IssuedDate>21/08/2012 12:16:24</IssuedDate>
    <Item>
      <Resultcode>1</Resultcode>
      <BookingTrackId>RASLV0300001022182012P0008005</BookingTrackId>
      <RiyaPNR>21AF697</RiyaPNR>
      <CRSPNR>5UYGJT</CRSPNR>
      <BaseOrigin>BOM</BaseOrigin>
      <BaseDestination>DXB</BaseDestination>
      <TourCode />
      <PaymentDetails>
        <Item>
          <CurrencyCode>INR</CurrencyCode>
          <Amount>27821.00</Amount>
        </Item>
      </PaymentDetails>
      <TravellerInfo>
    </Item>
```

<TicketNumber />  
<PaxType>ADT</PaxType>  
<Title>MR</Title>  
<FirstName>FirstName</FirstName>  
<LastName>LastName</LastName>  
<DateOfBirth>14/04/1983</DateOfBirth>  
<SegmentInformation>  
<Item>  
<AirlinePNR>FYLGH6</AirlinePNR>  
<FlightNumber>507</FlightNumber>  
<Origin>BOM</Origin>  
<Destination>DXB</Destination>  
<DepartureDateTime>26/08/2012 15:15</DepartureDateTime>  
<ArrivalDateTime>26/08/2012 16:45</ArrivalDateTime>  
<AirCraftType>332</AirCraftType>  
<CarrierCode>EK</CarrierCode>  
<ClassCode>E</ClassCode>  
<FareBasis>ESOWIN1</FareBasis>  
<FrequentFlyerNumber />  
<SpRequest />  
<MealsPreference />  
</Item>  
<MonetaryDetail>  
<BasicCurrencyCode>INR</BasicCurrencyCode>  
<CurrencyCode>INR</CurrencyCode>  
<BasicAmount>25345.00</BasicAmount>  
<TaxDetails>  
<item>  
<CurrencyCode />  
<TaxCode>YQ</TaxCode>  
<Amount>0.00</Amount>  
</item>  
<item>  
<CurrencyCode />  
<TaxCode>Other Taxes</TaxCode>  
<Amount>2476.00</Amount>  
</item>  
</TaxDetails>  
<TransactionFee>TransactionFee</TransactionFee>  
<TransactionFeeAmount>0.00</TransactionFeeAmount>  
<ServiceTax>ServiceTax</ServiceTax>  
<ServiceTaxAmount>0.00</ServiceTaxAmount>  
<GrossAmount>27821.00</GrossAmount>  
</MonetaryDetail>  
</SegmentInformation>  
</Item>  
</TravellerInfo>  
</Item>  
</ItineraryDetails>  
</BlockPnrResponse>

### 14.3 Method:

**BlockReservation (clsSecurity, InputRequest)**

## 15. TICKETING

### 15.1 XML Request (Sample):

```
<Ticketing>
  <BookingTrackId>RASLV0300001022182012P0008005</BookingTrackId>
  <Blockdetails>
    <Item>
      <ReservationInfo>
        <RiyaPnr>21AF697</RiyaPnr>
        <CRSPNR>5UYGJT</CRSPNR>
        <ValidatingCarrier>EK</ValidatingCarrier>
      </ReservationInfo>
    </Item>
  </Blockdetails>
</Ticketing>
```

### 15.2 XML Response (Sample):

```
<TicketingResponse>
  <ItinearyDetails>
    <CustomerDetails>
      <Title />
      <Firstname>testing</Firstname>
      <Lastname>testing</Lastname>
      <Address1>Address</Address1>
      <Address2 />
      <Address3 />
      <City />
      <State />
      <Country>IN</Country>
      <MailId>test@test.com</MailId>
      <PinCode />
      <ContactNo>ContactNo</ContactNo>
    </CustomerDetails>
    <TerminalContactDetails>
      <TerminalName>TerminalName</TerminalName>
      <Address1>Address</Address1>
      <Address2 />
      <City>SLV</City>
      <State>HP</State>
      <Country>IN</Country>
      <Phone>Phone</Phone>
```

<Email>test@test.com</Email>  
</TerminalContactDetails>  
<TotalSegments>1</TotalSegments>  
<TotalAmount>27821.00</TotalAmount>  
<OtherCharges>0.00</OtherCharges>  
<Adults>1</Adults>  
<Childs>0</Childs>  
<Infants>0</Infants>  
<TripType>O</TripType>  
<SegmentType>I</SegmentType>  
<IssuedDate>21/08/2012 12:17</IssuedDate>  
<Item>  
<Resultcode>1</Resultcode>  
<BookingTrackId>RASLV0300001022182012P0008005</BookingTrackId>  
<RiyaPNR>21AF697</RiyaPNR>  
<CRSPNR>5UYGJT</CRSPNR>  
<BaseOrigin>BOM</BaseOrigin>  
<BaseDestination>DXB</BaseDestination>  
<TourCode />  
<PaymentDetails>  
<Item>  
<CurrencyCode>INR</CurrencyCode>  
<Amount>27821.00</Amount>  
</Item>  
</PaymentDetails>  
<TravellerInfo>  
<Item>  
<TicketNumber>1769553193630</TicketNumber>  
<PaxType>ADT</PaxType>  
<Title>MR</Title>  
<FirstName>FirstName</FirstName>  
<LastName>LastName</LastName>  
<DateOfBirth />  
<SegmentInformation>  
<Item>  
<AirlinePNR>FYLGH6</AirlinePNR>  
<TicketNo>1769553193630</TicketNo>  
<FlightNumber>507</FlightNumber>  
<Origin>BOM</Origin>  
<Destination>DXB</Destination>  
<DepartureDateTime>26/08/2012 15:15</DepartureDateTime>  
<ArrivalDateTime>26/08/2012 16:45</ArrivalDateTime>  
<AirCraftType />  
<CarrierCode>EK</CarrierCode>  
<ClassCode>E</ClassCode>  
<FareBasis>ESOWIN1Y</FareBasis>  
<FrequentFlyerNumber />  
<SpRequest />  
<MealsPreference />  
</Item>  
<MonetaryDetail>  
<BasicCurrencyCode>INR</BasicCurrencyCode>

```

<CurrencyCode>INR</CurrencyCode>
<BasicAmount>25345.00</BasicAmount>
<TaxDetails>
<item>
<CurrencyCode />
<TaxCode>YQ</TaxCode>
<Amount>0.00</Amount>
</item>
<item>
<CurrencyCode />
<TaxCode>Other Taxes</TaxCode>
<Amount>2476.00</Amount>
</item>
</TaxDetails>
<TransactionFee>TransactionFee</TransactionFee>
<TransactionFeeAmount>0.00</TransactionFeeAmount>
<ServiceTax>ServiceTax</ServiceTax>
<ServiceTaxAmount>0.00</ServiceTaxAmount>
<GrossAmount>27821.00</GrossAmount>
</MonetaryDetail>
</SegmentInformation>
</Item>
</TravellerInfo>
</Item>
</ItineraryDetails>
</TicketingResponse>

```

### 15.3 Method:

**BlockTicketing (clsSecurity, InputRequest)**

## 16. AGENT ACCOUNT BALANCE

### 16.1 XML Request (Sample):

```

<AccountBalance>
<Item>
<TerminalId>RABOM030000101</TerminalId>
<PaymentMode>AT</PaymentMode>
</Item>
</AccountBalance>

```

## 16.2 Method:

**CheckAccountBalance (clsSecurity, InputRequest)**

## 16.3 Description:

- **TerminalId**: Indicates your WebTerminal ID
- **PaymentMode** :Type of booking account Topup or credit

## 16.4 Data Format & Description:

Field Name	Data Type	Description
<b>TerminalId</b>	String	It is your webTerminal code
<b>PaymentMode</b>	String	It specifies Type of payment mode(AT or CA)

## 16.5 XML Response (Sample):

```
<AccountBalanceResponse>  
  <Item>  
    <PaymentMode>AT</PaymentMode>  
    <Amount>150000.00</Amount>  
  </Item>  
</AccountBalanceResponse>
```

## 17. TRACK DETAILS

### 17.1 XML Request (Sample):

```
<TrackStatusRequest>
<!--Repetitions for Round trip -->
<item>
<BookingTrackID>RASXV0300001012012014T0002527</BookingTrackID>
</item>
</TrackStatusRequest>
```

### 17.2 Method:

TrackDetails (clsSecurity, InputRequest)

### 17.3 Description:

- **BookingTrackID** : Indicates Booking trackId which is from Booking response.

### 17.4 XML Response (Sample):

```
<TrackResponse>
<ItineraryDetails>
  <CustomerDetails>
    <Title />
    <Firstname />
    <Lastname />
    <Address />
    <Address2 />
    <Address3 />
    <City />
    <State />
    <Country />
    <MailId />
    <PinCode />
    <ContactNo />
```

```
</CustomerDetails>
<TerminalContactDetails>
  <TerminalName />
  <Address1 />
  <Address2 />
  <City />
  <State />
  <Country />
  <Phone />
  <Email />
</TerminalContactDetails>
<TotalSegments>2</TotalSegments>
<TotalAmount>12003.00</TotalAmount>
<OtherCharges />
<Adults>1</Adults>
<Childs>0</Childs>
<Infants>0</Infants>
<TripType>R</TripType>
<SegmentType>D</SegmentType>
<IssuedDate />
<Item>
  <Resultcode>1</Resultcode>
  <BookingTrackId>RASXV0300001012012014T0002527</BookingTrackId>
  <RiyaPNR>553AB20</RiyaPNR>
  <CRSPNR>N/A</CRSPNR>
  <BaseOrigin>MAA</BaseOrigin>
  <BaseDestination>BOM</BaseDestination>
  <TourCode />
  <PaymentDetails>
    <Item>
      <CurrencyCode>INR</CurrencyCode>
      <Amount>5340.00</Amount>
    </Item>
  </PaymentDetails>
</TravellerInfo>
  <Item>
    <TicketNumber>553AB20-1</TicketNumber>
    <PaxType>ADT</PaxType>
    <Title>Mr</Title>
    <FirstName>TestA</FirstName>
    <LastName>tsta</LastName>
    <DateOfBirth>18/01/1989</DateOfBirth>
    <SegmentInformation>
      <Item>
        <AirlinePNR>T9TWUD</AirlinePNR>
        <TicketNo>553AB20-1</TicketNo>
        <FlightNumber>273</FlightNumber>
        <Origin>MAA</Origin>
        <Destination>BOM</Destination>
      </Item>
    </SegmentInformation>
  </Item>
</TravellerInfo>
```



```
<DepartureDateTime>02/04/2014 08:30</DepartureDateTime>
<ArrivalDateTime>02/04/2014 10:35</ArrivalDateTime>
<AirCraftType />
<CarrierCode>SG</CarrierCode>
<ClassCode>H</ClassCode>
<FareBasis>H</FareBasis>
<FrequentFlyerNumber />
<BaggagePreference />
<MealsPreference />
</Item>
<MonetaryDetail>
  <BasicCurrencyCode>INR</BasicCurrencyCode>
  <CurrencyCode>INR</CurrencyCode>
  <BasicAmount>1820.00</BasicAmount>
  <TaxDetails>
    <item>
      <CurrencyCode />
      <TaxCode>YQ</TaxCode>
      <Amount>2950.00</Amount>
    </item>
    <item>
      <CurrencyCode />
      <TaxCode>PSF</TaxCode>
      <Amount>147.00</Amount>
    </item>
    <item>
      <CurrencyCode />
      <TaxCode>UDF</TaxCode>
      <Amount>187.00</Amount>
    </item>
    <item>
      <CurrencyCode />
      <TaxCode>JN</TaxCode>
      <Amount>236.00</Amount>
    </item>
    <item>
      <CurrencyCode />
      <TaxCode>SC</TaxCode>
      <Amount>0.00</Amount>
    </item>
  </TaxDetails>
  <TransactionFee />
  <TransactionFeeAmount />
  <ServiceTax />
  <ServiceTaxAmount />
  <GrossAmount>5340.00</GrossAmount>
</MonetaryDetail>
</SegmentInformation>
</Item>
```

```
</TravellerInfo>  
</Item>  
</ItineraryDetails>  
</TrackResponse>
```

## **18. WORK FLOW**

### **18.1 Exsisting Flow :( with out SSR )**

- **Availability**
- **Sell**
- **BookReservation**

### **18.2 New Flow :( with SSR )**

- **Availability**
- **SellVersion2**
- **BookReservationVersion2**

## 19. SUPPORT

The customers are expected to first send an email with their observation and query. On receiving the e-mail, the Riya technical team will analyze and reply within 24 Hours. The customer can escalate the matter on any on-going issues as per the below given escalation hierarchy. On all such cases a first level e-mail can be sent with the request and response XML, and in detail describing the issue faced with their relevant contact, so that Riya Technical team will be in touch at the earliest possible time.

