

VoteKit: A Python package for computational social choice research

Christopher Donnay¹, Moon Duchin¹, Jack Gibson², Zach Glaser², Andrew Hong³, Malavika Mukundan⁴, and Jennifer Wang⁵

¹ Cornell University ² MGGG Redistricting Lab ³ Stanford University ⁴ Boston University ⁵ Brown University

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Open Journals](#) ↗

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

The scholarly study of elections, known as *social choice theory*, centers on the provable properties of voting rules. Practical work in democracy reform focuses on designing or selecting systems of election to produce electoral outcomes that promote legitimacy and broad-based representation. For instance, the dominant electoral system in the United States is a one-person-one-vote/winner-take-all system, sometimes known as PSMD (plurality in single member districts); today, there is considerable reform momentum in favor of ranked choice voting because it is thought to mitigate the effects of vote-splitting and to strengthen prospects for minority representation, among other claimed properties.¹ Across the world, systems of election—and prospects for system change—vary substantially. From both a scholarly and a practical perspective, many questions arise about comparing the properties and tendencies of diverse systems of election in a rigorous manner.

VoteKit ([MGGG Redistricting Lab, 2023b](#)) is a Python package designed to facilitate just that kind of analysis, bringing together multiple types of functionality. Users can:

1. Create synthetic *preference profiles* (collections of ballots) with a choice of generative models and behavioral parameters;
2. Read in real-world *cast vote records* (CVRs) as observed examples of preference profiles; clean and process ballots, including by deduplication and handling of undervotes and overvotes;
3. Run a variety of *voting rules* to ingest preference profiles and output winner sets and rankings; and
4. Produce a wide range of *summary statistics* and *data visualizations* to compare and analyze profiles and election outcomes.

A tutorial that includes step-by-step example code can be found in the VoteKit documentation ([MGGG Redistricting Lab, 2024b](#)).

Statement of need

Since the 1990s, a fusion of economics and computer science has emerged under the name of *computational social choice*, studying questions of complexity and design and further advancing the axiomatic study of elections. But most of these innovations have been highly abstract, and there has been a significant gap in the literature—and in the landscape of software—between

¹Recent ranked-choice voting reforms include the adoption of instant runoff voting (IRV) in Maine, Alaska, New York City, and single transferable vote (STV) in Portland, Oregon. Advocacy groups claiming various pro-democratic properties of ranked choice include [Campaign Legal Center](#), [FairVote](#), and many others.

the theory and the practice of democracy. On the software side, researchers have built a multitude of different packages for generating and analyzing elections.² Most packages, to our knowledge, handle just one part of the research arc; for instance, PrefSampling (Boehmer et al., 2024) generates profiles but does not conduct elections, while VoteLib (Jan Šimbera, 2020) only conducts elections. Others, like PrefLibTools (Nicholas Mattei and Simon Rey, 2022) and PrefVoting (Eric Pacuit and Wesley H. Holliday, 2022), provide support for generating profiles and conducting single-winner elections. Packages with multi-winner capability, like abcvoting (Lackner et al., 2023) or Apportionment (Martin Lackner, 2022), do not support ranked voting. Note that single transferable voting (STV), a voting system actually used for political election in six countries, is curiously absent. VoteKit is built to provide an end-to-end pipeline that supports ranked, scored, and approval profiles as well as single- and multi-winner elections, with an emphasis on practical applicability.

Area of need: Generative models

For one concrete example of a literature and software gap, consider the construction of *generative models*. This term is often associated with large language models as paradigms of artificial intelligence; here, what is being generated is realistic voting rather than realistic language. In this setting, a generative model of voting is a probability distribution on the set of all possible ballots that can be cast in a given election style; profiles can be sampled from a generative model to produce simulated or synthetic elections. Having sources of rich, varied, and realistic data is essential to an empirically grounded research program to probe the properties of voting rules. Good generative models are also a fundamental tool to advise reformers deciding between alternative electoral systems in a new locality, as they enable generation of synthetic profiles keyed to the scale, demographics, and election styles considered for that specific place.

VoteKit implements many of the models typically used in computational social choice research,³ as well as newer parametrized models that give users the ability to generate profiles that are designed to comport with real-world ranking behavior and particularly to generate polarized elections. Two leading choices are based on classic statistical ranking mechanisms, called the Plackett–Luce (PL) and Bradley–Terry (BT) models; another model called the Cambridge Sampler (CS) draws from historical ranking data in Cambridge, MA city council elections. These models have flexible parameters—allowing users to vary voting bloc proportions, candidate strength within slates, and polarization between blocs—that can be specified or randomly sampled.

Area of need: Comparison and communication

Community groups looking to build local support for a shift in electoral systems often ask researchers to provide modeling studies that can help decide on a course of action—for example, when Portland, Oregon recently shifted its city council system to STV. VoteKit implements voting rules that stakeholders often seek to compare, with parameters designed to be tailored by the user to the specific locality. Available voting rules include:

- **Ranking-based (ordinal).** Plurality/SNTV, STV and IRV, (generalized) Borda, Alaska,⁴

²See for instance the extensive array of open-source tools on the Computational Social Choice (COMSOC) community page (Ulle Endriss and Simon Rey, 2024) including the widely used collection of ranked data called PrefLib (Nicholas Mattei and Simon Rey, 2022). See also the materials provided by FairVote, including their DataVerse and GitHub (FairVote, 2024). The survey (Boehmer et al., 2024) provides an impressively comprehensive list of numerical experiments on elections. The PRAGMA Project (<https://perma.cc/2P6V-8ZER>) echoes our statement of need, noting that the current literature and software falls short in practical applicability and that the understanding of real and synthetic data is “very limited.”

³Frequently used models include Impartial Culture (IC), Impartial Anonymous Culture (IAC), and spatial models. In a meta-analysis of 163 papers (Boehmer et al., 2024), the authors report that IC and Euclidean (spatial) models make up more than 75% of the election experiments found in 163 papers.

⁴Our implementation of the Alaska method is an SNTV/STV hybrid that uses single non-transferable vote to choose a set of finalists, then runs STV on the same preference profile to fill the seats. Alaska’s elections run

77 Top-Two, Dominating sets/Smith method, Condo-Borda,⁵ Sequential RCV.

78 ■ **Score-based (cardinal).** Range voting, Cumulative, Limited.

79 ■ **Approval-based (set).** Approval voting, Bloc plurality.

80 This list does not include every method that has attracted theoretical investigation; rather, it
81 is oriented to methods used or considered for political representation, such as the final-four
82 system in Alaska or the sequential RCV in Utah local elections. See generally (Amorós et
83 al., 2016; Emerson, 2013; McCune et al., 2023; Reynolds et al., 2008; Tideman, 1995) for
84 references. In addition, VoteKit is flexible enough to allow users to write custom voting rules.

85 Reform advocates also need to describe voting mechanisms and their likely outcomes effectively
86 to members of their communities. The end-to-end pipeline provided by VoteKit allows
87 advocates to toggle different system settings and compare expected outcomes. For example,
88 Figure 1 is reprinted from a report on reform proposals for the chambers of the Washington state
89 legislature. Using the codebase that formed the foundation of VoteKit, researchers compared
90 the expected outcomes for minority representation under six possible electoral systems.




Figure 1: A comparison of a variety of electoral systems and their effect on minority representation in a case study of reform proposals for the Washington state legislature (MGGG Redistricting Lab, 2021d). Even within ranked-choice proposals, certain options, like System 0 (based on single-member districts), are projected to be less successful for minority representation, while other systems, like System 1 (based on multi-member districts), predict that candidates of choice for people of color (“POC”) are elected more in line with the POC share of population or citizen voting age population (“CVAP”).

this in two distinct stages with four finalists and one seat; the top-two system amounts to running this with two finalists and one seat.

⁵Here, candidates are ordered by dominating sets (so that earlier ones in the list beat later ones in the list head-to-head), and ties are broken by Borda score. Note that this is distinct from Black’s method (Black, 1986), which uses Borda score as a backup system in case the smallest dominating set is not a singleton.

Area of need: Resources for research

Previous research works such as (Elkind et al., 2017) have compared properties of generative models; VoteKit has functionality to fully replicate this work and facilitates robust comparisons across a more comprehensive and up-to-date list of models. It also offers new analytical tools that will support research on elections. Some examples are shown in Figure 2. At left is a *ballot graph*, which shows the possible ballots, connected by elementary moves. At right is a visualization of similarity and difference between profiles produced by various generative methods, enabling comparisons in the style of (Szufa et al., 2020).




Figure 2: At left, the ballot graph for a 3-candidate election. The edges record swap moves and extension/truncation. (Note that the ballot $A > B > C$ is identified with the ballot $A > B$, since they are informationally equivalent in putting C last.) At right, a multidimensional scaling (MDS) plot shows similarity and difference among 80 synthetic profiles of 1000 ballots each, made with variations on the Cambridge Sampler (CS), Bradley-Terry (BT), and Plackett-Luce (PL) models. Compare Figure 1 in (Benadè et al., 2024). The letters represent different parameter settings related to candidate strength, and the image shows that these parameters create substantially different profiles, measured by L^1 difference in distributions.

Finally, VoteKit interacts seamlessly with a wide range of actual vote data, such as thousands of political elections collected by FairVote and a cleaned repository of over 1000 Scottish STV local government elections (FairVote, 2024; MGGG Redistricting Lab, 2023a). Previously, the use of real data in election research was often extremely limited; for instance, a recent survey reports that the single most popular “real-life” dataset has been a survey of 5000 respondents’ sushi preferences (Boehmer et al., 2024).

Projects

A significant number of white papers and scholarly articles by members of the MGGG Redistricting Lab and collaborators have used VoteKit (and its predecessor codebase) in recent years. These include the following.

- A large number of case studies in ranked-choice modeling, such as studies for the city councils of Chicago, IL (MGGG Redistricting Lab, 2019b) and Lowell, MA (MGGG Redistricting Lab, 2019a) and a range of jurisdictions across the Pacific Northwest MGGG Redistricting Lab (2021c);
- A study modeling the impact of proposed legislation called the Fair Representation Act, which would convert U.S. Congressional elections to the single transferable vote system (MGGG Redistricting Lab, 2022);

- 116 ▪ A detailed study isolating the impacts of varying hypotheses about voter behavior and
117 candidate availability on the Massachusetts legislature ([MGGG Redistricting Lab, 2024a](#));
- 118 ▪ A peer-reviewed article for an election law audience on the impact of STV elections on
119 minority representation ([Benadè et al., 2021](#));
- 120 ▪ A peer-reviewed article for a CS/econ audience that probes whether STV delivers
121 proportional representation ([Benadè et al., 2024](#)); and
- 122 ▪ A peer-reviewed article for an CS/operations research audience on optimizing to “learn”
123 blocs and slates in real-world elections ([Duchin et al., 2024](#)).

124 Acknowledgements

125 This work was initiated in a research cluster in Summer 2023, funded by the Democracy Fund
126 and graciously hosted at the Faculty of Computing and Data Sciences at Boston University
127 and the Tisch College of Civic Life at Tufts University. Major contributors to the initiation of
128 the project include Brenda Macias, Emarie De La Nuez, Greg Kehne, Jordan Phan, Rory Erlich,
129 James Turk, and David McCune. Earlier code contributions were made by Chanel Richardson,
130 Anthony Pizzimenti, Gabe Schoenbach, Dylan Phelan, Thomas Weighill, Dara Gold, and
131 Amy Becker; recent code contributors include Peter Rock, Kevin Quinn, and Divij Sinha.
132 The authors also thank Deb Otis, Jeanne Clelland, and Michael Parsons for helpful feedback.
133 FairVote’s data repository in Dataverse (https://dataverse.harvard.edu/dataverse/rcv_cvrs)
134 and RCV Cruncher code on GitHub (https://github.com/fairvotereform/rcv_cruncher/) are
135 open-source efforts that provided inspiration for the current project.

136 References

- 137 Amorós, P., Puy, M. S., & Martínez, R. (2016). Closed primaries versus top-two primaries.
138 *Public Choice*, 167, 21–35. <https://doi.org/10.1007/s11127-016-0328-5>
- 139 Benadè, G., Buck, R., Duchin, M., Gold, D., & Weighill, T. (2021). *Ranked choice voting and*
140 *proportional representation*. <https://doi.org/10.2139/ssrn.3778021>
- 141 Benadè, G., Donnay, C., Duchin, M., & Weighill, T. (2024). Proportionality for ranked voting,
142 in theory and practice. In *Preprint*. <https://mggg.org/PRVTP>.
- 143 Black, D. (1986). *The theory of committees and elections*. Springer Netherlands. <https://doi.org/10.1007/978-94-009-4225-7>
- 144
- 145 Boehmer, N., Faliszewski, P., Janeczko, Ł., Kaczmarczyk, A., Lisowski, G., Pierczyński, G.,
146 Rey, S., Stolicki, D., Szufa, S., & Wąs, T. (2024). Guide to numerical experiments on
147 elections in computational social choice. In K. Larson (Ed.), *Proceedings of the thirty-*
148 *third international joint conference on artificial intelligence, IJCAI-24* (pp. 7962–7970).
149 International Joint Conferences on Artificial Intelligence Organization. [https://doi.org/10.](https://doi.org/10.24963/ijcai.2024/881)
150 [24963/ijcai.2024/881](https://doi.org/10.24963/ijcai.2024/881)
- 151 Duchin, Shmoys, & Tapp. (2024). Learning blocs and slates from ranked-choice ballots.
152 *Preprint*.
- 153 Elkind, E., Faliszewski, P., Laslier, J.-F., Skowron, P., Slinko, A., & Talmon, N. (2017).
154 What do multiwinner voting rules do? An experiment over the two-dimensional euclidean
155 domain. *Proceedings of the AAAI Conference on Artificial Intelligence*, 31(1). <https://doi.org/10.1609/aaai.v31i1.10612>
- 156
- 157 Emerson, P. (2013). The original borda count and partial voting. *Social Choice and Welfare*,
158 40, 353–358. <https://doi.org/10.1007/s00355-011-0603-9>

- 159 Eric Pacuit and Wesley H. Holliday. (2022). *Pref_voting*. [https://github.com/voting-tools/](https://github.com/voting-tools/pref_voting)
160 [pref_voting](https://github.com/voting-tools/pref_voting)
- 161 FairVote. (2024). *RCV cruncher*. https://github.com/fairvotereform/rcv_cruncher/
- 162 Jan Šimbera. (2020). *Votelib*. <https://github.com/simberaj/votelib>
- 163 Lackner, M., Regner, P., & Krenn, B. (2023). Abcvoting: A Python package for approval-
164 based multi-winner voting rules. *Journal of Open Source Software*, 8(81), 4880. <https://doi.org/10.21105/joss.04880>
165
- 166 Martin Lackner. (2022). *Apportionment*. <https://github.com/martinlackner/apportionmentb>
- 167 McCune, D., Martin, E., Latina, G., & Simms, K. (2023). *A comparison of sequential ranked-*
168 *choice voting and single transferable vote*. <https://doi.org/10.1007/s42001-024-00249-8>
- 169 MGGG Redistricting Lab. (2019a). Findings on the city of lowell's election systems. In *White*
170 *Paper*. <https://mggg.org/Lowell-Detailed-Report>.
- 171 MGGG Redistricting Lab. (2019b). Study of reform proposals for chicago city council. In
172 *White Paper*. <https://mggg.org/publications/Chicago.pdf>.
- 173 MGGG Redistricting Lab. (2021a). Analysis of election systems for oregon state. In *White*
174 *Paper*. <https://mggg.org/Oregon>.
- 175 MGGG Redistricting Lab. (2021b). Analysis of election systems for the chelan county,
176 washington board of county commissioners. In *White Paper*. [https://mggg.org/Chelan_](https://mggg.org/Chelan_County)
177 [County](https://mggg.org/Chelan_County).
- 178 MGGG Redistricting Lab. (2021c). Analysis of election systems for the tukwila, WA school
179 district. In *White Paper*. <https://mggg.org/Tukwila>.
- 180 MGGG Redistricting Lab. (2021d). Analysis of election systems for washington state. In *White*
181 *Paper*. <https://mggg.org/Washington>.
- 182 MGGG Redistricting Lab. (2022). Modeling the Fair Representation Act. In *White Paper*.
183 <https://mggg.org/FRA-Report>.
- 184 MGGG Redistricting Lab. (2023a). *Scottish STV election repo*. [https://github.com/mggg/](https://github.com/mggg/scot-elex)
185 [scot-elex](https://github.com/mggg/scot-elex)
- 186 MGGG Redistricting Lab. (2023b). *VoteKit*. <https://github.com/mggg/VoteKit>
- 187 MGGG Redistricting Lab. (2024a). Comparing electoral systems for the massachusetts
188 legislature. In *White Paper*. <https://mggg.org/MA-RCV>.
- 189 MGGG Redistricting Lab. (2024b). *VoteKit documentation*. [https://votekit.readthedocs.io/](https://votekit.readthedocs.io/en/latest/)
190 [en/latest/](https://votekit.readthedocs.io/en/latest/)
- 191 Nicholas Mattei and Simon Rey. (2022). *PrefLib-tools*. [https://github.com/PrefLib/](https://github.com/PrefLib/preflibtools)
192 [preflibtools](https://github.com/PrefLib/preflibtools)
- 193 Reynolds, A., Reilly, B., & Ellis, A. (2008). *Electoral system design: The new international*
194 *IDEA handbook*. International Institute for Democracy; Electoral Assistance.
- 195 Szufa, S., Faliszewski, P., Skowron, P., Slinko, A., & Talmon, N. (2020). [Drawing a map of elec-](#)
196 [tions in the space of statistical cultures](#). *Proceedings of the 19th International Conference*
197 *on Autonomous Agents and MultiAgent Systems*, 1341–1349. ISBN: 9781450375184
- 198 Tideman, N. (1995). The single transferable vote. *Journal of Economic Perspectives*, 9(1),
199 27–38. <https://doi.org/10.1257/jep.9.1.27>
- 200 Ulle Endriss and Simon Rey. (2024). *COMSOC community site*. [https://comsoc-community.](https://comsoc-community.org/tools)
201 [org/tools](https://comsoc-community.org/tools)