

Simple Markdown Example

PDF/LaTeX version

Jenny Rieck

Derek Beaton

May 13, 2019

Introduction

For reference, see [RMarkdown Driven Development](#) by Emily Riederer for a comprehensive overview of how to best structure RMarkdown for projects, packages, and other development-driven tasks.

In general for this RMarkdown file we follow Emily's fourth example with a directory structure, minimized redundancies, and heavy-duty code elsewhere. This RMarkdown, generally, serves as place to describe, analyze, and visualize our data. Thus, this text is shown at the top of the output, but actually appears after several R code chunks, which exist between the **Introduction** heading and YAML header information (which you see as title, authors, dates, etc...).

Most of the RMarkdown files in this directory will show generally the same content, but help highlight the different ways you can use RMarkdown, `knitr`, `pandoc`, `LaTeX`, and various package built for those, such as `beamer` (`LaTeX`) for presentations, and `papaja` & `rticles` (R/RMarkdown) for writing manuscripts that export to `LaTeX` or MS Word. If you decide to write MS Word documents through RMarkdown, you should also use the [redoc package](#).

R chunks: A word of caution

It is good practice to name your R chunks. If you do not, then the R chunks will still produce the intended material. However, when you do name them, you should ensure they have unique names (else, you will likely see some cryptic and not always informative error messages).

Tables

There are multiple approaches and packages to help visualize tables or tabular information. Let's start by looking at a simple summary of all the continuous variables. First, we will visualize the summary table through two methods within R: `knitr::kable` and the `kableExtra` package, followed by `grid` and `gridExtra`. Next, we will use the same data and illustrate what happens when we pass it to Python through `reticulate`.

In this section we will also show the code chunks that generate these tables and visuals, which are embedded in the RMarkdown document.

knitr and kableExtra

To make HTML and LaTeX tables in RMarkdown, one of the easiest and most common options is through `knitr`. The `knitr` package is, effectively, the tool to make RMarkdown documents go from R & RMarkdown (plus other code and LaTeX) into PDFs or HTML pages. We'll start with the `knitr::kable()`.

```
example_table <- amerge_subset[, c("AGE", "MOCA", "CDRSB", "WholeBrain",  
  "Hippocampus", "MidTemp")]  
example_table_Dx <- amerge_subset[, c("DX", "AGE", "MOCA", "CDRSB",  
  "WholeBrain", "Hippocampus", "MidTemp")]
```

```
kable(summary(example_table))
```

AGE	MOCA	CDRSB	WholeBrain	Hippocampus	MidTemp
Min. :55.00	Min. :16.00	Min. :0.000	Min. : 817421	Min. : 3731	Min. :12213
1st Qu.:67.20	1st Qu.:22.00	1st Qu.:0.000	1st Qu.: 984410	1st Qu.: 6510	1st Qu.:18535
Median :71.90	Median :24.00	Median :1.000	Median :1051621	Median : 7223	Median :20186
Mean :71.92	Mean :23.89	Mean :1.202	Mean :1057026	Mean : 7150	Mean :20302
3rd Qu.:76.60	3rd Qu.:26.00	3rd Qu.:2.000	3rd Qu.:1120570	3rd Qu.: 7834	3rd Qu.:22088
Max. :89.60	Max. :30.00	Max. :5.500	Max. :1486036	Max. :10602	Max. :32189

But that is not particularly nice looking. So we can use some parameters to make this table look better (which depend on having LaTeX).

```
kable(summary(example_table), format = "latex", booktabs = T)
```

AGE	MOCA	CDRSB	WholeBrain	Hippocampus	MidTemp
Min. :55.00	Min. :16.00	Min. :0.000	Min. : 817421	Min. : 3731	Min. :12213
1st Qu.:67.20	1st Qu.:22.00	1st Qu.:0.000	1st Qu.: 984410	1st Qu.: 6510	1st Qu.:18535
Median :71.90	Median :24.00	Median :1.000	Median :1051621	Median : 7223	Median :20186
Mean :71.92	Mean :23.89	Mean :1.202	Mean :1057026	Mean : 7150	Mean :20302
3rd Qu.:76.60	3rd Qu.:26.00	3rd Qu.:2.000	3rd Qu.:1120570	3rd Qu.: 7834	3rd Qu.:22088
Max. :89.60	Max. :30.00	Max. :5.500	Max. :1486036	Max. :10602	Max. :32189

With `booktabs` and `latex` format, we've made the table look a little better. But can we make it look even better than that? We can with `kableExtra`.

```
kable(summary(example_table), format = "latex", booktabs = T) %>%
  kable_styling(font_size = 10, position = "center")
```

AGE	MOCA	CDRSB	WholeBrain	Hippocampus	MidTemp
Min. :55.00	Min. :16.00	Min. :0.000	Min. : 817421	Min. : 3731	Min. :12213
1st Qu.:67.20	1st Qu.:22.00	1st Qu.:0.000	1st Qu.: 984410	1st Qu.: 6510	1st Qu.:18535
Median :71.90	Median :24.00	Median :1.000	Median :1051621	Median : 7223	Median :20186
Mean :71.92	Mean :23.89	Mean :1.202	Mean :1057026	Mean : 7150	Mean :20302
3rd Qu.:76.60	3rd Qu.:26.00	3rd Qu.:2.000	3rd Qu.:1120570	3rd Qu.: 7834	3rd Qu.:22088
Max. :89.60	Max. :30.00	Max. :5.500	Max. :1486036	Max. :10602	Max. :32189

We can take the table look even further with additional options, like “stripes”.

```
kable(summary(example_table), format = "latex", booktabs = T) %>%
  kable_styling(font_size = 10, position = "center", latex_options = "striped")
```

AGE	MOCA	CDRSB	WholeBrain	Hippocampus	MidTemp
Min. :55.00	Min. :16.00	Min. :0.000	Min. : 817421	Min. : 3731	Min. :12213
1st Qu.:67.20	1st Qu.:22.00	1st Qu.:0.000	1st Qu.: 984410	1st Qu.: 6510	1st Qu.:18535
Median :71.90	Median :24.00	Median :1.000	Median :1051621	Median : 7223	Median :20186
Mean :71.92	Mean :23.89	Mean :1.202	Mean :1057026	Mean : 7150	Mean :20302
3rd Qu.:76.60	3rd Qu.:26.00	3rd Qu.:2.000	3rd Qu.:1120570	3rd Qu.: 7834	3rd Qu.:22088
Max. :89.60	Max. :30.00	Max. :5.500	Max. :1486036	Max. :10602	Max. :32189

Given that we have redundant information in the table (min/max, etc...) we can do a better job and make an even nicer table with an `apply()`, and then use multiple `kable` and `kableExtra` features to make a really nice table.

```

better_example_table <- apply(example_table, 2, summary)

kable(better_example_table, format = "latex", booktabs = T, digits = 2) %>%
  kableExtra::add_header_above(c(Statistic = 1, Demographic = 1,
    Clinical = 2, Brain = 3)) %>% kable_styling(font_size = 10,
    position = "center", latex_options = "striped") %>% row_spec(0,
    angle = 15, bold = T)

```

Statistic	Demographic	Clinical		Brain		
	AGE	MOCA	CDRSB	WholeBrain	Hippocampus	MidTemp
Min.	55.00	16.00	0.0	817421.2	3731.00	12213.00
1st Qu.	67.20	22.00	0.0	984409.9	6510.00	18535.00
Median	71.90	24.00	1.0	1051621.3	7223.00	20186.00
Mean	71.92	23.89	1.2	1057025.6	7149.61	20301.93
3rd Qu.	76.60	26.00	2.0	1120569.5	7834.00	22088.00
Max.	89.60	30.00	5.5	1486035.6	10602.00	32189.00

grid and gridExtra

Sometimes we need tables to be graphics. This is where the `grid` and `gridExtra` packages come in. The `grid` package uses `grobs` to turn items—tables, figures, all sorts of things—into configurable parts of a figure.

```
grid.table(better_example_table)
```

	MOCA	CDRSB	WholeBrain	Hippocampus
	16	0	817421.228648	3731
	22	0	984409.906002	6510
	24	1	1051621.329331	7223
9774	23.8902255639098	1.20225563909774	1057025.5509328	7149.613533834
	26	2	1120569.496532	7834
	30	5.5	1486035.644341	10602

But it's clear we have a few extra things we should do to make this figure of a table look better.

```

better_example_table_round <- apply(better_example_table, 2,
  format, digits = 2, nsmall = 2)

grid.table(better_example_table_round)

```

	AGE	MOCA	CDRSB	WholeBrain	Hippocampus	MidTemp
<i>Min.</i>	55.00	16.00	0.00	817421.23	3731.00	12213.00
<i>1st Qu.</i>	67.20	22.00	0.00	984409.91	6510.00	18535.00
<i>Median</i>	71.90	24.00	1.00	1051621.33	7223.00	20186.00
<i>Mean</i>	71.92	23.89	1.20	1057025.55	7149.61	20301.93
<i>3rd Qu.</i>	76.60	26.00	2.00	1120569.50	7834.00	22088.00
<i>Max.</i>	89.60	30.00	5.50	1486035.64	10602.00	32189.00

However, the `grid` and `gridExtra` packages can be difficult to customize many of the pieces. Therefore it might be easier to stick to the LaTeX approaches with `kable` or it is well worth checking out the [gt package](#).

Python via reticulate

What if you now love RMarkdown but are still really into Python? Not a problem. The [reticulate](#) package has you covered. It's an R package to connect to your Python installation and bring the data or results back into R, but with some of the same features as you're used to in either Python or R. Let's start out with a *head to head* of R's `head()` vs. Python's `.head()`.

In R we write the call in RMarkdown as if we would normally in R:

```
head(example_table)
```

```

##      AGE MOCA CDRSB WholeBrain Hippocampus MidTemp
## 2002 64.8  28   2.5  1135556.6         7960   21867
## 2003 63.6  24   2.0  1070369.5         7611   21580
## 2007 83.4  23   2.5   920710.1         5614   20567
## 2010 62.9  27   0.5   986402.9         8004   20358
## 2011 69.9  25   1.5   987822.5         6686   20366
## 2018 76.4  26   1.5  1004817.0         7774   19531

```

Unlike the previous code chunks, we have to tell RMarkdown that the language it should expect is `python` instead of `R`.

```
print(r.example_table.head())
```

```
##          AGE  MOCA  CDRSB   WholeBrain  Hippocampus  MidTemp
## 2002  64.8  28.0   2.5  1.135557e+06      7960.0  21867.0
## 2003  63.6  24.0   2.0  1.070369e+06      7611.0  21580.0
## 2007  83.4  23.0   2.5  9.207101e+05      5614.0  20567.0
## 2010  62.9  27.0   0.5  9.864029e+05      8004.0  20358.0
## 2011  69.9  25.0   1.5  9.878225e+05      6686.0  20366.0
```

For Python via R we also need to use the `.` (dot notation) because of Python's object oriented approach. From the `r` object, we get the `example_table` attribute and then perform the `head` method. That's because Python needs to know about the object coming from R.

Here be .dragons

For those more familiar with R style that stems from the S language origin or Google's style guide, the `.` can be a substantial source of confusion both here and in the `tidyverse`. In base R, it is a valid character for user defined items. But in base R it is *also* used for objects and classes (see, e.g., `.print()`). In the `tidyverse` the `.` has a special purpose when alone (not amongst other characters), often as a placeholder for where to pass a variable as an argument into a function.

In R: use `.` either with caution or reckless abandon.

Passsssing back and foRth

That subtitle is a stretch! With the `reticulate` package and R we can pass items between the the two languages/environments. And, depending on which language, we use that language's preferred/standard approach of referring to attributes or objects. In this next example we call into the `.describe()` method in Python, which is similar to R's `summary()`, but allows/requires us to define certain parameters.

```
perc = [.25, .50, .75]
desc = r.example_table.describe(percentiles = perc)
print(desc)
```

```
##          AGE          MOCA          CDRSB   WholeBrain  Hippocampus  \
## count  665.000000  665.000000  665.000000  6.650000e+02   665.000000
## mean   71.922556   23.890226   1.202256   1.057026e+06  7149.613534
## std     6.868621    3.279405   1.343238   1.036727e+05  1086.040463
## min    55.000000   16.000000   0.000000   8.174212e+05  3731.000000
## 25%    67.200000   22.000000   0.000000   9.844099e+05  6510.000000
## 50%    71.900000   24.000000   1.000000   1.051621e+06  7223.000000
## 75%    76.600000   26.000000   2.000000   1.120569e+06  7834.000000
## max    89.600000   30.000000   5.500000   1.486036e+06 10602.000000
##
##          MidTemp
## count    665.000000
## mean   20301.933835
## std    2675.571327
## min   12213.000000
## 25%   18535.000000
## 50%   20186.000000
## 75%   22088.000000
## max   32189.000000
```

We can visualize the results directly using the `print()` method. But like previous results shown in R, we can do a lot better. We can pass the `desc` object back to R with the `$` notation (generally for lists or simple classes in R). When we retrieve an object from python (via `py$`), we can then do what we would usually do in R. Here, we go back to `kable()` and `kable_styling()` with some of the parameters to make very nice looking LaTeX tables.

```
kable(py$desc, digits = 2, format = "latex", booktabs = T) %>%
  kable_styling(font_size = 10, position = "center", latex_options = "striped")
```

	AGE	MOCA	CDRSB	WholeBrain	Hippocampus	MidTemp
count	665.00	665.00	665.00	665.0	665.00	665.00
mean	71.92	23.89	1.20	1057025.6	7149.61	20301.93
std	6.87	3.28	1.34	103672.7	1086.04	2675.57
min	55.00	16.00	0.00	817421.2	3731.00	12213.00
25%	67.20	22.00	0.00	984409.9	6510.00	18535.00
50%	71.90	24.00	1.00	1051621.3	7223.00	20186.00
75%	76.60	26.00	2.00	1120569.5	7834.00	22088.00
max	89.60	30.00	5.50	1486035.6	10602.00	32189.00

Analyses

Visualizations & Graphics