

Discrete BCF vs SBCF with Odd Ratio Cost function

Jens and Lennard

Results with cost function

The cost for a variable selected in the binary tree is defined as:

$$cost_i = \frac{\max\{p\}}{p_i}$$

10 Covaraite

Table 1: Results with 10 Covariates.

subgroup	BCF				S BCF			
	<i>N</i>	<i>share</i>	<i>CACCE</i>	σ_{CACCE}	<i>N</i>	<i>share</i>	<i>CACCE</i>	σ_{CACCE}
negative effect	66	0.66	-1.988	0.238	70	0.70	-1.993	0.234
positive effect	67	0.67	2.020	0.202	73	0.73	2.012	0.221

The *BCF* algorithm detected both subgroups in 36 data sets, while the *SBCF* detected both subgroups in 43 data sets.




Figure 1: 10 Covariates

50 Covariates

Table 2: Results with 50 Covariates.

subgroup	BCF				S BCF			
	N	$share$	$CACCE$	σ_{CACCE}	N	$share$	$CACCE$	σ_{CACCE}
negative effect	42	0.42	-2.074	0.277	56	0.56	-2.035	0.266
positive effect	44	0.44	2.033	0.253	58	0.58	2.030	0.242

The *BCF* algorithm detected both subgroups in 10 data sets, while the *SBCF* detected both subgroups in 22 data sets.




Figure 2: 50 Covariates

Table 3: Results with 100 Covariates.

subgroup	BCF				S BCF			
	N	$share$	$CACCE$	σ_{CACCE}	N	$share$	$CACCE$	σ_{CACCE}
negative effect	36	0.36	-1.982	0.255	50	0.5	-1.980	0.234
positive effect	41	0.41	2.003	0.167	60	0.6	2.017	0.184

100 Covaraites

The *BCF* algorithm detected both subgroups in 10 data sets, while the *SBCF* detected both subgroups in 22 data sets.




Figure 3: 100 Covariates