GeoELAN v2.5 2023-06-04

This is the manual for GeoELAN, a tool for annotating action-camera GPS logs via the ELAN annotation software.

Please cite this document as

Larsson, J. 2022. GeoELAN Manual. Lund: Lund University Humanities Lab. https://github.com/jenslar/geoelan

Acknowledgments

GeoELAN was developed with support from the Bank of Sweden Tercentenary Foundation (Grant nos NHS14-1665:1 and IN17-0183:1).

We would also like to acknowledge the The Language Archive, Max Planck Institute for Psycholinguistics in Nijmegen for their tireless efforts in developing ELAN, and making it available for free.

Introduction

GeoELAN is a command-line tool that geo-references time-aligned text-annotations of observed phenomena in audiovisual recordings, captured with a recent GoPro or Garmin VIRB action camera, see Larsson et al 2021. In other words, GeoELAN is used for annotating action camera GPS logs with the help of ELAN.

By annotating a section representing an on-site utterance, a plant that is in view, or anything else that was captured, the annotation can be automatically linked to the corresponding coordinates. The nature of the workflow also means consultants not physically present at the the time of recording may evaluate observed phenomena to be geo-referenced post-collection. As the name implies, the free ELAN annotation software plays a central role and is required to annotate events. The final output can be points, polylines, or polygons (circles), in the form of annotated KML and GeoJSON-files. Henceforth, "GoPro" refers to a GoPro Hero 5 Black or later, and "VIRB" to the Garmin VIRB Ultra 30. Note that while GeoELAN functionality differs slightly between Garmin and GoPro due to differences in

formats and file structure, the general workflow and the final output are the same.

Note that **the Garmin VIRB Ultra 30 is no longer produced**, so use a recent GoPro instead.

We, and maybe others, still have and use VIRBs, so GeoELAN will continue to support these.

GeoELAN is multi-functional tool that can

- geo-reference ELAN-annotations of GoPro and VIRB footage (i.e. annotate GPS logs) and generate annotated points, lines, or circles.
- inspect the content of your GoPro GPMF data, or Garmin FIT-files.
- locate and match all relevant files belonging to the same recording session (clips, telemetry-files).
- automatically concatenate clips for a specific recording, and generate an ELAN-file with linked media.

Requirements

- An action camera with a built-in GPS. Supported devices are:
 - GoPro Hero Black 5 or newer (Max, and Fusion cameras have not been tested)
 - Garmin VIRB Ultra 30 (documentation)
- ELAN (documentation)
- FFmpeg (for concatenating video)
- Rust toolchain (optional, only required for compiling GeoELAN from source)

Installation

- Download the zip-file from https://github.com/jenslar/geoelan or use git clone
 https://github.com/jenslar/geoelan.git.
- See the bin directory for pre-compiled executables for Linux, macOS, and Windows.

Compile and install from source

You can also compile GeoELAN from source. Depending on your operating system, this may require installing additional software, and some understanding of working in a terminal. The basic steps are:

- 1. Install the Rust programming language
- 2. Get the GeoELAN source from https://github.com/jenslar/geoelan
- 3. cd geoelan (you should be in the folder containing Cargo.toml)
- 4. cargo build --release
- 5. cargo install --path . (optional, makes geoelan a global command)

Before you start

Practical advice

- **Keep the original files!** GeoELAN can only work with unedited files, since these contain unique identifiers used for synchronisation and/or telemetry, including the GPS-log. Converting videos to make them smaller will discard both identifiers and telemetry. GeoELAN will use low-resolution footage by default anyway, and the high-resolution footage can be ignored via the **--low-res-only** flag for cam2eaf.
- All VIRB telemetry, such as the GPS-log, is stored as a separate file. Keep all files on the microSD,
 unless you are absolutely certain which files are relevant.

Running GeoELAN

- GeoELAN is a command line tool and has no graphical user interface.
- FFmpeg is required to concatenate clips. (cam2eaf)
- If you use macOS and GeoELAN does not run, see https://support.apple.com/en-us/HT202491.

Device compatibility

- Garmin: Only VIRB Ultra 30 has been tested extensively, but earlier VIRB models may still work.
- GoPro: Only "main line" Hero cameras with GPS have been tested, but Max and Fusion cameras may still work.

GPS

Make sure the GPS is turned on and has acquired a satellite lock. This may take a couple of minutes or longer, especially if you have not used the camera for a while or have traveled far between uses.

Verifying a satellite lock:

- For **VIRB**, the GPS-icon should be steady, not blinking (it may log coordinates while the icon is still blinking, but do not rely on this being the norm).
- For **GoPro**, the GPS-icon should be white, not gray.

It may be difficult to acquire a satellite lock and/or reliably log position in areas with heavy overhead vegetation or dense cities with very tall buildings. Using a headstrap, instead of a cheststrap sometimes helps.

GPS logging behaviour:

- GoPro logs dummy coordinates if no lock has been acquired. GeoELAN will not use these.
 - Verify lock by running: geoelan i -g GH010006.MP4 --gps which will list number of bad points.
- VIRB does not log position at all until a lock has been acquired.

Annotating in ELAN

- It is best to limit each kind of observed phenomena you wish to geo-reference to a single ELAN-tier, so...
- ...to keep e.g. place names and plant sightings within the same ELAN-file make a separate tier for each (see the example walkthrough in the next section). Then you can just re-run GeoELAN on the same ELAN-file and select another tier to geo-reference along with other output options.

Example walkthrough

This section describes how GeoELAN can be used to geo-reference ELAN-annotations. Please refer to the detailed sections if you get stuck. Note that all input video clips must be the unprocessed, original MP4 (GoPro + VIRB) and FIT-files (VIRB). The so-called FIT-files mentioned throughout this manual are where the VIRB logs GPS-data and other kinds of telemetry during a recording session. These need to be matched to the corresponding video recording (see *The FIT-format and the Garmin VIRB* for further information). GeoELAN will help with all of this, with the exception of annotating your data.

As noted below, some of the commands differ slightly between GoPro and VIRB due to differences in

file and data structures.

The basic steps are:

- 1. Record video with a recent GoPro or Garmin VIRB action camera.
- 2. Use GeoELAN to concatenate the video clips and generate an ELAN-file.
- 3. Annotate spatially interesting sections in ELAN.
- 4. Use GeoELAN to geo-reference the annotations, resulting in annotated KML and GeoJSON files.

Input files

VIRB

- VIRB0001-1.MP4, any clip in a recording session (remaining clips located automatically)
- FIT-file with corresponding GPS-data (located automatically)

GoPro

• GH010026.MP4, any clip in a recording session (remaining clips located automatically)

Output files

VIRB + GoPro

 KML and GeoJSON files with ELAN annotation content synchronised and mapped to the corresponding points as descriptions. See the command eaf2geo for other options.

Step 1/3: Generate an ELAN-file with linked media files

In step 1 we will locate all video clips (GoPro + VIRB) and FIT-files (VIRB) that belong to a specific recording session, process these, and generate an ELAN-file with linked media files.

VIRB

Command

```
geoelan virb2eaf --video INDIR/VIRB0001-1.MP4 --indir INDIR/ --outdir OUTDIR/
```

Output files

```
OUTDIR/VIRB0001-1/

VIRB0001-1.mp4 High-resolution video (concatenated)

VIRB0001-1_LO.mp4 Low-resolution video for ELAN (concatenated)

VIRB0001-1.wav Extracted audio for ELAN (concatenated)

VIRB0001-1.eaf ELAN-file with pre-linked media files

VIRB0001-1.kml Overview KML-file with all points logged during the recording session FFmpeg concatenation file, paths to input clips
```

GoPro

Command

```
geoelan gopro2eaf --video INDIR/GH010026.MP4 --indir INDIR/ --outdir OUTDIR/
```

Output files

```
OUTDIR/GH010026/

GH010026.mp4 High-resolution video (concatenated)

GH010026_LO.mp4 Low-resolution video for ELAN (concatenated)

GH010026.wav Extracted audio for ELAN (concatenated)

GH010026.eaf ELAN-file with pre-linked media files

GH010026.kml Overview KML-file with all points logged during the recording session FFmpeg concatenation file, paths to input clips
```

Explanation of the command

GeoELAN locates and concatenates all clips for the recording session the clip VIRB0001–1.MP4 /GH010026.MP4 is part of, then generates an ELAN-file with linked media files.

The relevant sub-commands are virb2eaf/gopro2eaf, depending on camera.

By specifying any clip in the recording session via --video, the remaining clips (GoPro + VIRB), including the corresponding FIT-file (VIRB), will be automatically located if they exist in the specified input directory (--indir). Sub-directories will be searched as well. The result, including the corresponding FIT-file for VIRB cameras, will be saved to the specified outout directory (--outdir).

If low-resolution clips (.GLV/.LRV) are located, a concatenated low-resolution video will be linked in the ELAN-file. If not, the concatenated high-resolution video will be linked instead.

GeoELAN defaults to *not* insert a tier with geo-data in the ELAN-file due to the effect this may have on performance. To do so, use the **--geotier** flag (see *Geo-data in ELAN*).

TIP: For longer recording sessions, resulting in many video clips, step 1 is usually much faster if --indir and --outdir is not on the same physical hard drive. Those with an SSD (standard on most modern laptops) should be fine running step 1. on a single drive however.

Step 2/3: Annotate events in ELAN

Next, ELAN is used with the ELAN-file from step 1 to annotate events that should be geo-referenced in step 3. Feel free to create any tier structure you may need. Tokenized tiers can not be geo-referenced, but otherwise any tier is fine, including deeply nested, referred tiers.

GeoELAN will geo-reference annotations from a single tier (selectable in step 3). Thus, if you want to generate a KML-file with e.g. indigenous place names mentioned on-site during the recording, those place names must be limited to a single tier. If there are other spatial categories or groupings you wish to explore, simply create a new tier for each. In step 3 you can then re-run GeoELAN as many times as required, then select a different tier and/or options on each run.

When the annotations are geo-referenced in step 3, the annotation values in the selected tier will be used as descriptions for the synchronized, corresponding points in the KML and GeoJSON-files. Points corresponding to unannotated sections of the ELAN-file will either be discarded or have no description, depending on which options you use in step 3.

An annotated event can relate to anything observed in the recording and can be represented as either points or polylines in the output KML-file. If you are unsure which best applies to what you have in mind for your data, or how this may affect how you annotate, here are a few ideas for each kind.

Points could concern documenting:

- the location of a plant or a geographical feature, e.g. annotate the timespan either is visible in the video.
- an uttered place name or an animal cry, e.g. annotate the timespan it is uttered or heard on-site.

For these specific cases, the exact time spans of the annotations are not that important. It should be enough to ensure the annotation lasts for the duration of the place name being uttered, or for as long as the plant is visible. If unsure, add a another second to the annotation timespan. An average coordinate will be calculated for those that were logged within each annotation's time span, so as long as the camera wearer does not stray too far from the observation point, the result should be accurate enough.

Lines could concern documenting:

- various types of movement through the landscape. To annotate the movement of
 "walking up-hill" as it is observed visually in the recording set the annotation's start time
 at the bottom of the hill and its end at the top, or for as long as the motion can be
 observed.
- a narrative reflecting on the immediate surroundings as they change over time. E.g.
 comments on visible landscape features, or perhaps the re-construction of an historical event as it unfolded over space and time.

Step 3/3: Generate a KML-file from geo-referenced ELAN annotations

Now that we have a few annotations, GeoELAN will geo-referenence these by determining which points were logged within each annotation's timespan. Note the different commands between GoPro and VIRB.

This is where you choose the approriate geographical representations for your annotated phenomena. Here are suggestions for the examples in step 2.

_						
P	0	П	n	٠	C	٠
	v	ı		u	3	

- the location of a plant or a geographical feature
- · an uttered place name or an animal cry

To get a single, average coordinate for each annotation in the KML and GeoJSON-files, use the --geoshape point-single option.

Lines:

- types of movement through the landscape
- narrative reflecting on the immediate surroundings

Two line options may apply to the above. To get a continuous polyline alternating between marked (annotated) and unmarked (un-annotated) events, use the option --geoshape line-all. To get a broken-up polyline representing marked events only, use the option --geoshape line-multi.

There are other options, such as *circle* output. It is similar to point output, for which radius and height can be specified (all circles will have the same size). For a more detailed overview of the possibilities, see the **--geoshape** option for the command *eaf2geo*. Experiment! If you realise one representation is not appropriate after all, re-run GeoELAN with a different option.

VIRB

Command

```
geoelan eaf2geo --eaf VIRB0001-1.eaf --fit 2003-01-02-12-00-00.fit --geoshape point-single
```

Output files

GoPro

Command

```
geoelan eaf2geo --eaf GH010026.eaf --gpmf INDIR/GH010026.MP4 --geoshape point-single
```

Important: GH010026.MP4 must be the original video generated by the camera, indicated by INDIR from step 1/3.

Output files

```
OUTDIR/GH010026/

— ... Existing files

— GH010026_point-single.kml New KML-file, one point per annotation in the selected tier

— GH010026_point-single.geojson New GeoJSON-file, one point per annotation in the selected tier
```

Explanation of the command

GeoELAN geo-references all annotations in a single ELAN-tier (selectable from a list) for the specified ELAN-file, then generates annotated KML and GeoJSON files where each point represents a single annotation.

The relevant sub-command is eaf2geo. By specifying an ELAN-file (--eaf) and the corresponding GoPro MP4-file (--gpmf) or VIRB FIT-file (--fit), GeoELAN will synchronise the annotations with the coordinates contained within the MP4/FIT-file.

--geoshape point-single lets GeoELAN know that each, respective annotation should be distilled into a single point, meaning that the generated KML-file will contain as many points as there are annotations in the selected tier. Each point inherits the corresponding annotation value as its description. The KML-file is named according to the selected --geoshape option, in this case VIRB0001-1_point-single.kml/GH010026_point-single.kml.

For the example command for VIRB, the user will be presented with a list of recording sessions present in the FIT-file (see *The FIT-format and the Garmin VIRB*). GoPro MP4-files lack the appropriate metadata to display such as list.

Commands

There are six commands:

Command	Alias	Description
cam2eaf	g2e	Generate an ELAN-file, and link
eaf2geo	e2g	Geo-reference ELAN-annotations
		and generate annotated KML/GeoJSON
locate	1	Locate and match video clips and/or FIT-files
inspect	i	Inspect the contents of a GoPro MP4-file or any Garmin FIT-file
manual	m	View or save this manual to disk

To see help for a specific command, run geoelan <COMMAND> --help.

The most relevant commands are probably cam2eaf and eaf2geo. locate is there to help with locating and matching video clips and/or FIT-files that belong to the same recording session, but this functionality partly exists in cam2eaf as well. inspect will print the data contents of a GoPro MP4/Garmin FIT-file, but will do so in an unprocessed form. It is intended more as a technical aid for troubleshooting or to verify the contents of MP4/FIT-files. manual is for viewing or saving the full manual.

$Time\ adjustment\ with\ -\text{-}{\tt time-offset}$

If the action camera has not adjusted for the current time zone, several commands have a **--time -offset** option. It takes a +/- value in hours that will be applied to all timestamps in the output, e.g. **--time-offset** 7 will add seven hours to all timestamps.

Reducing the number of coordinates with --downsample

For the commands cam2eaf, and eaf2geo, the output may contain coordinates in some form (a

KML/GeoJSON-file or as annotations in an ELAN-file). Since the VIRB GPS logs at 10Hz, the resulting files may become too heavy to work with in some cases, such as loading a KML-file in Google Earth. GoPro logs at 10 or 18Hz depending on model, but saves points as a cluster each second. Since it is only the cluster that gets timestamped, and not the individual points, GeoELAN averages these to a single, timestamped point at the same interval the cluster was originally logged (roughly once/second).

--downsample can be used for both ELAN and KML/GeoJSON output to reduce the number of coordinates that are imported/exported. It is especially advised for KML-files that are to be loaded into Google Earth, since a 2 hour VIRB recording may contain more than 70 000 logged points. --downsample takes a positive numerical value that is effectively a divisor: --downsample 10 means an average coordinate will be calculated for every cluster of 10 points. For 70 000 logged points, a value of 100 means the output will contain 700 points and so on. If the user sets --downsample to a value that exceeds the total number of points logged by the GPS, it will be changed to the largest applicable value (resulting in a single point for the entire recording as opposed to none at all). Extreme values may also affect the result in unexpected ways, depending on gaps in the GPS-data.

If 'cam2eaf' or 'eaf2geo' return errors

Try the **inspect** command on problematic MP4/FIT-files. This way you can verify whether points were actually logged or not. If the file is corrupt the error message will also be printed.

FFmpeg

For the command cam2eaf FFmpeg is required. If you intend to use the *static build* for FFmpeg as described in the appendix under *FFmpeg*, point to it using --ffmpeg PATH/T0/FFMPEG/ffmpeg (ffmpeg.exe on Windows). If the --ffmpeg option is not used, geoelan will assume ffmpeg is available as a global command and complain accordingly if it is not.

TIP: GeoELAN will never overwrite existing files without permission. Should you accidentally delete the generated ELAN-file with the output media files intact, just re-run the cam2eaf command. It will automatically skip concatenating videos, but still generate a new ELAN-file.

TIP: In the tables for the respective command sections, arguments listed under 'Flags' do not

take a value, whereas those listed under 'Options' do. If a default value is listed, it will be automatically set, unless the user specifies otherwise.

cam2eaf

- Camera model: GoPro, VIRB
- Command/alias: cam2eaf / c2e
- Help: geoelan cam2eaf --help
- Basic usage: geoelan cam2eaf --indir INDIR/ --video GH010006.MP4 --outdir OUTDIR/

cam2eaf generates an ELAN-file with pre-linked media files. All clips in the specified recording session will be automatically located, grouped, and concatenated. A WAV-file from the full video is also extracted. By default the low-resolution footage is used (if found), use the --link-high-res flag to link the high-resolution footage. The corresponding coordinates can optionally be added a tier.

Note that the --fit and --uuid parameters are only valid for VIRB.

Flags

Short	Long	Description
	fullgps	Use the full-res GPS log for the ELAN geotier
	dryrun	Show results but do not process or copy files
	geotier	Insert tier with synchronised coordinates in ELAN-file
	link-high-res	Link high-resolution video in ELAN-file
-1	low-res-only	Only concatenate low-res clips (.LRV/.GLV), ignores high-res clips

Options

Short	Long	Description	Default	Required
	ffmpeg	Custom path to	ffmpeg	
		FFmpeg		
-f	fit	[VIRB] FIT-file		unless -u or -v
-i	indir	Input path for		yes
		locating files		
-0	outdir	Output path for	geoelan	
		resulting files		
-t	time-offset	Time offset in +/-	0	
		hours		
-u	uuid	[VIRB] UUID for a clip		unless -f or -v
		in the relevant		
		session		
-v	video	GoPro/VIRB clip in the		unless -f or -u
		relevant session		

Examples GoPro

GoPro Example 1

geoelan	cam2eaf	-v GH010026.MP4	-i INDIR/	-o OUTDIR/	geotier
	command	clip in session	input directory	output directory	insert coordinate
					tier

Result: Locates all clips for the recording session containing the clip GH010026.MP4 (-g) in the input directory INDIR/ (-i). These will be concatenated, and the audio track exported as a WAV for use in ELAN. The resulting files are then copied to the output directory OUTDIR/ (-o). The generated ELAN-file will also have synchronised coordinates inserted as a tier (--geotier).

Examples VIRB

Note: Recording session can be specified using one of **--fit**, **--uuid**, **--video**. These options are mutually exclusive. **--fit** returns a list of sessions present in the FIT-file, from which the

user can select the relevant one. --uuid and --video require no further user input.

Note: Using --fullgps together with --geotier will result in very large ELAN-files. Additionally, trying to edit the 'geotier' may make ELAN sluggish or unsresponsive.

VIRB Example 1

Result: Locates all clips for the recording session containing the clip VIRB0001–1.MP4 (-v) in the input directory INDIR/ (-i). These will be concatenated, and the audio track exported as a WAV for use in ELAN. The resulting files are then copied together with the corresponding FIT-file to the output directory OUTDIR/ (-o). The generated ELAN-file will also have synchronised coordinates inserted as a tier (--geotier).

VIRB Example 2

geoelan	cam2eaf	-f 2017-01-28-	-i INDIR/	-o OUTDIR/	low-res-only
		05-16-40.FIT			
	command	FIT-file	input directory	output directory	do not
					concatenate hi-
					res MP4

Result: The relevant recording session is specified via the FIT-file 2017–01–28–05–16–40. fit (-f). This presents the user with a list of sessions to select from, which allows GeoELAN to locate matching clips in the input directory INDIR/ (-i). Only the low-resolution clips (--low-res-only) will be concatenated. All resulting files are then copied together with the corresponding FIT-file to the output directory OUTDIR/ (-o).

Tip: If you are unsure of the whereabouts of the FIT-file, make the search wider. Specifying the root of an external hard drive as input directory (--indir) will make the search process

take slightly longer, but should work well. Otherwise, just specify the FIT-file separately (-fit), which can be useful if it is located outside of the input directory.

eaf2geo

• Camera model: GoPro, VIRB

• Command/alias: eaf2geo / e2g

• Help: geoelan eaf2geo --help

• Basic usage: geoelan eaf2geo --eaf VIRB0001-1.eaf --fit 2017-01-28-05-16-40.fit

eaf2geo generates KML and GeoJSON files by geo-referencing all annotations in the specified tier. The user is presented with a list of tier names to select from. Referred tiers are fine, but tokenized tiers can not be used, since these lack time stamps. Several output options exist via the --geoshape option, such as points or polylines (see below). In the resulting KML and GeoJSON files, any point that intersects with an annotation's timespan will inherit the annotation value as a description.

Flags

Short	Long	Description
	cdata	KML-option, added visuals in Google
		Earth

Options

Short	Long	Description	Default	Possible	Required
-d	downsample	Downsample	1		
		factor for			
		coordinates			
-е	eaf	ELAN-file			yes
-f	fit	VIRB FIT-file			unless -g
-g	gpmf	GoPro MP4-file			unless -f

Short	Long	Description	Default	Possible	Required
	geoshape	Output options	point-all	point-all,	
		for KML-file		point-multi,	
				point-single,	
				line-all, line-	
				multi, circle-	
				2d, circle-3d	
	height	Circle height	10.0		
		('circle-3d')			
	radius	Circle radius	2.0		
		('circle-2d',			
		'circle-3d')			
-t	time-offset	Time offset, +/-	0		
		hours			
	vertices	Circle	40		
		vertices/roundne			
		ss ('circle-2d',			
		'circle-3d')			

Example 1

geoelan	eaf2geo	-g GH010026.MP4	-e GH010026.eaf	geoshape line-
				all
	command	original GoPro MP4-	ELAN-file	output option
		file		

Result: Geo-references annotations in the ELAN-file GH010026.eaf (-e) and generates KML and GeoJSON files with a continous poly-line, alternating between marked (annotated) and unmarked (unannotated) sections (--geoshape line-all).

Example 2

geoelan	eaf2geo	-f 2017-01-28-05-	-e VIRB0001-1.eaf	geoshape point-
		16-40.fit		single
	command	FIT-file	ELAN-file	output option

Result: Geo-references annotations in the ELAN-file VIRB0001–1.eaf (-e) and generates KML and GeoJSON files with a single point per annotation (--geoshape point-single). Since no video is specified (i.e. the first clip in the recording session), the user will be presented with a list of UUIDs in the specified FIT-file 2017–01–28–05–16–40.fit (-f) to choose from, each representing the first clip in a recording session.

The geoshape option


Different geographical representations can be generated, including points and lines. Six possible --geoshape values are accepted:

Option	Description
point-all	All logged points exported (default if no option passed)
point-multi	Exported points correspond to marked/annotated events only
point-single	A single, averaged point for each annotation
line-all	Polyline from all logged points
line-multi	Polyline, corresponds to marked/annotated events only
circle-2d	2D polygon, corresponds to marked/annotated events only
circle-3d	3D polygon, corresponds to marked/annotated events only

--downsample can be used with all these options, but will be ignored for point-single, circle-2d /circle-3d allows for further customisation, such as height (circle-3d, KML-only) and radius. The circle options work in the same way as point-single and are currently only a visual flair, since radius and height are not yet derived from ELAN annotation values.


point-all

All points logged during the recording session will be exported. Any point that intersects with the time span of an annotation will inherit the annotation value as the coordinate description. Points that do not, will have no description.



point-multi

Only points that intersect with the time span of an annotation will be exported and will inherit the annotation text as the coordinate description. Points that have no corresponding annotation will be discarded. *Useful for including points corresponding to marked events only*.



```
|
Description for each point in section:
"Dayum" (placename)
```


point-single


Only points that intersect with the time span of an annotation will be considered for export. The difference to point-multi is that each annotation will only generate a single point: an average of those logged within the annotation's time span. Note that a custom --downsample value will be ignored for point-single since it may affect the result negatively. --downsample also has little use here, since the number of points in the output will not be affected and will be quite low compared to the other options. Useful for distilling marked events, such as place names, to a single point for each event.



line-all


All points logged during the recording session will be exported, resulting in a continuous polyline. Subsections that intersect with an annotation inherit the annotation value as a description, whereas those that do not will have no description.





line-multi

Only points that intersect with the time span of an annotation will be exported, resulting in a brokenup line. Each sub-section inherits the value of the annotation it intersects with. *Useful for representing* paths corresponding to marked events only.



circle-2d, circle-3d

circle-2d, and circle-3d work almost exactly like point-single with the difference that a circle is generated around the calculated average point. It is mostly a visual flair and its shape is currently not affected by annotation values. circle-2d is flat against the ground, whereas circle-3d can take a height value to become a cylindrical 3D shape (only applies to KML, not GeoJSON). If circle output is specified, three more options become available:

Option	Description	Default
height	Height relative to ground in meters (circle-3d)	
radius	Radius in meters (circle-2d, circle-3d)	2.0
vertices	Roundness, valid range 3 - 255 (3 will literally be triangle)	40

The 'cdata' option

Only affects KML-files. Using --cdata will insert extra information into the KML-file in the form of HTML inside the <description> element for each point (see the CDATA section in Google's KML documentation). This will cause an information bubble to pop-up in Google Earth when a point is clicked on, as a visual flair for e.g. presentations.

locate

- Camera model: GoPro, VIRB
- Command/alias: locate / 1
- Help: geoelan locate --help
- Basic usage: geoelan locate --indir INDIR/ --kind gopro

locate will locate and match original GoPro and VIRB clips in the input path. For VIRB, corresponding FIT-file/s will also be matched. By optionally specifying a UUID (--uuid, --fit) or a clip (--video) in a specific session, only paths for the files in that recording session will be returned. If you are unsure of the location of all VIRB-files, use an input path closer to the root, such as the root of an external hard drive. If duplicate files are found, only the first one encountered will be reported.

Flags

Short	Long	Description
	duplicates	Include duplicate VIRB files in match
		results

Short	Long	Description
	quiet	Do not print file-by-file search
		progress

Options

Short	Long	Description	Possible	Required
-i	indir	Input path for		yes
		locating files		
-k	kind	Camera brand	virb, gopro	unless -v, -u, -f
-f	fit	VIRB FIT-file for		
		selecting session		
-u	uuid	UUID for VIRB clip in		
		session		
-v	video	GoPro or VIRB clip in		
		session		

Example 1

geoelan	locate	-i INDIR/	kind gopro
	sub-command	input directory	consider GoPro files

Result: Locates all GoPro clips in INDIR/ (-i) and groups them in recording sessions.

Example 2

geoelan	locate	-i INDIR/	-v VIRB0001-1.MP4
	sub-command	search directory	first clip in session

Result: Camera brand is detected automatically (in this case VIRB). Locates all clips in INDIR/ (-i) for the recording session that contains VIRB0001-1.MP4 (-v) together with the corresponding FIT-file.

inspect

- Camera model: GoPro, VIRB
- Command/alias: inspect / i
- Help: geoelan inspect --help
- Basic usage:
 - GoPro: geoelan inspect --gpmf GH010026.MP4
 - VIRB: geoelan inspect --fit 2017-01-28-05-16-40.fit

inspect prints an overview or the detailed contents of a GoPro MP4 or a Garmin FIT-file. If a Garmin VIRB MP4 is passed with no other options, the embedded UUID will be printed. Options include filtering to print only a sub-set of the data, such as GPS-data only, data corresponding to a specific recording session, or both. locate is more of a technical aid to, for example, verify that the GPS really did log coordinates. KML or GeoJSON files can also be generated.

Flags

Short	Long	Description
	debug	Print FIT definitions and data while
		parsing
	kml	Generate a KML-file
	ikml	Generate an indexed KML-file
	json	Generate a GeoJSON-file.
	verbose	Print raw data
	gps	Print processed GPS data
	meta	Print MP4 custom user data (udta
		atom)
	atoms	Print MP4 atom hierarchy
-0	offsets	[GoPro] Print DEVC byte offsets for
		GoPro MP4-file
- s	session	[VIRB] Select session from a list.
		GoPro: Merges session data.

Note that the --offsets flag can only be used if the GoPro MP4-file was specified via the --gpmf option below. It has no use for other MP4-files.

Options

Short	Long	Description	Required
-f	fit	FIT-file	unless − g , − v
-g	gpmf	GoPro-file (MP4 or raw GPMF-file)	unless -f , -v
-t	type	[GoPro, VIRB] Data type	
-v	video	MP4-file	

Note that --type takes a string for GoPro and a numerical identifier for VIRB. --video accepts any MP4-file. See the sections below.

Inspecting telemetry

inspect will mostly print raw values that require further processing to be of use. The exact nature of this data differs between GoPro and Garmin. For GPS data, the flag --gps can be used for either device to print a processed GPS-log showing coordinates in decimal degrees etc. The other GeoELAN commands, such as eaf2geo, always convert data to the relevant forms.

If a GoPro MP4 or a Garmin FIT-file can not be properly parsed, GeoELAN will often return an error message that may hint at the issue. Try **inspect** on files that raise errors with the other commands.

GoPro

GoPro cameras log and embed all telemetry within the MP4-files. In contrast to Garmin FIT, data types have no numerical identifier (see below) so internal text descriptions are used instead. GPS is identified as "GPS (Lat., Long., Alt., 2D speed, 3D speed)", for example.

To list all data types logged in a GoPro MP4-file, run:

```
geoelan inspect --gpmf GOPROVIDEO.MP4
```

This will list all data streams (DEVC is an internal container of sorts that holds the data listed):

```
Unique data stream types (1018 DEVC streams in total):

Accelerometer
Average luminance
Exposure time (shutter speed)
Face Coordinates and details
GPS (Lat., Long., Alt., 2D speed, 3D speed)
Gyroscope
Image uniformity
Predominant hue[[hue, weight], ...]
Scene classification[[CLASSIFIER_FOUR_CC,prob], ...]
Sensor ISO
Sensor read out time
White Balance RGB gains
White Balance temperature (Kelvin)
```

Find the data type you wish to inspect further in the list. To print GPS data in its "raw" form, run:

```
geoelan inspect --gpmf GOPROVIDEO.MP4 --type "GPS (Lat., Long., Alt., 2D speed, 3D speed)"
```

Note the citation marks. These are necessary to pass the description as a single string to GeoELAN. Your terminal shell may otherwise try to interpret anything delimited by space as a command or a parameter, which will fail. Unlike FIT, GPMF has no numerical identifier for data types.

GPS specifically, can be printed in a more conventional form via the flag --gps:

```
geoelan inspect --gpmf GOPROVIDEO.MP4 --gps
```

Generate a KML-file with:

```
geoelan inspect --gpmf GOPROVIDEO.MP4 --kml
```

DEVC byte offsets

To list the byte offsets for GPMF DEVC containers (these hold raw GPMF data), run:

```
geoelan inspect --gpmf GOPROVIDEO.MP4 --offsets
```

This returns a table listing byte offset in the MP4-file (@XXXXX), container size, and duration covered in milliseconds e.g.:

```
DEVC @332392 size: 4836 duration: 1001ms
DEVC @681939 size: 4840 duration: 1001ms
DEVC @1037851 size: 4904 duration: 1001ms
DEVC @1326489 size: 4924 duration: 1001ms
```

Images

Original GoPro JPEG-images can also be inspected. These will contain much less GPMF data than the MP4-files, and are currently not used elsewhere in GeoELAN's workflow. If no named data shows up in the summary, try geoelan inspect --gpmf GOPROIMAGE.JPG --verbose to print the raw data. Early GoPro models do not embed GPMF data in JPEG-images.

Garmin FIT

The FIT-format is quite different to GoPro's GPMF, apart from being a separate file. There is among other things, additional information about VIRB recording sessions. The VIRB starts logging to a FIT-file the moment the camera is turned on, and only stops when it is turned off. This means that a single FIT-file may contain data for multiple recording sessions. Data is logged continuously - even between recordings.

Inside a FIT-file, data is identified by a numerical identifier. For example, GPS data is 160, also referred to as <code>gps_metadata</code> in the FIT Software Development Kit (FIT SDK). <code>inspect</code> lists both identifiers in the summary table.

To list all data types logged in a VIRB FIT-file, run:

```
geoelan inspect --fit FITFILE.FIT
```

This will return a table:

Global ID	Message type	Count
0	file_id	
18	session	j 1
19	l lap	1
20	record	6209
21	event	1
22	UNKNOWN_TYPE_22	2
23	device_info	3
34	activity	1
49	file_creator	1
104	UNKNOWN_TYPE_104	104
160	gps_metadata	60114
161	camera_event	24
162	timestamp_correlation	1
164	gyroscope_data	20405
165	accelerometer_data	20405
167	. – – –	59
208	magnetometer_data	20405
209	-	6209
210	•	1 1
219	UNKNOWN_TYPE_219	1 1
• • • • • • • • • • • • • • • • • • • •	Total	: 133948

Find the data type you wish to inspect further in the list and take note note of the "Global ID". To print GPS data in its "raw" form, run:

```
geoelan inspect --fit FITFILE.FIT --type 160
```

GPS specifically, can be printed in a more conventional form via the flag --gps:

```
geoelan inspect --fit FITFILE.FIT --gps
```

Generate a KML-file with:

```
geoelan inspect --fit FITFILE.FIT --kml
```

To print a single type of data belonging to a specific recording session (VIRB only) use --session:

```
geoelan inspect --fit FITFILE.FIT --type 160 --session
```

This will return a table listing all VIRB recording sessions together with an input prompt (UUIDs

shortened to fit):

Type the number in the "Session" column for the relevant session and press enter. The output will now be limited to the selected recording session, which also applies when generating KML/GeoJSON-files.

You could also specify an original VIRB video via --video, or a UUID directly (any UUID in the session) via --uuid to achieve the same result.

To find out the embedded UUID of a VIRB MP4-file, run:

```
geoelan inspect --video VIRBVIDEO.MP4
```

This will return the embedded UUID:

```
UUID: VIRBactioncameraULTRA30_Expansive_1920_1440_29.9700_3937280306_3af2a648_1_299_2021-05-03-14-23-23.fit
```

Most FIT-files, from e.g. watches, bike computers, will work with inspect. Custom developer data is also supported. However some FIT features are exclusive to VIRB, such as UUID and selecting sessions, and other features are not implemented, such as compressed timestamp headers. In such cases, the tool will report the error and exit. Missing features may or may not be implemented in future versions.

Tip: For those who wish to dig deeper, the Garmin FIT Software Development Kit contains a spreadsheet, **Profile.xlsx**, which lists the kinds of data a FIT-file may contain. Not all of those apply to every device however, and undocumented data types exist.

Video/MP4-files

MP4-files have a few options, besides inspecting embedded GoPro GPMF data. Access these by using the --video option.

The --meta flag will show raw (i.e. bytes) content for the so-called udta atom for any MP4-file. GoPro also embeds undocumented GPMF data in the udta atom which will also be listed, whereas Garmin logs a unique identifier here. The --atoms flag will show the MP4 atom hierarchy. To most users these will not be of much use, but may provide technical context for troubleshooting. If --atoms is not enough, try the command line tool AtomicParsley.

For example, for a GoPro video run:

```
geoelan inspect --video GOPROVIDEO.MP4
```

This returns:

```
Identified as GoPro MP4 file with MUID:
[2509914837, 3557475640, 2388862468, 1050529312, 132486099, 723984, 3197894656, 0]
To inspect GPMF run 'geoelan inspect --gpmf GOPROVIDEO.MP4'
```

Then try:

```
geoelan inspect --video GOPROVIDEO.MP4 --atoms # Prints MP4 data strucutre
geoelan inspect --video GOPROVIDEO.MP4 --meta # Prints raw udta data and GPMF data if present
```

manual

- Command/alias: manual / m
- Help: geoelan manual --help
- Basic usage: geoelan manual --pdf

manual exports or prints the contents of this file to screen, bute the full PDF-manual is also embedded within the compiled executable for convenience. Running geoelan manual with no flag prints the full manual to screen.

Flags

Short	Long	Description
		Print full plain text version to screen
	pdf	Save the full manual as a PDF to
		current directory
	pdf-a4	Save the A4-guide as a PDF to
		current directory

Appendix

A few notes and help texts on ELAN, telemetry formats, video processing etc.

References

Larsson, Jens, Niclas Burenhult, Nicole Kruspe, Ross. S Purves, Mikael Rothstein and Peter Sercombe. 2020. Integrating behavioral and geospatial data on the timeline: towards new dimensions of analysis. *International Journal of Social Research Methodology*. doi: 10.1080/13645579.2020.1763705

ELAN (Version 6.4) [Computer software]. 2022. Nijmegen: Max Planck Institute for Psycholinguistics. Retrieved from https://archive.mpi.nl/tla/elan

GoPro and Garmin telemetry formats

As of GeoELAN v2.0 GoPro Hero 5 Black and newer is supported. There are significant differences between Garmin's FIT-format and GoPro's GPMF-format. Here are a few:

	Garmin FIT	GoPro GPMF
Storage form	Separate file (binary)	Embedded in MP4 (binary)
Time stamps	Explicit, absolute time stamps for	Absolute time stamps for GPS log
	each data point	only, otherwise have to be derived
		from MP4 timing

	Garmin FIT	GoPro GPMF
GPS	10Hz, individual points time	10 or 18Hz, logged in one-second
	stamped	clusters. Only the cluster is time
		stamped.

For performance reasons both GoPro GPMF and Garmin FIT are binary formats, and thus can't be viewed in a text editor.

Documentation and development

Support for GPMF (GoPro) and FIT (VIRB) formats were written from scratch for GeoELAN with the help of the official documentation for both formats.

- Garmin FIT development kit and documentation: https://developer.garmin.com/fit/
- GoPro GPMF documentation and example code: https://github.com/gopro/gpmf-parser

GoPro

File structure

GoPro recording sessions are split over multiple clips depending on recording time, quality settings, and SD card size. GoPro provide an estimate here: https://community.gopro.com/s/article/GoPro-Camera-File-Chaptering-Information?language=en_US

SD Cards

GoPro cameras use micro SD Cards. GoPro provide recommendations here:

https://community.gopro.com/s/article/microSD-Card-Considerations?language=en_US.

Internal file layout

Since Hero 5 Black all GoPro cameras use a telemetry format called GPMF developed by GoPro. Currently, the best overview can be found in their Github repository: https://github.com/gopro/gpmf-parser. (Note that GeoELAN does not make use of GoPro's parser. Instead, we developed a GPMF-parser from scratch tailored for our needs).

Garmin VIRB

Note that the Garmin VIRB Ultra 30 is no longer available for purchase. Garmin currently has no replacement product.

File structure

Example VIRB SDCard file structure:

```
DCIM

VIRB0001-1.GLV Recording session split up
VIRB0001-1.MP4 as 10 minutes clips. Low (GLV)
VIRB0001-2.GLV and high (MP4) resolution clips.

VIRB0001-2.MP4

GMetrix

2017-01-01-12-00-00.fit Telemetry files, a.k.a "FIT-files".
May contain data, such as GPS-logs, for multiple recording sessions.
```

The VIRB and the FIT-format

To pair and match VIRB video clips belonging to the same recording sessions with a FIT-file unique identifiers (UUID) are embedded both within the original video clips and the FIT-files. Preserving these are key to synchronise and extract relevant GPS-data.

When synchronising and locating data, GeoELAN will sometimes list all sessions present in the FIT-file.


As a help, the number of video clips and the *UUID for the first clip* in each session is listed.

A single FIT-file may contain telemetry for multiple recording sessions. When the camera is turned on, it immediately starts logging data into a new FIT-file, regardless of a video being recorded or not. The camera will keep logging to this file until completely turned off. If turned on again, a new FIT-file will be created. All data points in a FIT-file are explicitly timestamped, which technically allows synchronisation against any data type in the file. Further, with the help of the built-in GPS, absolute timestamps can be derived for all data types. These can be used for documentation purposes or to synchronise against external data sources.


For geo-referenced annotations, GeoELAN always embeds absolute timestamps in the resulting KML-file.

The VIRB cameras split up recording sessions into video clips, each approximately 10 minutes in length, with no option to turn this off. To link VIRB video to its corresponding telemetry (e.g. coordinates logged by the GPS during the recording session), both the clips and the FIT-file contain UUIDs. When the user starts recording, a "video recording session start" message is logged to the current FIT-file together with the UUID embedded in the first clip, denoting the start of a recording session. Similarly, when recording ends, a "video recording session end" message is logged together with the UUID embedded in the last clip in the session. Since all logged FIT-data is timestamped, this creates a timeline for the session that can be related to any logged data in the FIT-file.

Matching MP4 and FIT-files via embedded UUIDs



Logging telemetry and boundaries for a recording session in a FIT-file





The VIRB logs location, barometric pressure, and rotation among many other data types. Since the FIT-format is not a text based data format, and thus cannot be inspected using a text editor, the <code>inspect</code> command allows for some exploration of a FIT-file (see command <code>inspect</code>). GeoELAN will also help out with matching recording sessions to the corresponding FIT-files (see commands <code>virb2eaf</code>, and <code>locate</code>).

Preserving UUIDs

Concatenating or converting the video clips will usually discard the UUIDs, so the user is advised to save the original video clips. The inspect command can be used to display the UUID for a specific VIRB MP4-file, just run geoelan inspect --video VIRBVIDEO.MP4 with no other options.

Most of the commands allow for selecting UUID from those present in the relevant FIT-file when matching files or geo-referencing annotations. The **locate** command can also be used to locate all files for a specific session.

Video file management and options

On the VIRB MicroSD card, the low-resolution clips have a .GLV extension. These are generated by the VIRB for quick viewing on the internal camera display. If available, GeoELAN will prefer to link these in the ELAN-file over the high-resolution video due to their smaller size (both resolutions will still be concatenated by default). GeoELAN will not be able to identify the low-resolution .GLV as such if renamed to .MP4 and they may even be mistaken for the high-resolution versions. If you only require the low-resolution videos to be concatenated, use the --low-res-only flag when running virb2eaf. This will ignore the high-resolution .MP4-files as a concatenation target, with an option to copy these as-is (--copy) to the output directory (see the *virb2eaf* section for further information).

FFmpeg

The gopro2eaf and virb2eaf sub-commands require FFmpeg for concatenating MP4-clips and to

extract the audio track as a WAV-file (required to display a wave form in ELAN while annotating).

The video and audio streams are by default only concatenated, not converted, to avoid data loss and to save time, but note that **VIRB UUID and GoPro telemetry will still be discarded - save the original files**. See the *virb2eaf* section for more information.

There are two main options for installing FFmpeg:

- 1. Download the static build of FFmpeg, and specify its path using the --ffmpeg option
- 2. Install via a package manager. FFmpeg will be automatically available to cam2eaf in this case.

Static build The *static build* option means that the relevant media codecs are included in a single, executable file that can be used as is. The FFmpeg download page provides links to static builds for macOS, Windows and Linux. Put the downloaded ffmpeg-file in a convenient location and use the --ffmpeg option when running gopro2eaf or virb2eaf. Optionally moving or symlinking this file to a directory in PATH will yield the same result as using a package manager below.

Package manager Installing via a package manager means the ffmpeg command can be executed from anywhere in a terminal. Linux distributions usually come with one preinstalled. For macOS Homebrew is a popular choice, whereas Windows has Chocolatey (or WSL). This option means you do not have to specify the location of ffmpeg each time gopro2eaf or virb2eaf is run. If a package manager is not for you, go with the static build for your platform.

ELAN

ELAN is a completely free, advanced application for time-aligned annotations of audiovisual media developed by the The Language Archive, Max Planck Institute for Psycholinguistics in Nijmegen. While it is well-known in academia, and particularly in the humanities for transcribing recordings, its use goes well beyond this, since anything observed can be annotated, and thus time-aligned (GeoELAN is but one example). Since annotations are kept aligned in parallel on separate tiers - as many as required, similar to multi-track audio editors - the possibilites are almost endless. The ELAN

Annotation Format is XML-based which makes it both human-readable and fairly straightforward to parse.

- Download (Windows, macOS, Linux): https://archive.mpi.nl/tla/elan/download
- Documentation: https://archive.mpi.nl/tla/elan/documentation

GeoELAN Rust crates

GeoELAN is written in Rust and uses three custom libraries (aka crates) that were developed from scratch in parallel with the tool itself. This was partly due to the need to get to know the formats better, but mainly because the only existing option was to create bindings to existing libraries in several other programming languages. Since these Rust crates are still in development they are not yet available on crates.io, but can if needed be copied from the GeoELAN source and used with the Apache 2.0 license attached to GeoELAN until released properly.

Three crates were developed for GeoELAN:

- eaf-rs: Read, write, and process EAF-files. Uses quick-xml and its serialization support via serde.
- gpmf-rs: Read GoPro GPMF-files. Either directly from GoPro MP4-files, or "raw" GPMF-files (e.g. a track extracted to file with FFmpeg).
- fit-rs: Read Garmin FIT-files. Supports custom developer messages. Some added bloat due to VIRB-specific functionality that seemed better to include in fit-rs directly.
- mp4iter: A simple crate to move around, search atoms on FourCC, and read values in an MP4 container. Includes finding byte offsets for tracks (trak) via atom hdlr component name, and deriving duration for the longest track. This crate does not (and will not) support any kind of media en/decoding. See https://developer.apple.com/library/archive/documentation/QuickTime/QTFF for more information on the QuickTime/MP4 container.

Data extracted with both <code>gpmf-rs</code> and <code>fit-rs</code> will mostly require further processing. Support for this is built-in for some data types (e.g. GPS data, since this is fundamental for GeoELAN), but for others you will have to develop and expand on this yourself. A first pass, extracting and parsing data, should always work for both crates. GeoELAN's <code>inspect</code> command with the <code>--verbose</code> flag prints data in this "raw" form.

GeoELAN A4 Guide, v2.5, 2023-06-04

Jens Larsson jens.larsson@humlab.lu.se

geoelanhelp	General help
geoelan COMMANDhelp	Help for specific COMMAND, e.g. geoelan eaf2geohelp

	Workflow	Example
1.	Concatenate media files, generate ELAN-file	geoelan virb2eafvideo VIRB0001-1.MP4indir DIR_TO_SEARCH/outdir OUTDIR/
2.	Annotate the generated ELAN-file. One tier for each event type.	
3.	Geo-reference annotations on selected tier. Outputs KML/GeoJSON.	geoelan eaf2geoeaf VIRB0001-1.eaffit FITFILE.fitgeoshape point- single

Command	Description	Example
cam2eaf	[GoPro] Generate ELAN-file with geo- tier	geoelan cam2eaf -v VIDEO.MP4 -i INDIR/ -o OUTDIR/geo -tier
cam2eaf	[VIRB] Generate ELAN-file with geotier	geoelan cam2eaf -v VIDEO.MP4 -i INDIR/ -o OUTDIR/geo -tier
eaf2geo	Geo-reference annotations and generate KML-file	geoelan eaf2geo -e ELANFILE.eaf -f FITFILE.fitgeoshape point-single

Command	Description	Example
locate	Locate and match MP4 and/or FIT-files	geoelan locate -i INDIR/csv
inspect	Print the contents of a FIT/GPMF-file	<pre>geoelan inspect -f FITFILE.fitverbose</pre>
		geoelan inspect -g GOPRO_VIDEO.mp4verbose
manual	View or save manual as PDF	geoelan manualpdf

Argument	Description	Applicable to	Possible values
downsample	Point output divisor (e.g. 10: 7200 points → 720 points)	gopro2eaf,virb2eaf, eaf2geo	1 (default) to max number of logged points
geoshape	Point/s or line/s in output KML	eaf2geo	See table below
cdata	Extended information bubble in Google Earth	eaf2geo	

geoshape value	Description	Shape	Note
point-all	Points intersecting with an	Points	
	annotation will gain a		
	description		
point-multi	Points intersecting with an	Points	
	annotation will be exported		
point-single	Each annotation will be	Points	Ignoresdownsample
	averaged to a single point		
line-all	Points intersecting with an	Line, continuous	
	annotation will gain a		
	description		

geoshape value	Description	Shape	Note
line-multi	Each annotation will be	Line, broken-up	
	exported as a line		
circle-2d	Each annotation will	Circle	Ignoresdownsample
	generate a circle (c.f.		
	point-single)		
circle-3d	Each annotation will	Circle	Ignoresdownsample
	generate a cylinder (c.f.		
	point-single)		

References

Larsson, Jens, Niclas Burenhult, Nicole Kruspe, Ross. S Purves, Mikael Rothstein and Peter Sercombe. 2020. Integrating behavioral and geospatial data on the timeline: towards new dimensions of analysis. *International Journal of Social Research Methodology*. doi: 10.1080/13645579.2020.1763705

ELAN (Version 6.4) [Computer software]. 2022. Nijmegen: Max Planck Institute for Psycholinguistics. Retrieved from https://archive.mpi.nl/tla/elan