

Bulk SMS HTTP API Specification

Send bulk messages

API Used to send bulk messages.

[http://<ipaddress>:<port>/bulksms/bulksms?username=XXXXX&password=XXXXX&message=XXXXXX&type=X&dlr=X&source=XXXXX&destination=XXXXXXXXXX\[&curl=XXXXX&url=XXXXX&destport=XXXXX&tagname=XXXXXX&udf1=XXXXX&udf2=XXX&ip=XXXXXXXXX\]](http://<ipaddress>:<port>/bulksms/bulksms?username=XXXXX&password=XXXXX&message=XXXXXX&type=X&dlr=X&source=XXXXX&destination=XXXXXXXXXX[&curl=XXXXX&url=XXXXX&destport=XXXXX&tagname=XXXXXX&udf1=XXXXX&udf2=XXX&ip=XXXXXXXXX])

[http://<ipaddress>:<port>/bulksms/bulkpush?username=XXXXX&password=XXXXX&message=XXXXXX&type=X&dlr=X&source=XXXXX&destination=XXXXXXXXXX\[&curl=XXXXX&url=XXXXX&destport=XXXXX&tagname=XXXXXX&udf1=XXXXX&udf2=XXX&ip=XXXXXXXXX\]](http://<ipaddress>:<port>/bulksms/bulkpush?username=XXXXX&password=XXXXX&message=XXXXXX&type=X&dlr=X&source=XXXXX&destination=XXXXXXXXXX[&curl=XXXXX&url=XXXXX&destport=XXXXX&tagname=XXXXXX&udf1=XXXXX&udf2=XXX&ip=XXXXXXXXX])

[http://<ipaddress>:<port>/bulksms/postsms?username=XXXXX&password=XXXXX&message=XXXXXX&type=X&dlr=X&source=XXXXX&destination=XXXXXXXXXX\[&curl=XXXXX&url=XXXXX&destport=XXXXX&tagname=XXXXXX&udf1=XXXXX&udf2=XXX&ip=XXXXXXXXX\]](http://<ipaddress>:<port>/bulksms/postsms?username=XXXXX&password=XXXXX&message=XXXXXX&type=X&dlr=X&source=XXXXX&destination=XXXXXXXXXX[&curl=XXXXX&url=XXXXX&destport=XXXXX&tagname=XXXXXX&udf1=XXXXX&udf2=XXX&ip=XXXXXXXXX])

Request		Parameters
Sr. No	Parameter Name	Description
1.	username	Name of the user
2.	password	Password for the respective user
3.	message	Message content
4.	type	Indicates the type of message. Values for " type ":- 0: Plain Text 1: Flash Message 2: Unicode 3: Binary 4: WAP Push 6: Unicode Flash 8: OTA
5.	dlr	Indicates whether the client wants delivery report for this message Range of values for " dlr ":- 0: No Delivery report required 1: Delivery report required

6.	source	Sender of the message
7.	destination	Destination to which message has to be send. More than one destination has to be separated by ','
8.	curl	Client dlr url to receive delivery report of message
9.	url	Url to be send with message in case of type 4
10.	destport	Destination port is required in case of type 3 i.e binary message
11.	tagname	Tagname for the given message which will be used as unique reference for the message
12.	udf1	Any extra user defined field value
13.	udf2	Any extra user defined field value
14.	ip	Ip address of client

Response		
Sr. No	Error Codes	Description
1.	1701 <destination>:<message-id>,1701 <destination>:<message-id>,1701 <destination>:<message-id>,...	In case of message send successfully
2.	1702	One of the parameter is missing
3.	1703	Bad Username Password. Means user authentication failed
4.	1704	Bad type
5.	1705	Bad message
6.	1706	Invalid MSISDN
7.	1707	Bad source/sender
8.	1709	Bind failed
9.	1710	Unknown error
10.	1713	To many destinations
11.	1715	Response timeout
12.	1025	Insufficient user credit
13.	1028	Spam message
14.	1032	DND Destination
15.	1033	Message template mismatch
16.	1035	User opt out
17.	1041	Duplicate message
18.	1042	Explicit DND

Response:

Success response in case of url pattern /bulksms/bulksms

<ErrorCode>:<Destination>|<Messageid>,<ErrorCode>:<Destination>|<Messageid>,...

Success response in case of url pattern /bulksms/bulkpush

<ErrorCode>|<Destination>|<Messageid>|<Country>|<Operator>|<MessageCount>|<CrDed>,
<ErrorCode>|<Destination>|<Messageid>|<Country>|<Operator>|<MessageCount>|<CrDed>,
.....

Success response in case of url patten /bulksms/postsms

<Messageid>,<Messageid>.....

Response in case of failure.for url pattern /bulksms/bulksms, /bulksms/bulkpush

<ErrorCode>|<Destination>

Response in case of failure for url pattern /bulksms/postsms

<ErrorCode Description>