

Analysing inter-key intervals: Beyond means, medians and pause frequencies

Jens Roeser Sven De Maeyer Mark Torrance

Mariëlle Leijten Luuk Van Waes

jens.roeser@ntu.ac.uk


SIG 27 Conference
University of Antwerp

Dec 15, 2020


The problem: what's a pause?

- ▶ Keystroke data are heavily skewed.
- ▶ Skew reflects cognitive processes.
- ▶ How can we distinguish between fluent and disfluent key transitions?
- ▶ Fixed thresholds: 0.5 or 2 secs?
- ▶ Key transitions normal for learners might be as long as pauses of experienced writers.


Ppt id: 210 (M=290, SD=240)



Ppt id: 22 (M=145, SD=94)



Ppt id: 88 (M=242, SD=162)



The problem: what's a pause?

- ▶ Keystroke data are heavily skewed.
- ▶ Skew reflects cognitive processes.
- ▶ How can we distinguish between fluent and disfluent key transitions?
- ▶ Fixed thresholds: 0.5 or 2 secs?
- ▶ Key transitions normal for learners might be as long as pauses of experienced writers.
- ▶ Pause size depends on:
 - writing skills / style
 - position in text, sentence, word
 - experience with target language (in L2)
 - process of interest (lexical, motor, orthographic)
 - writing task

Research focus

- ▶ How do we deal with the heavy tail without losing information or, imposing pause thresholds?
- ▶ Finding a principled way to extract:
 1. by-ppt typing estimates
 2. by-ppt pause frequencies

Method

- ▶ Implementation of the copy-typing process as statistical model in Stan (Carpenter et al., [2016](#)); code based on Sorensen et al. ([2016](#)) and Vasishth et al. ([2017](#)).
- ▶ Bigram-keystroke interval data: Dutch subset of copy-task corpus (Van Waes et al., [2019](#); Van Waes et al., [2020](#))
- ▶ Lexical and non-lexical copy-typing context

Consonants task

tjxgfl pgkfkq dtdrgt npwdvf

LF-bigrams task

een chaotische cowboy

LF-bigrams task

een chaotische cowboy



e^e^n c^h^a^o^t^i^s^c^h^e c^o^w^b^o^y

LF-bigrams task

een chaotische cowboy



e^e^n c^h^a^o^t^i^s^c^h^e c^o^w^b^o^y



162 97 107 141 800 148 278 132 199 94 154 177 870 88 274 611

LF-bigrams task


een chaotische cowboy



$e^e n$ $c^h a^o t^i s^c h^e$ $c^o w^b o^y$



162 97 107 141 800 148 278 132 199 94 154 177 870 88 274 611



Baseline analysis: Mixed-Effects Model


$$y_{ij} \sim \text{LogNormal}(\alpha + u_i + w_j, \sigma_e^2)$$

Baseline analysis: Mixed-Effects Model

$$y_{ij} \sim \text{LogNormal}(\alpha + u_i + w_j, \sigma_e^2)$$


- ▶ α : population-level IKI
- ▶ σ_e^2 : error variance
- ▶ Participants: u_i
- ▶ Bigrams: w_j

Model of copy-typing: standard analysis




een chao...


Model of copy-typing: standard analysis




Model of copy-typing: mixture model




Model of copy-typing: mixture model



Model of copy-typing: mixture model



Model of copy-typing: mixture model



Finite Mixture of two log-Gaussians

$$y_{ij} \sim \theta_i \cdot \text{LogNormal}(\alpha + \delta + u_i + w_j, \sigma_{e'}^2) + \\ (1 - \theta_i) \cdot \text{LogNormal}(\alpha + u_i + w_j, \sigma_e^2)$$

- ▶ α : fluent IKI (e.g. no buffer update; no difficulty)
- ▶ δ : buffer update; other difficulty (finding correct key)
- ▶ θ : disfluency probability (by ppt i)
- ▶ $\sigma_{e'}^2$: variance larger than σ_e^2

Model comparisons

Predictive performance estimated as the *expected log predictive density* (\widehat{elpd}) (Vehtari et al., 2015, 2017). Models are ordered by predictive performance (model with highest predictive performance in top row). Standard error in parentheses.

		Consonants task		LF-bigrams task	
Models	Distribution	$\widehat{\Delta elpd}$	\widehat{elpd}	$\widehat{\Delta elpd}$	\widehat{elpd}
MoG	$2 \times$ Log-normal				
LMM	Log-normal				

Note. LMM = Linear mixed effects model; MoG = Mixture of Gaussians


Model comparisons

Predictive performance estimated as the *expected log predictive density* (\widehat{elpd}) (Vehtari et al., 2015, 2017). Models are ordered by predictive performance (model with highest predictive performance in top row). Standard error in parentheses.


		Consonants task		LF-bigrams task	
Models	Distribution	$\Delta\widehat{elpd}$	\widehat{elpd}	$\Delta\widehat{elpd}$	\widehat{elpd}
MoG	$2 \times$ Log-normal	–	-37,069 (101)	–	-33,178 (113)
LMM	Log-normal	-281 (25)	-37,350 (99)	-994 (63)	-34,173 (121)

Note. LMM = Linear mixed effects model; MoG = Mixture of Gaussians


Population estimates




Population estimates




Population estimates




Population estimates




Population estimates




By-participant (fluent) typing intervals




By-participant (fluent) typing intervals




By-participant (fluent) typing intervals




By-participant disfluency probability



By-participant disfluency probability



By-participant disfluency probability



Conclusion


- ▶ Better fit for mixture models over standard analysis.
- ▶ Capture writing process as a mixture of fluent and disfluent key transitions.
- ▶ Advantages of mixture models for writing research:
 1. map on cascading models of writing.
 2. capture disfluencies in a principled way.
 3. represent the probabilistic nature of disfluencies.
 4. provide reliable typing estimates and pause frequencies.

Thanks for listening!

email: jens.roeser@ntu.ac.uk

R-scripts, *Stan*-code, slides, preprint:

<https://github.com/jensroes/Typing-disfluency>




References I

- Almond, R., Deane, P., Quinlan, T., Wagner, M. & Sydorenko, T. (2012). *A preliminary analysis of keystroke log data from a timed writing task* (tech. rep. Research Report No. RR-12-23). Princeton, NJ, Educational Testing Service.
- Baaijen, V. M., Galbraith, D. & de Glopper, K. (2012). Keystroke analysis: Reflections on procedures and measures. *Written Communication*, 29(3), 246–277.
- Carpenter, B., Gelman, A., Hoffman, M. D., Lee, D., Goodrich, B., Betancourt, M., Brubaker, M. A., Guo, J., Li, P. & Riddell, A. (2016). Stan: A probabilistic programming language. *Journal of Statistical Software*, 20.
- Sorensen, T., Hohenstein, S. & Vasishth, S. (2016). Bayesian linear mixed models using Stan: A tutorial for psychologists, linguists, and cognitive scientists. *Quantitative Methods for Psychology*, 12(3), 175–200.


References II

- Van Waes, L., Leijten, M., Pauwaert, T. & Van Horenbeeck, E. (2019). A multilingual copy task: Measuring typing and motor skills in writing with inputlog. *Journal of open research software*, 7(30), 1–8.
- Van Waes, L., Leijten, M., Roeser, J., Olive, T. & Grabowski, J. (2020). Designing a copy task to measure typing and motor skills in writing research [submitted]. *Journal of Writing Research*.
- Vasishth, S., Chopin, N., Ryder, R. & Nicenboim, B. (2017). Modelling dependency completion in sentence comprehension as a Bayesian hierarchical mixture process: A case study involving Chinese relative clauses. *ArXiv e-prints*.
- Vehtari, A., Gelman, A. & Gabry, J. (2015). Pareto smoothed importance sampling. *arXiv preprint arXiv:1507.02646*.
- Vehtari, A., Gelman, A. & Gabry, J. (2017). Practical Bayesian model evaluation using leave-one-out cross-validation and WAIC. *Statistics and Computing*, 27(5), 1413–1432.

Disfluency typing-speed trade-off




Disfluency typing-speed trade-off




Observed vs. predicted IKIs


□ y_{obs}




Observed vs. predicted IKIs




Observed vs. predicted IKIs




Observed vs. predicted IKIs




Observed vs. predicted IKIs




Observed vs. predicted IKIs




Planning cascade in writing




Planning cascade in writing




Keystroke transitions are not normal distributed



Keystroke transitions are not normal distributed



Keystroke transitions are not normal distributed



Long intervals are not bigram specific

