ICS Engineering Manual

for an ICS Inventory System

	Name (Role/Title)
Author	Jeong Han Lee, (han.lee@esss.se)
Reviewer	TBD
Owner	ICS
Approver	ICS

Contents

Description	Engineering Manual
Document number	ESS-XXXXXXXX
Date	June 14, 2017
Revision	0.1
State	Early Draft
Classification	Public

1 Overview

1.1 Scope

- The purpose of this document is to describe how the ICS inventory system works.
- The purpose of this document is to provide the predefined bar codes in order to help users to stock any equipmen with only given bar code scanner.

1.2 Target Audience

This document is targeted to ICS engineers and technical stakeholders of the ICS inventory system.

2 Frequently Usage Case

2.1 MTCA

2.1.1 MTCA IOxOS IFC1410

2.1.2 MRF EVR-300DC

2.2 Network Device

2.2.1 MOXA Nport 6650

2.2.2 HP Network Switch

3 Predefined Bar Codes

3.1 Vendor Codes

undefined

ess

mrf

ioxos

wiener

moxa

nat

concurrent

schroff

struck

dell

samsung

hp

ibm

caen

raritan

dymo

3.2 FormFactor Codes

undefined

mtca

pcie

cpci

pmc

vme

3.3 ICS Location Codes

undefined

icslab

utgard

site

ess

3.4 Status Codes

undefined

stock

inservice

disposed

3.5 Model Codes

undefined

vme-evm-300

mtca-evr-300u

pcie-evr-300dc

Moxa-Nport-6650

Dyno-LabelWriter-450-Duo

NAT-MCH-PHYS

microSD-EVO-32G

4 Action Bar Codes

Clear all scanned PVs

——— place holder ———-

Enable Label Printing after JIRA action (JC)

Disable Label Printing after JIRA action (JC)

——— place holder ———-

Create an JIRA issue

Update an JIRA issue (Scan Hash ID and other fields first)

Delete an JIRA issue (Scan Hash ID first)

Define the Child (Scan Hash ID later)

Define the Parent (Scan Hash ID later)

——— place holder ———-

Save and append each scanned PV to CSV file which JIRA can import (per day)

Push the scanned PVs to RDB and JIRA

Push the scanned PVs to RDB

——— place holder ———-

Save and overwrite each scanned PV in each csv file (per second)

Save and overwrite each scanned PV in each json file (per second)