

## ▼ Kaggle 신용카드 사기 검출 (Google Drive Mount)

<https://www.kaggle.com/mlg-ulb/creditcardfraud>

### Credit Card Fraud Detection

- creditcard.csv (284,807 \* 31)
- Class : 0 (정상), 1 (사기)
- 사기 검출(Fraud Detection), 이상 탐지(Anomaly Detection)

```
import warnings
warnings.filterwarnings('ignore')
```

## ▼ I. Google Drive Mount

- 'creditCardFraud.zip' 파일을 구글드라이브에 업로드 후 진행

```
from google.colab import drive

drive.mount('/content/drive')

Mounted at /content/drive
```

- 마운트 결과 확인

```
!ls -l '/content/drive/My Drive/Colab Notebooks/datasets/creditCardFraud.zip'

-rw----- 1 root root 69155672 Mar  4 04:46 '/content/drive/My Drive/Colab Notebooks/dataset
```

## ▼ II. Data Preprocessing

### ▼ 1) Unzip 'creditCardFraud.zip'

- Colab 파일시스템에 'creditcard.csv' 파일 생성

```
!unzip /content/drive/My Drive/Colab Notebooks/datasets/creditCardFraud.zip

Archive: /content/drive/My Drive/Colab Notebooks/datasets/creditCardFraud.zip
  inflating: creditcard.csv
```

- creditcard.csv 파일 확인

```
!!s -l
```

```
total 147304
-rw-r--r-- 1 root root 150828752 Sep 20 2019 creditcard.csv
drwx----- 5 root root      4096 Mar  9 02:19 drive
drwxr-xr-x 1 root root      4096 Mar  5 14:37 sample_data
```

## 2) 데이터 읽어오기

- pandas DataFrame

```
%%time
```

```
import pandas as pd
```

```
DF = pd.read_csv('creditcard.csv')
```

```
DF.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 284807 entries, 0 to 284806
Data columns (total 31 columns):
#   Column      Non-Null Count  Dtype
---  -
0   Time        284807 non-null  float64
1   V1          284807 non-null  float64
2   V2          284807 non-null  float64
3   V3          284807 non-null  float64
4   V4          284807 non-null  float64
5   V5          284807 non-null  float64
6   V6          284807 non-null  float64
7   V7          284807 non-null  float64
8   V8          284807 non-null  float64
9   V9          284807 non-null  float64
10  V10         284807 non-null  float64
11  V11         284807 non-null  float64
12  V12         284807 non-null  float64
13  V13         284807 non-null  float64
14  V14         284807 non-null  float64
15  V15         284807 non-null  float64
16  V16         284807 non-null  float64
17  V17         284807 non-null  float64
18  V18         284807 non-null  float64
19  V19         284807 non-null  float64
20  V20         284807 non-null  float64
21  V21         284807 non-null  float64
22  V22         284807 non-null  float64
23  V23         284807 non-null  float64
24  V24         284807 non-null  float64
25  V25         284807 non-null  float64
```

```

26 V26      284807 non-null float64
27 V27      284807 non-null float64
28 V28      284807 non-null float64
29 Amount   284807 non-null float64
30 Class     284807 non-null int64
dtypes: float64(30), int64(1)
memory usage: 67.4 MB
CPU times: user 2.16 s, sys: 88.3 ms, total: 2.25 s
Wall time: 2.27 s

```

```
DF.head()
```

	Time	V1	V2	V3	V4	V5	V6	V7	
<b>0</b>	0.0	-1.359807	-0.072781	2.536347	1.378155	-0.338321	0.462388	0.239599	0.098
<b>1</b>	0.0	1.191857	0.266151	0.166480	0.448154	0.060018	-0.082361	-0.078803	0.085
<b>2</b>	1.0	-1.358354	-1.340163	1.773209	0.379780	-0.503198	1.800499	0.791461	0.247
<b>3</b>	1.0	-0.966272	-0.185226	1.792993	-0.863291	-0.010309	1.247203	0.237609	0.377
<b>4</b>	2.0	-1.158233	0.877737	1.548718	0.403034	-0.407193	0.095921	0.592941	-0.270

- 0 (정상) Class와 1 (사기) Class 개수

```
DF.Class.value_counts()
```

```

0    284315
1      492
Name: Class, dtype: int64

```

- 0 (정상) Class와 1 (사기) Class 비율

```
(DF.Class.value_counts() / DF.shape[0]) * 100
```

```

0    99.827251
1     0.172749
Name: Class, dtype: float64

```

### 3) Time 열(Column) 삭제

```
DF.drop('Time', axis = 1, inplace = True)
```

```
DF.head(1)
```

V1

V2

V3

V4

V5

V6

V7

V8

## ▼ 4) train\_test\_split

- X (Input), y (Output) 지정

```
X = DF.iloc[:, :-1]
y = DF.iloc[:, -1]
```

```
X.shape, y.shape
```

```
((284807, 29), (284807,))
```

### ▼ (1) Without 'stratify'

```
from sklearn.model_selection import train_test_split
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y,
                                                    test_size = 0.3,
                                                    random_state = 2045)
```

```
X_train.shape, y_train.shape, X_test.shape, y_test.shape
```

```
((199364, 29), (199364,), (85443, 29), (85443,))
```

- Train\_Data와 Test\_Data의 1 (부정) 비율이 불균형

```
print('Train_Data :', '\n', (y_train.value_counts() / y_train.shape[0]) * 100)
print('Test_Data :', '\n', (y_test.value_counts() / y_test.shape[0]) * 100)
```

```
Train_Data :
0    99.825445
1     0.174555
Name: Class, dtype: float64
Test_Data :
0    99.831467
1    0.168533
Name: Class, dtype: float64
```

### ▼ (2) With 'Stratify'

```
from sklearn.model_selection import train_test_split
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y,
```

```
test_size = 0.3,
stratify = y,
random_state = 2045)
```

```
X_train.shape, y_train.shape, X_test.shape, y_test.shape
```

```
((199364, 29), (199364,), (85443, 29), (85443,))
```

- Train\_Data와 Test\_Data의 1 (부정) 비율이 균형

```
print('Train_Data :','\n', (y_train.value_counts() / y_train.shape[0]) * 100)
print('Test_Data :','\n', (y_test.value_counts() / y_test.shape[0]) * 100)
```

```
Train_Data :
0    99.827451
1     0.172549
Name: Class, dtype: float64
Test_Data :
0    99.826785
1     0.173215
Name: Class, dtype: float64
```

### III. Modeling

#

#

#

## The End

#

#

#

✓ 0초 오전 11:19에 완료됨

