

# **Business Rule Engine**

## **Detailed Listing of Actions**

**for Jare Version 0.77**

## Table of Contents

Overview.....	3
Prerequisites.....	4
Add Leading Spaces.....	5
Add Leading Zeros.....	6
Append Value.....	7
Prepend Value.....	8
Trim Value.....	9
Concatenate Values.....	10
Lowercase Value.....	11
Uppercase Value.....	12
Replace Value.....	13
Set Value (String).....	14
Set Value (Date).....	15
Set Value (Number).....	16
Substring Value.....	17
Set Todays Date.....	18
Absolute Value.....	19
Acosinus Value.....	20
Cosinus Value.....	21
Cosinush Value.....	22
Asinus Value.....	23
Sinus Value.....	24
Sinush Value.....	25
Atangens Value.....	26
Tangens Value.....	27
Tangensh Value.....	28
Square Root Value.....	29
Square Value.....	30
Add Values.....	31
Subtract Values.....	32
Add Percentage.....	33
Subtract Percentage.....	34
Devide Values.....	35
Multiply Values.....	36
Round Value.....	37

## Overview

This document contains a detailed listing of the available actions for the Business Rule Engine „Jare“. It lists the available data types, their combinations and possible optional or required parameters.

Actions are defined on the rulegroup level. When a rulegroup fails or passes then none, one or multiple actions can be executed. Actions are executed in the sequence that they have been defined. It is also possible to define actions that are execute when the rulegroup passes and actions when the rulegroup fails at the same time.

A condition must be specified when to execute the action – when the rulegroup fails or passes. Additionally a field - and it's type - must be specified that will be updated by the action.

Sometimes an action will require additional values to be passed to it. This can either be the value of another field or a defined fixed value.

The values selected in the action from "Field to retrieve data", "Parameter 1", "Parameter 2" and "Parameter 3" are passed to the action in this sequence. The "Field to retrieve data" is optional and indicates from which other field a value should be retrieved. It can be specified but must not be.

If for example the action requires two values (arguments) then either "Field to retrieve data" and "Parameter 1" have to be specified or alternatively "Parameter 1" and "Parameter 2" (in this case "Field to retrieve data" is left blank). Then in turn the "Field to update" will be updated with the resulting value.

## **Prerequisites**

The default date format used is: yyyy-MM-dd (four digits for the year, two digits for the month and two digits for the day of the month). If not otherwise specified for String to Date conversions, it is assumed that the value is provided in this format. Date formats need to be according to the Java SimpleDateFormat Class format definitions.

All data types listed here are Java related data types.

## Add Leading Spaces

Purpose:	Add leading spaces to a value until a given length of the value is reached
Java Class:	StringAction
Interface Name:	add leading spaces

Applicable to:

Value 1	Value 2	Return Type
String	Integer	String
Note:		
Optional Value(s)	Explanation	

## Add Leading Zeros

Purpose:	Add leading zeros to a value until a given length of the value is reached
Java Class:	StringAction
Interface Name:	add leading zeros

Applicable to:

Value 1	Value 2	Return Type
String	Integer	String
Note:		
Optional Value(s)	Explanation	

## Append Value

Purpose:	Append a given value to the end of another value
Java Class:	StringAction
Interface Name:	append

Applicable to:

Value 1	Value 2	Return Type
String	String	String
String	Integer	String
String	Long	String
Note:		
Optional Value(s)	Explanation	
Value 3: String	Separator to be used between the values	

## Prepend Value

Purpose:	Prepend a given value to the start of another value
Java Class:	StringAction
Interface Name:	prepend

Applicable to:

Value 1	Value 2	Return Type
String	String	String
String	Integer	String
String	Long	String
Note:		
Optional Value(s)	Explanation	
Value 3: String	Separator to be used between the values	



## Trim Value

Purpose:	Remove all leading and trailing space characters from a String
Java Class:	StringAction
Interface Name:	trim

Applicable to:

Value 1	Value 2	Return Type
String		String
Note:		
Optional Value(s)	Explanation	

## Concatenate Values

Purpose:	Concatenate two values
Java Class:	StringAction
Interface Name:	append value

Applicable to:

Value 1	Value 2	Return Type
String	Double	String
String	Float	String
String	Long	String
String	Integer	String
String	String	String
Note:		
Optional Value(s)	Explanation	
Value 3: String	Separator to be used between the value	

## Lowercase Value

Purpose:	Change a value to it's lowercase representation
Java Class:	StringAction
Interface Name:	lowercase

Applicable to:

Value 1	Value 2	Return Type
String		String
Note:		
Optional Value(s)	Explanation	

## Uppercase Value

Purpose:	Change a value to it's uppercase representation
Java Class:	StringAction
Interface Name:	uppercase

Applicable to:

Value 1	Value 2	Return Type
String		String
Note:		
Optional Value(s)	Explanation	

## Replace Value

Purpose:	Replace a given value – or part of it - with another value
Java Class:	StringAction
Interface Name:	replace

Applicable to:

Value 1	Value 2	Return Type
String	String	String
Note: Value 2 has to contain a regular expression. All found occurrences of the regular expression will be replaced with value 3.		
Required Value(s)	Explanation	
Value 3: String	the replacement for the original value or parts of it	

## Set Value (String)

Purpose:	Sets a given value of a string
Java Class:	StringAction
Interface Name:	set value (string)

Applicable to:

Value 1	Value 2	Return Type
String		String
Note:		
Optional Value(s)	Explanation	

## Set Value (Date)

Purpose:	Sets a given value of a date
Java Class:	DateAction
Interface Name:	set value (date)

Applicable to:

Value 1	Value 2	Return Type
Date		Date
String		Date
Note:		
Optional Value(s)	Explanation	
Value 2: String	In case the given date is a String, this value optionally defines the date format of the date.	

## Set Value (Number)

Purpose:	Sets a given value of a number
Java Class:	MathAction
Interface Name:	absolute

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Float		Float
Long		Long
Integer		Integer
Boolean		Boolean
Note:		
Optional Value(s)	Explanation	



## Substring Value

Purpose:	Sets the value to a given substring
Java Class:	StringAction
Interface Name:	set value (String)

Applicable to:

Value 1	Value 2	Return Type
String	Integer	String
Note: Value 2 defines from which position of the value the substring will start		
Optional Value(s)	Explanation	
Value 3: Integer	Defines at which position the substring will end	

## Set Todays Date

Purpose:	Set the value to the current date
Java Class:	DateAction
Interface Name:	

Applicable to:

Value 1	Value 2	Return Type
String		String
Note: Value 1 contains the date format to use		
Optional Value(s)	Explanation	
Value 2: Integer	Define an offset of days – positive or negative – that will be added to the current date	

## Absolute Value

Purpose:	Calculates the absolute value of a given value
Java Class:	MathAction
Interface Name:	absolute

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Float		Float
Long		Long
Integer		Integer
Note:		
Optional Value(s)	Explanation	

## Acosinus Value

Purpose:	Calculates the acosinus of a given value
Java Class:	MathAction
Interface Name:	acosinus

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Note:		
Optional Value(s)	Explanation	

## Cosinus Value

Purpose:	Calculates the cosinus of a given value
Java Class:	MathAction
Interface Name:	cosinus

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Note:		
Optional Value(s)	Explanation	

## Cosinush Value

Purpose:	Calculates the cosinush of a given value
Java Class:	MathAction
Interface Name:	cosinush

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Note:		
Optional Value(s)	Explanation	

## Asinus Value

Purpose:	Calculates the asinus of a given value
Java Class:	MathAction
Interface Name:	asinus

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Note:		
Optional Value(s)	Explanation	

## Sinus Value

Purpose:	Calculates the sinus of a given value
Java Class:	MathAction
Interface Name:	sinus

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Note:		
Optional Value(s)	Explanation	



## Sinush Value

Purpose:	Calculates the sinush of a given value
Java Class:	MathAction
Interface Name:	sinush

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Note:		
Optional Value(s)	Explanation	

## Atangens Value

Purpose:	Calculates the atangens of a given value
Java Class:	MathAction
Interface Name:	atangens

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Note:		
Optional Value(s)	Explanation	

## Tangens Value

Purpose:	Calculates the tangens of a given value
Java Class:	MathAction
Interface Name:	tangens

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Note:		
Optional Value(s)	Explanation	

## Tangensh Value

Purpose:	Calculates the tangensh of a given value
Java Class:	MathAction
Interface Name:	tangensh

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Note:		
Optional Value(s)	Explanation	

## Square Root Value

Purpose:	Calculates the square root of a given value
Java Class:	MathAction
Interface Name:	square root

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Float		Double
Integer		Double
Long		Double
Note:		
Optional Value(s)	Explanation	

## Square Value

Purpose:	Calculates the square of a given value
Java Class:	MathAction
Interface Name:	square

Applicable to:

Value 1	Value 2	Return Type
Double		Double
Float		Double
Long		Long
Integer		Long
Note:		
Optional Value(s)	Explanation	

## Add Values

Purpose:	Calculates the sum of two values
Java Class:	MathAction
Interface Name:	sum

Applicable to:

Value 1	Value 2	Return Type
Double	Double	Double
Float	Float	Float
Integer	Integer	Integer
Integer	Long	Long
Long	Integer	Long
Long	Long	Long
Note:		
Optional Value(s)	Explanation	

## Subtract Values

Purpose:	Subtracts two values
Java Class:	MathAction
Interface Name:	subtract

Applicable to:

Value 1	Value 2	Return Type
Date	Date	Long
Double	Double	Double
Float	Float	Float
Integer	Integer	Integer
Integer	Long	Integer
Long	Integer	Long
Long	Long	Long
Note:		
Optional Value(s)	Explanation	



## Add Percentage

Purpose:	Add a percentage of a value to the value
Java Class:	MathAction
Interface Name:	add percentage

Applicable to:

Value 1	Value 2	Return Type
Double	Double	Double
Double	Float	Double
Double	Integer	Double
Integer	Double	Double
Integer	Float	Double
Integer	Integer	Double
Long	Double	Double
Long	Float	Double
Long	Integer	Double
Note:		
Optional Value(s)	Explanation	

## Subtract Percentage

Purpose:	Subtract a percentage of a value from the value
Java Class:	MathAction
Interface Name:	subtract percentage

Applicable to:

Value 1	Value 2	Return Type
Double	Double	Double
Double	Float	Double
Double	Integer	Double
Integer	Double	Double
Integer	Float	Double
Integer	Integer	Double
Long	Double	Double
Long	Float	Double
Long	Integer	Double
Note:		
Optional Value(s)	Explanation	

## Devide Values

Purpose:	Calculates the devision of two values
Java Class:	MathAction
Interface Name:	devide

Applicable to:

Value 1	Value 2	Return Type
BigDecimal	BigDecimal	BigDecimal
Double	Double	Double
Double	Integer	Double
Float	Float	Float
Integer	Integer	Double
Integer	Long	Double
Long	Integer	Double
Long	Double	Double
Long	Long	Double
Note:		
Optional Value(s)	Explanation	

## Multiply Values

Purpose:	Multiplies two values
Java Class:	MathAction
Interface Name:	multiply

Applicable to:

Value 1	Value 2	Return Type
Double	Double	Double
Double	Integer	Double
Float	Float	Float
Integer	Integer	Long
Integer	Long	Long
Long	Double	Double
Long	Integer	Long
Long	Long	Long
Note:		
Optional Value(s)	Explanation	

## Round Value

Purpose:	Rounds a given value
Java Class:	MathAction
Interface Name:	round

Applicable to:

Value 1	Value 2	Return Type
Double		Long
Float		Integer
Note:		
Optional Value(s)	Explanation	