

Lab 1b) Jercan Ioana

Lexic.txt

Alphabet:

- a. Upper (A-Z) and lower case letters (a-z) of the English alphabet;
- b. Decimal digits (0-9);
 - Special characters: + - * / = < > >= == % , [] {}
- c.

1. Special symbols:

- Operators: + - * / = < > >= == %
- Separators: space , [] {}, ()
- Reserved words: array int string char const else if then while execute read write

2. Identifiers

a sequence of letters and digits, such that the first character is a letter; the rule is:

identifier = smallletter { letter | digit | "0" }

smallletter = "a" | "b" | ... | "z"

letter = "A" | "B" | ... | "Z" | "a" | "b" | ... | "z"

digit = "0" | "1" | "2" ... | "9"

nonZerodigit = "1" | "2" ... | "9"

3. Constants:

- Integer:
Number_const = "0" | ["+" | "-"] nonZeroDigit { "0" | nonZeroDigit }
- Character:
Character = " ' " { letter | digit | special_symbol } " ' "
special_symbol = "_" | "." | " " | "!" | ",",
- String:
string_const = " \ " " { letter | digit | special_symbol } " \ "

Syntax.in

Program = declist cmpdstmt

```

decllist = declaration | declaration decllist
declaration = type IDENTIFIER ";"
vartype = "INT" | "STRING" | "CHAR"
arraydecl = "ARRAY" "[" vartype "]" "[" nr "]"
type = vartpe | arraydecl
cmpstmt = "{" stmtlist "}"
stmtlist = stmt | stmt stmtlist
stmt = simplstmt ";" | structstmt
simplstmt = assignstmt | iostmt
assignstmt = IDENTIFIER "=" expression
expression = expression "+" term | expression "-" term | term
term = term "*" factor | term "/" factor | term "%" factor | factor
factor = "(" expression ")" | list
list = IDENTIFIER | arrayelement | const
iostmt = "READ" "(" IDENTIFIER ")" | "WRITE" "(" list ")"
structstmt = cmpdstmt | ifstmt | whilestmt
ifstmt = "IF" "(" condition ")" "THEN" stmt ["ELSE" stmt]
whilestmt = "WHILE" "(" condition ")" "EXECUTE" stmt
condition = expression RELATION expression
RELATION = "<" | "<=" | "=" | ">=" | ">" | "<>"

```

Token.in

array int string const else if then while execute read write + - * / = < <= > >= == % , [] {}

```

p1. Maximum of 3 numbers
{
int a;
int b;
int c;
{
read(a);
read(b);

```

```

read(c);
int max;
max = 0;
if (a > b) then {
    max = a;
    if (max > c) {
        write(max);
    }
    else
        max = c;
}
else if (c > b) then {
    max = c;
    else
        max = b;
}
}
write(max);
}

```

p2. Checking if a number is prime

```

{
int a;
int d;
{
read(a);

d = 2;
int number;
number = a;
while (d < number) execute {
    if ( number % d == 0) then {
        prime = 0;
    }
    else
        prime = 1;
}

d = d+1;
if (prime == 0) then {
    write ("Number is not prime");
    else
        write("Number is prime");
}
}
}
p3. Sum of n numbers
{
int sum;
int n;

```

```
int a;
{
sum = 0;
read(n);
while (n > 0) {
    read(a);
    sum = sum + a;
    n = n-1;
}
    write (sum);
}
p1err.
{
int !a; //identifiers cannot have as first letter a special character, only alphabet letters
string s = "aaa;
}
```