

On this page

# Manifold API

Programmatic access to [Manifold](#).

## CAUTION

Our API was historically hosted on `https://manifold.markets/api`, but we recently moved to give the API its own domain at `api.manifold.markets`.

Please migrate any code you have to the new domain. The old domain will disappear at some point in the future.

## CAUTION

Our API is still in alpha — things may change or break at any time!

If you have questions, come chat with us on [Discord](#). We'd love to hear about what you build!

If you notice any errors or omissions in this documentation, please let us know on Discord, or fix it yourself by [submitting a pull request](#).

## Get Started

In your terminal:

```
curl "https://api.manifold.markets/v0/markets?limit=1" -X GET
```

You can also [go to the url directly](#) in your browser to see the response of any GET request.

GET requests with parameters should have the parameters in the query string. POST and PUT requests should have a body with a JSON object with one property per parameter:

```
curl "https://api.manifold.markets/v0/bet" -X POST -H 'Content-Type: application/json' \
-H 'Authorization: Key {...}' \
--data-raw '{"amount":1, \
            "outcome":"YES", \
            "contractId":"i95HLfK9N6hu5H7orfNj"}'
```

API responses should always either have a body with a JSON result object (if the response was a 200) or with a JSON object representing an error (if the response was a 4xx or 5xx).

All times are UNIX timestamps in milliseconds since epoch. (Javascript timestamps.)

As a point of naming, a topic (the tag on a question) is called a "group" in the code and in the api, and a question is called a "contract" in the code and sometimes a "market" in the api.

## Authentication

Some APIs are not associated with any particular user. Other APIs require authentication.

APIs that require authentication accept an `Authorization` header in one of two formats:

- **Authorization: Key {key}**. A Manifold API key associated with a user account. Each account may have zero or one API keys. To generate an API key for your account, visit your user profile, click "edit", and click the "refresh" button next to the API key field at the bottom. You can click it again any time to invalidate your existing key and generate a new one.
- **Authorization: Bearer {jwt}**. A signed JWT from Firebase asserting your identity. This is what our web client uses. It will probably be annoying for you to generate and we will not document it further here.

## Usage Guidelines

There is a rate limit of 500 requests per minute per IP. Please don't use multiple IP addresses to circumvent this limit.

## Licensing

Use of the Manifold API is subject to our [Terms of Service](#). Key points:

- **Permitted uses:** Building bots, automated trading systems, algorithmic tools, and integrations that interact with Manifold.
- **Prohibited uses:** Scraping the site through means other than the API; circumventing rate limits or security measures.
- **AI training data:** You may not use API data to train AI/ML models for commercial purposes without obtaining a data license from us. Academic research, personal projects, and non-commercial use are permitted. Contact [data@manifold.markets](mailto:data@manifold.markets) for commercial licensing.

We reserve the right to modify, suspend, or terminate API access at any time for abuse, excessive usage, or violation of our Terms.

## Fees

- Comments placed through the API will incur a \$M1 transaction fee.

## Data Downloads & Licensing

For bulk data downloads (historical markets, trades, comments) and commercial data licensing, see our [Data documentation](#).

## Useful resources

We're open source!

[common/src/api/schema.ts](#) - type definitions of the apis, including parameters and return values.

## Endpoints

**GET /v0/user/[username]**

Get a user by their username. Remember that usernames may change.

Requires no auth.

Response type: **User**

```
type User = {  
  id: string // user's unique id  
  createTime: number  
  
  name: string // display name, may contain spaces  
  username: string // username, used in urls  
  url: string // link to user's profile  
  avatarUrl?: string  
  
  bio?: string  
  bannerUrl?: string  
  website?: string  
  twitterHandle?: string  
  discordHandle?: string  
  
  isBot?: boolean  
  isAdmin?: boolean // is Manifold team  
  isTrustworthy?: boolean // is Moderator  
  isBannedFromPosting?: boolean  
  userDeleted?: boolean  
  
  // Note: the following are here for convenience only and may be removed  
  // in the future.  
  balance: number  
  totalDeposits: number  
  lastBetTime?: number  
  currentBettingStreak?: number  
}
```

## GET /v0/user/[username]/lite

Get basic user display info by username

Requires no auth.

Response type: `DisplayUser`

```
type DisplayUser = {  
  id: string  
  name: string // display name, may include spaces  
  username: string // username, used in urls  
  avatarUrl?: string  
}
```

## GET /v0/user/by-id/[id]

Get a user by their unique ID. Many other API endpoints return this as the `userId`.

Requires no auth.

Response type: `User`

## GET /v0/user/by-id/[id]/lite

Get a user's display info by unique ID

Requires no auth

Response type: `DisplayUser`

## **GET /v0/me**

Return the [authenticated](#) user.

Response type: `User`

## **GET /v0/user/[username]/bets (Deprecated)**

Get bets by a particular user.

Requires no auth.

*This api is deprecated in favor of the more versatile [/v0/bets/](#) api.*

## **GET /v0/get-user-portfolio**

Get a user's live portfolio metrics.

Requires no auth.

Parameters:

- `userId`: The ID of the user.

Response type: `LivePortfolioMetrics`

```
type PortfolioMetrics = {  
  investmentValue: number  
  cashInvestmentValue: number  
  balance: number  
  cashBalance: number  
  spiceBalance: number  
  totalDeposits: number  
  totalCashDeposits: number  
  loanTotal: number  
  timestamp: number // Unix timestamp in milliseconds  
  profit?: number  
  userId: string  
}  
  
type LivePortfolioMetrics = PortfolioMetrics & {  
  dailyProfit: number  
}
```

## GET /v0/get-user-portfolio-history

Get a user's portfolio history over a specified period.

Requires no auth.

Parameters:

- `userId`: The ID of the user.
- `period`: The time period for the portfolio history. Enum values: 'daily', 'weekly', 'monthly', 'allTime'.



Response type: Array of `PortfolioMetrics`

## **GET /v0/groups**

Get all topics, in order of descending creation time, 500 at a time. This endpoint returns only public topics, not curated or private ones.

Parameters:

- `beforeTime`: Optional. Get only topics created before this time.
- `availableToUserId`: Optional. Get only topics that the user has access to.

Requires no auth.

Response type: Array of `Group`

## **GET /v0/group/[slug]**

Get a topic by its slug.

Requires no auth.

## **GET /v0/group/by-id/[id]**

Get a topic by its unique ID.

Requires no auth.

## GET /v0/group/by-id/[id]/markets (Deprecated)

Get markets tagged with this topic.

Requires no auth.

*This api is deprecated in favor of the more versatile [/v0/markets](#) api below.*

## GET /v0/markets

List all markets, ordered by creation date descending.

Parameters:

- `limit`: Optional. How many markets to return. The maximum is 1000 and the default is 500.
- `sort`: Optional. One of 'created-time', 'updated-time', 'last-bet-time', or 'last-comment-time' to sort by that timestamp. Defaults to 'created-time'.
- `order`: Optional. One of 'asc' or 'desc'. Defaults to 'desc'.
- `before`: Optional. The ID of the market before which the list will start. For example, if you ask for the most recent 10 markets, and then perform a second query for 10 more markets with `before=[the id of the 10th market]`, you will get markets 11 through 20.
- `userId`: Optional. Include only markets created by this user.
- `groupId`: Optional. Include only markets tagged with this topic.

Requires no auth.

Example request:

```
curl "https://api.manifold.markets/v0/markets?limit=1" -X GET
```

Example response:

```
[
  {
    "id": "EvIhzcJXwhL0HavaszD7",
    "creatorUsername": "Austin",
    "creatorName": "Austin",
    "createdTime": 1653850472294,

    "creatorAvatarUrl": "https://lh3.googleusercontent.com/a-/A0h14GiZyl1lBehuBMGyN-mstaUtgE4xdI22lLw=s96-c",
    "closeTime": 1653893940000,
    "question": "Will I write a new blog post today?",
    "url": "https://manifold.markets/Austin/will-i-write-a-new-blog-post-today",
    "pool": 146.73022894879944,
    "probability": 0.8958175225896258,
    "p": 0.08281474972181882, //This is the probability around which the market liquidity is "centered".
    "totalLiquidity": 102.65696071594805,
    "outcomeType": "BINARY",
    "mechanism": "cpmm-1",
    "volume": 241,
    "volume24Hours": 0,
    "isResolved": true,
    "resolution": "YES",
    "resolutionTime": 1653924077078
  },
  ...
]
```

Response type: Array of `LiteMarket`

```
// Information about a market, but without bets or comments
type LiteMarket = {
  // Unique identifier for this market
  id: string

  // Attributes about the creator
  creatorId: string
  creatorUsername: string
  creatorName: string
  creatorAvatarUrl?: string

  // Market attributes
  createTime: number // When the market was created
  closeTime?: number // Min of creator's chosen date, and resolutionTime
  question: string

  // Note: This url always points to https://manifold.markets, regardless
  // of what instance the api is running on.
  // This url includes the creator's username, but this doesn't need to be
  // correct when constructing valid URLs.
  // i.e. https://manifold.markets/Austin/test-market is the same as
  // https://manifold.markets/foo/test-market
  url: string

  outcomeType: string // BINARY, FREE_RESPONSE, MULTIPLE_CHOICE, NUMERIC,
  // PSEUDO_NUMERIC, BOUNTIED_QUESTION, POLL, or ...
  mechanism: string // dpm-2, cpmm-1, or cpmm-multi-1

  probability: number
  pool: { outcome: number } // For CPMM markets, the number of shares in
```

*the liquidity pool. For DPM markets, the amount of mana invested in each answer.*

*p?: number // CPMM markets only, probability constant in  $y^p * n^{(1-p)} = k$*

*totalLiquidity?: number // CPMM markets only, the amount of mana deposited into the liquidity pool*

*value?: number // PSEUDO\_NUMERIC markets only, the current market value, which is mapped from probability using min, max, and isLogScale.*

*min?: number // PSEUDO\_NUMERIC markets only, the minimum resolvable value*

*max?: number // PSEUDO\_NUMERIC markets only, the maximum resolvable value*

*isLogScale?: bool // PSEUDO\_NUMERIC markets only, if true `number = (max - min + 1)^probability + minstart - 1`, otherwise `number = min + (max - min) \* probability`*

*volume: number*

*volume24Hours: number*

*isResolved: boolean*

*resolutionTime?: number*

*resolution?: string*

*resolutionProbability?: number // Used for BINARY markets resolved to MKT*

*uniqueBettorCount: number*

*lastUpdatedTime?: number*

*lastBetTime?: number*

*token?: 'MANA' | 'CASH' // mana or prizecash question*

*siblingContractId?: string // id of the prizecash or mana version of this question that you get to by toggling.*

*}*

## GET /v0/market/[marketId]

Get information about a single market by ID. Includes answers, but not bets and comments. Use `/bets` or `/comments` with a market ID to retrieve bets or comments.

Requires no auth.

Example request:

```
curl "https://api.manifold.markets/v0/market/3zspH9sSzMlbFQLn9GKR" -X GET
```

Example response:

```
{
  "id": "lEoqtnDgJzft6apSKzYK",
  "creatorUsername": "Angela",
  "creatorName": "Angela",
  "createdTime": 1655258914863,
  "creatorAvatarUrl": "https://firebasestorage.googleapis.com/v0/b/mantic-
markets.appspot.com/o/user-images%2FAngela%2F50463444807_edfd4598d6_o.jpeg?
alt=media&token=ef44e13b-2e6c-4498-b9c4-8e38bdaf1476",
  "closeTime": 1655265001448,
  "question": "What is good?",
  "description": "Resolves proportionally to the answer(s) which I find
most compelling. (Obviously I'll refrain from giving my own
answers)\n\n(Please have at it with philosophy, ethics, etc
etc)\n\n\nContract resolved automatically.",
  "url": "https://manifold.markets/Angela/what-is-good",
  "pool": null,
  "outcomeType": "FREE_RESPONSE",
```

```
"mechanism": "dpm-2",
"volume": 112,
"volume24Hours": 0,
"isResolved": true,
"resolution": "MKT",
"resolutionTime": 1655265001448,
"token": "MANA",
"answers": [
  {
    "createdTime": 1655258941573,
    "avatarUrl": "https://firebasestorage.googleapis.com/v0/b/mantic-
markets.appspot.com/o/user-images%2FAngela%2F50463444807_edfd4598d6_o.jpeg?
alt=media&token=ef44e13b-2e6c-4498-b9c4-8e38bdaf1476",
    "id": "1",
    "username": "Angela",
    "number": 1,
    "name": "Angela",
    "contractId": "lEoqtnDgJzft6apSKzYK",
    "text": "ANTE",
    "userId": "qe2QqIl0keWsbljfeF3MexpSJ9i2",
    "probability": 0.66749733001068
  },
  {
    "name": "Isaac King",
    "username": "IsaacKing",
    "text": "This answer",
    "userId": "y1hb6k7txdZPV5mgypPFApZ7nQl2",
    "id": "2",
    "number": 2,
    "avatarUrl":
"https://lh3.googleusercontent.com/a-/A0h14GhNVri0vxK2VUAmE-jvYZwC-
XIymatzVirT0Bqb2g=s96-c",
    "contractId": "lEoqtnDgJzft6apSKzYK",
```

```
"createdTime": 1655261198074,
"probability": 0.008922214311142757
},
{
  "createdTime": 1655263226587,
  "userId": "jbgplxty4kUKIa1MmgZk22byJq03",
  "id": "3",
  "avatarUrl": "https://firebasestorage.googleapis.com/v0/b/mantic-
markets.appspot.com/o/user-images%2FMartin%2Fgiphy.gif?
alt=media&token=422ef610-553f-47e3-bf6f-c0c5cc16c70a",
  "text": "Toyota Camry",
  "contractId": "lEqtnDgJzft6apSKzYK",
  "name": "Undox",
  "username": "Undox",
  "number": 3,
  "probability": 0.008966714133143469
},
{
  "number": 4,
  "name": "James Gruett",
  "userId": "5LZ4LgYuySdL1huCWe7bti02ghx2",
  "text": "Utility (Defined by your personal utility function.)",
  "createdTime": 1655264793224,
  "contractId": "lEqtnDgJzft6apSKzYK",
  "username": "JamesGruett",
  "id": "4",
  "avatarUrl": "https://lh3.googleusercontent.com/a-/A0h14GjC83uMe-
fEfzd6QvxiK6ZqZdlMytuHxevgMYIkpAI=s96-c",
  "probability": 0.09211463154147384
}
]
}
```



Response type: A `FullMarket`

```
// A complete market, along with answers (for free response markets)
type FullMarket = LiteMarket & {
  answers?: Answer[] // multi markets only
  shouldAnswersSumToOne?: boolean // multi markets only, whether answers
are dependant (that is add up to 100%, typically used when only one answer
should win). Always true for dpm-2 multiple choice and free response
  addAnswersMode?: 'ANYONE' | 'ONLY_CREATOR' | 'DISABLED' // multi markets
only, who can add answers

  options?: { text: string; votes: number }[] // poll only

  totalBounty?: number // bounty only
  bountyLeft?: number // bounty only

  description: JSONContent // Rich text content. See
https://tiptap.dev/guide/output#option-1-json
  textDescription: string // string description without formatting, images,
or embeds
  coverImageUrl?: string
  groupSlugs?: string[] // topics tagged in this market
}
```

## **GET /v0/slug/[marketSlug]**

Get information about a single market by slug (the portion of the URL path after the username).

Requires no auth.

Example request:

```
curl "https://api.manifold.markets/v0/slug/will-carrick-flynn-win-the-general" -X GET
```

Response type: A `FullMarket`

## GET /v0/search-markets

Search or filter markets, Similar to the [browse page](#).

Requires no auth.

Parameters:

- `term`: The search query in question. Can be empty string.
- `sort`: Optional. One of `most-popular` (default), `newest`, `score`, `daily-score`, `freshness-score`, `24-hour-vol`, `liquidity`, `subsidy`, `last-updated`, `close-date`, `start-time`, `resolve-date`, `random`, `bounty-amount`, `prob-descending`, or `prob-ascending`.
- `filter`: Optional. Closing state. One of `all` (default), `open`, `closed`, `resolved`, `news`, `closing-90-days`, `closing-week`, `closing-month`, or `closing-day`.
- `contractType`: Optional. `ALL` (default), `BINARY` (yes/no), `MULTIPLE_CHOICE` (both dependent and independent), `DEPENDENT_MULTIPLE_CHOICE` (traditional multiple choice where only one answer can be correct), `INDEPENDENT_MULTIPLE_CHOICE` (set markets where multiple answers can be YES simultaneously), `BOUNTY`, `POLL`, or ... (see code)
- `topicSlug`: Optional. Only include questions with the topic tag with this slug.

- `creatorId`: Optional. Only include questions created by the user with this id.
- `limit`: Optional. Number of contracts to return from 0 to 1000. Default 100.
- `offset`: Optional. Number of contracts to skip. Max 1000 — use `sort=newest` with `beforeTime` for deeper pagination.
- `beforeTime`: Optional. Millisecond timestamp cursor for efficient pagination with `sort=newest`. Returns only markets created before this time. Pass the `createdTime` of the last result from the previous page.
- `liquidity`: Optional. Minimum liquidity per contract (or per answer according to tier map)
- `creatorId`: Optional. Only markets from creator id.

Requires no auth.

Example request:

```
curl https://api.manifold.markets/v0/search-markets?term=biden&sort=liquidity&filter=resolved&contractType=BINARY&limit=2 -X GET
```

To paginate through all markets sorted by newest, use the `beforeTime` cursor:

```
# Page 1
curl "https://api.manifold.markets/v0/search-markets?sort=newest&limit=100"
# Page 2: pass the createdTime of the last result from page 1
curl "https://api.manifold.markets/v0/search-markets?sort=newest&limit=100&beforeTime=1706000000000"
```

Response type: Array of `LiteMarket`.

## GET /v0/market/[marketId]/prob

Get the current probability (or probabilities for multiple choice markets) for a market with max 1s cache.

Parameters:

- `id`: Required. The ID of the market.

Example request:

```
curl "https://api.manifold.markets/v0/market/9t61v9e7x4/prob" -X GET
```

Example response:

```
{  
  "prob": 0.62  
}
```

For non-binary markets (e.g. multiple choice, set) you get a dictionary of probabilities for each answer id.

Example response:

```
{  
  "answerProbs": {  
    "PI806hsqn2": 0.670156962142921,  
    "t05sp2SAlA": 0.3298430378570791  
  }  
}
```

```
}  
}
```

## GET /v0/market-probs

Get the current probabilities for multiple markets in a single request with max 1s cache.

Parameters:

- `ids`: Required. An array of market IDs, up to length 100.

Example request:

```
curl "https://api.manifold.markets/v0/market-probs?  
ids=9t61v9e7x4&ids=ZNlNdzz690" -X GET
```

Example response:

```
{  
  "9t61v9e7x4": {  
    "prob": 0.62  
  },  
  "ZNlNdzz690": {  
    "answerProbs": {  
      "answer1": 0.67,  
      "answer2": 0.33  
    }  
  }  
}
```

```
}  
}
```

## GET /v0/market/[marketId]/positions

Get positions information about a single market.

Parameters:

- `order`: Optional. `shares` or `profit` (default). The field to order results by.
- `top`: Optional. The number of top positions (ordered by `order`) to return.
- `bottom`: Optional. The number of bottom positions (ordered by `order`) to return.
- `userId`: Optional. The user ID to query by. If provided, only the position for this user will be returned.
- `answerId`: Optional. The answer ID to query by. If provided, only the positions for this answer will be returned.

Requires no auth.

Example request:

```
curl  
"https://api.manifold.markets/v0/market/kupKInoLsjMuiDiNfogm/positions?  
top=1&bottom=1" -X GET
```

Example response:

```
[
  {
    "from": {
      "day": {
        "value": 23.479030029570662,
        "profit": 0,
        "invested": 23.479030029570662,
        "prevValue": 23.479030029570662,
        "profitPercent": 0
      },
      "week": {
        "value": 0,
        "profit": 8.479030029570673,
        "invested": 15,
        "prevValue": 0,
        "profitPercent": 56.52686686380448
      },
      "month": {
        "value": 0,
        "profit": 8.479030029570673,
        "invested": 15,
        "prevValue": 0,
        "profitPercent": 56.52686686380448
      }
    },
    "loan": 1.7123642870400002,
    "payout": 23.479030029570673,
    "profit": 8.479030029570673,
    "userId": "IpTiw0Ts96VIzeoxu66tfitUcBZ2",
    "invested": 15,
    "userName": "Lucas Goldfein",
    "hasShares": true,
```

```
"contractId": "kupKInoLsjMuiDiNfogg",
"hasNoShares": true,
"lastBetTime": 1678924706057,
"totalShares": {
  "NO": 89.17418492518308
},
"hasYesShares": false,
"userUsername": "LucasGoldfein56b1",
"profitPercent": 56.52686686380448,
"userAvatarUrl":
https://lh3.googleusercontent.com/a/AEdFTp5e7cFzq1moc91CKqaAgyEleoNTjtEL9ke8c,
"maxSharesOutcome": "NO"
},
{
  "from": {
    "day": {
      "value": 5.008090894597479,
      "profit": 0,
      "invested": 5.008090894597479,
      "prevValue": 5.008090894597479,
      "profitPercent": 0
    },
    "week": {
      "value": 0,
      "profit": -4.991909105402519,
      "invested": 10,
      "prevValue": 0,
      "profitPercent": -49.919091054025195
    },
    "month": {
      "value": 0,
      "profit": -4.991909105402519,
```



```

        "invested": 10,
        "prevValue": 0,
        "profitPercent": -49.919091054025195
    }
},
"loan": 1.14157619136,
"payout": 5.008090894597481,
"profit": -4.991909105402519,
"userId": "JNkmw38JICdw6ySJ9RgWK7WyBdE2",
"invested": 10,
"userName": "Sylvie",
"hasShares": true,
"contractId": "kupKInoLsjMuiDiNfoggm",
"hasNoShares": true,
"lastBetTime": 1678914591730,
"totalShares": {
    "NO": 19.020906016751987
},
"hasYesShares": false,
"userUsername": "sylv",
"profitPercent": -49.919091054025195,
"userAvatarUrl":
https://lh3.googleusercontent.com/a/AATXAJyo0ZtkrJBItDvRE0HvcRDn8txM-\_v033jFc,
    "maxSharesOutcome": "NO"
}
]

```

Response type: An array of `ContractMetric`

```

// A single position in a market
type ContractMetric = {

```

```
contractId: string
from:
  | {
    // includes, day, week, month
    [period: string]: {
      profit: number
      profitPercent: number
      invested: number
      prevValue: number
      value: number
    }
  }
  | undefined
hasNoShares: boolean
hasShares: boolean
hasYesShares: boolean
invested: number
loan: number
maxSharesOutcome: string | null
payout: number
profit: number
profitPercent: number
totalShares: {
  [outcome: string]: number
}
userId: string
userUsername: string
userName: string
userAvatarUrl: string
lastBetTime: number
}
```

## GET /v0/get-user-contract-metrics-with-contracts

Get a user's contract metrics and their corresponding contracts, ordered by profit or last bet time. This is useful for displaying a user's portfolio.

Requires no auth. When authenticated, the response may include metrics from private markets that are visible to you.

Parameters:

- `userId`: Required. The ID of the user.
- `limit`: Required. The number of contracts to return.
- `offset`: Optional. The number of contracts to skip for pagination. Default 0.
- `order`: Optional. The sort order for the contracts. One of `lastBetTime` (default) or `profit`.
- `perAnswer`: Optional. If `true` for multiple choice markets, metrics will be returned for each answer. If `false` (default), only summary metrics for the market are returned.

Response type: an object with `metricsByContract` and `contracts`.

- `metricsByContract`: A dictionary mapping a contract ID to an array of `ContractMetric` objects.
- `contracts`: An array of `MarketContract` objects.

Example response:

```
{
  "metricsByContract": {
    "xv86CDBe0flxF2epv03f": [
```

```
{
  "from": {
    "day": {
      "value": 132936.84161688015,
      "profit": 0,
      "invested": 132936.84161688015,
      "prevValue": 132936.84161688015,
      "profitPercent": 0
    },
    "week": {
      "value": 132936.84161688015,
      "profit": 0,
      "invested": 132936.84161688015,
      "prevValue": 132936.84161688015,
      "profitPercent": 0
    },
    "month": {
      "value": 132936.84161688015,
      "profit": 0,
      "invested": 132936.84161688015,
      "prevValue": 132936.84161688015,
      "profitPercent": 0
    }
  },
  "loan": 0,
  "payout": 132936.84161688015,
  "profit": 73386.56039227714,
  "userId": "AJwLWoo3xue32XIiAVrL5SyR1WB2",
  "answerId": null,
  "invested": 63625.999354329724,
  "userName": "Ian Philips",
  "hasShares": true,
  "contractId": "xv86CDBe0flxF2epv03f",
```

```
    "totalSpent": {
      "NO": 63625.999354329724,
      "YES": 0
    },
    "hasNoShares": true,
    "lastBetTime": 1719868394000,
    "totalShares": {
      "NO": 132936.84161688015
    },
    "hasYesShares": false,
    "userUsername": "ian",
    "profitPercent": 109.48224425971169,
    "userAvatarUrl": "https://firebasestorage.googleapis.com/v0/b
    "totalAmountSold": 7480.277829512599,
    "maxSharesOutcome": "NO",
    "totalAmountInvested": 67030.55905411561
  }
]
},
"contracts": [
  {
    "p": 0.47784802346618205,
    "id": "xv86CDBe0flxF2epv03f",
    "pool": {
      "NO": 11520.402666342714,
      "YES": 1043748.1561188638
    },
    "prob": 0,
    "slug": "will-tesla-stock-reach-275-by-88-of-e836ca33649e",
    "volume": 21510052.08761673,
    "question": "Will TSLA reach >$ 275 before 8pm EST on 8/8?",
    "closeTime": 1723166651449,
    "creatorId": "nHX1qmzRItUHm3ifj7wNNR8hGf62",
```

```
"mechanism": "cpmm-1",
"viewCount": 20625,
"dailyScore": 0,
"elasticity": 1.3259613990620638,
"groupSlugs": [
  "ev",
  "tsla",
  "tesla",
  "wall-street-bets"
],
"isResolved": true,
"marketTier": "crystal",
"resolution": "N0",
"resolverId": "nHX1qmzRItUHm3ifj7wNNR8hGf62",
"visibility": "public",
"createdTime": 1715825810671,
"creatorName": "TSLABull",
"description": {
  "type": "doc",
  "content": [
    {
      "type": "paragraph",
      "content": [
        {
          "text": "text removed",
          "type": "text"
        }
      ]
    }
  ]
},
"lastBetTime": 1723187716841,
```

```
"outcomeType": "BINARY",
"probChanges": {
  "day": 0,
  "week": 0,
  "month": 0
},
"subsidyPool": 0,
"collectedFees": {
  "creatorFee": 173884.84121027112,
  "platformFee": 172931.0356998528,
  "liquidityFee": 0
},
"coverImageUrl": "https://storage.googleapis.com/mantic-markets.a
"volume24Hours": 0,
"freshnessScore": 0,
"resolutionTime": 1723166651449,
"totalLiquidity": 100000,
"conversionScore": 0.1337930700139641,
"creatorUsername": "MolbyDick",
"importanceScore": 0.0740977547170235,
"lastCommentTime": 1741622281671,
"lastUpdatedTime": 1741622283813,
"popularityScore": 0,
"creatorAvatarUrl": "https://lh3.googleusercontent.com/a-/ALV-
UjXY86BCu6RTvqG8yEFc5Y7D_S97tCf20j02Z8tVPKaaUqG14DA9PLqiLMFEeMfNIzqYYE4tIzI_B
TG4N8zJWXs8h_RcZDoD0KDs__GbJIprIrRmH0xBPqyMPjM6JiRSy1sfS72DHbE53wywXJmkbjC8pw
am1HyumXwhHQ8TmgD7hUTB7yokY1_OnpMRIYz_I26jS_8xrIRYiLTpn4tz1ehGr5MBXc52cHtH0FI
Fajv1VVUfjMr0mDhzwcB0uEArrgF0lQ1aSuwd2JN11ZJo7Y7p4gyPbmMDureFH9Ppk6xmGp53c3N5
N1_L1xoWufgpSeq0GaYVcpChDe_uWm5muiM39lzL5xdzCh5CLJn2Hsfl0bP9H_Ei2mQXM_JQa0PHt
Pp_VCPDMPg8cLpToFGPcmYguqw6Kw87iUow37UNBwG_vKFyI9_k0QWVT6dXpSSMYpts6Ui-
K0v__LGb_ybFWH0dHGR_KA_WNNWZyoH8IDbwiGhUATlBS8qTwS7MDrON0E7K2MJCxCbVQdmXFNr
wNaONG7j3nIva0XIArN1glV07JsXI0QYPkPHFnWWq0DMoq0BJHBcna922FE=s96-c",
"uniqueBettorCount": 501,
```

```
      "creatorCreatedTime": 1713057686215,  
      "initialProbability": 0.5,  
      "uniqueBettorCountDay": 0,  
      "resolutionProbability": 0.01,  
      "token": "MANA",  
      "boosted": false  
    }  
  ]  
}
```

## GET /v0/users

List all users, ordered by creation date descending.

Parameters:

- `limit`: Optional. How many users to return. The maximum is 1000 and the default is 500.
- `before`: Optional. The ID of the user before which the list will start. For example, if you ask for the most recent 10 users, and then perform a second query for 10 more users with `before=[the id of the 10th user]`, you will get users 11 through 20.

Requires no auth.

Example request:

```
curl "https://api.manifold.markets/v0/users?limit=1" -X GET
```

Example response:



```
[
  {
    "id": "igi2zGXsfxYPgB0DJTXVJVmwC0r2",
    "createdTime": 1639011767273,
    "name": "Austin",
    "username": "Austin",
    "url": "https://manifold.markets/Austin",
    "avatarUrl": "https://lh3.googleusercontent.com/a-/A0h14GiZyl1lBehuBMGyJYmstaUtgE4xdI22LLw=s96-c",
    "bio": "I build Manifold! Always happy to chat; reach out on Discord or f on https://calendly.com/austinchen/manifold!",
    "bannerUrl": "https://images.unsplash.com/photo-1501523460185-2aa5d2a0f981.2.1&ixid=MnwxMjA3fDB8MHxwaG90by1wYWdlfHx8fGVufDB8fHx8&auto=format&fit=crop&w=1000&h=1000&q=80",
    "website": "https://blog.austn.io",
    "twitterHandle": "akrolsmir",
    "discordHandle": "akrolsmir#4125",
    "balance": 9122.607163564959,
    "totalDeposits": 10339.004780544328,
    "totalPnLCached": 9376.601262721899
  }
]
```

Response type: Array of `User`

## **POST /v0/bet**

Place a new bet or limit order.

Parameters:

- `amount`: The amount to bet, in mana, before fees.
- `contractId`: The ID of the market to bet on.
- `outcome`: Optional. `YES` (default) or `NO`
- `limitProb`: Optional. Makes this a limit order. `limitProb` is a number from `0.01` to `0.99` representing the probability price to set a limit order at (like 0.01 is 1%). Can only be two decimal digits - a whole percent.

If the limit crosses the market price, the bet will execute immediately in the direction of `outcome` up to the limit. If not all the bet is filled, the rest will remain as an open limit order.

- For example, if the current market probability is `50%`:
  - A `M$10` bet on `YES` with `limitProb=0.4` would not be filled until the market probability moves down to `40%` and someone bets `M$15` of `NO` to match your bet odds.
  - A `M$100` bet on `YES` with `limitProb=0.6` would fill partially or completely depending on current unfilled limit bets and the AMM's liquidity. Any remaining portion of the bet not filled would remain to be matched against in the future.
- An unfilled limit order bet can be cancelled using the cancel API.
- `expiresAt`: Optional. When the limit order should be automatically canceled.
- `expiresMillisAfter`: Optional. Milliseconds after creation when the limit order should be automatically canceled.
- `dryRun`: Optional. If true, the bet will not be placed and the API will return a simulated result.

Requires Auth.

Example request

```
curl -X POST https://api.manifold.markets/v0/bet \  
-H 'Authorization: Key YOUR_API_KEY' \  
-H 'Content-Type: application/json' \  
-d '{  
  "amount": 10,  
  "contractId": "CONTRACT_ID_HERE",  
  "outcome": "YES",  
  "limitProb": 0.70,  
  "expiresMillisAfter": 86400000  
}'
```

Response type: A `Bet`.

## POST /v0/multi-bet

Place multiple YES bets on a sums-to-one multiple choice market, targeting the same number of shares on each selected answer.

This is only available on `cpmm-multi-1` markets with `shouldAnswersSumToOne=true` and requires at least two answers in the market. The provided `amount` is spent across the selected answers to purchase equal shares per answer at execution time. If a `limitProb` is provided, each leg will only execute up to that price; any unfilled remainder stays as open limit orders until `expiresAt` or cancellation.

Parameters:

- `contractId`: The ID of the market to bet on.
- `answerIds`: Array of answer IDs to buy on. Minimum length 2. Market must have `shouldAnswersSumToOne=true`.
- `amount`: Total amount to spend across the selected answers.
- `limitProb`: Optional. A number from `0.01` to `0.99` with two decimal places (whole percentage points). Acts as a per-leg limit price.
- `expiresAt`: Optional. Unix timestamp (ms). Any unfilled portion will be canceled at this time.

#### Notes:

- Only `YES` is supported; `outcome` is implicitly `YES`.
- The API returns only the primary bets on the selected answers. Internal arbitrage trades created to keep probabilities summing to 100% are not included in the response.

#### Example request:

```
curl -X POST https://api.manifold.markets/v0/multi-bet \  
-H 'Authorization: Key YOUR_API_KEY' \  
-H 'Content-Type: application/json' \  
-d '{  
  "contractId":"tQudZcEtIp",  
  "amount":100,  
  "answerIds":["Ncus9Qtty2","CAqyQ8A0Sn","Pc860AUEsn"]  
}'
```

#### Example response (array of bets, one per selected answer):

```
[
  {
    "orderAmount": 100.00000000000003,
    "amount": 33.333333333333286,
    "shares": 125.88308682212488,
    "isFilled": true,
    "fills": [
      {
        "matchedBetId": null,
        "shares": 110.27413685175395,
        "amount": 33.333333333333286,
        "timestamp": 1755718208318,
        "fees": {
          "creatorFee": 0,
          "platformFee": 0,
          "liquidityFee": 0
        }
      },
      {
        "matchedBetId": null,
        "shares": 15.313505455862867,
        "amount": 0,
        "timestamp": 1755718208324,
        "fees": {
          "creatorFee": 0,
          "platformFee": 0,
          "liquidityFee": 0
        }
      },
      {
        "matchedBetId": null,
        "shares": 0.29544451450806264,
```

```
    "amount": 0,
    "timestamp": 1755718208329,
    "fees": {
      "creatorFee": 0,
      "platformFee": 0,
      "liquidityFee": 0
    }
  },
  "contractId": "tQudZcEtIp",
  "outcome": "YES",
  "isCancelled": false,
  "loanAmount": 0,
  "answerId": "Ncus9Qtty2",
  "probBefore": 0.2568360631674096,
  "probAfter": 0.2721147216493064,
  "createdTime": 1755718208333,
  "fees": {
    "creatorFee": 0,
    "platformFee": 0,
    "liquidityFee": 0
  },
  "isRedemption": false,
  "visibility": "public",
  "betId": "z12cULd0yq5N",
  "betGroupId": "05bd5240dfca66b2556b77e8"
},
{
  "orderAmount": 100.00000000000003,
  "amount": 33.33333333333334,
  "shares": 125.88308682212511,
  "isFilled": true,
  "fills": [
```

```
{
  "matchedBetId": null,
  "shares": 110.27413685175412,
  "amount": 33.3333333333334,
  "timestamp": 1755718208318,
  "fees": {
    "creatorFee": 0,
    "platformFee": 0,
    "liquidityFee": 0
  }
},
{
  "matchedBetId": null,
  "shares": 15.31350545586281,
  "amount": 0,
  "timestamp": 1755718208324,
  "fees": {
    "creatorFee": 0,
    "platformFee": 0,
    "liquidityFee": 0
  }
},
{
  "matchedBetId": null,
  "shares": 0.2954445145081763,
  "amount": 0,
  "timestamp": 1755718208330,
  "fees": {
    "creatorFee": 0,
    "platformFee": 0,
    "liquidityFee": 0
  }
}
```

```
],
"contractId": "tQudZcEtIp",
"outcome": "YES",
"isCancelled": false,
"loanAmount": 0,
"answerId": "CAqyQ8A0Sn",
"probBefore": 0.2568360631674102,
"probAfter": 0.27211472164930733,
"createdTime": 1755718208333,
"fees": {
  "creatorFee": 0,
  "platformFee": 0,
  "liquidityFee": 0
},
"isRedemption": false,
"visibility": "public",
"betId": "hAnEp02d0spd",
"betGroupId": "05bd5240dfca66b2556b77e8"
},
{
  "orderAmount": 100.00000000000003,
  "amount": 33.33333333333334,
  "shares": 125.88308682212511,
  "isFilled": true,
  "fills": [
    {
      "matchedBetId": null,
      "shares": 110.27413685175384,
      "amount": 33.33333333333334,
      "timestamp": 1755718208318,
      "fees": {
        "creatorFee": 0,
        "platformFee": 0,
```



```
      "liquidityFee": 0
    },
  },
  {
    "matchedBetId": null,
    "shares": 15.313505455863208,
    "amount": 0,
    "timestamp": 1755718208324,
    "fees": {
      "creatorFee": 0,
      "platformFee": 0,
      "liquidityFee": 0
    }
  },
  {
    "matchedBetId": null,
    "shares": 0.29544451450806264,
    "amount": 0,
    "timestamp": 1755718208330,
    "fees": {
      "creatorFee": 0,
      "platformFee": 0,
      "liquidityFee": 0
    }
  }
],
"contractId": "tQudZcEtIp",
"outcome": "YES",
"isCancelled": false,
"loanAmount": 0,
"answerId": "Pc860AUEsn",
"probBefore": 0.25683606316740987,
"probAfter": 0.27211472164930683,
```

```
"createdTime": 1755718208333,  
"fees": {  
  "creatorFee": 0,  
  "platformFee": 0,  
  "liquidityFee": 0  
},  
"isRedemption": false,  
"visibility": "public",  
"betId": "p9L5NP009tCz",  
"betGroupId": "05bd5240dfca66b2556b77e8"  
}  
]
```

Response type: Array of `Bet`-like objects (same fields as a `Bet`) with additional `betId` and `betGroupId`.

## **POST /v0/bet/cancel/[id]**

Cancel a limit order.

## **POST /v0/market**

Create a new market.

This costs mana:

| Market Type     | Creation Cost                               |
|-----------------|---------------------------------------------|
| BINARY          | M\$50                                       |
| PSEUDO_NUMERIC  | M\$250                                      |
| MULTIPLE_CHOICE | M\$25/answer or M\$25 for no preset answers |

Parameters:

- `outcomeType`: `BINARY`, `MULTIPLE_CHOICE`, `PSEUDO_NUMERIC`, `POLL`, or `BOUNTIED_QUESTION`.
- `question`: The headline question for the market.
- `description`: Optional. A description for the market. Note: for formatted text instead use:
  - `descriptionHtml`: string with html
  - `descriptionMarkdown`: string with markdown
  - `descriptionJson`: stringified [TipTap json](#)
- `closeTime`: Optional. When the market will close. Defaults to 7 days from now.
- `visibility`: Optional. `public` (default) or `unlisted`. Controls whether the market can be shown on homepage and in search results.
- `groupIds`: Optional. An array of topics to tag this market with.
- `extraLiquidity`: Optional.

For binary markets, you must also provide:

- `initialProb`: An initial probability for the market, between 1 and 99.

For numeric markets, you must also provide:

- `min`: The minimum value that the market may resolve to.
- `max`: The maximum value that the market may resolve to.
- `isLogScale`: If true, your numeric market will increase exponentially from min to max.
- `initialValue`: An initial value for the market, between min and max, exclusive.

For multiple choice markets, you must also provide:

- `answers`: An array of strings, each of which will be a valid answer for the market.
- `addAnswersMode`: Optional. Controls who can add answers to the market after it has been created. Must be one of `'DISABLED' | 'ONLY_CREATOR' | 'ANYONE'`. Defaults to `'DISABLED'`.
- `shouldAnswersSumToOne`: Optional. If `true`, makes this market auto-arbitrage so that probabilities add up to 100% and restricts market resolution accordingly.

For bountied questions, you must also provide:

- `totalBounty`: The total amount of mana to be distributed to the best answers.

For polls, you must also provide:

- `answers`: An array of strings, each of which will be an option for the poll.

Requires Auth.

Response type: `LiteMarket`

## **POST /v0/market/[marketId]/answer**

Add a valid answer for the market. Currently only supports `MULTIPLE_CHOICE` markets.

Parameter:

- `text`: The answer text.

Requires Auth.

## **POST /v0/market/[marketId]/add-liquidity**

Add mana to liquidity pool. Does not boost.

Parameter:

- `amount`: Amount of M\$ to add

Requires Auth.

## **POST /v0/market/[marketId]/add-bounty**

Add mana to a bounty question's reward.

Parameters:

- `amount`: Amount of M\$ to add

Requires Auth.

Response type: Txn

## **POST /v0/market/[marketId]/award-bounty**

Distribute a bounty market reward.

Parameters:

- `amount`: Amount of M\$ to add
- `commentId`: The comment to award the bounty to.

Requires Auth.

Response type: Txn

## **POST /v0/market/[marketId]/close**

Set the close time of a market.

Parameter:

- `closeTime`: Optional. Milliseconds since the epoch to close the market at. If not provided, close the market immediately.

Requires Auth.

## **POST /v0/market/[marketId]/group**

Add or remove a topic tag from a market.

Parameters:

- `groupId`: The ID of the topic.
- `remove`: Optional. Set to `true` to un-tag the topic.

**Requires Auth.** Must be admin/moderator/creator of topic if curated/private. Must be market creator or site moderator if topic is public.

## POST /v0/market/[marketId]/resolve

Resolve a market. The required payload format depends on the market type.

### For Binary Markets

- **outcome**: One of `YES`, `NO`, `MKT`, or `CANCEL`.
- **probabilityInt** (optional): The probability to use for a `MKT` resolution.

### For Free Response or Multiple Choice Markets

The resolution payload format depends on the market's `shouldAnswersSumToOne` setting:

**1. When `shouldAnswersSumToOne` is true (the default for dpm-2 free response and multiple choice):**

Use the weighted resolution format:

```
{
  "outcome": "MKT", // or CANCEL, or a number indicating the selected
                    answer index
  "resolutions": [
    { "answer": <number>, "pct": <number> }
  ]
}
```

- Each object in the `resolutions` array assigns a weight (`pct`) to an answer (indicated by its index). The weights must add up to 100.

## 2. When `shouldAnswersSumToOne` is false:

Resolve each answer individually, as you would for a binary market. For each answer, issue a separate resolve request with a payload that includes:

- **outcome:** Either `"YES"` (if the answer is resolved as a win) or `"NO"` (if resolved as a loss).
- **answerId:** The unique identifier for the answer (as returned in the full market's `answers` array).

For example, to resolve an individual answer:

```
{
  "outcome": "YES", // or "NO"
  "answerId": "<answerId>"
}
```



This approach treats each answer as an independent binary resolution, ensuring that the actual answer identifier is included in the payload.

### For Numeric Markets

- **outcome:** Either `CANCEL` or a number indicating the selected numeric bucket ID.
- **value:** The value that the market resolves to.
- **probabilityInt:** Required if `value` is provided. It should equal:
  - For log scale:  $\log_{10}(\text{value} - \text{min} + 1) / \log_{10}(\text{max} - \text{min} + 1)$
  - Otherwise:  $(\text{value} - \text{min}) / (\text{max} - \text{min})$

Requires Auth.

## POST /v0/market/[marketId]/sell

Sell shares in a market.

Parameters:

- **outcome:** `YES` or `NO`. Which kind of shares you are selling - defaults to the kind you have.
- **shares:** Optional. How many shares you are selling - defaults to all.
- **answerId:** Required on multi choice. The ID of the answer you are selling your position in.

Requires Auth.

## POST /v0/comment

Create a comment in the specified market. Only supports top-level comments for now.

### Parameters:

- `contractId`: The ID of the market to comment on.
- `content`: The comment to post, formatted as [TipTap json](#), OR
- `html`: The comment to post, formatted as an HTML string, OR
- `markdown`: The comment to post, formatted as a markdown string.

Requires Auth.

## GET /v0/comments

Get a list of comments for a contract or user, ordered by creation date descending.

### Parameters:

- `contractId`: Optional. The ID of the market to read comments of.
- `contractSlug`: Optional. The slug of the market to read comments of.
- `limit`: Optional. How many comments to return. The default and maximum are both 1000.
- `page`: Optional. For pagination with `limit`
- `userId`: Optional. Get only comments created by this user.
- `order`: Optional. One of [`likes`, `newest`, `oldest`]

Requires no auth.

## GET /v0/bets

Gets a list of bets, ordered by creation date descending.

## Parameters:

- `userId`: Optional. Include only bets by the user with this ID.
- `username`: Optional. Include only bets by the user with this username.
- `contractId`: Optional. Include only bets on the market with this ID. Can be multiple ids.
- `contractSlug`: Optional. Include only bets on the market with this slug.
- `limit`: Optional. How many bets to return. The default and maximum are both 1000.
- `before`: Optional. Include only bets created before the bet with this ID.
  - For example, if you ask for the most recent 10 bets, and then perform a second query for 10 more bets with `before=[the id of the 10th bet]`, you will get bets 11 through 20.
- `after`: Optional. Include only bets created after the bet with this ID.
  - For example, if you request the 10 most recent bets and then perform a second query with `after=[the id of the 1st bet]`, you will receive up to 10 new bets, if available.
- `beforeTime`: Optional. Include only bets created before this timestamp.
- `afterTime`: Optional. Include only bets created after this timestamp.
- `kinds`: Optional. Specifies subsets of bets to return. Possible kinds: `open-limit` (open limit orders, including ones on closed and resolved markets).
- `order`: Optional. `asc` or `desc` (default). The sorting order for returned bets.

## Example request:

```
curl "https://api.manifold.markets/v0/bets?
username=Manifold&contractSlug=will-i-be-able-to-place-a-limit-ord" -X GET
```

Response type: An array of `Bet`.

Example response:

```
[
  // Limit bet, partially filled.
  {
    "isFilled": false,
    "amount": 15.596681605353808, //The amount that has already been
    filled.
    "userId": "IPT0zEqrpkWmEzh6hwvAyY9PqFb2",
    "contractId": "Tz5dA01GkK50KiQfZeDL",
    "probBefore": 0.5730753474948571,
    "isCancelled": false,
    "outcome": "YES",
    "fees": { "creatorFee": 0, "liquidityFee": 0, "platformFee": 0 },
    "shares": 31.193363210707616,
    "limitProb": 0.5,
    "id": "yXB8lVbs86TKkhWA1FVi",
    "loanAmount": 0,
    "orderAmount": 100, //The original amount placed on the limit order
    when it was created. The amount remaining can be calulated as orderAmount -
    amount.
    "probAfter": 0.5730753474948571,
    "createdTime": 1659482775970,
    "fills": [
      {
        "timestamp": 1659483249648,
        "matchedBetId": "MfrMd5HTiGASDXzqibr7",
        "amount": 15.596681605353808,
        "shares": 31.193363210707616
      }
    ]
  }
],
```

```
// Normal bet (no limitProb specified).
{
  "shares": 17.350459904608414,
  "probBefore": 0.5304358279113885,
  "isFilled": true,
  "probAfter": 0.5730753474948571,
  "userId": "IPT0zEqrpkWmEzh6hwvAyY9PqFb2",
  "amount": 10,
  "contractId": "Tz5dA01GkK5QKiQfZeDL",
  "id": "1LPJHNz5oAX4K6YtJlP1",
  "fees": {
    "platformFee": 0,
    "liquidityFee": 0,
    "creatorFee": 0.4251333951457593
  },
  "isCancelled": false,
  "loanAmount": 0,
  "orderAmount": 10,
  "fills": [
    {
      "amount": 10,
      "matchedBetId": null,
      "shares": 17.350459904608414,
      "timestamp": 1659482757271
    }
  ],
  "createdTime": 1659482757271,
  "outcome": "YES"
}
```

## GET /v0/managrams (Deprecated)

Gets a list of managrams, ordered by creation time descending.

Parameters:

- `toId`: Optional. Returns managrams sent to this user.
- `fromId`: Optional. Returns managrams sent from this user.
- `limit`: Optional. How many managrams to return. The maximum and the default are 100.
- `before`: Optional. The `createdTime` before which you want managrams
- `after`: Optional. The `createdTime` after which you want managrams

Requires no auth.

*This api is deprecated in favor of the more versatile [/v0/txns/](#) api below.*

## **POST /v0/managram**

Send mana to another user.

Parameters:

- `toIds`: An array of user IDs to send to.
- `amount`: The amount of mana (must be  $\geq 10$ ) to send to each user.
- `message`: Optional. A message to include.

## **GET /v0/leagues**

Get a list of league standings for a particular user or season.

### Parameters:

- `userId`: Optional. Returns only leagues for this user.
- `season`: Optional. Number. Returns only a particular season.
- `cohort`: Optional. String. The snake-cased quirky name of a league - returns only this particular league

Requires no auth.

## **GET /v0/txns**

Get a list of transactions, ordered by creation date descending.

### Parameters:

- `token`: Optional. Type of token (e.g., 'CASH', 'MANA')
- `offset`: Optional. Number of records to skip (for pagination). Default is 0.
- `limit`: Optional. Maximum number of records to return. The default and maximum are both 100.
- `before`: Optional. Include only transactions created before this timestamp.
- `after`: Optional. Include only transactions created after this timestamp.
- `toId`: Optional. Include only transactions to the user with this ID.
- `fromId`: Optional. Include only transactions from the user with this ID.
- `category`: Optional. Include only transactions of this category.

Requires no auth.

Example request:

```
curl "https://api.manifold.markets/v0/txns?limit=10&category=MANA_PAYMENT"  
-X GET
```

Response type: An array of `Txn`.

Example response:

```
[  
  {  
    "id": "INKcoBUVT914i1XUJ6rG",  
    "data": {  
      "groupId": "e097e0c5-3ce0-4eb2-9ca7-6554f86b84cd",  
      "message": "Puzzles for Progress",  
      "visibility": "public"  
    },  
    "toId": "AJwLWoo3xue32XIiAVrL5SyR1WB2",  
    "token": "M$",  
    "amount": 2500,  
    "fromId": "j07sUhIDTQbAJ3w86akzncTlpRG2",  
    "toType": "USER",  
    "category": "MANA_PAYMENT",  
    "fromType": "USER",  
    "createdTime": 1695665438987,  
    "description": "Mana payment 2500 from MichaelWheatley to  
j07sUhIDTQbAJ3w86akzncTlpRG2"  
  },  
  ...  
]
```



Note: This API corresponds to the `txns` postgres table and does not include bets and liquidity injections.

## GET /v0/get-boost-history

Get a paginated list of all contract and post boosts, including whether each boost was paid with mana, cash, or granted for free.

Requires no auth.

Parameters:

- `contractId`: Optional. Only return boosts for this contract.
- `postId`: Optional. Only return boosts for this post.
- `userId`: Optional. Only return boosts created by this user.
- `includePending`: Optional. Include unfunded cash boosts that have not completed payment yet. Defaults to `false`.
- `limit`: Optional. Number of boosts to return. Default `100`, max `1000`.
- `offset`: Optional. Number of boosts to skip. Default `0`.

Response type:

```
type BoostHistoryEntry = {  
  id: number  
  contentType: 'contract' | 'post'  
  contentId: string  
  contractId: string | null  
  postId: string | null
```

```
title: string
slug: string | null
url: string | null
userId: string
userName: string
userUsername: string
createdTime: number
startTime: number
endTime: number
funded: boolean
paymentType: 'free' | 'mana' | 'cash'
isFree: boolean
manaPurchaseTxnId: string | null
}
```

Example request:

```
curl "https://api.manifold.markets/v0/get-boost-history?
limit=50&includePending=true"
```

## Websockets

Manifold provides a real-time websocket server that allows you to subscribe to updates about markets, bets, and other events. The websocket endpoint is available at

`wss://api.manifold.markets/ws` and `wss://api.dev.manifold.markets/ws`.

## Message Format

All messages sent to and from the server must be valid JSON strings. Each client message must include:

- `type`: The type of message ('identify', 'subscribe', 'unsubscribe', or 'ping')
- `txid`: A unique number identifying this message

The server will respond to each client message with an acknowledgement:

```
{
  "type": "ack",
  "txid": 123,
  "success": true
}
```

## Subscribing to Topics

To subscribe to updates, send a message with:

```
{
  "type": "subscribe",
  "txid": 123,
  "topics": ["global/new-bet", "contract/[marketId]"]
}
```

Available topics:

### Global topics

- `global/new-bet` - All new bets across all markets
- `global/new-contract` - All new markets being created
- `global/new-comment` - All new comments across all markets
- `global/new-subsidy` - All new liquidity subsidies
- `global/updated-contract` - Updates to any public market

### Per-contract topics (replace `[marketId]` with the actual market ID)

- `contract/[marketId]` - General market updates
- `contract/[marketId]/new-bet` - New bets on this market
- `contract/[marketId]/new-comment` - New comments on this market
- `contract/[marketId]/new-subsidy` - New liquidity subsidies on this market
- `contract/[marketId]/new-answer` - New answers added to this market (for multiple choice markets)
- `contract/[marketId]/updated-answers` - Updates to answers on this market
- `contract/[marketId]/orders` - Updates to limit orders on this market
- `contract/[marketId]/chart-annotation` - New chart annotations on this market
- `contract/[marketId]/user-metrics/[userId]` - Updates to a user's position in this market

### Other topics

- `user/[userId]` - Updates to a user's public information
- `answer/[answerId]/update` - Updates to a specific answer
- `tv_schedule` - Updates to the TV schedule

## Example Usage

Here's an example of how to connect and subscribe to global bet updates using Node.js:

```
import { APIRealtimeClient } from 'common/api/websocket-client'

const client = new APIRealtimeClient('wss://api.manifold.markets/ws')

// Subscribe to all new bets
client.subscribe(['global/new-bet'], (msg) => {
  console.log('New bet:', msg.data)
})

// Subscribe to a specific market's updates
client.subscribe(['contract/1234'], (msg) => {
  console.log('Market update:', msg.data)
})
```

Or using plain WebSocket:

```
const ws = new WebSocket('wss://api.manifold.markets/ws')
let txid = 0

ws.onopen = () => {
  // Subscribe to global bets
  ws.send(
    JSON.stringify({
      type: 'subscribe',
      txid: txid++,
      topics: ['global/new-bet'],
    })
  )
}
```

```
)  
}  
  
ws.onmessage = (event) => {  
  const msg = JSON.parse(event.data)  
  if (msg.type === 'broadcast') {  
    console.log('Received broadcast:', msg.data)  
  }  
}  
  
// Send periodic pings to keep connection alive  
setInterval(() => {  
  ws.send(  
    JSON.stringify({  
      type: 'ping',  
      txid: txid++,  
    })  
  )  
}, 30000)
```

The server will send broadcast messages in this format:

```
{  
  "type": "broadcast",  
  "topic": "global/new-bet",  
  "data": {  
    // Bet data  
  }  
}
```

Note: The websocket connection requires periodic pings (every 30-60 seconds) to stay alive. If no ping is received for 60 seconds, the connection will be terminated.

## Internal API

Manifold has some internal API endpoints that are not part of the official API. These are largely undocumented, but a few are mentioned here for third-party use until a more permanent solution is implemented. These endpoints are not preceded by `/v0` and are even more subject to sudden changes than the official API endpoints.

### **POST** `/unresolve`

Unresolves a market. Requires auth.

Parameters:

- `contractId`: The ID of the market to unresolve.

## Changelog

- 2026-03-09: Add `/get-boost-history` documentation
- 2024-10-30: Remove undefined parameter from `/v0/market/[marketId]/sell` and remove `sell-shares-dpm` endpoint
- 2023-12-19: Formatting & copy improvements. Updated parameters and return types.
- 2023-12-18: `manifold.markets/api` -> `api.manifold.markets`. Please migrate old code.
- 2023-12-12: New flat api structure (reverted)

- 2023-10-27: Update `/search-markets` to allow all the same search options as our search
- 2023-09-29: Add `/managrams` and `/managram` endpoints
- 2023-05-15: Change the response of the `/market/{marketId}/sell` POST endpoint from `{"status": "success"}` to a full `Bet`, with an additional `"status": "success"` field
- 2023-04-03: Add `/market/[marketId]/group` POST endpoint.
- 2023-03-21: Add `/market/[marketId]/positions` and `/search-markets` endpoints
- 2022-11-22: Update `/market` GET to remove `bets` and `comments`
- 2022-10-17: Update `/market` POST to allow `visibility` and `groupId`; mark `closeTime` as optional; remove `tags`
- 2022-09-24: Expand market POST docs to include new market types (`PSEUDO_NUMERIC`, `MULTIPLE_CHOICE`)
- 2022-07-15: Add user by username and user by ID APIs
- 2022-06-08: Add paging to markets endpoint
- 2022-06-05: Add new authorized write endpoints
- 2022-02-28: Add `resolutionTime` to markets, change `closeTime` definition
- 2022-02-19: Removed user IDs from bets
- 2022-02-17: Released our v0 API, with `/markets`, `/market/[marketId]`, and `/slug/[slugId]`

 [Edit this page](#)