

Metaculus API

2.0.0 OAS3

</static/openapi.ecb2b0e1cd96.yml>

Welcome to the official Metaculus API!

API Data Access

The following data access restrictions and request throttling apply to the main Metaculus instance at metaculus.com. If you are running a custom instance, these restrictions do not apply.

⚠ All API requests require valid authentication credentials. Unauthenticated requests will be rejected with an authentication error. Ensure you include your API token in the **Authorization** header for all requests. See the "How to Authenticate" section below for setup instructions.

All Authenticated Accounts

All users, given authentication, have access to the following data via the API:

- **Your own data:** Your predictions, scores, comments, and other personal data are always available.
- **Question text & resolution values:** Open question text is always available. For closed questions, you can access the text and resolution value of any question you have predicted on.
- **Staff comments:** Comments authored by Metaculus staff are available. To access comments, you must filter by **author** (your own user ID) or **author_is_staff=true**.
- **Community Prediction (limited):** The current value of the Community Prediction is available on a small set of ~50 questions. On all other questions, aggregation data (Community Prediction and other aggregates) is not included in API responses.

Bot Benchmarking Access Tier

An additional access tier is available for bot makers. This tier grants current Community Prediction, question text, and resolution access on a larger set of ~250 open questions and ~250 resolved questions, intended for training and evaluation purposes. To request access, please email api-requests@metaculus.com.

Non-commercial & Commercial Use

If you want to make non-commercial use of Metaculus data (scientific, hobbyist, etc.), please get in touch — we generally welcome such projects. For commercial use inquiries, also contact us at api-requests@metaculus.com.

If you have questions, ideas, or feedback, please contact our team at api-requests@metaculus.com. We are excited to keep building upon this initial version of the API, and we'd like to keep making it more useful to you. Our aim is to support the forecasting community – we're listening!

Get Started in 15 Seconds

1. Most of the API is (hopefully) self-explanatory. You'll find all the documentation below.
2. If you're testing the waters or doing a one-off analysis, you can dive right in!
3. If you're building an application that connects to the Metaculus API, you'll need to authenticate.

How to Authenticate

You can see your current API token (or generate one) at your [settings](#) page, under the header "API Access".

You can then add the token to your requests using the *Authorization* HTTP header. The token should be prefixed by the string literal "Token", with whitespace separating the two strings.

Example:

Authorization: Token 9944b09199c62bcf9418ad846dd0e4bbdfc6ee4b

How to generate a continuous cdf?

Generating a CDF to predict on a continuous question can be a bit tricky. We only accept predictions in the form of a 201 point CDF, represented as a list of floats, so getting scaling right is very important.

► Expand for CDF generation details and examples

Servers

<https://www.metaculus.com> - Production Server

Authorize



In the updated version of Metaculus, standalone questions no longer exist. Instead, the feed is made up of Post entities, where each post can contain various types of content objects. These include:

- Individual questions

Feed

- Groups of questions
- Conditional pairs
- Notebooks



The primary entry point for retrieving feed data and interacting with both Posts and Questions is the </api/posts/> endpoint.

GET**/api/posts/** Retrieve posts feed

Retrieves a feed of posts with various filters.

Parameters

[Try it out](#)

Name

Description

tournaments
array[string]
(query)

Tournament slug. You can apply multiple filters.

statuses
array[string]
(query)

Post statuses. You can apply multiple filters.

Available values : upcoming, closed, resolved, open

upcoming
closed
resolved

Name	Description
forecaster_id integer <i>(query)</i>	Filters posts where the specified user has submitted a forecast on a question within the post. 123
with_cp boolean <i>(query)</i>	Include Community Prediction data in the response. Note: aggregation data is only available for certain questions depending on your API access tier (see above). When enabled on a group post, only the top 3 subquestions include CP; use the post details endpoint for all subquestions. <i>Default value : false</i> true
include_cp_history boolean <i>(query)</i>	Include full aggregation history in the response. <i>Default value : false</i> true
include_descriptions boolean <i>(query)</i>	With this flag enabled, each post question will include the description, fine_print, and resolution_criteria fields in its response. true
not_forecaster_id integer <i>(query)</i>	Filters posts where the specified user has not submitted a forecast on a question within the post. 123

Name	Description
<code>open_time__gt</code> <code>string(\$date-time)</code> <i>(query)</i>	Post open timestamp filter: <code>open_time__<operator></code> . Supported operators: <code>gt</code> , <code>gte</code> , <code>lt</code> , <code>lte</code> . 2024-01-01
<code>published_at__gt</code> <code>string(\$date-time)</code> <i>(query)</i>	Post publication timestamp filter: <code>published_at__<operator></code> . Supported operators: <code>gt</code> , <code>gte</code> , <code>lt</code> , <code>lte</code> . 2024-01-01
<code>scheduled_resolve_time__gt</code> <code>string(\$date-time)</code> <i>(query)</i>	Scheduled resolution timestamp filter: <code>scheduled_resolve_time__<operator></code> . Supported operators: <code>gt</code> , <code>gte</code> , <code>lt</code> , <code>lte</code> . 2024-01-01
<code>forecast_type</code> <code>array[string]</code> <i>(query)</i>	Forecast type. You can apply multiple filters. <i>Available values</i> : binary, multiple_choice, numeric, discrete, date, conditional, group_of_questions, notebook -- binary multiple_choice numeric "
<code>limit</code> <code>integer</code> <i>(query)</i>	Number of posts to return per page (pagination limit). 20

Name	Description
offset integer (query)	Number of posts to skip (pagination offset). 0
for_main_feed boolean (query)	Filter posts suitable for the main feed. true
categories array[string] (query)	Category slugs to filter by. You can apply multiple filters. nuclear health-pandemics
order_by string (query)	Order by specific fields. For DESC sorting, add - prefix, e.g. -published_at . Sorting option descriptions: • hotness : Composite score based on post approval time, relevant news, votes, comments, and question metrics (movement, open time, resolution). Uses a decay function where scores decrease over time (posts older than 3.5 days decay with $(\text{days}/3.5)^{-2}$). • score : User-specific forecasting performance score. Requires forecaster_id parameter to be provided. <i>Available values</i> : published_at, open_time, vote_score, comment_count, forecasts_count, scheduled_close_time, scheduled_resolve_time, user_last_forecasts_date, unread_comment_count, weekly_movement, divergence, hotness, score --

Responses

Code	Description	Links
200	A paginated list of posts Media type application/json Controls Accept header. Examples Post With Numeric Question Example Value Schema <pre>id : 15858, "name": "Health & Pandemics", "slug": "biosecurity", "emoji": "🦠", "section": "hot_categories" }], "created_at": "2020-01-25T04:09:23.208127Z", "published_at": "2020-01-27T00:00:00Z", "edited_at": "2024-10-03T08:38:21.381658Z", "curation_status": "approved", "comment_count": 270, "status": "resolved", "resolved": true, "actual_close_time": "2020-11-01T00:00:00Z", "scheduled_close_time": "2020-11-01T00:00:00Z", "scheduled_resolve_time": "2022-05-06T16:00:00Z", "open_time": "2020-01-27T00:00:00Z", "nr_forecasters": 546, "question": { "id": 3530, "title": "How many people will die as a result of the 2019 novel coronavirus (COVID-19) before 2021?", "description": "", </pre>	No links

GET	/api/posts/{postId}/	Retrieve post details	 
-----	----------------------	-----------------------	---

Try it out

Parameters

Name	Description
postId ★ required integer (path)	The ID of the post to retrieve
	postId

Responses

Code	Description	Links
200	Post details Media type application/json Controls Accept header. Example Value Schema <pre>{ "id": 1, "title": "Binary Post title", "short_title": "Binary Post url title", "slug": "numeric-post", "author_id": 1000, "author_username": "metaculus", "projects": { "site_main": [{ "id": 144,</pre>	No links

Code	Description	Links
	<pre>"type": "site_main", "name": "Metaculus Community", "slug": "string", "prize_pool": "0.00", "start_date": "2026-04-11T20:20:47.733Z", "close_date": "2026-04-11T20:20:47.733Z", "html_metadata_json": "", "is_ongoing": true, "user_permission": "string", "created_at": "2026-04-11T20:20:47.733Z", "edited_at": "2026-04-11T20:20:47.733Z", "default_permission": "forecaster", "visibility": "normal"</pre>	

Questions & Forecasts

POST

/api/questions/forecast/

Submit forecasts for questions

^

🔒

This endpoint supports multiple simultaneous predictions, so the base object is a list of forecasts. Pass one forecast object for single questions and multiple forecast objects for group of questions or conditional forecasts.

Parameters

Try it out

No parameters

Request body required

application/json

Examples:

Binary Question

Example Value

Schema

```
[  
  {  
    "question": 1,  
    "probability_yes": 0.63  
  }  
]
```

Responses

Code	Description	Links
201	Forecasts submitted successfully	No links
400	Invalid request format	No links

POST **/api/questions/withdraw/** Withdraw current forecasts for questions



This endpoint supports multiple simultaneous withdrawals, so the base object is a list of withdrawals. Pass one withdrawal object for single questions and multiple withdrawal objects for group of questions or conditional forecasts.

Parameters

[Try it out](#)

No parameters

Request body **required**

[application/json](#)

Example Value Schema

```
[
  {
    "question": 0
  }
]
```

Comments

**POST** **/api/comments/create/** Create a new comment

Submit a new comment on a post

Parameters[Try it out](#)

No parameters

Request body required[application/json](#)**Examples:**[Example of a comment creation](#)**Example Value** Schema

```
{
  "included_forecast": false,
  "is_private": false,
  "on_post": 1,
}
```

```
"text": "Bot comment"
}
```

Responses

Code	Description	Links
201	Comment created successfully Media type application/json Controls Accept header. Example Value Schema <pre>{ "id": 0, "author": { "id": 0, "username": "string", "is_bot": true, "is_staff": true }, "parent_id": 0, "root_id": 0, "created_at": "2026-04-11T20:20:47.743Z", "text": "string", "on_post": 0, "included_forecast": true, "is_private": true, "vote_score": 0, "changed_my_mind": { "count": 0, "for_this_user": true }, "mentioned_users": [</pre>	No links

Code	Description	Links
400	<pre>{ "id": 0, "username": "string" }</pre> Invalid request format	No links

GET **/api/comments/** Retrieve comments



Fetch comments with filters for author and pagination. If API access is restricted, you must include at least one of: **author=<your own user ID>** and/or **author_is_staff=true** - requests without one of these filters will be rejected.

Parameters

Try it out

Name	Description
post integer (query)	ID of the post to filter comments by. post
author integer (query)	Filter comments by author user ID. Use your own user ID to retrieve your comments. author 
author_is_staff boolean (query)	When set to true , returns root-level comments authored by Metaculus staff (staff replies to other comments are not included). Treated as an 'OR' filter with author .

Name	Description
	--
limit integer (query)	Number of comments to retrieve. limit
offset integer (query)	Offset for pagination. offset
is_private boolean (query)	Filter between private comments (for the current user) and public comments. Defaults to false. <i>Default value : false</i> false
use_root_comments_pagination boolean (query)	If true, pagination will only apply to root comments, and all child comments will be included for those root comments. --
sort string (query)	Sort comments by creation date. Use -created_at for descending order. <i>Available values : -created_at, created_at</i> --
focus_comment_id integer (query)	The ID of a comment to place at the top of the results.

Name	Description
	focus_comment_id

Responses

Code	Description	Links
200	List of comments Media type application/json Controls Accept header. Example Value Schema <pre>{ "total_count": 0, "count": 0, "next": "string", "previous": "string", "results": [{ "id": 0, "author": { "id": 0, "username": "string", "is_bot": true, "is_staff": true }, "parent_id": 0, "root_id": 0, "created_at": "2026-04-11T20:20:47.745Z", "text": "string", </pre>	No links

Code	Description	Links
400	<pre>"on_post": 0, "included_forecast": true, "is_private": true, "vote_score": 0, "changed_my_mind": { "count": 0,</pre> Invalid request format	No links

Utilities & Data

Tip: You can also access data downloads through the Metaculus website without using the API directly. On any question page, click the ellipsis menu () in the top-right corner and select "Download data". A modal will appear with the same options available in the endpoints below.



GET **/api/data/download/** Download data as a Zip file of CSVs



Downloads question data, forecast data, and optionally comments, scores, and key factors as a Zip file of CSVs. You must provide at least one of **post_id**, **question_id**, or **project_id** to specify the data to download.

Note: This is a restricted endpoint. To request access, please email api-requests@metaculus.com. Additionally, the **project_id** parameter is only accepted if your account has been whitelisted for that specific project, to prevent heavy data requests.

This endpoint may time out for large data exports. If your download fails due to a timeout, use the **/api/data/email/** endpoint instead, which processes the export asynchronously.

Parameters

Try it out

Name	Description
post_id integer	The ID of the post to download data for.

Name	Description
(query)	post_id
question_id integer (query)	The ID of the question to download data for. question_id
project_id integer (query)	The ID of the project to download data for. project_id
sub_question integer (query)	If the post contains a group or conditional question, specify a sub-question ID to download data for only that sub-question. sub_question
aggregation_methods string (query)	Comma-separated list of aggregation methods to include. or all to include all available methods. Valid methods: recency_weighted , unweighted , metaculus_prediction , single_aggregation . single_aggregation is only available to site admins. If not provided, only recency_weighted is included. Including this parameter triggers a recalculation of aggregations, which may increase response time. aggregation_methods
minimize boolean (query)	If false, includes all data points in recalculated aggregations (requires aggregation_methods). May result in very large files or server timeouts for questions with many forecasts. <i>Default value : true</i> true

Name	Description
<code>include_bots</code> <code>boolean</code> <i>(query)</i>	Whether to include bot forecasts in aggregation recalculations. Requires <code>aggregation_methods</code> . If not given, uses the question's <code>include_bots_in_aggregations</code> setting. --
<code>user_ids</code> <code>array[integer]</code> <i>(query)</i>	A list of user IDs to recalculate aggregations for only those users' forecasts. Requires <code>aggregation_methods</code> . Only available to staff and whitelisted users.
<code>include_comments</code> <code>boolean</code> <i>(query)</i>	If true, includes a CSV file containing all public comments. <i>Default value : false</i> false
<code>include_scores</code> <code>boolean</code> <i>(query)</i>	If true, includes a CSV file containing all scores. <i>Default value : true</i> true
<code>include_key_factors</code> <code>boolean</code> <i>(query)</i>	If true, includes key factors data in the download. <i>Default value : false</i> false

Responses

Code	Description	Links
200	Zip file containing CSVs (question_data.csv, forecast_data.csv, and optionally comment_data.csv, score_data.csv) Media type application/zip Controls Accept header. Example Value Schema <pre>{ "question_data.csv": { "Question ID": 3, "Question URL": "string", "Question Title": "string", "Post ID": 0, "Post Curation Status": "pending", "Post Published Time": "2026-04-11T20:20:47.747Z", "Default Project": "string", "Default Project ID": 0, "Categories": "string", "Leaderboard Tags": "string", "Label": "string", "Question Type": "binary", "MC Options (Current)": "string", "MC Options (All)": "string", "MC Options History": "string", "Lower Bound": 0, "Open Lower Bound": true, "Upper Bound": 0, "Open Upper Bound": true, "Continuous Range": "string", "Open Time": "2026-04-11T20:20:47.747Z", "CP Reveal Time": "2026-04-11T20:20:47.747Z", "Scheduled Close Time": "2026-04-11T20:20:47.747Z" } }</pre>	No links

POST

/api/data/email/ Email data as a Zip file of CSVs

Schedules an email to be sent to the authenticated user containing question data, forecast data, and optionally comments, scores, and key factors as a 7in file of CSVs. Useful for large data exports that may time out with a direct download. Accepts the same parameters as </api/data/download/> . You must provide at least one of `post_id` , `question_id` , or `project_id` .

Note: This is a restricted endpoint. To request access, please email api-requests@metaculus.com. Additionally, the `project_id` parameter is only accepted if your account has been whitelisted for that specific project.

The email attachment has a size limit of 25 MB. If your export exceeds this limit, try removing `include_comments` to reduce the file size.

Parameters

[Try it out](#)

No parameters

Request body required

[application/json](#)

Example Value Schema

```
{
  "post_id": 0,
  "question_id": 0,
  "project_id": 0,
  "sub_question": 0,
  "aggregation_methods": [
    "string"
  ],
  "minimize": true,
  "include_bots": true,
  "user_ids": [
    0
  ],
  "include_comments": false,
  "include_scores": true,
  "include_key_factors": false
}
```

Responses

Code	Description	Links
200	Email scheduled successfully	No links
Media type		
application/json		
Controls Accept header.		
Example Value Schema		
{ "message": "Email scheduled to be sent" }		

Schemas



```

Post {
  id integer
  example: 1
  title string
  example: Binary Post title
  short_title string
  example: Binary Post url title
  slug string
  example: numeric-post
  author_id integer
  example: 1000
  author_username string
  example: metaculus
  projects {...}
  created_at string($date-time)
  example: 2024-10-16T12:56:51.751385Z
  published_at string($date-time)
  nullable: true
  open_time string($date-time)
  nullable: true
  edited_at string($date-time)
  curation_status string
  example: pending
  Enum:

  comment_count Array [ 4 ]
  integer
  example: 10
  status string
  example: pending

  Combination of curation status and post lifecycle statuses
  Enum:

  nr_forecasters Array [ 7 ]
  integer
  example: 5
  question Question {...}
  conditional Conditional {...}
  group_of_questions GroupOfQuestions {...}
  user_permission string
  example: forecaster
  Enum:

  vote Array [ 2 ]
  Vote {...}
  forecasts_count integer
  example: 0

```

```
}
```

```
Project {  
  id integer  
    example: 144  
  type string  
    example: site_main  
  name string  
    example: Metaculus Community  
  slug string  
    nullable: true  
  prize_pool string  
    example: 0.00  
  start_date string($date-time)  
    nullable: true  
  close_date string($date-time)  
    nullable: true  
  html_metadata_json string  
    example:  
  is_ongoing boolean  
    nullable: true  
  user_permission string  
    nullable: true  
  created_at string($date-time)  
  edited_at string($date-time)  
  default_permission string  
    example: forecaster  
  visibility string  
    example: normal  
  Enum:  
    Array [ 3 ]  
}
```

```
Category {  
  id integer  
    example: 3690  
  name string  
    example: Nuclear Technology & Risks  
  slug string  
    example: nuclear  
  description string  
    example: Nuclear Technology & Risks  
}
```

```
Tag {
  name      string
           example: Space
}
```

```
Conditional {
  id          integer
           example: 1
  condition   Question {...}
  condition_child Question {...}
  question_yes Question {...}
  question_no Question {...}
}
```

```
GroupOfQuestions {
  id          integer
           example: 1
  description  string
  resolution_criteria string
  fine_print   string
  group_variable string
  graph_type   string
  Enum:
    Array [ 2 ]

  questions [...]
}
```

```

Question {
  id integer
  example: 2
  title string
  example: Binary Question
  description string
  example: string
  created_at string($date-time)
  open_time string($date-time)
  scheduled_resolve_time string($date-time)
  actual_resolve_time string($date-time)
  nullable: true
  resolution_set_time string($date-time)
  nullable: true
  scheduled_close_time string($date-time)
  actual_close_time string($date-time)
  type string
  example: binary
  Enum:

  options Array [ 5 ]
  [...]
  all_options_ever [...]
  options_history [...]
  status string
  example: upcoming
  Enum:

  possibilities Array [ 4 ]
  resolution QuestionPossibilities {...}
  string
  nullable: true
  open_upper_bound boolean
  nullable: false
  open_lower_bound boolean
  nullable: false
  inbound_outcome_count integer
  nullable: true
  example: 200
  resolution_criteria string
  example: string
  fine_print string
  example: string
  label string
  nullable: true
  unit string
  nullable: false
  required: false
  example: $

```

```
    scaling
  }

  Vote {
    score
    user_vote
  }

  default:
  QuestionScaling {...}

  integer
  example: 0
  string
  nullable: true
```

```

QuestionScaling {
  range_max      number($float)
                  nullable: true

                  The lower boundary of the input range. If the question is Discrete, it will be 1/2 a bucket
                  width below the nominal lowest inbound outcome.

  range_min      number($float)
                  nullable: true

                  The upper boundary of the input range. If the question is Discrete, it will be 1/2 a bucket
                  width above the nominal highest inbound outcome.

  zero_point     number($float)
                  nullable: true

                  Only populated if the question has logarithmic scaling. See 'continuous_range' for exact
                  locations where the CDF gets evaluated.

  open_upper_bound boolean
                  nullable: true

                  Whether the upper bound is open.

  open_lower_bound boolean
                  nullable: true

                  Whether the lower bound is open.

  inbound_outcome_count integer
                        example: 200
                        nullable: true

                        Total number of possible outcomes within the question's range (does not include out of
                        bounds).

  continuous_range      [...]
}

```

```

QuestionPossibilities  {
  description:
    WARNING: this is a deprecated field and may be removed without notice.

  oneOf ->
    {...}
    {...}
}

```

```

Forecast  {
  oneOf ->
    BinaryForecast    {...}
    ContinuousForecast {...}
    MultipleChoiceForecast {...}
    ConditionalForecast [...]
    GroupForecast    [...]
}

```

```

BinaryForecast  {
  question*      integer
  probability_yes* number($float)

  Probability for a binary outcome

  end_time       string($date-time)
  The timestamp when the forecast is automatically withdrawn

}

```

```

ContinuousForecast {
  question* integer
  ID of the numeric question (not post)

  continuous_cdf* [...]
  distribution_input {...}
  end_time string($date-time)
  The timestamp when the forecast is automatically withdrawn
}

```

```

MultipleChoiceForecast {
  question* integer
  probability_yes_per_category* {...}
  end_time string($date-time)
  The timestamp when the forecast is automatically withdrawn
}

```

```

ConditionalForecast [
Forecast for conditional questions (if Yes/No scenarios)

```

```

ConditionalForecast {
  question* integer
  probability_yes* number($float)
}]

```

```
GroupForecast  [  
  Group forecast of Binary, Numeric or Date subquestions  
  
  GroupForecast  {  
    oneOf ->  
      BinaryForecast  {...}  
      ContinuousForecast  {...}  
  }]  
  
Withdrawal  {  
  question* integer  
}
```

```
Comment {
  id integer
  Unique identifier for the comment.

  author {...}
  parent_id integer
  nullable: true
  ID of the comment being replied to (if applicable).

  root_id integer
  nullable: true
  ID of the root comment in the thread.

  created_at string($date-time)
  Timestamp when the comment was created.

  text string
  The content of the comment.

  on_post integer
  ID of the post the comment belongs to.

  included_forecast boolean
  If the user's last forecast is included.

  is_private boolean
  If the comment is private.

  vote_score integer
  Total vote score for the comment.

  changed_my_mind {...}
  mentioned_users [...]
  user_vote integer
  Current user's vote on this comment (-1, 0, 1).
}
```

QuestionDataCSV	{
description:	Warning: this data may be out of date, please consult the README included in the zip file for the most up to date information.
Question ID	integer <i>example: 3</i> The ID of the question.
Question URL	string The URL of the question page.
Question Title	string The title of the (sub)question.
Post ID	integer The ID of the post containing the question.
Post Curation Status	string <i>example: pending</i> Enum: Array [4]
Post Published Time	string(\$date-time) The time the post was published.
Default Project	string The default project for the Post.
Default Project ID	integer The ID of the default project for the Post.
Categories	string Comma-separated list of category slugs for the post.
Leaderboard Tags	string Comma-separated list of leaderboard tags for the post.
Label	string For sub questions only. The label of the question.
Question Type	string <i>example: binary</i> The type of the question.

	the type of the question.
	Enum:
	Array [4]
MC Options (Current)	string
	For multiple choice questions only. The current set of options.
MC Options (All)	string
	For multiple choice questions only. All options including removed ones.
MC Options History	string
	For multiple choice questions only. History of option changes.
Lower Bound	number
	For continuous questions only. The minimum value of the input range. For date questions, formatted as a date string.
Open Lower Bound	boolean
	Whether the lower bound of the range is open.
Upper Bound	number
	For continuous questions only. The maximum value of the input range. For date questions, formatted as a date string.
Open Upper Bound	boolean
	Whether the upper bound of the range is open.
Continuous Range	string
	For continuous questions only. A human-readable representation of the question range.
Open Time	string(\$date-time)
	The time the question was opened.
CP Reveal Time	string(\$date-time)
	The time the CP was revealed. This is also the default setting for when Spot Scores are evaluated.
Scheduled Close Time	string(\$date-time)
	The time the question is scheduled to close.
Actual Close Time	string(\$date-time)
	The time the question actually closed.
Resolution	string

	The nominal resolution of the question. E.g. 'no', 'yes' for binary, '2022-01-01' for date, etc.
Resolution Known Time	<code>string(\$date-time)</code> The time the question resolution was publicly known.
Include Bots in Aggregates	<code>boolean</code> Whether bots are included in the aggregates.
Question Weight	<code>number</code> The weight of the question within its post.
}	

ForecastDataCSV	{
Question ID	integer <i>example: 3</i> The ID of the question this forecast is made on.
Forecaster ID	integer <i>example: 421323</i> The forecaster's ID. None if forecast is an Aggregation.
Forecaster Username	string <i>example: John Doe</i> The forecaster's username or aggregation method.
Is Bot	boolean Whether the forecaster is a bot account.
Start Time	string(\$date-time) The start time of the prediction.
End Time	string(\$date-time) The end time of the prediction.
Forecaster Count	integer <i>example: 3</i> The number of forecasts that contributed to this Aggregation. null if not an Aggregation.
Probability Yes	number(\$float) <i>example: 0.5</i> For Binary Questions only. The prediction value in range [0, 1].
Probability Yes Per Category	string <i>example: [0.2, 0.5, 0.3]</i> For Multiple Choice Questions only. The predictions for the possible outcomes, all in range [0, 1].
Continuous CDF	string <i>example: [0.01, 0.02, 0.03, ..., 0.74, 0.75]</i> For Continuous Questions only. The CDF of the prediction as a list of 201 values.
Probability Below Lower Bound	number(\$float) For Continuous Questions only. The probability mass below the lower bound.
Probability Above	number(\$float)

Upper Bound	For Continuous Questions only. The probability mass above the upper bound.
5th Percentile	number For Continuous Questions only. The 5th percentile of the forecast distribution.
25th Percentile	number For Continuous Questions only. The 25th percentile of the forecast distribution.
Median	number For Continuous Questions only. The median (50th percentile) of the forecast distribution.
75th Percentile	number For Continuous Questions only. The 75th percentile of the forecast distribution.
95th Percentile	number For Continuous Questions only. The 95th percentile of the forecast distribution.
Probability of Resolution	number(\$float) The probability assigned to the actual resolution value, if resolved.
PDF at Resolution	number(\$float) For Continuous Questions only. The PDF value at the resolution point.
}	

```
ScoreDataCSV {
  description: Warning: this data may be out of date, please consult the README included in the zip file
               for the most up to date information.

  Question ID integer
               example: 42
               The ID of the question the score is for.

  User ID integer
            example: 12345
            The ID of the user who made the score.

  User Username string
                 example: john_doe
                 The username of the user who made the score.

  Score Type string
              example: peer
              The type of score.

              Enum:

  Score Array [ 6 ]
          number($float)
          example: 85.5
          The score value.

  Coverage number($float)
            example: 0.95
            The coverage that earned this score.
}
```

```
CommentDataCSV {
  description:
    Warning: this data may be out of date, please consult the README included in the zip file
    for the most up to date information.

  Post ID      integer
               example: 101

               The ID of the post the comment is on.

  Author ID    integer
               example: 202

               The ID of the author of the comment.

  Author Username string
               example: jane_doe

               The username of the author of the comment.

  Parent Comment ID integer
                  example: 303

                  The ID of the parent comment, if any.

  Root Comment ID integer
                  example: 404

                  The ID of the root comment, if any.

  Created At    string($date-time)
               example: 2023-10-01T12:34:56Z

               The time the comment was created.

  Comment Text  string
               example: This is a sample comment text.

               The text of the comment.
}
```

```
DataZip {  
  description:
```

Warning: this data may be out of date, please consult the README included in the zip file for the most up to date information. A zip file containing CSVs for Question data, Forecast data, and (optionally) Scoring data, Comment data, and Key Factor data.

```
    question_data.csv    QuestionDataCSV  {...}  
    forecast_data.csv   ForecastDataCSV  {...}  
    score_data.csv      ScoreDataCSV    {...}  
    comment_data.csv    CommentDataCSV  {...}  
    key_factor_data.csv {...}  
  }
```