

Lecture 9: CNN Architectures

Administrative


A2 due Wed May 2

Midterm: In-class Tue May 8. Covers material through Lecture 10 (Thu May 3).

Sample midterm released on piazza.

Midterm review session: Fri May 4 discussion section

Last time: Deep learning frameworks



Last time: Deep learning frameworks

- (1) Easily build big computational graphs
- (2) Easily compute gradients in computational graphs
- (3) Run it all efficiently on GPU (wrap cuDNN, cuBLAS, etc)

Today: CNN Architectures

Case Studies


- AlexNet
- VGG
- GoogLeNet
- ResNet

Also....

- NiN (Network in Network)
- Wide ResNet
- ResNeXT
- Stochastic Depth
- Squeeze-and-Excitation Network
- DenseNet
- FractalNet
- SqueezeNet
- NASNet

Review: LeNet-5

[LeCun et al., 1998]



Conv filters were 5x5, applied at stride 1

Subsampling (Pooling) layers were 2x2 applied at stride 2
i.e. architecture is [CONV-POOL-CONV-POOL-FC-FC]

Case Study: AlexNet

[Krizhevsky et al. 2012]

Architecture:

CONV1

MAX POOL1

NORM1

CONV2

MAX POOL2

NORM2

CONV3

CONV4

CONV5

Max POOL3

FC6

FC7

FC8





Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

First layer (CONV1): 96 11x11 filters applied at stride 4


=>

Q: what is the output volume size? Hint: $(227-11)/4+1 = 55$

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

First layer (CONV1): 96 11x11 filters applied at stride 4

=>


Output volume **[55x55x96]**

Q: What is the total number of parameters in this layer?

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

First layer (CONV1): 96 11x11 filters applied at stride 4

=>


Output volume **[55x55x96]**

Parameters: $(11 \times 11 \times 3) \times 96 = 35\text{K}$

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

After CONV1: 55x55x96


Second layer (POOL1): 3x3 filters applied at stride 2

Q: what is the output volume size? Hint: $(55-3)/2+1 = 27$

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

After CONV1: 55x55x96

Second layer (POOL1): 3x3 filters applied at stride 2


Output volume: 27x27x96

Q: what is the number of parameters in this layer?

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

After CONV1: 55x55x96

Second layer (POOL1): 3x3 filters applied at stride 2

Output volume: 27x27x96

Parameters: 0!

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]

Input: 227x227x3 images

After CONV1: 55x55x96

After POOL1: 27x27x96

...




Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]

Full (simplified) AlexNet architecture:

[227x227x3] INPUT

[55x55x96] CONV1: 96 11x11 filters at stride 4, pad 0

[27x27x96] MAX POOL1: 3x3 filters at stride 2

[27x27x96] NORM1: Normalization layer

[27x27x256] CONV2: 256 5x5 filters at stride 1, pad 2

[13x13x256] MAX POOL2: 3x3 filters at stride 2

[13x13x256] NORM2: Normalization layer

[13x13x384] CONV3: 384 3x3 filters at stride 1, pad 1

[13x13x384] CONV4: 384 3x3 filters at stride 1, pad 1

[13x13x256] CONV5: 256 3x3 filters at stride 1, pad 1

[6x6x256] MAX POOL3: 3x3 filters at stride 2

[4096] FC6: 4096 neurons

[4096] FC7: 4096 neurons

[1000] FC8: 1000 neurons (class scores)




Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]

Full (simplified) AlexNet architecture:

[227x227x3] INPUT

[55x55x96] CONV1: 96 11x11 filters at stride 4, pad 0

[27x27x96] MAX POOL1: 3x3 filters at stride 2

[27x27x96] NORM1: Normalization layer

[27x27x256] CONV2: 256 5x5 filters at stride 1, pad 2

[13x13x256] MAX POOL2: 3x3 filters at stride 2

[13x13x256] NORM2: Normalization layer

[13x13x384] CONV3: 384 3x3 filters at stride 1, pad 1

[13x13x384] CONV4: 384 3x3 filters at stride 1, pad 1


[13x13x256] CONV5: 256 3x3 filters at stride 1, pad 1

[6x6x256] MAX POOL3: 3x3 filters at stride 2

[4096] FC6: 4096 neurons

[4096] FC7: 4096 neurons

[1000] FC8: 1000 neurons (class scores)



Details/Retrospectives:

- first use of ReLU
- used Norm layers (not common anymore)
- heavy data augmentation
- dropout 0.5
- batch size 128
- SGD Momentum 0.9
- Learning rate 1e-2, reduced by 10 manually when val accuracy plateaus
- L2 weight decay 5e-4
- 7 CNN ensemble: 18.2% -> 15.4%

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]

Full (simplified) AlexNet architecture:

[227x227x3] INPUT

[55x55x96] CONV1: 96 11x11 filters at stride 4, pad 0

[27x27x96] MAX POOL1: 3x3 filters at stride 2

[27x27x96] NORM1: Normalization layer

[27x27x256] CONV2: 256 5x5 filters at stride 1, pad 2

[13x13x256] MAX POOL2: 3x3 filters at stride 2

[13x13x256] NORM2: Normalization layer

[13x13x384] CONV3: 384 3x3 filters at stride 1, pad 1

[13x13x384] CONV4: 384 3x3 filters at stride 1, pad 1


[13x13x256] CONV5: 256 3x3 filters at stride 1, pad 1

[6x6x256] MAX POOL3: 3x3 filters at stride 2

[4096] FC6: 4096 neurons

[4096] FC7: 4096 neurons

[1000] FC8: 1000 neurons (class scores)



[55x55x48] x 2

Historical note: Trained on GTX 580 GPU with only 3 GB of memory. Network spread across 2 GPUs, half the neurons (feature maps) on each GPU.

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]

Full (simplified) AlexNet architecture:

[227x227x3] INPUT

[55x55x96] CONV1: 96 11x11 filters at stride 4, pad 0

[27x27x96] MAX POOL1: 3x3 filters at stride 2

[27x27x96] NORM1: Normalization layer

[27x27x256] CONV2: 256 5x5 filters at stride 1, pad 2

[13x13x256] MAX POOL2: 3x3 filters at stride 2

[13x13x256] NORM2: Normalization layer

[13x13x384] CONV3: 384 3x3 filters at stride 1, pad 1

[13x13x384] CONV4: 384 3x3 filters at stride 1, pad 1


[13x13x256] CONV5: 256 3x3 filters at stride 1, pad 1

[6x6x256] MAX POOL3: 3x3 filters at stride 2

[4096] FC6: 4096 neurons

[4096] FC7: 4096 neurons

[1000] FC8: 1000 neurons (class scores)



CONV1, CONV2, CONV4, CONV5:
Connections only with feature maps
on same GPU

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case Study: AlexNet

[Krizhevsky et al. 2012]

Full (simplified) AlexNet architecture:

[227x227x3] INPUT

[55x55x96] CONV1: 96 11x11 filters at stride 4, pad 0

[27x27x96] MAX POOL1: 3x3 filters at stride 2

[27x27x96] NORM1: Normalization layer

[27x27x256] CONV2: 256 5x5 filters at stride 1, pad 2

[13x13x256] MAX POOL2: 3x3 filters at stride 2

[13x13x256] NORM2: Normalization layer

[13x13x384] CONV3: 384 3x3 filters at stride 1, pad 1

[13x13x384] CONV4: 384 3x3 filters at stride 1, pad 1


[13x13x256] CONV5: 256 3x3 filters at stride 1, pad 1

[6x6x256] MAX POOL3: 3x3 filters at stride 2

[4096] FC6: 4096 neurons

[4096] FC7: 4096 neurons


[1000] FC8: 1000 neurons (class scores)




CONV3, FC6, FC7, FC8:
Connections with all feature maps in
preceding layer, communication
across GPUs

Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.


ImageNet Large Scale Visual Recognition Challenge (ILSVRC) winners



ImageNet Large Scale Visual Recognition Challenge (ILSVRC) winners




ImageNet Large Scale Visual Recognition Challenge (ILSVRC) winners



ZFNet

[Zeiler and Fergus, 2013]




AlexNet but:

CONV1: change from (11x11 stride 4) to (7x7 stride 2)

CONV3,4,5: instead of 384, 384, 256 filters use 512, 1024, 512

ImageNet top 5 error: 16.4% \rightarrow 11.7%

ImageNet Large Scale Visual Recognition Challenge (ILSVRC) winners



Case Study: VGGNet

[Simonyan and Zisserman, 2014]

Small filters, Deeper networks

8 layers (AlexNet)


-> 16 - 19 layers (VGG16Net)

Only 3x3 CONV stride 1, pad 1
and 2x2 MAX POOL stride 2

11.7% top 5 error in ILSVRC'13

(ZFNet)


-> 7.3% top 5 error in ILSVRC'14



Case Study: VGGNet

[Simonyan and Zisserman, 2014]

Q: Why use smaller filters? (3x3 conv)




Case Study: VGGNet

[Simonyan and Zisserman, 2014]

Q: Why use smaller filters? (3x3 conv)

Stack of three 3x3 conv (stride 1) layers
has same **effective receptive field** as
one 7x7 conv layer

Q: What is the effective receptive field of
three 3x3 conv (stride 1) layers?




Case Study: VGGNet

[Simonyan and Zisserman, 2014]

Q: Why use smaller filters? (3x3 conv)

Stack of three 3x3 conv (stride 1) layers
has same **effective receptive field** as
one 7x7 conv layer

[7x7]



Case Study: VGGNet


[Simonyan and Zisserman, 2014]

Q: Why use smaller filters? (3x3 conv)

Stack of three 3x3 conv (stride 1) layers
has same **effective receptive field** as
one 7x7 conv layer

But deeper, more non-linearities

And fewer parameters: $3 * (3^2 C^2)$ vs.
 $7^2 C^2$ for C channels per layer



INPUT: [224x224x3] memory: $224 \times 224 \times 3 = 150K$ params: 0 (not counting biases)

CONV3-64: [224x224x64] memory: $224 \times 224 \times 64 = 3.2M$ params: $(3 \times 3 \times 3) \times 64 = 1,728$

CONV3-64: [224x224x64] memory: $224 \times 224 \times 64 = 3.2M$ params: $(3 \times 3 \times 64) \times 64 = 36,864$

POOL2: [112x112x64] memory: $112 \times 112 \times 64 = 800K$ params: 0

CONV3-128: [112x112x128] memory: $112 \times 112 \times 128 = 1.6M$ params: $(3 \times 3 \times 64) \times 128 = 73,728$

CONV3-128: [112x112x128] memory: $112 \times 112 \times 128 = 1.6M$ params: $(3 \times 3 \times 128) \times 128 = 147,456$

POOL2: [56x56x128] memory: $56 \times 56 \times 128 = 400K$ params: 0

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 128) \times 256 = 294,912$

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 256) \times 256 = 589,824$

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 256) \times 256 = 589,824$

POOL2: [28x28x256] memory: $28 \times 28 \times 256 = 200K$ params: 0

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 256) \times 512 = 1,179,648$

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

POOL2: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: 0

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$


CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

POOL2: [7x7x512] memory: $7 \times 7 \times 512 = 25K$ params: 0

FC: [1x1x4096] memory: 4096 params: $7 \times 7 \times 512 \times 4096 = 102,760,448$

FC: [1x1x4096] memory: 4096 params: $4096 \times 4096 = 16,777,216$

FC: [1x1x1000] memory: 1000 params: $4096 \times 1000 = 4,096,000$



VGG16

INPUT: [224x224x3] memory: $224 \times 224 \times 3 = 150K$ params: 0 (not counting biases)

CONV3-64: [224x224x64] memory: $224 \times 224 \times 64 = 3.2M$ params: $(3 \times 3 \times 3) \times 64 = 1,728$

CONV3-64: [224x224x64] memory: $224 \times 224 \times 64 = 3.2M$ params: $(3 \times 3 \times 64) \times 64 = 36,864$

POOL2: [112x112x64] memory: $112 \times 112 \times 64 = 800K$ params: 0

CONV3-128: [112x112x128] memory: $112 \times 112 \times 128 = 1.6M$ params: $(3 \times 3 \times 64) \times 128 = 73,728$

CONV3-128: [112x112x128] memory: $112 \times 112 \times 128 = 1.6M$ params: $(3 \times 3 \times 128) \times 128 = 147,456$

POOL2: [56x56x128] memory: $56 \times 56 \times 128 = 400K$ params: 0

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 128) \times 256 = 294,912$

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 256) \times 256 = 589,824$

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 256) \times 256 = 589,824$

POOL2: [28x28x256] memory: $28 \times 28 \times 256 = 200K$ params: 0

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 256) \times 512 = 1,179,648$

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

POOL2: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: 0

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

POOL2: [7x7x512] memory: $7 \times 7 \times 512 = 25K$ params: 0


FC: [1x1x4096] memory: 4096 params: $7 \times 7 \times 512 \times 4096 = 102,760,448$

FC: [1x1x4096] memory: 4096 params: $4096 \times 4096 = 16,777,216$

FC: [1x1x1000] memory: 1000 params: $4096 \times 1000 = 4,096,000$

TOTAL memory: $24M \times 4 \text{ bytes} \approx 96\text{MB} / \text{image}$ (for a forward pass)

TOTAL params: 138M parameters



VGG16

INPUT: [224x224x3] memory: $224 \times 224 \times 3 = 150K$ params: 0 (not counting biases)

CONV3-64: [224x224x64] memory: $224 \times 224 \times 64 = 3.2M$ params: $(3 \times 3 \times 3) \times 64 = 1,728$

CONV3-64: [224x224x64] memory: $224 \times 224 \times 64 = 3.2M$ params: $(3 \times 3 \times 64) \times 64 = 36,864$

POOL2: [112x112x64] memory: $112 \times 112 \times 64 = 800K$ params: 0

CONV3-128: [112x112x128] memory: $112 \times 112 \times 128 = 1.6M$ params: $(3 \times 3 \times 64) \times 128 = 73,728$

CONV3-128: [112x112x128] memory: $112 \times 112 \times 128 = 1.6M$ params: $(3 \times 3 \times 128) \times 128 = 147,456$

POOL2: [56x56x128] memory: $56 \times 56 \times 128 = 400K$ params: 0

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 128) \times 256 = 294,912$

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 256) \times 256 = 589,824$

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 256) \times 256 = 589,824$

POOL2: [28x28x256] memory: $28 \times 28 \times 256 = 200K$ params: 0

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 256) \times 512 = 1,179,648$

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

POOL2: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: 0

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

POOL2: [7x7x512] memory: $7 \times 7 \times 512 = 25K$ params: 0

FC: [1x1x4096] memory: 4096 params: $7 \times 7 \times 512 \times 4096 = 102,760,448$

FC: [1x1x4096] memory: 4096 params: $4096 \times 4096 = 16,777,216$

FC: [1x1x1000] memory: 1000 params: $4096 \times 1000 = 4,096,000$

Note:

Most memory is in early CONV

Most params are in late FC

TOTAL memory: $24M * 4 \text{ bytes} \approx 96\text{MB} / \text{image}$ (only forward! ~ 2 for bwd)

TOTAL params: 138M parameters

INPUT: [224x224x3] memory: $224 \times 224 \times 3 = 150K$ params: 0 (not counting biases)

CONV3-64: [224x224x64] memory: $224 \times 224 \times 64 = 3.2M$ params: $(3 \times 3 \times 3) \times 64 = 1,728$

CONV3-64: [224x224x64] memory: $224 \times 224 \times 64 = 3.2M$ params: $(3 \times 3 \times 64) \times 64 = 36,864$

POOL2: [112x112x64] memory: $112 \times 112 \times 64 = 800K$ params: 0

CONV3-128: [112x112x128] memory: $112 \times 112 \times 128 = 1.6M$ params: $(3 \times 3 \times 64) \times 128 = 73,728$

CONV3-128: [112x112x128] memory: $112 \times 112 \times 128 = 1.6M$ params: $(3 \times 3 \times 128) \times 128 = 147,456$

POOL2: [56x56x128] memory: $56 \times 56 \times 128 = 400K$ params: 0

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 128) \times 256 = 294,912$

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 256) \times 256 = 589,824$

CONV3-256: [56x56x256] memory: $56 \times 56 \times 256 = 800K$ params: $(3 \times 3 \times 256) \times 256 = 589,824$

POOL2: [28x28x256] memory: $28 \times 28 \times 256 = 200K$ params: 0

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 256) \times 512 = 1,179,648$

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [28x28x512] memory: $28 \times 28 \times 512 = 400K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

POOL2: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: 0

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

CONV3-512: [14x14x512] memory: $14 \times 14 \times 512 = 100K$ params: $(3 \times 3 \times 512) \times 512 = 2,359,296$

POOL2: [7x7x512] memory: $7 \times 7 \times 512 = 25K$ params: 0


FC: [1x1x4096] memory: 4096 params: $7 \times 7 \times 512 \times 4096 = 102,760,448$

FC: [1x1x4096] memory: 4096 params: $4096 \times 4096 = 16,777,216$

FC: [1x1x1000] memory: 1000 params: $4096 \times 1000 = 4,096,000$

TOTAL memory: $24M \times 4 \text{ bytes} \approx 96\text{MB} / \text{image}$ (only forward! ~ 2 for bwd)

TOTAL params: 138M parameters



VGG16


Common names

Case Study: VGGNet


[Simonyan and Zisserman, 2014]

Details:

- ILSVRC'14 2nd in classification, 1st in localization
- Similar training procedure as Krizhevsky 2012
- No Local Response Normalisation (LRN)
- Use VGG16 or VGG19 (VGG19 only slightly better, more memory)
- Use ensembles for best results
- FC7 features generalize well to other tasks



ImageNet Large Scale Visual Recognition Challenge (ILSVRC) winners




Case Study: GoogLeNet


[Szegedy et al., 2014]

Deeper networks, with computational efficiency

- 22 layers
- Efficient “Inception” module
- No FC layers
- Only 5 million parameters!
12x less than AlexNet
- ILSVRC’14 classification winner
(6.7% top 5 error)




Inception module




Case Study: GoogLeNet

[Szegedy et al., 2014]

“Inception module”: design a good local network topology (network within a network) and then stack these modules on top of each other




Inception module



Case Study: GoogLeNet

[Szegedy et al., 2014]




Apply parallel filter operations on the input from previous layer:

- Multiple receptive field sizes for convolution (1×1 , 3×3 , 5×5)
- Pooling operation (3×3)

Concatenate all filter outputs together depth-wise

Case Study: GoogLeNet

[Szegedy et al., 2014]



Apply parallel filter operations on the input from previous layer:

- Multiple receptive field sizes for convolution (1×1 , 3×3 , 5×5)
- Pooling operation (3×3)

Concatenate all filter outputs together depth-wise


Q: What is the problem with this?
[Hint: Computational complexity]

Case Study: GoogLeNet

[Szegedy et al., 2014]

Q: What is the problem with this?
[Hint: Computational complexity]

Example:



Naive Inception module


Case Study: GoogLeNet

[Szegedy et al., 2014]

Example:

Q1: What is the output size of the
1x1 conv, with 128 filters?

Q: What is the problem with this?
[Hint: Computational complexity]




Naive Inception module

Case Study: GoogLeNet

[Szegedy et al., 2014]

Example:

Q1: What is the output size of the
1x1 conv, with 128 filters?




Q: What is the problem with this?
[Hint: Computational complexity]

Case Study: GoogLeNet

[Szegedy et al., 2014]

Example:

Q2: What are the output sizes of all different filter operations?



Q: What is the problem with this?
[Hint: Computational complexity]


Case Study: GoogLeNet

[Szegedy et al., 2014]

Q: What is the problem with this?
[Hint: Computational complexity]

Example:

Q2: What are the output sizes of all different filter operations?




Case Study: GoogLeNet

[Szegedy et al., 2014]

Q: What is the problem with this?
[Hint: Computational complexity]

Example:

Q3: What is output size after
filter concatenation?



Naive Inception module

Case Study: GoogLeNet


[Szegedy et al., 2014]

Q: What is the problem with this?
[Hint: Computational complexity]

Example:

Q3: What is output size after
filter concatenation?

$$28 \times 28 \times (128 + 192 + 96 + 256) = 28 \times 28 \times 672$$



Naive Inception module


Case Study: GoogLeNet

[Szegedy et al., 2014]

Example:

Q3: What is output size after filter concatenation?

$$28 \times 28 \times (128 + 192 + 96 + 256) = 28 \times 28 \times 672$$



Q: What is the problem with this?
[Hint: Computational complexity]

Conv Ops:

[1×1 conv, 128] $28 \times 28 \times 128 \times 1 \times 1 \times 256$

[3×3 conv, 192] $28 \times 28 \times 192 \times 3 \times 3 \times 256$

[5×5 conv, 96] $28 \times 28 \times 96 \times 5 \times 5 \times 256$

Total: 854M ops


Case Study: GoogLeNet

[Szegedy et al., 2014]

Example:

Q3: What is output size after filter concatenation?

$$28 \times 28 \times (128 + 192 + 96 + 256) = 28 \times 28 \times 672$$



Q: What is the problem with this?
[Hint: Computational complexity]

Conv Ops:

- [1x1 conv, 128] $28 \times 28 \times 128 \times 1 \times 1 \times 256$
- [3x3 conv, 192] $28 \times 28 \times 192 \times 3 \times 3 \times 256$
- [5x5 conv, 96] $28 \times 28 \times 96 \times 5 \times 5 \times 256$

Total: 854M ops

Very expensive compute

Pooling layer also preserves feature depth, which means total depth after concatenation can only grow at every layer!


Case Study: GoogLeNet

[Szegedy et al., 2014]

Example:

Q3: What is output size after filter concatenation?


$$28 \times 28 \times (128 + 192 + 96 + 256) = 529k$$




Q: What is the problem with this?
[Hint: Computational complexity]

Solution: “bottleneck” layers that use 1×1 convolutions to reduce feature depth


Reminder: 1x1 convolutions



1x1 CONV
with 32 filters
→
(each filter has size
 $1 \times 1 \times 64$, and performs a
64-dimensional dot
product)




Reminder: 1x1 convolutions



1x1 CONV
with 32 filters


preserves spatial
dimensions, reduces depth!

Projects depth to lower
dimension (combination of
feature maps)




Case Study: GoogLeNet

[Szegedy et al., 2014]



Naive Inception module




Inception module with dimension reduction


Case Study: GoogLeNet

[Szegedy et al., 2014]

1x1 conv “bottleneck”
layers




Naive Inception module



Inception module with dimension reduction

Case Study: GoogLeNet

[Szegedy et al., 2014]



Inception module with dimension reduction

Using same parallel layers as naive example, and adding “ 1×1 conv, 64 filter” bottlenecks:

Conv Ops:

- [1×1 conv, 64] $28 \times 28 \times 64 \times 1 \times 1 \times 256$
- [1×1 conv, 64] $28 \times 28 \times 64 \times 1 \times 1 \times 256$
- [1×1 conv, 128] $28 \times 28 \times 128 \times 1 \times 1 \times 256$
- [3×3 conv, 192] $28 \times 28 \times 192 \times 3 \times 3 \times 64$
- [5×5 conv, 96] $28 \times 28 \times 96 \times 5 \times 5 \times 64$
- [1×1 conv, 64] $28 \times 28 \times 64 \times 1 \times 1 \times 256$



Total: 358M ops

Compared to 854M ops for naive version
Bottleneck can also reduce depth after pooling layer

Case Study: GoogLeNet

[Szegedy et al., 2014]


Stack Inception modules
with dimension reduction
on top of each other



Case Study: GoogLeNet

[Szegedy et al., 2014]

Full GoogLeNet
architecture




Stem Network:
Conv-Pool-
2x Conv-Pool

Case Study: GoogLeNet

[Szegedy et al., 2014]


Full GoogLeNet
architecture



Case Study: GoogLeNet

[Szegedy et al., 2014]


Full GoogLeNet
architecture



Case Study: GoogLeNet

[Szegedy et al., 2014]

Full GoogLeNet
architecture




Classifier output
(removed expensive FC layers!)

Case Study: GoogLeNet

[Szegedy et al., 2014]

Full GoogLeNet
architecture




Auxiliary classification outputs to inject additional gradient at lower layers
(AvgPool-1x1Conv-FC-FC-Softmax)

Case Study: GoogLeNet

[Szegedy et al., 2014]

Full GoogLeNet
architecture



22 total layers with weights


(parallel layers count as 1 layer => 2 layers per Inception module. Don't count auxiliary output layers)

Case Study: GoogLeNet


[Szegedy et al., 2014]

Deeper networks, with computational efficiency


- 22 layers
- Efficient “Inception” module
- No FC layers
- 12x less params than AlexNet
- ILSVRC’14 classification winner (6.7% top 5 error)



Inception module



ImageNet Large Scale Visual Recognition Challenge (ILSVRC) winners




Case Study: ResNet

[He et al., 2015]

Very deep networks using residual connections

- 152-layer model for ImageNet
- ILSVRC'15 classification winner (3.57% top 5 error)
- Swept all classification and detection competitions in ILSVRC'15 and COCO'15!



Case Study: ResNet



[He et al., 2015]

What happens when we continue stacking deeper layers on a “plain” convolutional neural network?

Case Study: ResNet

[He et al., 2015]

What happens when we continue stacking deeper layers on a “plain” convolutional neural network?





Q: What's strange about these training and test curves?
[Hint: look at the order of the curves]

Case Study: ResNet

[He et al., 2015]

What happens when we continue stacking deeper layers on a “plain” convolutional neural network?



56-layer model performs worse on both training and test error
-> The deeper model performs worse, but it's not caused by overfitting!

Case Study: ResNet

[He et al., 2015]

Hypothesis: the problem is an *optimization* problem, deeper models are harder to optimize

Case Study: ResNet

[He et al., 2015]

Hypothesis: the problem is an *optimization* problem, deeper models are harder to optimize



The deeper model should be able to perform at least as well as the shallower model.

A solution by construction is copying the learned layers from the shallower model and setting additional layers to identity mapping.

Case Study: ResNet

[He et al., 2015]


Solution: Use network layers to fit a residual mapping instead of directly trying to fit a desired underlying mapping



Case Study: ResNet

[He et al., 2015]

Solution: Use network layers to fit a residual mapping instead of directly trying to fit a desired underlying mapping





Case Study: ResNet

[He et al., 2015]

Full ResNet architecture:

- Stack residual blocks
- Every residual block has two 3x3 conv layers





Case Study: ResNet

[He et al., 2015]

Full ResNet architecture:

- Stack residual blocks
- Every residual block has two 3x3 conv layers
- Periodically, double # of filters and downsample spatially using stride 2 (/2 in each dimension)





Case Study: ResNet

[He et al., 2015]

Full ResNet architecture:

- Stack residual blocks
- Every residual block has two 3x3 conv layers
- Periodically, double # of filters and downsample spatially using stride 2 (/2 in each dimension)
- Additional conv layer at the beginning





Case Study: ResNet

[He et al., 2015]

Full ResNet architecture:


- Stack residual blocks
- Every residual block has two 3x3 conv layers
- Periodically, double # of filters and downsample spatially using stride 2 (/2 in each dimension)
- Additional conv layer at the beginning
- No FC layers at the end (only FC 1000 to output classes)



Case Study: ResNet

[He et al., 2015]


Total depths of 34, 50, 101, or
152 layers for ImageNet



Case Study: ResNet

[He et al., 2015]


For deeper networks
(ResNet-50+), use “bottleneck”
layer to improve efficiency
(similar to GoogLeNet)



Case Study: ResNet

[He et al., 2015]

For deeper networks
(ResNet-50+), use “bottleneck”
layer to improve efficiency
(similar to GoogLeNet)



Case Study: ResNet

[He et al., 2015]

Training ResNet in practice:

- Batch Normalization after every CONV layer
- Xavier 2/ initialization from He et al.
- SGD + Momentum (0.9)
- Learning rate: 0.1, divided by 10 when validation error plateaus
- Mini-batch size 256
- Weight decay of 1e-5
- No dropout used

Case Study: ResNet

[He et al., 2015]

Experimental Results

- Able to train very deep networks without degrading (152 layers on ImageNet, 1202 on Cifar)
- Deeper networks now achieve lower training error as expected
- Swept 1st place in all ILSVRC and COCO 2015 competitions

MSRA @ ILSVRC & COCO 2015 Competitions

- **1st places** in all five main tracks
 - ImageNet Classification: “Ultra-deep” (quote Yann) **152-layer** nets
 - ImageNet Detection: **16%** better than 2nd
 - ImageNet Localization: **27%** better than 2nd
 - COCO Detection: **11%** better than 2nd
 - COCO Segmentation: **12%** better than 2nd

Case Study: ResNet

[He et al., 2015]

Experimental Results


- Able to train very deep networks without degrading (152 layers on ImageNet, 1202 on Cifar)
- Deeper networks now achieve lower training error as expected
- Swept 1st place in all ILSVRC and COCO 2015 competitions

MSRA @ ILSVRC & COCO 2015 Competitions



- **1st places** in all five main tracks
 - ImageNet Classification: “Ultra-deep” (quote Yann) 152-layer nets
 - ImageNet Detection: 16% better than 2nd
 - ImageNet Localization: 27% better than 2nd
 - COCO Detection: 11% better than 2nd
 - COCO Segmentation: 12% better than 2nd

ILSVRC 2015 classification winner (3.6% top 5 error) -- better than “human performance”! (Russakovsky 2014)

ImageNet Large Scale Visual Recognition Challenge (ILSVRC) winners



Comparing complexity...





An Analysis of Deep Neural Network Models for Practical Applications, 2017.

Figures copyright Alfredo Canziani, Adam Paszke, Eugenio Culurciello, 2017. Reproduced with permission.

Comparing complexity...



Inception-v4: Resnet + Inception!



An Analysis of Deep Neural Network Models for Practical Applications, 2017.

Figures copyright Alfredo Canziani, Adam Paszke, Eugenio Culurciello, 2017. Reproduced with permission.


Comparing complexity...




An Analysis of Deep Neural Network Models for Practical Applications, 2017.

Figures copyright Alfredo Canziani, Adam Paszke, Eugenio Culurciello, 2017. Reproduced with permission.

Comparing complexity...




GoogLeNet:
most efficient




An Analysis of Deep Neural Network Models for Practical Applications, 2017.

Figures copyright Alfredo Canziani, Adam Paszke, Eugenio Culurciello, 2017. Reproduced with permission.

Comparing complexity...




AlexNet:
Smaller compute, still memory
heavy, lower accuracy




An Analysis of Deep Neural Network Models for Practical Applications, 2017.

Figures copyright Alfredo Canziani, Adam Paszke, Eugenio Culurciello, 2017. Reproduced with permission.

Comparing complexity...





ResNet:
Moderate efficiency depending on
model, highest accuracy



An Analysis of Deep Neural Network Models for Practical Applications, 2017.

Figures copyright Alfredo Canziani, Adam Paszke, Eugenio Culurciello, 2017. Reproduced with permission.

Forward pass time and power consumption



An Analysis of Deep Neural Network Models for Practical Applications, 2017.


Figures copyright Alfredo Canziani, Adam Paszke, Eugenio Culurciello, 2017. Reproduced with permission.

Other architectures to know...


Network in Network (NiN)

[Lin et al. 2014]


- Mlpconv layer with “micronetwork” within each conv layer to compute more abstract features for local patches
- Micronetwork uses multilayer perceptron (FC, i.e. 1×1 conv layers)
- Precursor to GoogLeNet and ResNet “bottleneck” layers
- Philosophical inspiration for GoogLeNet



(a) Linear convolution layer



(b) Mlpconv layer




Figures copyright Lin et al., 2014. Reproduced with permission.

Identity Mappings in Deep Residual Networks

[He et al. 2016]


- Improved ResNet block design from creators of ResNet
- Creates a more direct path for propagating information throughout network (moves activation to residual mapping pathway)
- Gives better performance




Wide Residual Networks

[Zagoruyko et al. 2016]

- Argues that residuals are the important factor, not depth
- Use wider residual blocks ($F \times k$ filters instead of F filters in each layer)
- 50-layer wide ResNet outperforms 152-layer original ResNet
- Increasing width instead of depth more computationally efficient (parallelizable)



Basic residual block




Wide residual block

Improving ResNets... Aggregated Residual Transformations for Deep Neural Networks (ResNeXt)

[Xie et al. 2016]

- Also from creators of ResNet
- Increases width of residual block through multiple parallel pathways (“cardinality”)
- Parallel pathways similar in spirit to Inception module




Improving ResNets...


Deep Networks with Stochastic Depth

[Huang et al. 2016]

- Motivation: reduce vanishing gradients and training time through short networks during training
- Randomly drop a subset of layers during each training pass
- Bypass with identity function
- Use full deep network at test time



ImageNet Large Scale Visual Recognition Challenge (ILSVRC) winners



Improving ResNets...


“Good Practices for Deep Feature Fusion”

[Shao et al. 2016]

- Multi-scale ensembling of Inception, Inception-Resnet, Resnet, Wide Resnet models
- ILSVRC'16 classification winner

	Inception-v3	Inception-v4	Inception-Resnet-v2	Resnet-200	Wrn-68-3	Fusion (Val.)	Fusion (Test)
Err. (%)	4.20	4.01	3.52	4.26	4.65	2.92 (-0.6)	2.99

ImageNet Large Scale Visual Recognition Challenge (ILSVRC) winners





Improving ResNets...

Squeeze-and-Excitation Networks (SENet)

[Hu et al. 2017]

- Add a “feature recalibration” module that learns to adaptively reweight feature maps
- Global information (global avg. pooling layer) + 2 FC layers used to determine feature map weights
- ILSVRC’17 classification winner (using ResNeXt-152 as a base architecture)




Beyond ResNets...

FractalNet: Ultra-Deep Neural Networks without Residuals

[Larsson et al. 2017]

- Argues that key is transitioning effectively from shallow to deep and residual representations are not necessary
- Fractal architecture with both shallow and deep paths to output
- Trained with dropping out sub-paths
- Full network at test time




Figures copyright Larsson et al., 2017. Reproduced with permission.

Beyond ResNets...

Densely Connected Convolutional Networks

[Huang et al. 2017]

- Dense blocks where each layer is connected to every other layer in feedforward fashion
- Alleviates vanishing gradient, strengthens feature propagation, encourages feature reuse



Efficient networks...

SqueezeNet: AlexNet-level Accuracy With 50x Fewer Parameters and <0.5Mb Model Size

[Iandola et al. 2017]

- Fire modules consisting of a ‘squeeze’ layer with 1x1 filters feeding an ‘expand’ layer with 1x1 and 3x3 filters
- AlexNet level accuracy on ImageNet with 50x fewer parameters
- Can compress to 510x smaller than AlexNet (0.5Mb)





Figure copyright Iandola, Han, Moskewicz, Ashraf, Dally, Keutzer, 2017. Reproduced with permission.

Meta-learning: Learning to learn network architectures...

Neural Architecture Search with Reinforcement Learning (NAS)

[Zoph et al. 2016]

- “Controller” network that learns to design a good network architecture (output a string corresponding to network design)
- Iterate:
 - 1) Sample an architecture from search space
 - 2) Train the architecture to get a “reward” R corresponding to accuracy
 - 3) Compute gradient of sample probability, and scale by R to perform controller parameter update (i.e. increase likelihood of good architecture being sampled, decrease likelihood of bad architecture)





Meta-learning: Learning to learn network architectures...

Learning Transferable Architectures for Scalable Image Recognition

[Zoph et al. 2017]

- Applying neural architecture search (NAS) to a large dataset like ImageNet is expensive
- Design a search space of building blocks (“cells”) that can be flexibly stacked
- NASNet: Use NAS to find best cell structure on smaller CIFAR-10 dataset, then transfer architecture to ImageNet



Summary: CNN Architectures

Case Studies

- AlexNet
- VGG
- GoogLeNet
- ResNet

Also....

- NiN (Network in Network)
- Wide ResNet
- ResNeXT
- Stochastic Depth
- Squeeze-and-Excitation Network
- DenseNet
- FractalNet
- SqueezeNet
- NASNet

Summary: CNN Architectures

- VGG, GoogLeNet, ResNet all in wide use, available in model zoos
- ResNet current best default, also consider SENet when available
- Trend towards extremely deep networks
- Significant research centers around design of layer / skip connections and improving gradient flow
- Efforts to investigate necessity of depth vs. width and residual connections
- Even more recent trend towards meta-learning
- Next time: Recurrent neural networks