

# Reproducible Reports

SCR Week 11

## 1. Create your Rproject of this week's course material

Open from this week's course material the `.RProject` file, and check out the differences between the Project Options and the Global Options.

## 2. From `.Rmd` to `.pdf` and to `.html`

If you haven't done so yet, try to knit the default R Markdown file

You can obtain the default R Markdown file in RStudio by

File --> New File --> R Markdown.

## 3. Tutorial R Markdown

Try to see whether you can get quickly through the tutorial on: <http://rmarkdown.rstudio.com/lesson-1.html>

## 4. Your own Rproject

Reproduce the `.pdf` files and the lecture IO-slides presentation from the R Markdown source files of this week's lecture material.

## 5. Things that affect the knitting of your R Markdown file (and perhaps your final grade)

The more more dynamic your document, the more easily it becomes buggy for someone to reproduce your code. In this exercise we discuss some of the common errors that occur while sharing `.Rmd` files.

### a Pandoc Error 49

#### i keep\_tex or keep\_md

Include either one of the following `keep_tex` or `keep_md` parameters in the YAML header of your R Markdown file. What extra files are made in the directory of your Rproject?

```
---
output:
  pdf_document:
    keep_tex: yes
---
```

or



Figure 1: An example of chinese characters

```
---
output:
  html_document:
    keep_md: yes
---
```

### Answer

We get either an extra `.tex` file or the extra `md` file. Depending on the R Markdown file we are trying to knit.

### ii Strange symbols

Are you able to knit Chinese characters as text in an RMarkdown file? Try it out! When you receive an error, it may refer to a line number. When you've put the Chinese characters in your text, you should be able to find this line number in the `.md` or `.tex` file.

### b Some not-so-smart-to-do things: Do try them at home!

#### i

Why should you NOT have an R chunk in your R Markdown file that will evaluate the code `rs.restartR()`?

#### Answer

You won't be able to knit your markdown file anymore, and therefore cannot create the dynamic document / reproducible report...

Try it out yourself by putting the `eval` argument to `TRUE`:

```
.rs.restartR()
```

#### ii

Will `View(mtcars)` get evaluated when knitting an R Markdown file?

### c Standalone

Should we always start an R Markdown file with `rm(list = ls())` such that objects that are left in your workspace cannot negatively affect the R code chunks? Or is an R Markdown file **standalone**?

If you don't know the answer to this question, try to experiment and see whether your R Markdown file can make use of the variables in your global space (these are the variables that show when you type `ls()` in your R console).

## d Rick Roll: Know your meme

How can you Rick Roll someone within R Markdown? You need to be able to open an internet browser.. and use e.g. a youtube url to Rick Astley's video clip.

Rickrolling: <https://en.wikipedia.org/wiki/Rickrolling>

## 6 Use `rmarkdown::render` from the R console

By using the function `rmarkdown::render()` from your R console, see whether you can reproduce the .pdf files and the lecture IO-slides presentation from the R Markdown source files of this week's lecture material.

## 7 Optional: Play with Pandoc from your terminal

By using pandoc in your terminal, see whether you can reproduce the exercises from the **Markdown** source files of this week's lecture material. Note, that we are specifically talking about the markdown files and not the R Markdown files..

*Hint: use the terminal commands that show in the "RMarkdown console" when you render your Rmd file in the usual way (via the button 'knit' or `rmarkdown::render()`)*

## 8 Optional: R Markdown Gallery

Check out the (gallery)[<http://rmarkdown.rstudio.com/gallery.html>] and challenge yourself to reproduce at least one of them on your own computer.

## 9 Practicing R again: Yahtzee and Maximum-Likelihood estimation

The following poker-themed combinations of five dice appear in the game of yahtzee:

- *Yahtzee* (five of a kind; e.g., 5 ones, 5 twos, or 5 threes)
- *Carre* (four of a kind)
- *Three of a kind*
- *Full house* (three and two of a kind)
- *Large Straight* (five sequential dice)
- *Small straight* (four sequential dice)

For the next exercises try to write your answers conform a consistent style of coding in R. Also, try to see where the `%>%` can be implemented, or not.

**a**

All possible rolls with five dice are collected in `all.rolls`. Note that 12222 appears five times because there are five ways to roll 12222 (12222, 21222, 22122, 22212, and 22221).

The following code is constructing `all.rolls`:

```
all.rolls <- apply(t(apply(as.matrix(expand.grid(1:6,1:6,1:6,1:6,1:6)
),1,sort)),1,paste,collapse="")
```

Rewrite this code in something more readable.

*Hint: you may use the %>% operator.*

**b**

What is the probability of rolling 11344? Note that the order doesn't matter here.

**c**

The next code will be used to investigate which rolls are yahtzee, carre, three of a kind, full house, large straight, and small straight. Could you make the code for the `full.set` by using the variables in the the following code?

```
N <- all.rolls %>% length()

#yahtzee
five.set <- c("11111","22222","33333","44444","55555","66666")
is.five <- substr(all.rolls, 1, 5) %in% five.set

# carre

four.set <- c("1111", "2222", "3333", "4444", "5555", "6666")
is.four <- rep(FALSE, N)
is.four <- substr(all.rolls, 1, 4) %in% four.set | is.four
is.four <- substr(all.rolls, 2, 5) %in% four.set | is.four

# three of a kind
three.set <- c("111", "222", "333", "444", "555", "666")
is.three <- rep(FALSE, N)
is.three <- substr(all.rolls, 1, 3) %in% three.set | is.three
is.three <- substr(all.rolls, 2, 4) %in% three.set | is.three
is.three <- substr(all.rolls, 3, 5) %in% three.set | is.three

# full house
two.set <- c("11", "22", "33", "44", "55", "66")
# full.set <- _ _ _
# is.full <- substr(all.rolls, 1, 5) %in% full.set

# large straight
large.set <- c("12345", "23456")
is.large <- substr(all.rolls, 1, 5) %in% large.set

# small straight
small.set <- c("1234", "2345", "3456")
is.small <- rep(FALSE, N)
is.small <- substr(all.rolls, 1, 4) %in% small.set | is.small
is.small <- substr(all.rolls, 2, 5) %in% small.set | is.small
```

**d**

Create a `data.frame` containing `all.rolls`, `is.five`, `is.four`, `is.three`, `is.full`, `is.large`, and `is.small`.

**e**

Compute the probability that a single roll results in a particular poker-themed combination, for each of the combinations.

**f**

Write code to repeatedly roll five dice until a roll yields a full house. How many rolls were necessary?

Make sure to set a seed (`set.seed()`) s.t. others can obtain the exact same results.

**g**

Use a for-loop to execute the code from item f for `B <- 1000` times. Save the number of rolls needed to get a full house in a vector.

Make sure to set a seed (`set.seed()`) s.t. others can obtain the exact same results.

**h**

The counts we have obtained in item g were the results from sampling processes from a negative binomial distribution function. The number of rolls can be seen as the number of trials until (and including) the occurrence of a success. Plot the negative binomial cumulative distribution function (cdf) of the results (each of the B counts). You may use `pnbinom()`, or you can program the cdf yourself.

**i**

Plot the log-likelihood *all* the numbers of rolls together (item c). The vertical axis should represent the log-likelihood, and the horizontal axis the probability. Make two plots. The first plot shows the log-likelihood for a probability in the interval (0 - 1), the second plot shows the log-likelihood for the probability in the interval (0 - 0.2). Last, what is the maximum likelihood estimator?

*Hint: make sure that the vertical axis of the second plot is scaled nicely s.t. the shape is clearly a parabola*

## 9 Optional: Yahtzee roll function

Program your own Google's R Style `YahtzeeRoll` function.

The function does not need to have any input arguments, it returns a list of two items. From the first item of the list we can retrieve the values of your roll of six dices and in the second item of the list it is explained whether and which of poker-themed combinations you may have obtained.

## 10 Optional: A last fair dice problem

Make a while-loop in which you roll three dice until they are all equal (111, 222, ... 666). How many rolls do you need?

Make sure to set a seed (`set.seed()`) s.t. others can obtain the exact same results.