

# Basics

---

Computer Science  $\subset$  Mathematics

- Usually at least one problem that involves solving mathematically.
- Problems often require mathematical analysis to be solved efficiently.
- Using a bit of math before coding can also shorten and simplify code.

# Finding patterns and formulas

- Some problems have solutions that form a pattern.

# Finding patterns and formulas

- Some problems have solutions that form a pattern.
- By finding the pattern, we solve the problem.
- Could be classified as mathematical ad-hoc problem.
- Requires mathematical intuition.

# Finding patterns and formulas

- Some problems have solutions that form a pattern.
- By finding the pattern, we solve the problem.
- Could be classified as mathematical ad-hoc problem.
- Requires mathematical intuition.
- Useful tricks:
  - Solve some small instances by hand.
  - See if the solutions form a pattern.

# Finding patterns and formulas

- Some problems have solutions that form a pattern.
- By finding the pattern, we solve the problem.
- Could be classified as mathematical ad-hoc problem.
- Requires mathematical intuition.
- Useful tricks:
  - Solve some small instances by hand.
  - See if the solutions form a pattern.
- Does the pattern involve some overlapping subproblem?

# Finding patterns and formulas

- Some problems have solutions that form a pattern.
- By finding the pattern, we solve the problem.
- Could be classified as mathematical ad-hoc problem.
- Requires mathematical intuition.
- Useful tricks:
  - Solve some small instances by hand.
  - See if the solutions form a pattern.
- Does the pattern involve some overlapping subproblem?  
We might need to use DP.



# Finding patterns and formulas

- Some problems have solutions that form a pattern.
- By finding the pattern, we solve the problem.
- Could be classified as mathematical ad-hoc problem.
- Requires mathematical intuition.
- Useful tricks:
  - Solve some small instances by hand.
  - See if the solutions form a pattern.
- Does the pattern involve some overlapping subproblem?  
We might need to use DP.
- Knowing reoccurring identities and sequences can be helpful.

# Arithmetic progression

- Often we see a pattern like

$2, 5, 8, 11, 14, 17, 20, \dots$

# Arithmetic progression

- Often we see a pattern like

2, 5, 8, 11, 14, 17, 20, ...

- This is called a arithmetic progression.

$$a_n = a_{n-1} + c$$

# Arithmetic progression

- Depending on the situation we may want to get the  $n$ -th element

$$a_n = a_1 + (n - 1)c$$

- Or the sum over a finite portion of the progression

$$S_n = \frac{n(a_1 + a_n)}{2}$$

# Arithmetic progression

- Depending on the situation we may want to get the  $n$ -th element

$$a_n = a_1 + (n - 1)c$$

- Or the sum over a finite portion of the progression

$$S_n = \frac{n(a_1 + a_n)}{2}$$

- Remember this one?

$$1 + 2 + 3 + 4 + 5 + \dots + n = \frac{n(n + 1)}{2}$$

# Geometric progression

- Other types of pattern we often see are geometric progressions

1, 2, 4, 8, 16, 32, 64, 128, ...

# Geometric progression

- Other types of pattern we often see are geometric progressions

1, 2, 4, 8, 16, 32, 64, 128, ...

- More generally

$a, ar, ar^2, ar^3, ar^4, ar^5, ar^6, \dots$

$$a_n = ar^{n-1}$$

# Geometric progression

- Sum over a finite portion

$$\sum_{i=0}^n ar^i = \frac{a(1 - r^n)}{(1 - r)}$$



# Geometric progression

- Sum over a finite portion

$$\sum_{i=0}^n ar^i = \frac{a(1 - r^n)}{(1 - r)}$$

- Or from the  $m$ -th element to the  $n$ -th

$$\sum_{i=m}^n ar^i = \frac{a(r^m - r^{n+1})}{(1 - r)}$$

# Little bit about logarithm

- Sometimes doing computation in logarithm can be an efficient alternative.

# Little bit about logarithm

- Sometimes doing computation in logarithm can be an efficient alternative.
- In both C++(`<cmath>`) and Java(`java.lang.Math`) we have the natural logarithm

```
double log(double x);
```

# Little bit about logarithm

- Sometimes doing computation in logarithm can be an efficient alternative.
- In both C++(`<cmath>`) and Java(`java.lang.Math`) we have the natural logarithm

```
double log(double x);
```

and logarithm in base 10

```
double log10(double x);
```

# Little bit about logarithm

- Sometimes doing computation in logarithm can be an efficient alternative.
- In both C++(`<cmath>`) and Java(`java.lang.Math`) we have the natural logarithm

```
double log(double x);
```

and logarithm in base 10

```
double log10(double x);
```

- And also the exponential

```
double exp(double x);
```

## Example

- For example, what is the first power of 17 that has  $k$  digits in base  $b$ ?

# Example

- For example, what is the first power of 17 that has  $k$  digits in base  $b$ ?
- **Naive solution:** Iterate over powers of 17 and count the number of digits.

# Example

- For example, what is the first power of 17 that has  $k$  digits in base  $b$ ?
- **Naive solution:** Iterate over powers of 17 and count the number of digits.
- But the powers of 17 grow exponentially!

$$17^{16} > 2^{64}$$

- What if  $k = 500$  ( $\sim 1.7 \cdot 10^{615}$ ), or something larger?



# Example

- For example, what is the first power of 17 that has  $k$  digits in base  $b$ ?
- **Naive solution:** Iterate over powers of 17 and count the number of digits.
- But the powers of 17 grow exponentially!

$$17^{16} > 2^{64}$$

- What if  $k = 500$  ( $\sim 1.7 \cdot 10^{615}$ ), or something larger?
- Impossible to work with the numbers in a normal fashion.
- Why not log?

# Example

- Remember, we can calculate the length of a number  $n$  in base  $b$  with  $\lfloor \log_b(n) \rfloor + 1$ .

# Example

- Remember, we can calculate the length of a number  $n$  in base  $b$  with  $\lfloor \log_b(n) \rfloor + 1$ .
- But how do we do this with only  $\ln$  or  $\log_{10}$ ?

# Example

- Remember, we can calculate the length of a number  $n$  in base  $b$  with  $\lfloor \log_b(n) \rfloor + 1$ .
- But how do we do this with only  $\ln$  or  $\log_{10}$ ?
- Change base!

$$\log_b(a) = \frac{\log_d(a)}{\log_d(b)} = \frac{\ln(a)}{\ln(b)}$$

- Now we can at least count the length without converting bases

# Example

- We still have to iterate over the powers of 17, but we can do that in log

$$\ln(17^{x-1} \cdot 17) = \ln(17^{x-1}) + \ln(17)$$

# Example

- We still have to iterate over the powers of 17, but we can do that in  $\log$

$$\ln(17^{x-1} \cdot 17) = \ln(17^{x-1}) + \ln(17)$$

- More generally

$$\log_b(xy) = \log_b(x) + \log_b(y)$$

- For division

$$\log_b\left(\frac{x}{y}\right) = \log_b(x) - \log_b(y)$$

## Example

- We can simplify this even more.
- The solution to our problem is in mathematical terms, finding the  $x$  for

$$\log_b(17^x) = k - 1$$

# Example

- We can simplify this even more.
- The solution to our problem is in mathematical terms, finding the  $x$  for

$$\log_b(17^x) = k - 1$$

- One more handy identity

$$\log_b(a^c) = c \cdot \log_b(a)$$



# Example

- We can simplify this even more.
- The solution to our problem is in mathematical terms, finding the  $x$  for

$$\log_b(17^x) = k - 1$$

- One more handy identity

$$\log_b(a^c) = c \cdot \log_b(a)$$

- Using this identity and the ones we've covered, we get

$$x = \left[ (k - 1) \cdot \frac{\ln(10)}{\ln(17)} \right]$$

# Base conversion

- Speaking of bases.

# Base conversion

- Speaking of bases.
- What if we actually need to use base conversion?

# Base conversion

- Speaking of bases.
- What if we actually need to use base conversion?
- Simple algorithm

```
vector<int> toBase(int base, int val) {  
    vector<int> res;  
    while(val) {  
        res.push_back(val % base);  
        val /= base;  
    }  
    return val;  
}
```

- Starts from the 0-th digit, and calculates the multiple of each power.

# Working with doubles

- Comparing doubles, sounds like a bad idea.

# Working with doubles

- Comparing doubles, sounds like a bad idea.
- What else can we do if we are working with real numbers?

# Working with doubles

- Comparing doubles, sounds like a bad idea.
- What else can we do if we are working with real numbers?
- We compare them to a certain degree of precision.

# Working with doubles

- Comparing doubles, sounds like a bad idea.
- What else can we do if we are working with real numbers?
- We compare them to a certain degree of precision.
- Two numbers are deemed equal if their difference is less than some small epsilon.

```
const double EPS = 1e-9;
```

```
if (abs(a - b) < EPS) {  
    ...  
}
```



# Working with doubles

- Less than operator:

```
if (a < b - EPS) {  
    ...  
}
```

- Less than or equal:

```
if (a <= b + EPS) {  
    ...  
}
```

- The rest of the operators follow.

# Working with doubles

- This allows us to use comparison based algorithms.

# Working with doubles

- This allows us to use comparison based algorithms.
- For example `std::set<double>`.

```
struct cmp {  
    bool operator() {double a, double b} {  
        return a < b - EPS;  
    }  
};
```

```
set<double, cmp> doubleSet();
```

- Other STL containers can be used in similar fashion.

# Number Theory

---

- Problem statements often end with the sentence

*“... and output the answer modulo  $n$ .”*

- Problem statements often end with the sentence

*“... and output the answer modulo  $n$ .”*

- This implies that we can do all the computation with integers *modulo  $n$* .

- Problem statements often end with the sentence

*“... and output the answer modulo  $n$ .”*

- This implies that we can do all the computation with integers *modulo  $n$* .
- The integers, modulo some  $n$  form a structure called a *ring*.

- Problem statements often end with the sentence

*“... and output the answer modulo  $n$ .”*

- This implies that we can do all the computation with integers *modulo  $n$* .
- The integers, modulo some  $n$  form a structure called a *ring*.
- Special rules apply, also loads of interesting properties.



Some of the allowed operations:

- Addition and subtraction modulo  $n$

$$(a \bmod n) + (b \bmod n) = (a + b \bmod n)$$

$$(a \bmod n) - (b \bmod n) = (a - b \bmod n)$$

- Multiplication

$$(a \bmod n)(b \bmod n) = (ab \bmod n)$$

- Exponentiation

$$(a \bmod n)^b = (a^b \bmod n)$$

- *Note:* We are only working with integers.

- What about division?

- What about division? NO!

- What about division? NO!
- We could end up with a fraction!
- Division with  $k$  equals multiplication with the *multiplicative inverse* of  $k$ .

- What about division? **NO!**
- We could end up with a fraction!
- Division with  $k$  equals multiplication with the *multiplicative inverse* of  $k$ .
- The *multiplicative inverse* of an integer  $a$ , is the element  $a^{-1}$  such that

$$a \cdot a^{-1} = 1 \pmod{n}$$

- What about logarithm?

- What about logarithm? YES!
  - But difficult.

- What about logarithm? YES!
  - But difficult.
  - Basis for some cryptography such as elliptic curve, Diffie-Hellmann.
- Google “Discrete Logarithm” if you want to know more.



- **Prime number** is a positive integer greater than 1 that has no positive divisor other than 1 and itself.
- **Greatest Common Divisor** of two integers  $a$  and  $b$  is the largest number that divides both  $a$  and  $b$ .
- **Least Common Multiple** of two integers  $a$  and  $b$  is the smallest integer that both  $a$  and  $b$  divide.
- **Prime factor** of a positive integer is a prime number that divides it.
- **Prime factorization** is the decomposition of an integer into its prime factors. By the fundamental theorem of arithmetic, every integer greater than 1 has a unique prime factorization.

# Extended Euclidean algorithm

- The Euclidean algorithm is a recursive algorithm that computes the GCD of two numbers.

```
int gcd(int a, int b){  
    return b == 0 ? a : gcd(b, a % b);  
}
```

- Runs in  $O(\log^2 N)$ .