HTML 5 Modern

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <!--Judul Tab Browser-->
    <title>The Material Part 1 Learn HTML5 Modern</title>
  </head>
  <p>
    <!-- Main Content -->


        <!-- Chapter 1 -->
    <!-- Sect. 3.1 - Simple Heading as Example test -->
    <h1> Chapter 1 - Headings </h1>


    <p>HTML provides not only plain paragraph tags, but siz separate header tags to indicate headings of various sizes and thicknesses. Enumerated as heading 1 through heading 6, heading 1 has the largest and thickest text while heading 6 is the smallest and thinnest, down to paragraph level. This topic datails proper usage of these tags</p>


    <h1> Hello World!</h1> <!-- Judul besar Main Content -->
    <p> This is a simple paragraph</p>
    <h2> Heading 2 </h2> <!-- Judul Subbab Main Content -->
    <h3> Heading 3 </h3> <!-- Judul subbab didalam subbab -->
    <h4> Heading 4 </h4>
    <h5> Heading 5 </h5>
    <h6> Heading 6 </h6>


    <!-- Example Document (Extra intendation to ilustrate Hierarchy) -->
```

```
<h1> Main Title (Judul utama) </h1>
<p>Introduction (Pengantar/Pendahuluan) </p>
  <h2> Reasons</h2>

    <h3> Reason 1 </h3>
    <p> Paragraph </p>

    <h3> Reason 2 </h3>
    <p> Paragraph </p>

  <h2> In Conclusion </h2>
  <p> Paragraph </p>

  <br> <!-- Spacing line like enter-->

      <!-- Chapter 2 - Paragraph -->
<h1> Chapter 2 - Paragraph </h1>
<p> (P) Defines a Paragraph </p>
<br><p> (br) Defines is Inserts a single line break (Same as like enter)</p> <!--Inserts a single line break (Same as like enter) -->
<pre> Defines (pre) pre-formatted text </pre>
<p> paragraph are the most basic HTML element. This Topic explains and demonstrates the usage of the paragraph element in HTML</p>

<br> <!-- Spacing line like enter-->

      <!-- Chapter 3 - Text Formatting -->
<h1> Chapter 3 - Text formatting </h1>

  <!-- Chapter 3.1 - Highlighting-->
 <h2> 3.1 Highlighting </h2>
```

 Here is some Content from an article that contains the <mark>(mark) Search query</mark> that we are looking for. Highlighting the text will make it easier for the user to find what what they are looking for.

<!-- Chapter 3.2 - Bold, Italic and Underline -->

<h2> Chapter 3.2 Bold, Italic and Underline </h2>

<!-- Bold Text -->

<h3>Bold Text</h3>

 to bold text use the (strong) or (b) tags

 (strong) Bold Text Here

or

  (b) Bold Text Here

What's the difference? Semantics (strong) is used to indicate that the text is fundamentally or semanticallyimportant to the surrounding text, while (b) Bold indicates no such importance and simply represents text that should

be bolded.

 If you were to use (b) a text-to-speech program would not say the word(s) any differently than any of the other words around it - you are simply drawing attention to them without adding any additional importance. By using (strong) , though, the same program would want to speak those word(s) with a different tone of voice to convey that the text is important in some way

<!-- Italid -->

<h3> Italic (tulisan miring) </h3>

 to Italicicze text, use the (em) or (i)

 (em) Italicized Text Here

or

 (i) Italicized Text Here

<!-- Underlined Text -->

<h3>Underline Text</h3>

 while the <u>(u = underlined text)</u> element itself was deprecated in HTML 4, it was reintroduced with alternate semantic meaning in HTML 5 - to represent an unarticulated, non-textual annotation. you might use such a rendering to indicate misspelled text on the page, or a chinese proper name mark

 This Paragraph contains some <u> (u = underlined text) mispelled </u> text.

<!-- Chapter 3.3 - Abbreviation -->

<h2> Chapter 3.3 - Abbriviation </h2>

 To mark some Expression as an abbriviation, use <abbr title="">(abbr)</abbr> tag

 I like to writte <abbr title="Hypertext Markup Language"> (abbr title="Hypertext Markup Language") HTML</abbr> !

<P> If Present, the title attribute is used to present the full description of such abbriviation </P>

<!-- Chapter 3.4 - Inserted, Deleted, or Stricken -->

<h2> Chapter 3.4 - Inserted, Deleted, or Stricken </h2>

<!-- Inserted -->

<h3>Inserted</h3>

To mark text as inserted, use the <ins>(ins)</ins> tag:

<ins> (ins) </ins> New Text

```
<!-- deleted -->
<h3>Deleted</h3>

<p> To mark text as inserted, use the <del>(del)</del> tag: </p>

<p><del> (del) </del>Deleted Text</p>

<!-- Stricken -->
 <h3>Stricken</h3>

 <p> To mark text as stricken, use the <s>(Stricken)</s> tag:</p>

<p><s>(Stricken)</s> Struck-Through text here </p>

<!-- Chapter 3.5 - Superscript & Subscript -->
<h2> Chapter 3.5 - Superscript & Subscript </h2>

<p>To offset text either upwared or downward you can use the tags <sup>(sup = Superscript)</sup> and <sub>(Subscript)</sub></p>

<!-- Superscript-->
<h3>Superscript</h3>

<p>To create Superscript:</p>
<p><sup>Superscript</sup> Here </p>\

 <!-- Subscript-->
<h3>Subscript</h3>

<p>To create Subscript:</p>
```

_{Subscript} Here

 <!-- Spacing line like enter -->

<!-- Chapter 4 - Anchors & Hyperlinks -->

<h1> Chapter 4 - Anchors & Hyperlinks </h1>

<table>
<thead>
<tr>
<th> Parameters </th>
<th> Details </th>
</tr>
</thead>
<tbody>
<tr>
<td>href</td>
<td>Specifies the destination address. It can be an absolute or relative URL, or the name of an anchor. An absolute URL is the complete URL of a website like http://example.com/. A relative URL points to another directory and/or document inside the same website, e.g. /about-us/ points to the directory “about-us” inside the root directory (/). When pointing to another directory without explicitly specifying the document, web servers typically return the document “index.html” inside that directory.</td>
</tr>
<tr>
<td>hreflang</td>
<td> Specifies the language of the resource linked by the href attribute (which must be present with this one). use language values from BCP 47 for HTML5 and RFC 1766 for HTML 4. </td>
</tr>
<tr>
<td>rel</td>
</tr>
</table>

<td> Specifies the relationship between the current decoment and the linked document. for HTML5, the values must be defined in the specification or registered in the microformats wiki . </td>

</tr>

<tr>

<td>target</td>

<td>specifies where to open the link, e.g. in a new tab or window. possible values are _blank, _self, _parent, _top and framename (deprecated). forcing such behaviour is not recommended since it violates the control of the user over a website.</td>

</tr>

<tr>

<td>title</td>

<td>specifies extra information about a link. The information is most often shown as a tooltip Text when the cursor moves over the link . THis attributes is note retrickted to links, it can be used on almost all HTML tags.</td>

</tr>

<tr>

<td>download</td>

<td>Specifies that the target will be downloaded when a user clicks on the hyperlink. The Value of the attribute will be the name of the downloaded file. There are on restrictions on allowed values, and the browser will automatically detect the correct file extension and add it to the file (.img, .pdf, etc.) if the values is ommited, the original filename is used.</td>

</tr>

</tbody>

</table>

<!-- Chapter 4.1 - Link to another site -->

<h2> 4.1 Link to another site </h2>

This is the basic use of the (a href="http://example.com/") element:

(a href="http://example.com/) Link to example.com (/a) then output is Link to example.com

 <!-- Spasing line like Enter -->

To denote that this link leads to an external website, you can use the external link type:

<!-- External site -->

 (a href="http://example.com/ rel="external") Link to example site (/a) then output is Link to example site

 <!-- Spasing line like Enter -->

You can link to a site that uses a protocol other that HTTP. For example, to link to an FTP site, you can do,

<!-- FTP Site -->

(a href="ftp:example.com/") This could be a link to a FTP site(/a)

In this case, the difference is that this anchor tag is requesting that the user's browser connect to example.com using the File Transfer Protocol (FTP) rather than the Hypertext Transfer Protocol (HTTP).

(a href="http://FTPsite.com/") This Could be a link to a FTP site (/a) then output is This Could be a link to a FTP site

<!-- Chapter 4.2 - Link to another anchor -->

<h2> 4.2 Link to another anchor </h2>

Anchors can be used to jump to specifi tags on an HTML page. The <a> (a) tag can point the any element that has an id attribut. To learn more about IDs, visit the documentation about Classes and IDs. Anchors are mostly used to jump to a subsection of a page and are used in conjunction with header tags.

 Suppose you've created a page (page1.html) on many topics:

<!-- 1. First Topic -->

(h2) First Topic (/h2)

<!-- Content about the First Topic -->

(p) Content about the First Topic (p)

<!-- Second Topic -->

(h2) Second Topic (/h2)

<!-- Content about Second Topic -->

(p) Content about the second topic (/p)

 Once you have several sections, you may want to create a Table of Contents at the top of the page with quick-links (or boormarks) to specific sections.

 <!-- Spacing line like enter -->

 If you gave an id attribute to your topics, you could then link to them.

<!-- 2. First Topic -->

(h2 id="Topic1") First Topic (/h2)

<!-- Content about the First Topic -->

(p) Content about the First Topic (p)

<!-- Second Topic -->

(h2 id="Topic2") Second Topic (/h2)

<!-- Content about Second Topic -->

(p) Content about the second topic (/p)

 <!-- Spacing line like enter -->

Now you can use the anchor in your table of contents:

 (h1) Table of Contents (/h1)

(a href="#Topic1") Click to Jump to First Topic (/a) then output is

 Click to Jump to First Topic

(a href="#Topic2") Click to Jump to Second Topic (/a) then output is

 Click to Jump to Second Topic

 Theses anchors are also attached to the web page they're on (page1.html). So you can t link across the site from one page to the other by referencing the page and anchor name

Remember, you can always (a href="page1.html#Topic1") (Look back in the First Topic for supporting information) Look back in the First Topic for supporting information.

<!-- Chapter 4.3 - Link to a page on the same site -->

<h2> 4.3 Link to a page on the same site </h2>

 You can use a relative path to link to pages on the same website

(a href ="/example") Text Here (/a) then output is Text Here

 (a href ="http://example.com/page") Text Here (/a) then output is Text Here

Both of the above would go to the page file at the root directory of example.com

<!-- Chapter 4.4 - Link that dials a number -->

<h2> 4.4 Link that dials a number </h2>

if the valueof the href-attribute begins wit tel:, your device will dial the number when click it. This works on mobile devices or on computers/tablets running software - like skype or Facetime - that can make phone calls.

 (a href="tel:11234567890") Call Us (/a) then output is Call Us

 Most device and programs will prompt the user in some way to confirm the number they are about to dial.

<!-- Chapter 4.5 - Open Link in the new tab/window -->

<h2> 4.5 - Open Link in the New tab/Window </h2>

 (a href="example.com" target="_blank") Text Here (/a) then output is Text Here

The target attribute specifies where to open the link. by setting it to _blank, you tell the browser to open it in a new tab or windwow (per user preference).

<h3> SECURITY VULNERABILITY WARNING! </h3>

 Using target ="_blank" gives the opening site partial access to the window.opener object via JavaScript, which allows that page to then access and change the

window.opener.location of your page and potentiallu redirect users to malware or phising sites

 whenever using this for pages you do not control, add rel ="noopener" to your link to prevent the window.opener object from being sent with the request.

Currently, firefox does not support noopener, so you will need to use rel="noopener noreforrer" for maximum effect

<!-- Chapter 4.6 - Link that runs JavaScript -->

<h2> 4.6 Link that runs JavaScript</h2>

simply use the Javascript : protocol to run the text as Javascript instead of opening it as a normal link:

<!-- Javascript -->

 (a href="javascript :myFunction()") Run code (/a) then output is Run code

 You can also achieve the same thing using the onclick attribute:

<!-- onclick -->

 (a href="#" onclick="myFunction(); return false;") Run Code (/a) Then Output is Run Code

The return false; is necessary to prevent your page from scrolling to the top when the link to # is clicked. make sure to include all code you'd like to run before it, as returning will stop execution of further code.

 Also noteworthy, you can include an exclamation mark ! after the hastag in order to prevent the page from scrolling to the top. This works because any invalid slug will cause the link to not scroll anywhere on the page, because it couldn't locate the element it references (an element with id="!"). You could also just use any invalid slug (such as #scrollsNowhere) to achieve the same effect. In his case, return false; is not required:

 (a href="#!" onclick="myFunction();") Run Code (/a) Then output is Run Code

<h3>Should you be using any of this?</h3>

The answer is almost certainly no. Running JavaScript inline with the element like this is fairly bad practice. Consider using pure JavaScript solutions that look for the element in the page and bind a function to it instead. Listening for an event.

 Also consider whether this element is really a button instead of a link if so, you should use <button>Button</button>.

<!-- Chapter 4.7 - Link that runs email client -->

<h2> 4.7 Link that runs email Client </h2>

<h3>Basic usage</h3>

If the value of the href-attribute begins with mailto : it will try to open an email client on click:

 (a href="mailto : example@example.com") Send email (/a) Then Output is Send email

This will put the email address example@example.com as the recipient for the newly created email.

 <!-- Spacing line like enter -->

<h3> Cc & Bcc</h3>

You can also add address for cc- for bcc-recipients using the following syntax:

 (a href="mailto : example@example.com?cc-john@example.com&bcc=jane@example.com") Send email (/a) Then Output is

 Send email

 <!-- Spacing line like enter -->

<h3> Subject & body text </h3>

You can populate the subject and body for the new email as well

 (a href="mailto :example@example.com?subject=Example+subj&body=Message+text") Send email (/a) Then Output is Send email

Those values must be (a href="URL encode") URL encoded (/a) Then Output is URL encoded .

Clicking on a link with mailto : will try to open the default email client specified by your operating system or it will ask you to choose what client you want to use. Not all options specified after the recipients's address are supported in all email clients.

<!-- Chapter 5 - Lists -->

<h2> Chapter 5 - Lists</h2>

<!-- Chapter 5.1 - Ordered List -->

<h3> 5.1 - Ordered List</h3>

 An ordered list can be created with the (ol) tag and each list them can be created with (li) tag as in the example below:

(ol)

(li) Item (/li)

(li) Another item (/li)

(li) Yet Another item (/li)

(/ol)

 <!-- Spacing line like enter-->

 <!-- Spacing line like enter-->

Then Output is:

This will Produce a numbered list (which is the default style):

Item
Another item
Yet Another item

<h3>Manually Changing the numbers</h3>

 There are a couple of ways you can play with which numbers appear on the list items in ordered list. The first ways is to set a starting number, using the start attribute. The list will start at this defined number, and continue incrementing by on as usual

(ol start="3")
(li) Item (/li)
(li) Another item (/li)
(li) Yet Another item (/li)
(/ol)

 <!-- Spacing line like enter-->

 <!-- Spacing line like enter-->

Then Output is:

This will Produce a numbered list (which is the default style):

<ol start="3">
Item
Some Other item
 Yet Another item

You can also explicitly set a certain list item to a specific number. Further list items after one with a specified value will continue incrementing by one from that list item's value, ignoring where the parent list was at.

(li value="7") Value (/li)

 <!-- Spacing line like enter -->

 <!-- Spacing line like enter -->

Then Output is:

 <!-- Spacing line like enter -->

<li value="7"> Value

 It is also worth nothing that, by using the value attribute directly on a list them, you can override an ordered list's existing numbering system by restarting the numbering at a lower value. So if the parent list was already up to value 7, and encountered a list item at

value 4, then that list ite, would still display as 4 and continue counting from that point again.

(ol start="5")
(li) Item (li)
(li) Some other item (/li)
(li value="4") A Reset item (/li)
(li) Yet other item (/li>)

 <!-- Spacing line like enter -->

Then Output is:

<ol start="5">
Item
<li value="4">Some other item
 A Reset item
 Yet other item

 So the example above will produce a list that follows the numbering pattern of 5, 6, 4, 5, 6 - starting again at a number lower that the provious and duplicating the number 6 in the list.

 <!-- Spacing line like enter -->

Note: The start and value attributes only accept a number - even if the ordered list is tset to display as Roman numerals or letters.

 <!-- Spacing line like enter -->

 <!-- Spacing line like enter -->

version ≥ 5

 <!-- Spacing line like enter -->

 <!-- Spacing line like enter -->

You can reverse the numbering by adding reversed in your ol element:

 <!-- Spacing line like enter -->

 <!-- Spacing line like enter -->

<!-- Reversed - Kebalikan -->
(ol Reversed)
    (li) Item (li)
    (li) Some other item (/li)
    (li value="4") A Reset item (/li)
    (li) Yet other item (/li>)

 <!-- Spacing line like enter -->

Then Output is:

<!-- Reversed - Kebalikan -->
<ol reversed>
   Item
   Some Other Item

```
        <li value="4"> A Reset Item </li>
        <li> Yet Other Item </li>
    </ol>
</p>

<p>Reversed numbering is helpful if you're continually adding to a list, such as with new podcast episodes or presentations, abd you want the most recenty items appear first.</p>

<h3> Changing the type of numeral </h3>
<p>You can easily change the type of numeral shown in the list item marker by using the type attribute
</p>

<ol type="1|a|i|I"> </ol>
<table>
    <thead>
        <tr>
            <th>Type</th>
            <th> Description</th>
            <th>Examples</th>
        </tr>
    </thead>
    <tbody>
        <tr>
            <td> 1 </td>
            <td> Default value - Decimal numbers </td>
            <td> 1,2,3,4 </td>
        </tr>
        <tr>
            <td> a </td>
            <td> Alpabetically ordered (lowercase) </td>
```

```
            <td> a,b,c,d </td>
        </tr>
        <tr>
            <td> A </td>
            <td> Alphabetically Ordered (Uppercase) </td>
            <td> A,B,C,D </td>
        </tr>
        <tr>
            <td> i </td>
            <td> Roman numerals (lowercase) </td>
            <td> i,ii.iii, iv </td>
        </tr>
        <tr>
            <td> I </td>
            <td> Roman numerals (uppercase) </td>
            <td> I,II,III,IV</td>
        </tr>
    </tbody>
</table>

<P>You should use ol ol display a list of items, where the items have been intentionally ordered and order should be emphasized. if changing the order of the items does NOT make the list incorrect, you should use <b>(ul)</b></P>

<!-- Chapter 5.2 - Unordered List -->
<h3> 5.2 - Unordered List </h3>
<p> An ordered list can be created with the <b>(ol)</b> tag and each list them can be created with <b>(li)</b> tag as in the example below: </p>

<p>
```

(ul)

(li) Item (/li)

(li) Another Item (/li)

(li) Yet Another Item (/li)

(/ul)

 <!-- Spacing line like enter -->

 <!-- Spacing line like enter -->

Then Output is:

 <!-- Spacing line like enter -->

 Item

 Another Item

 Yet Another Item

You should use ul to display a list of items, where the order of the items is not important. if changing the order of the items makes the list incorrect, you should use (ol)

<!-- Chapter 5.3 - Nested List -->

<h3> 5.3 - Nested List </h3>

 You can nest lists to represent sub-item of a list item.

(ul)

(li) Item 1 (/li)

(li) Item 2

(ul)

(li) Sub-Item 2.1

(/li)

(li) Sub-Item 2.2 (/li)

(/ul)

(/li)

(li) Item 3 (/li)

(/ul)

 <!-- Spacing line like enter -->

Then Output is:

 Item 1

 Item 2

 Sub-Item 2.1

 Sub-Item 2.2

Item 3

 The nested list had to be a child of the li element.

You can nest different types of list, too:

(ol)

(li) Hello, List! (/li)

(li)

(ul)

(li) Hello, nested list! (/li)

(/ul)

(/li)

(/ol)

 <!-- Spacing Line like enter -->

 <!-- Spacing Line like enter -->

Then Output is:

 <!-- Spacing Line like enter -->

 Hello, List!

 Hello, nested list!

<!-- Chapter 5.4 - Description List -->

<h3> 5.4 - Description List</h3>

 A Description list (or definition list, as it was called before HTML 5) can be created with the dl elementt. it consists if name-value groups, where the name is given in the dt element, and the value is given in the dd element.

(dl)

(dt) name 1 (/dt)

(dt) name 2 (/dt)

(dd) Value for 2 (/dd)

(/dl)

 <!-- Spacing line like enter -->

 <!-- Spacing line like enter -->

Then Output Is:

 <!-- Spacing line like enter -->

<dl>

<dt> name 1 </dt>

<dd> Value for 1 </dd>

<dt> name 2 </dt>

<dd> Value for 2 </dd>

</dl>

 <!-- Spacing line like enter -->

 A name-value group can have more than one name and/or more than one value (which represent alternatives):

(dl)

(dt) name 1 (/dt>)

(dt) name 2 (/dt)

(dd) Value for 1 & 2 (/dd)

```
        <br> <!-- Spacing line like enter -->

        <b>(dt)</b> name 3 <b>(/dt)</b>      <br>
        <b>(dd)</b> Value for 3 <b>(/dd)</b>   <br>
        <b>(dd)</b> Value for 3 <b>(/dd)</b>    <br>
      <b>(/dl)</b>

      <br> <!-- Spacing line like enter -->
      <br> <!-- Spacing line like enter -->

      Then Output Is:

      <br> <!-- Spacing line like enter -->

      <dl>
        <dt> name 1 </dt>
        <dt> name 2</dt>
        <dd> Value for 1 & 2 </dd>

        <dt> name 3 </dt>
        <dd> Value for 3 </dd>
        <dd> Value for 3 </dd>
      </dl>
    </p>

  </body>
</html>
```