



Specifications

▼

Market Data Production

APIs to access Market Data

Market Data

1.0.0 OAS3

Trader API - Market data

[Contact Schwab Trader API team](#)

Servers

https://api.schwabapi.com/marketdata/v1

Authorize

Quotes

Get Quotes Web Service.

^

GET

/quotes

Get Quotes by list of symbols.

^

🔒

Parameters

Try it out

Name	Description
symbols string (query)	Comma separated list of symbol(s) to look up a quote Example : MRAD,EATOF,EBIZ,AAPL,BAC,AAAHX,AAAIX,\$DJI,\$SPX ,MVEN,SOBS,TOITF,CNSWF,AMZN 230317C01360000,DJX 231215C00290000,/ESH23,/ADUF23C0.55,AUD/CAD MRAD,EATOF,EBIZ,AAPL,BAC,AAAHX,AAAIX,\$D,
fields string (query)	Request for subset of data by passing coma separated list of root nodes, possible root nodes are quote, fundamental, extended, reference, regular. Sending quote, fundamental in request will return quote and fundamental data in response. Dont send this attribute for full response. Default value : all

quote,reference

indicative
boolean
(query)

Include indicative symbol quotes for all ETF symbols in request. If ETF symbol ABC is in request and indicative=true API will return quotes for ABC and its corresponding indicative quote for \$ABC.IV

Available values : true, false

Example : false

false

Responses

CodeDescriptionLinks

200Quote ResponseNo links

Media type

Examples

application

Search by Symbol!

Controls Accept header.

Example ValueSchema

```
{
  "AAPL": {
    "assetMainType": "EQUITY",
    "symbol": "AAPL",
    "quoteType": "NBBO",
    "realtime": true,
    "ssid": 1973757747,
    "reference": {
      "cusip": "037833100",
      "description": "Apple Inc",
      "exchange": "Q",
      "exchangeName": "NASDAQ"
    },
  },
  "quote": {
    "52WeekHigh": 169,
    "52WeekLow": 1.1,
    "askMICId": "MEMX",
    "askPrice": 168.41,
    "askSize": 400,
    "askTime": 1644854683672,
    "bidMICId": "IEGX",
    "bidPrice": 168.4,
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	Used to identify an individual request throughout the lifetime of the request and across systems.	string Example: 0a7f446a-7d74-49c8-a1e5-ca8ed59a3386

400

Error response for generic client error 400

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",
      "status": "400",
      "title": "Bad Request",
      "detail": "Missing header",
      "source": {
        "header": "Authorization"
      }
    },
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": "400",
      "title": "Bad Request",
      "detail": "Search combination should have min of 1.",
      "source": {
        "pointer": [
          "/data/attributes/symbol"
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed. <i>Example:</i> 977dbd7f-992e-44d2-a5f4-e213d29c8691	string
Schwab-Resource-Version	This is the requested API version.	string <i>Example:</i> 1

401

Error response for 401 Unauthorized

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 401,
      "title": "Unauthorized",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

charlesSCHWAB

Developer Portal

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed. <i>Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691</i>	string
Schwab-Resource-Version	This is the requested API version. <i>Example: 1</i>	string

500

Error response for 500 Internal Server Error

No links

Media type

application/json

Example Value Schema

```
{  "errors": [    {      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",      "status": 500,      "title": "Internal Server Error"    }  ]}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed. <i>Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691</i>	string
Schwab-Resource-Version	This is the requested API version. <i>Example: 1</i>	string

GET

/{{symbol_id}}/quotes

Get Quote by single symbol.

^

🔒

Parameters

Try it out

symbol_id * required

string
(path)

Symbol of instrument

Example : TSLA

TSLA

fields

string
(query)

Request for subset of data by passing coma separated list of root nodes, possible root nodes are quote, fundamental, extended, reference, regular. Sending **quote**, **fundamental** in request will return quote and fundamental data in response. Dont send this attribute for full response.

Default value : all

quote,reference

Responses

Code	Description	Links
200	Quote Response	No links

Media type

applicatio

Examples

Search by symk

Controls Accept header.

Example Value Schema

```
{
  "symbol": "AAPL",
  "empty": false,
  "previousClose": 174.56,
  "previousCloseDate": 163902960000
0,
  "candles": [
    {
      "open": 175.01,
      "high": 175.15,
      "low": 175.01,
      "close": 175.04,
      "volume": 10719,
      "datetime": 163913760000
    },
    {
      "open": 175.08,
      "high": 175.09,
      "low": 175.05,
      "close": 175.05,
      "volume": 500,
      "datetime": 1639137660000
    }
  ]
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	Used to identify an individual request throughout the lifetime of the request and across systems.	string Example: 0a7f446a-7d74-49c8-a1e5-ca8ed59a3386

400

Error response for generic client error 400

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",
      "status": "400",
      "title": "Bad Request",
      "detail": "Missing header",
      "source": {
        "header": "Authorization"
      }
    },
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": "400",
      "title": "Bad Request",
      "detail": "Search combination should have min of 1.",
      "source": {
        "pointer": [
          "/data/attributes/symbol
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed.	string Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

401

Error response for 401 Unauthorized

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 401,
      "title": "Unauthorized",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

404

Error response for 404 Not Found

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 404,
      "title": "Not Found",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

Error response for 500 Internal Server Error

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": 500,
      "title": "Internal Server Error"
    }
  ]
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed.	string Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

Option Chains

Get Option Chains Web Service.

GET /chains Get option chain for an optionable Symbol

Get Option Chain including information on options contracts associated with each expiration.

Parameters

Try it out

Name	Description
symbol * required	Enter one symbol
string (query)	Example : AAPL
	AAPL
contractType	Contract Type

(query)	--
strikeCount integer (query)	The Number of strikes to return above or below the at-the-money price strikeCount
includeUnderlyingQuote boolean (query)	Underlying quotes to be included --
strategy string (query)	OptionChain strategy. Default is SINGLE. ANALYTICAL allows the use of volatility, underlyingPrice, interestRate, and daysToExpiration params to calculate theoretical values. Available values : SINGLE, ANALYTICAL, COVERED, VERTICAL, CALENDAR, STRANGLE, STRADDLE, BUTTERFLY, CONDOR, DIAGONAL, COLLAR, ROLL --
interval number(\$double) (query)	Strike interval for spread strategy chains (see strategy param) interval
strike number(\$double) (query)	Strike Price strike
range string (query)	Range(ITM/NTWOTM etc.) range
fromDate string(\$date) (query)	From date(pattern: yyyy-MM-dd) fromDate
toDate string(\$date) (query)	To date (pattern: yyyy-MM-dd) toDate
volatility number(\$double) (query)	Volatility to use in calculations. Applies only to ANALYTICAL strategy chains (see strategy param) volatility

underlyingPrice
number(\$double)
(query)

Underlying price to use in calculations.
Applies only to ANALYTICAL strategy
chains (see strategy param)

underlyingPrice

interestRate
number(\$double)
(query)

Interest rate to use in calculations. Applies
only to ANALYTICAL strategy chains (see
strategy param)

interestRate

daysToExpiration
integer(\$int32)
(query)

Days to expiration to use in calculations.
Applies only to ANALYTICAL strategy
chains (see strategy param)

daysToExpiration

expMonth
string
(query)

Expiration month

Available values : JAN, FEB, MAR, APR,
MAY, JUN, JUL, AUG, SEP, OCT, NOV,
DEC, ALL

--

optionType
string
(query)

Option Type

optionType

entitlement
string
(query)

Applicable only if its retail token,
entitlement of client PP-PayingPro, NP-
NonPro and PN-NonPayingPro

Available values : PN, NP, PP

--

Responses

Code	Description	Links
200	The Chain for the symbol was returned successfully.	No links
	Media type	
	application/json	
	Controls Accept header.	
	Example Value	Schema

```
"symbol": "string",
"status": "string",
"underlying": {
  "ask": 0,
  "askSize": 0,
  "bid": 0,
  "bidSize": 0,
  "change": 0,
  "close": 0,
  "delayed": true,
  "description": "string",
  "exchangeName": "IND",
  "fiftyTwoWeekHigh": 0,
  "fiftyTwoWeekLow": 0,
  "highPrice": 0,
  "last": 0,
  "lowPrice": 0,
  "mark": 0,
  "markChange": 0,
  "markPercentChange": 0,
  "openPrice": 0,
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	Used to identify an individual request throughout the lifetime of the request and across systems.	string Example: 0a7f446a-7d74-49c8-a1e5-ca8ed59a3386

400

Error response for generic client error 400

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",
      "status": "400",
      "title": "Bad Request",
      "detail": "Missing header",
      "source": {
        "header": "Authorization"
      }
    },
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": "400",
      "title": "Bad Request",
      "detail": "Search combination should have min of 1.",
      "source": {
        "pointer": [
          "/data/attributes/symbol
```

Headers:

name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

401

Error response for 401 Unauthorized

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 401,
      "title": "Unauthorized",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

404

Error response for 404 Not Found

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
```

```
      "title": "Not Found",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

500

Error response for 500 Internal Server Error

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": 500,
      "title": "Internal Server Error"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

GET

/expirationchain
Get option expiration chain for an
ain optionable symbol



Get Option Expiration (Series) information for an optionable symbol.
Does not include individual options contracts for the underlying.

Parameters

Try it out

NameDescription

symbol * required
string
(query) Enter one symbol
Example : AAPL

AAPL

Responses

CodeDescriptionLinks

200
The Expiration Chain for the symbol was
returned successfully. No links

Media type

Examples

applicati

Get ExpirationCh

Controls Accept
header.

Example Value Schema

```
{
  "expirationList": [
    {
      "expirationDate": "2022-01-07",
      "daysToExpiration": 2,
      "expirationType": "W",
      "standard": true
    },
    {
      "expirationDate": "2022-01-14",
      "daysToExpiration": 9,
      "expirationType": "W",
      "standard": true
    },
    {
      "expirationDate": "2022-01-21",
      "daysToExpiration": 16,
      "expirationType": "S",
      "standard": true
    }
  ]
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	Used to identify an individual request throughout the lifetime of the request and across systems.	string <i>Example:</i> <code>0a7f446a-7d74-49c8-a1e5-ca8ed59a3386</code>

400

Error response for generic client error 400

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",
      "status": "400",
      "title": "Bad Request",
      "detail": "Missing header",
      "source": {
        "header": "Authorization"
      }
    },
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": "400",
      "title": "Bad Request",
      "detail": "Search combination should have min of 1.",
      "source": {
        "pointer": [
          "/data/attributes/symbol
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed.	string <i>Example:</i> <code>977dbd7f-992e-44d2-a5f4-e213d29c8691</code>
Schwab-Resource-Version	This is the requested API version.	string <i>Example:</i> 1

401

Error response for 401 Unauthorized

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 401,
      "title": "Unauthorized",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

404

Error response for 404 Not Found

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 404,
      "title": "Not Found",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

charlesSCHWAB

Developer Portal

500

Error response for 500 Internal Server Error

100 mins

Media type

application/json

Example Value

Schema

```
{  "errors": [    {      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",      "status": 500,      "title": "Internal Server Error"    }  ]}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed. <i>Example:</i> 977dbd7f-992e-44d2-a5f4-e213d29c8691	string
Schwab-Resource-Version	This is the requested API version.	string <i>Example: 1</i>

PriceHistory

Get Price History Web Service.

^

GET

/pricehistory

Get PriceHistory for a single symbol and date ranges.

^

🔒

Get historical Open, High, Low, Close, and Volume for a given frequency (i.e. aggregation). Frequency available is dependent on periodType selected. The datetime format is in EPOCH milliseconds.

Parameters

Try it out

Name	Description
symbol * required string (query)	The Equity symbol used to look up price history <i>Example : AAPL</i> AAPL

periodType

string
(query)

The chart period being requested.

Available values : day, month, year, ytd

--

period

integer(\$int32)
(query)

The number of chart period types.

If the periodType is

- **day** - valid values are 1, 2, 3, 4, 5, 10
- **month** - valid values are 1, 2, 3, 6
- **year** - valid values are 1, 2, 3, 5, 10, 15, 20
- **ytd** - valid values are 1

If the period is not specified and the periodType is

- **day** - default period is 10.
- **month** - default period is 1.
- **year** - default period is 1.
- **ytd** - default period is 1.

period

frequencyType

string
(query)

The time frequencyType

If the periodType is

- **day** - valid value is minute
- **month** - valid values are daily, weekly
- **year** - valid values are daily, weekly, monthly
- **ytd** - valid values are daily, weekly

If frequencyType is not specified, default value depends on the periodType

- **day** - defaulted to minute.
- **month** - defaulted to weekly.
- **year** - defaulted to monthly.
- **ytd** - defaulted to weekly.

Available values : minute, daily, weekly, monthly

--

frequency

integer(\$int32)
(query)

The time frequency duration

If the frequencyType is

- **minute** - valid values are 1, 5, 10, 15, 30
- **daily** - valid value is 1
- **weekly** - valid value is 1
- **monthly** - valid value is 1

If frequency is not specified, default value is 1

frequency

startDate

integer(\$int64)
(query)

The start date, Time in milliseconds since the UNIX epoch eg 1451624400000
If not specified startDate will be (endDate - period) excluding weekends and holidays.

startDate

endDate

integer(\$int64)
(query)

The end date, Time in milliseconds since the UNIX epoch eg 1451624400000
If not specified, the endDate will default to the market close of previous business day.

endDate

needExtendedHoursData

boolean
(query)

Need extended hours data

--

needPreviousClose

boolean
(query)

Need previous close price/date

--

Responses

Code

Description

Links

200

Get all candles for given date range

No links

Media type

applicatio

Examples

Search by symt

Controls Accept header.

Example Value Schema

```
{
  "symbol": "AAPL",
  "empty": false,
  "previousClose": 174.56,
  "previousCloseDate": 163902960000
0,
  "candles": [
    {
      "open": 175.01,
      "high": 175.15,
      "low": 175.01,
      "close": 175.04,
      "volume": 10719,
      "datetime": 1639137600000
    },
    {
      "open": 175.08,
```

400

Error response for generic client error 400

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",
      "status": "400",
      "title": "Bad Request",
      "detail": "Missing header",
      "source": {
        "header": "Authorization"
      }
    },
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": "400",
      "title": "Bad Request",
      "detail": "Search combination should have min of 1.",
      "source": {
        "pointer": [
          "/data/attributes/symbol
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed. <i>Example:</i> 977dbd7f-992e-44d2-a5f4-e213d29c8691	string
Schwab-Resource-Version	This is the requested API version.	string <i>Example:</i> 1

401

Error response for 401 Unauthorized

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 401,
      "title": "Unauthorized",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "detail": "Invalid credentials",
      "source": {
        "header": "Authorization"
      }
    }
  ]
}
```

```
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

404

Error response for 404 Not Found

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 404,
      "title": "Not Found",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

500

Error response for 500 Internal Server Error

No links

Media type

Example Value Schema

```
{
  "errors": [
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": 500,
      "title": "Internal Server Error"
    }
  ]
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed.	string <i>Example:</i> 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string <i>Example:</i> 1

Movers Get Movers Web Service.



GET /movers/{symbol_id} Get Movers for a specific index.  

Get a list of top 10 securities movement for a specific index.

Parameters Try it out

Name	Description
symbol_id * required string (path)	Index Symbol Available values : \$DJI, \$COMPX, \$SPX, NYSE, NASDAQ, OTCBB, INDEX_ALL, EQUITY_ALL, OPTION_ALL, OPTION_PUT, OPTION_CALL Example : \$DJI \$DJI

Sort

string
(query)

Sort by a particular attribute

Available values : VOLUME, TRADES, PERCENT_CHANGE_UP, PERCENT_CHANGE_DOWN

Example : VOLUME

VOLUME

frequency

integer(\$int32)
(query)

To return movers with the specified directions of up or down

Available values : 0, 1, 5, 10, 30, 60

Default value : 0

0

Responses

Code

Description

Links

200

Analytics for the symbol was returned successfully.

No links

Media type

application/j

Examples

Search by "\$|

Controls Accept header.

Example Value Schema

```
{
  "screeners": [
    {
      "change": 10,
      "description": "Dow jones",
      "direction": "up",
      "last": 100,
      "symbol": "$DJI",
      "totalVolume": 100
    },
    {
      "change": 10,
      "description": "Dow jones",
      "direction": "up",
      "last": 100,
      "symbol": "$DJI",
      "totalVolume": 100
    },
    {
      "change": 10,
      "description": "Dow jones",
      "direction": "up",
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	Used to identify an individual request throughout the lifetime of the request and across systems.	string <i>Example:</i> 0a7f446a-7d74-49c8-a1e5-ca8ed59a3386

400

Error response for generic client error 400

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",
      "status": "400",
      "title": "Bad Request",
      "detail": "Missing header",
      "source": {
        "header": "Authorization"
      }
    },
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": "400",
      "title": "Bad Request",
      "detail": "Search combination should have min of 1.",
      "source": {
        "pointer": [
          "/data/attributes/symbol
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed.	string <i>Example:</i> 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string <i>Example:</i> 1

401

Error response for 401 Unauthorized

No links

Media type

application/json

Example Value Schema


```
{
  "errors": [
    {
      "status": 401,
      "title": "Unauthorized",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

404

Error response for 404 Not Found

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 404,
      "title": "Not Found",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

Error response for 500 Internal Server Error

Media type

application/json

Example ValueSchema

```
{
  "errors": [
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": 500,
      "title": "Internal Server Error"
    }
  ]
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed.	string Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

MarketHoursGet MarketHours Web Service.

GET

/marketsGet Market Hours for different markets.

Get Market Hours for dates in the future across different markets.

Parameters

Try it out

Name	Description
markets * required	List of markets
array[string] (query)	Available values : equity, option, bond, future, forex

equity
option
bond
future
forex

date
string(\$date)
(query)

Valid date range is from currentdate to 1 year from today. It will default to current day if not entered. Date format:YYYY-MM-DD

date

Responses

Code	Description	Links						
200	OK Media type Examples appli Get getMarketHours Controls Accept header. Example Value Schema <pre>{ "equity": { "EQ": { "date": "2022-04-14", "marketType": "EQUITY", "product": "EQ", "productName": "equity", "isOpen": true, "sessionHours": { "preMarket": [{ "start": "2022-04-14T07:00:00-04:00", "end": "2022-04-14T09:30:00-04:00" }], "regularMarket": [{ "start": "2022-04-14T09:30:00-04:00", "end": "2022-04-14T16:00:00-04:00" }] } } } }</pre> Headers: <table><tr><th>Name</th><th>Description</th><th>Type</th></tr><tr><td>Schwab-Client-CorrelId</td><td>This Correlation ID is unique to the operation. The generated GUID can be used to track an individual service call if support is needed.</td><td>string Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691</td></tr></table> No links	Name	Description	Type	Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The generated GUID can be used to track an individual service call if support is needed.	string Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691	No links
Name	Description	Type						
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The generated GUID can be used to track an individual service call if support is needed.	string Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691						
400	Error response for generic client error 400	No links						

media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",
      "status": "400",
      "title": "Bad Request",
      "detail": "Missing header",
      "source": {
        "header": "Authorization"
      }
    },
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": "400",
      "title": "Bad Request",
      "detail": "Search combination should have min of 1.",
      "source": {
        "pointer": [
          "/data/attributes/symbol"
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

401

Error response for 401 Unauthorized

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 401,
      "title": "Unauthorized",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	<i>Example:</i> 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string <i>Example:</i> 1

500

Error response for 500 Internal Server Error

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": 500,
      "title": "Internal Server Error"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	<i>Example:</i> 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string <i>Example:</i> 1

GET

/markets
/{market_id}

Get Market Hours for a single market.



Get Market Hours for dates in the future for a single market.

Parameters

Try it out

market_id * required

string

(path)

market id

Available values : equity, option, bond, future, forex

equity

date

string(\$date)

(query)

Valid date range is from currentdate to 1 year from today. It will default to current day if not entered. Date format:YYYY-MM-DD

date

Responses

CodeDescriptionLinks

200OKNo links

Media type

application

Examples

Get market hours

Controls Accept header.

Example ValueSchema

```
{
  "equity": {
    "EQ": {
      "date": "2022-04-14",
      "marketType": "EQUITY",
      "exchange": "NULL",
      "category": "NULL",
      "product": "EQ",
      "productName": "equity",
      "isOpen": true,
      "sessionHours": {
        "preMarket": [
          {
            "start": "2022-04-14T07:00:00-04:00",
            "end": "2022-04-14T09:30:00-04:00"
          }
        ],
        "regularMarket": [
          {
            "start": "2022-04-14T09:30:00-04:00"
          }
        ]
      }
    }
  }
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The generated GUID can be used	string Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691

name	Description	Type
	to track an individual service call if support is needed.	

400

Error response for generic client error 400

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",
      "status": "400",
      "title": "Bad Request",
      "detail": "Missing header",
      "source": {
        "header": "Authorization"
      }
    },
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": "400",
      "title": "Bad Request",
      "detail": "Search combination should have min of 1.",
      "source": {
        "pointer": [
          "/data/attributes/symbol"
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

401

Error response for 401 Unauthorized

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
```

```
{
  "title": "Unauthorized",
  "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

404

Error response for 404 Not Found

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 404,
      "title": "Not Found",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

500

Error response for 500 Internal Server Error

No links

media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": 500,
      "title": "Internal Server Error"
    }
  ]
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed. <i>Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691</i>	string
Schwab-Resource-Version	This is the requested API version.	string <i>Example: 1</i>

Instruments

Get Instruments Web Service.

^

GET

/instruments

Get Instruments by symbols and projections.

^

🔒

Get Instruments details by using different projections. Get more specific fundamental instrument data by using fundamental as the projection.

Parameters

Try it out

Name	Description
symbol * required	symbol of a security
string (query)	symbol
projection * required	search by
string (query)	Available values : symbol-search, symbol-regex, desc-search, desc-regex, search, fundamental

Responses

Code	Description	Links
200	OK Media type Examples appli symbol=AAPL,BAC&p Controls Accept header. Example ValueSchema<pre>{ "instruments": [{ "cusip": "037833100", "symbol": "AAPL", "description": "Apple Inc", "exchange": "NASDAQ", "assetType": "EQUITY" }, { "cusip": "060505104", "symbol": "BAC", "description": "Bank Of America C orp", "exchange": "NYSE", "assetType": "EQUITY" }]}</pre>	No links
400	Error response for generic client error 400 Media type application/json	No links

```
{
  "errors": [
    {
      "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",
      "status": "400",
      "title": "Bad Request",
      "detail": "Missing header",
      "source": {
        "header": "Authorization"
      }
    },
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": "400",
      "title": "Bad Request",
      "detail": "Search combination should have min of 1.",
      "source": {
        "pointer": [
          "/data/attributes/symbol"
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

401

No links

Error response for 401 Unauthorized

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 401,
      "title": "Unauthorized",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation.	string Example: 977dbd7f-

name	Description	Type
	The GUID that is <i>992e-44d2-</i> generated can be <i>a5f4-</i> used to track an <i>e213d29c8691</i> individual service call if support is needed.	
Schwab-Resource-Version	This is the <i>requested API version.</i>	string <i>Example: 1</i>

500

Error response for 500 Internal Server Error

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": 500,
      "title": "Internal Server Error"
    }
  ]
}
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is <i>Example:</i> generated can be <i>977dbd7f-</i> used to track an <i>992e-44d2-</i> individual <i>a5f4-</i> service call if <i>e213d29c8691</i> support is needed.	
Schwab-Resource-Version	This is the <i>requested API version.</i>	string <i>Example: 1</i>

GET

/instruments
/{cusip_id}

Get Instrument by specific
cusip



Get basic instrument details by cusip

Parameters

Try it out

charles
SCHWAB

Developer Portal

cusip_id * required

string

(path)

cusip of a security

cusip_id

Responses

Code	Description	Links									
200	OK Media type Examples applicati Get getinstrume Controls Accept header. Example Value Schema <pre>{ "cusip": "037833100", "symbol": "AAPL", "description": "Apple Inc", "exchange": "NASDAQ", "assetType": "EQUITY" }</pre> Headers: <table><thead><tr><th>Name</th><th>Description</th><th>Type</th></tr></thead><tbody><tr><td>Schwab-Resource-Version</td><td>Used to identify desired and returned version of an API resource</td><td>integer Example: 3</td></tr><tr><td>Schwab-Client-CorrelId</td><td>Used to identify an individual request throughout the lifetime of the request and across systems.</td><td>string Example: 0a7f446a-7d74-49c8-a1e5-ca8ed59a3386</td></tr></tbody></table>	Name	Description	Type	Schwab-Resource-Version	Used to identify desired and returned version of an API resource	integer Example: 3	Schwab-Client-CorrelId	Used to identify an individual request throughout the lifetime of the request and across systems.	string Example: 0a7f446a-7d74-49c8-a1e5-ca8ed59a3386	No links
Name	Description	Type									
Schwab-Resource-Version	Used to identify desired and returned version of an API resource	integer Example: 3									
Schwab-Client-CorrelId	Used to identify an individual request throughout the lifetime of the request and across systems.	string Example: 0a7f446a-7d74-49c8-a1e5-ca8ed59a3386									
400	Error response for generic client error 400 Media type application/json Example Value Schema <pre>{ "errors": [{ "id": "6808262e-52bb-4421-9d31-6c0e762e7dd5",</pre>	No links									

```
    "title": "Bad Request",
    "detail": "Missing header",
    "source": {
      "header": "Authorization"
    }
  },
  {
    "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
    "status": "400",
    "title": "Bad Request",
    "detail": "Search combination should have min of 1.",
    "source": {
      "pointer": [
```

Headers:

Name	Description	Type
	This Correlation ID is unique to the operation.	string
Schwab-Client-CorrelId	The GUID that is generated can be used to track an individual service call if support is needed.	Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

401

Error response for 401 Unauthorized

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 401,
      "title": "Unauthorized",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed.	string Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691

name	Description	Type
Schwab-Resource-Version	This is the requested API version.	string Example: 1

404

Error response for 404 Not Found

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "status": 404,
      "title": "Not Found",
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca"
    }
  ]
}
```

Headers:

Name	Description	Type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed.	string Example: 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the requested API version.	string Example: 1

500

Error response for 500 Internal Server Error

No links

Media type

application/json

Example Value Schema

```
{
  "errors": [
    {
      "id": "0be22ae7-efdf-44d9-99f4-f138049d76ca",
      "status": 500,
      "title": "Internal Server Error"
    }
  ]
}
```

Headers:

name	description	type
Schwab-Client-CorrelId	This Correlation ID is unique to the operation. The GUID that is generated can be used to track an individual service call if support is needed.	string <i>Example:</i> 977dbd7f-992e-44d2-a5f4-e213d29c8691
Schwab-Resource-Version	This is the <i>requested API version</i> .	string <i>Example:</i> 1

Schemas



Bond

FundamentalInst

Instrument

InstrumentResponse

Hours

Interval

Screener

Candle

CandleList

EquityResponse

ExtendedMarket

ForexResponse

Fundamental

FutureOptionResponse

FutureResponse

IndexResponse

MutualFundResponse

OptionResponse

QuoteEquity

QuoteForex

QuoteFuture

QuoteFutureOption

QuoteIndex

QuoteMutualFund

QuoteOption

QuoteRequest

QuoteResponseObject

ReferenceEquity

ReferenceForex

ReferenceFuture

ReferenceFutureOption

ReferenceIndex

ReferenceMutualFund

ReferenceOption

RegularMarket

AssetMainType

EquityAssetSubType

MutualFundAssetSubType

ContractType

SettlementType

ExpirationType

FundStrategy

DivFreq

QuoteType

ErrorResponse

Error

ErrorSource

OptionChain

OptionContractMap

Underlying

OptionDeliverables

OptionContract

ExpirationChain

Expiration