

Table of Contents

Core Commands	1
List	1
Version	2
Help	2
Pipe	3
Shell	4

Core Commands

List

List all command names.

Short Name	Long Name	Description
-d	--description	Include the description
	--help	Print the help message
	--web-help	Open help in a browser

```
geoc list
```

```
carto map
filter cql2xml
geometry convert
geometry dd2pt
geometry geohash bounds
geometry geohash decode
geometry geohash encode
geometry geohash neighbors
geometry greatcirclearc
geometry offset
...
```

List all commands names with a short description.

```
geoc list -d
```

```
carto map = Create a cartographic map
filter cql2xml = Convert a CQL statement to an OCG XML Filter
geometry convert = Convert a geometry from one format to another
geometry dd2pt = Convert a decimal degrees formatted string into a Point
geometry geohash bounds = Calculate the geohashes for the given bounds
geometry geohash decode = Decode a GeoHash to a Geometry.
geometry geohash encode = Encode a Geometry as a GeoHash
geometry geohash neighbors = Get a geohash's neighbors
geometry greatcirclearc = Create a great circle arc.
geometry offset = Create a Geometry offset from the input Geometry
...
```

Version

Get the current version.

Short Name	Long Name	Description
	--help	Print the help message
	--web-help	Open help in a browser

```
geoc version
```

```
0.20.0-SNAPSHOT
```

Help

You can get help from any subcommand.

```
geoc vector buffer --help
```

geoc vector buffer: Buffer the features of the input Layer and save them to the output Layer

```
--help                : Print the help message (default: true)
--web-help             : Open help in a browser (default: false)
-c (--capstyle) VAL    : The cap style (default: round)
-d (--distance) VAL    : The buffer distance
-i (--input-workspace) VAL : The input workspace
-l (--input-layer) VAL  : The input layer
-o (--output-workspace) VAL : The output workspace
-q (--quadrantsegments) N : The number of quadrant segments (default: 8)
-r (--output-layer) VAL : The output layer
-s (--singlesided)     : Whether buffer should be single sided or not
                        (default: false)
```


Pipe

Combine multiple commands together with a pipe.

Short Name	Long Name	Description
-c	--commands	Commands separate by pipe
	--help	Print the help message
	--web-help	Open help in a browser

```
geoc pipe -c vector randompoints -n 10 -g -180,-90,180,90 | vector buffer -d 10
```

```
"id:Integer","the_geom:Polygon:EPSG:4326"
"0","POLYGON ((-164.59889101875683 63.88817589520292, -164.79103821472452
61.93727267504164, -165.36009569364396 60.06134157155202, -166.2841948957314
58.3324735650069, -167.52782320689136 56.817108083337445, -169.0431886885608
55.573479772177464, -170.77205669510593 54.64938057009005, -172.64798779859555
54.08032309117061, -174.59889101875683 53.88817589520292, -176.5497942389181
54.08032309117061, -178.42572534240773 54.64938057009005, -180.15459334895286
55.573479772177464, -181.6699588306223 56.817108083337445, -182.91358714178227
58.3324735650069, -183.8376863438697 60.06134157155202, -184.40674382278914
61.93727267504163, -184.59889101875683 63.88817589520292, -184.40674382278914
65.8390791153642, -183.8376863438697 67.71501021885382, -182.91358714178227
69.44387822539895, -181.6699588306223 70.9592437070684, -180.15459334895286
72.20287201822838, -178.42572534240773 73.12697122031578, -176.5497942389181
73.69602869923523, -174.59889101875683 73.88817589520292, -172.64798779859555
73.69602869923523, -170.77205669510593 73.12697122031578, -169.0431886885608
72.20287201822838, -167.52782320689136 70.9592437070684, -166.2841948957314
69.44387822539895, -165.36009569364396 67.71501021885382, -164.79103821472452
65.83907911536421, -164.59889101875683 63.88817589520292)))"
...
```



Shell

Run commands in an interactive shell.

Short Name	Long Name	Description
	--help	Print the help message
	--web-help	Open help in a browser

geoc shell



```
jericks — java ◀ geoc shell — 80x24
~ — java ◀ geoc shell
Last login: Wed Oct 5 18:18:54 on ttys002
jericks@Jareds-MacBook-Pro-2 ~ % geoc shell

geoc

geoc> █
```

You can now type commands in the interactive shell.

If you hit the **tab** key you can get command line completion.

You can use the tab key again to cycle through the suggested values and hit the **return** key to select one.

```
jericks — java ◀ geoc shell — 80x24
~ — java ◀ geoc shell
Last login: Wed Oct 5 18:18:54 on ttys002
[jericks@Jareds-MacBook-Pro-2 ~ % geoc shell]

geoc shell

[geoc>
carto      geometry  map      proj      shell     tile      version
filter    list      pipe    raster   style     vector
```

In this example, we are looking for the vector contains command, so after typing vector c and hitting tab, we get a list of all vector commands that begin with the letter c.



Once we have found our command, the shell will also provide completion for options.



```
jericks — java ◀ geoc shell — 80x24
~ — java ◀ geoc shell
geoc> vector buffer -
--capstyle          --output-workspace  -i
--distance          --quadrantsegments  -l
--help              --singlesided       -o
--input-layer       --web-help          -q
--input-workspace   -c                  -r
--output-layer      -d                  -s
```