

Table of Contents

Core Commands	1
List	1
Version	2
Help	2
Pipe	3
Shell	4

Core Commands

List

List all command names.

Short Name	Long Name	Description
-d	--description	Include the description
	--help	Print the help message
	--web-help	Open help in a browser

```
geoc list
```

```
carto map
filter cql2xml
geometry convert
geometry dd2pt
geometry geohash bounds
geometry geohash decode
geometry geohash encode
geometry geohash neighbors
geometry greatcirclearc
geometry offset
...
```

List all commands names with a short description.

```
geoc list -d
```

```
carto map = Create a cartographic map
filter cql2xml = Convert a CQL statement to an OGC XML Filter
geometry convert = Convert a geometry from one format to another
geometry dd2pt = Convert a decimal degrees formatted string into a Point
geometry geohash bounds = Calculate the geohashes for the given bounds
geometry geohash decode = Decode a GeoHash to a Geometry.
geometry geohash encode = Encode a Geometry as a GeoHash
geometry geohash neighbors = Get a geohash's neighbors
geometry greatcirclearc = Create a great circle arc.
geometry offset = Create a Geometry offset from the input Geometry
...
```

Version

Get the current version.

Short Name	Long Name	Description
	--help	Print the help message
	--web-help	Open help in a browser

```
geoc version
```

```
0.21.0-SNAPSHOT
```

Help

You can get help from any subcommand.

```
geoc vector buffer --help
```

geoc vector buffer: Buffer the features of the input Layer and save them to the output Layer

```
--help                : Print the help message (default: true)
--web-help             : Open help in a browser (default: false)
-c (--capstyle) VAL    : The cap style (default: round)
-d (--distance) VAL    : The buffer distance
-i (--input-workspace) VAL : The input workspace
-l (--input-layer) VAL  : The input layer
-o (--output-workspace) VAL : The output workspace
-q (--quadrantsegments) N : The number of quadrant segments (default: 8)
-r (--output-layer) VAL  : The output layer
-s (--singlesided)      : Whether buffer should be single sided or not
                        (default: false)
```


Pipe

Combine multiple commands together with a pipe.

Short Name	Long Name	Description
-c	--commands	Commands separate by pipe
	--help	Print the help message
	--web-help	Open help in a browser

```
geoc pipe -c vector randompoints -n 10 -g -180,-90,180,90 | vector buffer -d 10
```

```
"id:Integer","the_geom:Polygon:EPSG:4326"
"0","POLYGON ((-56.96245692742889 26.73495830052363, -57.15460412339658
24.784055080362347, -57.72366160231602 22.90812397687273, -58.64776080440343
21.17925597032761, -59.89138911556341 19.663890488658154, -61.40675459723287
18.420262177498177, -63.13562260377799 17.496162975410762, -65.01155370726761
16.927105496491325, -66.96245692742889 16.73495830052363, -68.91336014759017
16.927105496491325, -70.78929125107979 17.496162975410762, -72.51815925762492
18.420262177498174, -74.03352473929436 19.663890488658154, -75.27715305045434
21.17925597032761, -76.20125225254176 22.90812397687273, -76.7703097314612
24.784055080362343, -76.96245692742889 26.73495830052363, -76.7703097314612
28.685861520684913, -76.20125225254176 30.561792624174526, -75.27715305045434
32.29066063071965, -74.03352473929436 33.806026112389105, -72.51815925762492
35.049654423549086, -70.78929125107979 35.97375362563649, -68.91336014759017
36.54281110455593, -66.96245692742889 36.73495830052363, -65.01155370726761
36.54281110455594, -63.13562260377799 35.9737536256365, -61.40675459723287
35.049654423549086, -59.89138911556341 33.806026112389105, -58.64776080440343
32.29066063071965, -57.72366160231603 30.561792624174533, -57.15460412339659
28.685861520684917, -56.96245692742889 26.73495830052363)))"
...
```



Shell

Run commands in an interactive shell.

Short Name	Long Name	Description
	--help	Print the help message
	--web-help	Open help in a browser

geoc shell



```
jericks — java ◀ geoc shell — 80x24
~ — java ◀ geoc shell
Last login: Wed Oct 5 18:18:54 on ttys002
jericks@Jareds-MacBook-Pro-2 ~ % geoc shell

geoc

geoc> █
```

You can now type commands in the interactive shell.

If you hit the **tab** key you can get command line completion.

You can use the tab key again to cycle through the suggested values and hit the **return** key to select one.



```
jericks — java ◀ geoc shell — 80x24
~ — java ◀ geoc shell
Last login: Wed Oct 5 18:18:54 on ttys002
[jericks@Jareds-MacBook-Pro-2 ~ % geoc shell

geoc

geoc>
carto      geometry  map        proj        shell       tile        version
filter     list      pipe       raster      style       vector
```

In this example, we are looking for the vector contains command, so after typing vector c and hitting tab, we get a list of all vector commands that begin with the letter c.



Once we have found our command, the shell will also provide completion for options.



```
jericks — java ◀ geoc shell — 80x24
~ — java ◀ geoc shell
geoc> vector buffer -
--capstyle          --output-workspace  -i
--distance          --quadrantsegments  -l
--help              --singlesided      -o
--input-layer       --web-help          -q
--input-workspace   -c                  -r
--output-layer      -d                  -s
```