

# Table of Contents

Core Commands .....	1
List .....	1
Version .....	2
Help .....	2
Pipe .....	3
Shell .....	4

## Core Commands

### List

List all command names.

Short Name	Long Name	Description
-d	--description	Include the description
	--help	Print the help message
	--web-help	Open help in a browser

```
geoc list
```

```
carto map
filter cql2xml
geometry convert
geometry dd2pt
geometry geohash bounds
geometry geohash decode
geometry geohash encode
geometry geohash neighbors
geometry greatcirclearc
geometry offset
...
```

List all commands names with a short description.

```
geoc list -d
```

```
carto map = Create a cartographic map
filter cql2xml = Convert a CQL statement to an OCG XML Filter
geometry convert = Convert a geometry from one format to another
geometry dd2pt = Convert a decimal degrees formatted string into a Point
geometry geohash bounds = Calculate the geohashes for the given bounds
geometry geohash decode = Decode a GeoHash to a Geometry.
geometry geohash encode = Encode a Geometry as a GeoHash
geometry geohash neighbors = Get a geohash's neighbors
geometry greatcirclearc = Create a great circle arc.
geometry offset = Create a Geometry offset from the input Geometry
...
```

## Version

Get the current version.

Short Name	Long Name	Description
	--help	Print the help message
	--web-help	Open help in a browser

```
geoc version
```

```
0.20.0-SNAPSHOT
```

## Help

You can get help from any subcommand.

```
geoc vector buffer --help
```

geoc vector buffer: Buffer the features of the input Layer and save them to the output Layer

```
--help          : Print the help message (default: true)
--web-help      : Open help in a browser (default: false)
-c (--capstyle) VAL      : The cap style (default: round)
-d (--distance) VAL      : The buffer distance
-i (--input-workspace) VAL : The input workspace
-l (--input-layer) VAL    : The input layer
-o (--output-workspace) VAL : The output workspace
-q (--quadrantsegments) N : The number of quadrant segments (default: 8)
-r (--output-layer) VAL   : The output layer
-s (--singlesided)       : Whether buffer should be single sided or not
                          (default: false)
```


## Pipe

Combine multiple commands together with a pipe.

Short Name	Long Name	Description
-c	--commands	Commands separate by pipe
	--help	Print the help message
	--web-help	Open help in a browser

```
geoc pipe -c vector randompoints -n 10 -g -180,-90,180,90 | vector buffer -d 10
```

```
"id:Integer","the_geom:Polygon:EPSG:4326"
"0","POLYGON ((-45.83046084947583 18.75589331407234, -46.02260804544352
16.804990093911055, -46.59166552436296 14.92905899042144, -47.51576472645037
13.200190983876317, -48.75939303761035 11.684825502206863, -50.27475851927981
10.441197191046886, -52.00362652582493 9.51709798895947, -53.87955762931455
8.948040510040034, -55.83046084947583 8.755893314072338, -57.78136406963711
8.948040510040034, -59.65729517312673 9.51709798895947, -61.38616317967185
10.441197191046884, -62.9015286613413 11.684825502206863, -64.14515697250128
13.200190983876317, -65.0692561745887 14.929058990421439, -65.63831365350813
16.80499009391105, -65.83046084947583 18.75589331407234, -65.63831365350813
20.70679653423362, -65.0692561745887 22.582727637723234, -64.14515697250128
24.31159564426836, -62.9015286613413 25.826961125937814, -61.38616317967185
27.07058943709779, -59.65729517312673 27.994688639185203, -57.781364069637114
28.56374611810464, -55.83046084947583 28.75589331407234, -53.87955762931455
28.563746118104643, -52.00362652582493 27.994688639185206, -50.27475851927981
27.070589437097794, -48.75939303761035 25.826961125937814, -47.51576472645037
24.31159564426836, -46.591665524362966 22.58272763772324, -46.022608045443526
20.706796534233625, -45.83046084947583 18.75589331407234)))"
...
```



## Shell

Run commands in an interactive shell.

Short Name	Long Name	Description
	--help	Print the help message
	--web-help	Open help in a browser

geoc shell



```
jericks — java ◀ geoc shell — 80x24
~ — java ◀ geoc shell
Last login: Wed Oct 5 18:18:54 on ttys002
jericks@Jareds-MacBook-Pro-2 ~ % geoc shell

geoc

geoc> █
```

You can now type commands in the interactive shell.

If you hit the **tab** key you can get command line completion.

You can use the tab key again to cycle through the suggested values and hit the **return** key to select one.



```
jericks — java ◀ geoc shell — 80x24
~ — java ◀ geoc shell
Last login: Wed Oct 5 18:18:54 on ttys002
[jericks@Jareds-MacBook-Pro-2 ~ % geoc shell

geoc

geoc>
carto      geometry  map        proj        shell      tile        version
filter     list      pipe       raster      style      vector
```

In this example, we are looking for the vector contains command, so after typing vector c and hitting tab, we get a list of all vector commands that begin with the letter c.



Once we have found our command, the shell will also provide completion for options.



```
jericks — java ◀ geoc shell — 80x24
~ — java ◀ geoc shell
geoc> vector buffer -
--capstyle          --output-workspace  -i
--distance          --quadrantsegments  -l
--help              --singlesided      -o
--input-layer       --web-help          -q
--input-workspace   -c                  -r
--output-layer      -d                  -s
```