

# Table of Contents

|                               |   |
|-------------------------------|---|
| Style Commands .....          | 1 |
| Create .....                  | 1 |
| CSS to SLD .....              | 3 |
| SLD to Ysld .....             | 4 |
| Ysld to SLD .....             | 6 |
| Unique Values from Text ..... | 7 |

## Style Commands

### Create

Create a simple style.

| Short Name | Long Name        | Description                   |
|------------|------------------|-------------------------------|
| -s         | --style-options  | A style options               |
| -t         | --type           | The output type (sld or ysld) |
| -w         | --writer-options | The StyleWriter options       |
| -o         | --output         | The output file               |
|            | --help           | Print the help message        |
|            | --web-help       | Open help in a browser        |

#### Style Options:

- Fill properties
  - **fill** (color)
  - **fill-opacity** (0-1)
- Stroke properties
  - **stroke** (color)
  - **stroke-width** (double)
  - **stroke-opacity** (0-1)
- Shape properties
  - **shape** (color)
  - **shape-size** (double)
  - **shape-type** (circle, square, triangle, star, cross, or x)
- Label properties
  - **label** The field name (ID, NAME)

- **label-size** (12)
- **label-style** (normal, italic, oblique)
- **label-weight** (normal, bold)
- **label-family** (serif, Arial, Verdana)

```
geoc style create -s stroke=navy -s stroke-width=0.5 -t sld -o target/boundaries.sld
```

```
<?xml version="1.0" encoding="UTF-8"?><sld:StyledLayerDescriptor xmlns=
"http://www.opengis.net/sld" xmlns:sld="http://www.opengis.net/sld" xmlns:gml=
"http://www.opengis.net/gml" xmlns:ogc="http://www.opengis.net/ogc" version="1.0.0">
  <sld:UserLayer>
    <sld:LayerFeatureConstraints>
      <sld:FeatureTypeConstraint/>
    </sld:LayerFeatureConstraints>
    <sld:UserStyle>
      <sld:Name>Default Styler</sld:Name>
      <sld:FeatureTypeStyle>
        <sld:Name>name</sld:Name>
        <sld:Rule>
          <sld:LineSymbolizer>
            <sld:Stroke>
              <sld:CssParameter name="stroke">#000080</sld:CssParameter>
              <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>
            </sld:Stroke>
          </sld:LineSymbolizer>
        </sld:Rule>
      </sld:FeatureTypeStyle>
    </sld:UserStyle>
  </sld:UserLayer>
</sld:StyledLayerDescriptor>
```

```
geoc style create -s fill=white -s stroke=black -s stroke-width=1.5 -t ysld -o
target/boundaries.ysld
```

```

name: Default Styler
feature-styles:
- name: name
  rules:
  - scale: [min, max]
    symbolizers:
    - polygon:
        fill-color: '#FFFFFF'
        fill-opacity: 0.6
    - line:
        stroke-color: '#000000'
        stroke-width: 1.5

```

## CSS to SLD

Convert CSS to SLD.

| Short Name | Long Name        | Description             |
|------------|------------------|-------------------------|
| -i         | --input          | The input file or url   |
| -o         | --output         | The output file         |
| -w         | --writer-options | The StyleWriter options |
|            | --help           | Print the help message  |
|            | --web-help       | Open help in a browser  |

```
geoc style css2sld -i target/points.css -o target/points.sld
```

*points.css*

```

* {
  mark: symbol(circle);
  mark-size: 6px;
}

:mark {
  fill: red;
}

```

*points.sld*

```
<?xml version="1.0" encoding="UTF-8"?><sld:StyledLayerDescriptor xmlns=
"http://www.opengis.net/sld" xmlns:sld="http://www.opengis.net/sld" xmlns:gml=
"http://www.opengis.net/gml" xmlns:ogc="http://www.opengis.net/ogc" version="1.0.0">
  <sld:UserLayer>
    <sld:LayerFeatureConstraints>
      <sld:FeatureTypeConstraint/>
    </sld:LayerFeatureConstraints>
    <sld:UserStyle>
      <sld:Name>Default Styler</sld:Name>
      <sld:FeatureTypeStyle>
        <sld:Rule>
          <sld:PointSymbolizer>
            <sld:Graphic>
              <sld:Mark>
                <sld:WellKnownName>circle</sld:WellKnownName>
                <sld:Fill>
                  <sld:CssParameter name="fill">#ff0000</sld:CssParameter>
                </sld:Fill>
              </sld:Mark>
              <sld:Size>6</sld:Size>
            </sld:Graphic>
          </sld:PointSymbolizer>
        </sld:Rule>
        <sld:VendorOption name="ruleEvaluation">first</sld:VendorOption>
      </sld:FeatureTypeStyle>
    </sld:UserStyle>
  </sld:UserLayer>
</sld:StyledLayerDescriptor>
```

## SLD to Ysld

Convert SLD to Ysld

| Short Name | Long Name  | Description            |
|------------|------------|------------------------|
| -i         | --input    | The input file or url  |
| -o         | --output   | The output file        |
|            | --help     | Print the help message |
|            | --web-help | Open help in a browser |

```
geoc style sld2ysld -i target/points.sld -o target/points.ysld
```

*points.sld*

```
<?xml version="1.0" encoding="UTF-8"?><sld:StyledLayerDescriptor xmlns=
"http://www.opengis.net/sld" xmlns:sld="http://www.opengis.net/sld" xmlns:gml=
"http://www.opengis.net/gml" xmlns:ogc="http://www.opengis.net/ogc" version="1.0.0">
  <sld:UserLayer>
    <sld:LayerFeatureConstraints>
      <sld:FeatureTypeConstraint/>
    </sld:LayerFeatureConstraints>
    <sld:UserStyle>
      <sld:Name>Default Styler</sld:Name>
      <sld:FeatureTypeStyle>
        <sld:Rule>
          <sld:PointSymbolizer>
            <sld:Graphic>
              <sld:Mark>
                <sld:WellKnownName>circle</sld:WellKnownName>
                <sld:Fill>
                  <sld:CssParameter name="fill">#ff0000</sld:CssParameter>
                </sld:Fill>
              </sld:Mark>
              <sld:Size>6</sld:Size>
            </sld:Graphic>
          </sld:PointSymbolizer>
        </sld:Rule>
        <sld:VendorOption name="ruleEvaluation">first</sld:VendorOption>
      </sld:FeatureTypeStyle>
    </sld:UserStyle>
  </sld:UserLayer>
</sld:StyledLayerDescriptor>
```

*points.ysld*

```
name: Default Styler
feature-styles:
- name: name
  rules:
  - scale: [min, max]
    symbolizers:
    - point:
        size: 6
        symbols:
        - mark:
            shape: circle
            fill-color: '#FF0000'
  x-ruleEvaluation: first
```

# Ysld to SLD

Convert Ysld to SLD.

| Short Name | Long Name        | Description             |
|------------|------------------|-------------------------|
| -i         | --input          | The input file or url   |
| -o         | --output         | The output file         |
| -w         | --writer-options | The StyleWriter options |
|            | --help           | Print the help message  |
|            | --web-help       | Open help in a browser  |

```
geoc style ysld2sld -i target/points.ysld -o target/points.sld
```

*points.ysld*

```
name: Default Styler
feature-styles:
- name: name
  rules:
  - scale: [min, max]
    symbolizers:
    - point:
        size: 6
        symbols:
        - mark:
            shape: circle
            fill-color: '#FF0000'
  x-ruleEvaluation: first
```

*points.sld*

```
<?xml version="1.0" encoding="UTF-8"?><sld:StyledLayerDescriptor xmlns=
"http://www.opengis.net/sld" xmlns:sld="http://www.opengis.net/sld" xmlns:gml=
"http://www.opengis.net/gml" xmlns:ogc="http://www.opengis.net/ogc" version="1.0.0">
  <sld:UserLayer>
    <sld:LayerFeatureConstraints>
      <sld:FeatureTypeConstraint/>
    </sld:LayerFeatureConstraints>
    <sld:UserStyle>
      <sld:Name>Default Styler</sld:Name>
      <sld:FeatureTypeStyle>
        <sld:Name>name</sld:Name>
        <sld:Rule>
          <sld:PointSymbolizer>
            <sld:Graphic>
              <sld:Mark>
                <sld:WellKnownName>circle</sld:WellKnownName>
                <sld:Fill>
                  <sld:CssParameter name="fill">#FF0000</sld:CssParameter>
                </sld:Fill>
              </sld:Mark>
            <sld:Size>6</sld:Size>
          </sld:Graphic>
        </sld:PointSymbolizer>
      </sld:Rule>
      <sld:VendorOption name="ruleEvaluation">first</sld:VendorOption>
    </sld:FeatureTypeStyle>
  </sld:UserStyle>
</sld:UserLayer>
</sld:StyledLayerDescriptor>
```

## Unique Values from Text

Create a Style from reading values in the unique values format.

| Short Name | Long Name        | Description                                    |
|------------|------------------|--|
| -f         | --field          | The field                                      |
| -g         | --geometry-type  | The geometry type (point, linestring, polygon) |
| -i         | --input          | The input file or url                          |
| -t         | --type           | The output type (sld or ysl)                   |
| -o         | --output         | The output file                                |
| -w         | --writer-options | The StyleWriter options                        |
|            | --help           | Print the help message                         |
|            | --web-help       | Open help in a browser                         |

```
geoc style uniquevaluesfromtext -i target/units.txt -f UNIT -g polygon -t sld -o target/units.sld
```

*units.txt*

```
AHa=#aa0c74  
AHat=#b83b1f  
AHcf=#964642  
AHh=#78092e  
AHpe=#78092e  
AHt=#5f025a  
AHt3=#e76161  
Aa1=#fcedcd  
Aa2=#94474b
```

*units.sld*

```
<?xml version="1.0" encoding="UTF-8"?><sld:StyledLayerDescriptor xmlns=  
"http://www.opengis.net/sld" xmlns:sld="http://www.opengis.net/sld" xmlns:gml=  
"http://www.opengis.net/gml" xmlns:ogc="http://www.opengis.net/ogc" version="1.0.0">  
  <sld:UserLayer>  
    <sld:LayerFeatureConstraints>  
      <sld:FeatureTypeConstraint/>  
    </sld:LayerFeatureConstraints>  
    <sld:UserStyle>  
      <sld:Name>Default Styler</sld:Name>  
      <sld:FeatureTypeStyle>  
        <sld:Name>name</sld:Name>  
        <sld:Rule>  
          <ogc:Filter>  
            <ogc:PropertyIsEqualTo>  
              <ogc:PropertyName>UNIT</ogc:PropertyName>  
              <ogc:Literal>AHa</ogc:Literal>  
            </ogc:PropertyIsEqualTo>  
          </ogc:Filter>  
          <sld:PolygonSymbolizer>  
            <sld:Fill>  
              <sld:CssParameter name="fill">#aa0c74</sld:CssParameter>  
            </sld:Fill>  
          </sld:PolygonSymbolizer>  
          <sld:LineSymbolizer>  
            <sld:Stroke>  
              <sld:CssParameter name="stroke">#760851</sld:CssParameter>  
              <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>  
            </sld:Stroke>  
          </sld:LineSymbolizer>  
        </sld:Rule>  
        <sld:Rule>
```



```

<ogc:Filter>
  <ogc:PropertyIsEqualTo>
    <ogc:PropertyName>UNIT</ogc:PropertyName>
    <ogc:Literal>AHat</ogc:Literal>
  </ogc:PropertyIsEqualTo>
</ogc:Filter>
<sld:PolygonSymbolizer>
  <sld:Fill>
    <sld:CssParameter name="fill">#b83b1f</sld:CssParameter>
  </sld:Fill>
</sld:PolygonSymbolizer>
<sld:LineSymbolizer>
  <sld:Stroke>
    <sld:CssParameter name="stroke">#802915</sld:CssParameter>
    <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>
  </sld:Stroke>
</sld:LineSymbolizer>
</sld:Rule>
<sld:Rule>
  <ogc:Filter>
    <ogc:PropertyIsEqualTo>
      <ogc:PropertyName>UNIT</ogc:PropertyName>
      <ogc:Literal>AHcf</ogc:Literal>
    </ogc:PropertyIsEqualTo>
  </ogc:Filter>
  <sld:PolygonSymbolizer>
    <sld:Fill>
      <sld:CssParameter name="fill">#964642</sld:CssParameter>
    </sld:Fill>
  </sld:PolygonSymbolizer>
  <sld:LineSymbolizer>
    <sld:Stroke>
      <sld:CssParameter name="stroke">#69312e</sld:CssParameter>
      <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>
    </sld:Stroke>
  </sld:LineSymbolizer>
</sld:Rule>
<sld:Rule>
  <ogc:Filter>
    <ogc:PropertyIsEqualTo>
      <ogc:PropertyName>UNIT</ogc:PropertyName>
      <ogc:Literal>AHh</ogc:Literal>
    </ogc:PropertyIsEqualTo>
  </ogc:Filter>
  <sld:PolygonSymbolizer>
    <sld:Fill>
      <sld:CssParameter name="fill">#78092e</sld:CssParameter>
    </sld:Fill>
  </sld:PolygonSymbolizer>
  <sld:LineSymbolizer>
    <sld:Stroke>

```

```

        <sld:CssParameter name="stroke">#540620</sld:CssParameter>
        <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>
    </sld:Stroke>
</sld:LineSymbolizer>
</sld:Rule>
<sld:Rule>
    <ogc:Filter>
        <ogc:PropertyIsEqualTo>
            <ogc:PropertyName>UNIT</ogc:PropertyName>
            <ogc:Literal>AHpe</ogc:Literal>
        </ogc:PropertyIsEqualTo>
    </ogc:Filter>
    <sld:PolygonSymbolizer>
        <sld:Fill>
            <sld:CssParameter name="fill">#78092e</sld:CssParameter>
        </sld:Fill>
    </sld:PolygonSymbolizer>
    <sld:LineSymbolizer>
        <sld:Stroke>
            <sld:CssParameter name="stroke">#540620</sld:CssParameter>
            <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>
        </sld:Stroke>
    </sld:LineSymbolizer>
</sld:Rule>
<sld:Rule>
    <ogc:Filter>
        <ogc:PropertyIsEqualTo>
            <ogc:PropertyName>UNIT</ogc:PropertyName>
            <ogc:Literal>AHt</ogc:Literal>
        </ogc:PropertyIsEqualTo>
    </ogc:Filter>
    <sld:PolygonSymbolizer>
        <sld:Fill>
            <sld:CssParameter name="fill">#5f025a</sld:CssParameter>
        </sld:Fill>
    </sld:PolygonSymbolizer>
    <sld:LineSymbolizer>
        <sld:Stroke>
            <sld:CssParameter name="stroke">#42013e</sld:CssParameter>
            <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>
        </sld:Stroke>
    </sld:LineSymbolizer>
</sld:Rule>
<sld:Rule>
    <ogc:Filter>
        <ogc:PropertyIsEqualTo>
            <ogc:PropertyName>UNIT</ogc:PropertyName>
            <ogc:Literal>AHt3</ogc:Literal>
        </ogc:PropertyIsEqualTo>
    </ogc:Filter>
    <sld:PolygonSymbolizer>

```

```

    <sld:Fill>
      <sld:CssParameter name="fill">#e76161</sld:CssParameter>
    </sld:Fill>
  </sld:PolygonSymbolizer>
  <sld:LineSymbolizer>
    <sld:Stroke>
      <sld:CssParameter name="stroke">#a14343</sld:CssParameter>
      <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>
    </sld:Stroke>
  </sld:LineSymbolizer>
</sld:Rule>
<sld:Rule>
  <ogc:Filter>
    <ogc:PropertyIsEqualTo>
      <ogc:PropertyName>UNIT</ogc:PropertyName>
      <ogc:Literal>Aa1</ogc:Literal>
    </ogc:PropertyIsEqualTo>
  </ogc:Filter>
  <sld:PolygonSymbolizer>
    <sld:Fill>
      <sld:CssParameter name="fill">#fcedcd</sld:CssParameter>
    </sld:Fill>
  </sld:PolygonSymbolizer>
  <sld:LineSymbolizer>
    <sld:Stroke>
      <sld:CssParameter name="stroke">#b0a58f</sld:CssParameter>
      <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>
    </sld:Stroke>
  </sld:LineSymbolizer>
</sld:Rule>
<sld:Rule>
  <ogc:Filter>
    <ogc:PropertyIsEqualTo>
      <ogc:PropertyName>UNIT</ogc:PropertyName>
      <ogc:Literal>Aa2</ogc:Literal>
    </ogc:PropertyIsEqualTo>
  </ogc:Filter>
  <sld:PolygonSymbolizer>
    <sld:Fill>
      <sld:CssParameter name="fill">#94474b</sld:CssParameter>
    </sld:Fill>
  </sld:PolygonSymbolizer>
  <sld:LineSymbolizer>
    <sld:Stroke>
      <sld:CssParameter name="stroke">#673134</sld:CssParameter>
      <sld:CssParameter name="stroke-width">0.5</sld:CssParameter>
    </sld:Stroke>
  </sld:LineSymbolizer>
</sld:Rule>
</sld:FeatureTypeStyle>
</sld:UserStyle>

```

```
</sld:UserLayer>  
</sld:StyledLayerDescriptor>
```