Table of Contents

Co	Commands	1
]	st	1
1	rsion	2
]	elp	2
]	pe	3
9	ell	4

Core Commands

List

List all command names.

Short Name	Long Name	Description
-d	description	Include the description
	help	Print the help message
	web-help	Open help in a browser

```
geoc list
```

```
carto map
filter cql2xml
geometry convert
geometry dd2pt
geometry geohash bounds
geometry geohash decode
geometry geohash encode
geometry geohash neighbors
geometry greatcirclearc
geometry offset
...
```

List all commands names with a short description.

```
geoc list -d
```

```
carto map = Create a cartographic map

filter cql2xml = Convert a CQL statement to an OCG XML Filter

geometry convert = Convert a geometry from one format to another

geometry dd2pt = Convert a decimal degrees formatted string into a Point

geometry geohash bounds = Calculate the geohashes for the given bounds

geometry geohash decode = Decode a GeoHash to a Geometry.

geometry geohash encode = Encode a Geometry as a GeoHash

geometry geohash neighbors = Get a geohash's neighbors

geometry greatcirclearc = Create a great circle arc.

geometry offset = Create a Geometry offset from the input Geometry

...
```

Version

Get the current version.

Short Name	Long Name	Description
	help	Print the help message
	web-help	Open help in a browser

geoc version

0.19.0

Help

You can get help from any subcommand.

geoc vector buffer --help

```
geoc vector buffer: Buffer the features of the input Layer and save them to the output
Layer
--help
                             : Print the help message (default: true)
--web-help
                            : Open help in a browser (default: false)
-c (--capstyle) VAL
                            : The cap style (default: round)
 -d (--distance) VAL
                            : The buffer distance
-i (--input-workspace) VAL : The input workspace
-l (--input-layer) VAL
                         : The input layer
-o (--output-workspace) VAL : The output workspace
-q (--quadrantsegments) N : The number of quadrant segments (default: 8)
-r (--output-layer) VAL
                          : The output layer
-s (--singlesided)
                            : Whether buffer should be single sided or not
                               (default: false)
```


Pipe

Combine multiple commands together with a pipe.

Short Name	Long Name	Description
-c	commands	Commands separate by pipe
	help	Print the help message
	web-help	Open help in a browser

```
geoc pipe -c vector randompoints -n 10 -g -180,-90,180,90 | vector buffer -d 10
```

```
"id:Integer", "the_geom:Polygon:EPSG:4326"
"0", "POLYGON ((-161.06633641154258 61.782622706275646, -161.25848360751027
59.831719486114366, -161.8275410864297 57.955788382624746, -162.75164028851714
56.226920376079626, -163.9952685996771 54.71155489441017, -165.51063408134655
53.46792658325019, -167.23950208789168 52.54382738116278, -169.1154331913813
51.97476990224334, -171.06633641154258 51.782622706275646, -173.01723963170386
51.97476990224334, -174.89317073519348 52.54382738116278, -176.6220387417386
53.46792658325019, -178.13740422340805 54.71155489441017, -179.38103253456802
56.226920376079626, -180.30513173665545 57.955788382624746, -180.8741892155749
59.83171948611436, -181.06633641154258 61.782622706275646, -180.8741892155749
63.73352592643693, -180.30513173665545 65.60945702992655, -179.38103253456802
67.33832503647167, -178.13740422340805 68.85369051814112, -176.6220387417386
70.0973188293011, -174.89317073519348 71.0214180313885, -173.01723963170386
71.59047551030795, -171.06633641154258 71.78262270627565, -169.1154331913813
71.59047551030795, -167.23950208789168 71.0214180313885, -165.51063408134655
70.0973188293011, -163.9952685996771 68.85369051814112, -162.75164028851714
67.33832503647167, -161.8275410864297 65.60945702992655, -161.25848360751027
63.73352592643693, -161.06633641154258 61.782622706275646))"
```



Shell

Run commands in an interactive shell.

Short Name	Long Name	Description
	help	Print the help message
	web-help	Open help in a browser

geoc shell



You can now type commands in the interactive shell.

If you hit the **tab** key you can get command line completion.

You can use the tab key again to cycle through the suggested values and hit the **return** key to select one.



In this example, we are looking for the vector contains command, so after typing vector c and hitting tab, we get a list of all vector commands that begin with the letter c.



Once we have found our command, the shell will also provide completion for options.

