

Table of Contents

Workspace Recipes	1
Using Workspaces	1
Using a Directory Workspace	3
Investigating Workspaces	4
Creating Workspaces	5

Workspace Recipes

The Workspace classes are in the [geoscript.workspace](#) package.

A Workspace is a collection of Layers. You can create, add, remove, and get Layers. There are many different kinds of Workspaces in GeoScript including Memory, PostGIS, Directory (for Shapefiles), GeoPackage, and many more.

Using Workspaces

Create a Workspace

```
Workspace workspace = new Workspace()
```

Create a Layer

```
Schema schema = new Schema("cities", [  
    new Field("geom", "Point", "EPSG:4326"),  
    new Field("id", "Integer"),  
    new Field("name", "String")  
)  
Layer layer = workspace.create(schema)  
println layer
```

```
cities
```

Check whether a Workspace has a Layer by name

```
boolean hasCities = workspace.has("cities")  
println hasCities
```

```
true
```

Get a Layer from a Workspace

```
Layer citiesLayer = workspace.get('cities')  
println citiesLayer
```

```
cities
```

Add a Layer to a Workspace

```
Schema statesSchema = new Schema("states", [  
    new Field("geom", "Polygon", "EPSG:4326"),  
    new Field("id", "Integer"),  
    new Field("name", "String")  
])  
Layer statesLayer = new Layer("states", statesSchema)  
workspace.add(statesLayer)  
println workspace.has("states")
```

true

Get the names of all Layers in a Workspace

```
List<String> names = workspace.names  
names.each { String name ->  
    println name  
}
```

MySQL
Geobuf
PostGIS (JNDI)
Spatialite (JNDI)
Web Feature Server (NG)
PostGIS
Directory of spatial files (shapefiles)
GeoPackage
MySQL (JNDI)
H2 (JNDI)
Properties
Shapefile
Spatialite
H2

Remove a Layer from a Workspace

```
workspace.remove("cities")  
println workspace.has('cities')
```

false

Close the Workspace when you are done

```
workspace.close()
```

Using a Directory Workspace

A Directory Workspace is a directory of Shapefiles.

Create a Directory Workspace

```
Directory directory = new Directory("src/main/resources/data")
println directory.toString()
```

```
Directory[/home/travis/build/jericks/geoscript-groovy-
cookbook/src/main/resources/data]
```

View the Workspace's format

```
String format = directory.format
println format
```

```
Directory
```

View the Workspace's File

```
File file = directory.file
println file
```

```
/home/travis/build/jericks/geoscript-groovy-cookbook/src/main/resources/data
```

View the Workspace's list of Layer names

```
List names = directory.names
names.each { String name ->
    println name
}
```

```
states
```

Get a Layer by name

```
Layer layer = directory.get("states")
int count = layer.count
println "Layer ${layer.name} has ${count} Features."
```

Layer states has 49 Features.

Close the Directory when done.

```
directory.close()
```

Investigating Workspaces

Get available Workspace names

```
List<String> names = Workspace.getWorkspaceNames()
names.each { String name ->
    println name
}
```

```
MySQL
Geobuf
PostGIS (JNDI)
Spatialite (JNDI)
Web Feature Server (NG)
PostGIS
Directory of spatial files (shapefiles)
GeoPackage
MySQL (JNDI)
H2 (JNDI)
Properties
Shapefile
Spatialite
H2
```

Get parameters for a Workspace

```
List<Map> parameters = Workspace.getWorkspaceParameters("GeoPackage")
parameters.each { Map param ->
    println "Parameter = ${param.key} Type = ${param.type} Required?
    ${param.required}"
}
```

```

Parameter = dbtype Type = java.lang.String Required? true
Parameter = database Type = java.io.File Required? true
Parameter = user Type = java.lang.String Required? false
Parameter = passwd Type = java.lang.String Required? false
Parameter = namespace Type = java.lang.String Required? false
Parameter = Expose primary keys Type = java.lang.Boolean Required? false
Parameter = max connections Type = java.lang.Integer Required? false
Parameter = min connections Type = java.lang.Integer Required? false
Parameter = fetch size Type = java.lang.Integer Required? false
Parameter = Batch insert size Type = java.lang.Integer Required? false
Parameter = Connection timeout Type = java.lang.Integer Required? false
Parameter = validate connections Type = java.lang.Boolean Required? false
Parameter = Test while idle Type = java.lang.Boolean Required? false
Parameter = Evictor run periodicity Type = java.lang.Integer Required? false
Parameter = Max connection idle time Type = java.lang.Integer Required? false
Parameter = Evictor tests per run Type = java.lang.Integer Required? false
Parameter = Primary key metadata table Type = java.lang.String Required? false
Parameter = Session startup SQL Type = java.lang.String Required? false
Parameter = Session close-up SQL Type = java.lang.String Required? false
Parameter = Callback factory Type = java.lang.String Required? false

```

Creating Workspaces

Creating a Workspace from a connection string

You can create a Workspace from a connection string that contains paramters in key=value format with optional single quotes.

Create a Shapefile Workspace

```

String connectionString = "url='states.shp' 'create spatial index'=true"
Workspace workspace = Workspace.getWorkspace(connectionString)

```

Create a GeoPackage Workspace

```

connectionString = "dbtype=geopkg database=layers.gpkg"
workspace = Workspace.getWorkspace(connectionString)

```

Create a Spatialite Workspace

```

connectionString = "dbtype=spatialite database=layers.sqlite"
workspace = Workspace.getWorkspace(connectionString)

```

Creating a Workspace from a connection map

You can create a Workspace from a connection map that contains paramters.

Create a H2 Workspace

```
Map params = [dbtype: 'h2', database: 'test.db']
Workspace workspace = Workspace.getWorkspace(params)
```

Create a PostGIS Workspace

```
params = [
  dbtype: 'postgis',
  database: 'postgres',
  host: 'localhost',
  port: 5432,
  user: 'postgres',
  passwd: 'postgres'
]
workspace = Workspace.getWorkspace(params)
```

Create a GeoBuf Workspace

```
params = [file: 'layers.pbf', precision: 6, dimension: 2]
workspace = Workspace.getWorkspace(params)
```

Creating Directory Workspaces

Create a Directory Workspace from a directory name

```
Workspace workspace = new Directory("src/main/resources/shapefiles")
println workspace.format
workspace.names.each { String name ->
  println name
}
```

```
Directory
ocean
countries
```

Create a Directory Workspace from a File directory

```
Workspace workspace = new Directory(new File("src/main/resources/shapefiles"))
println workspace.format
workspace.names.each { String name ->
  println name
}
```

Directory
ocean
countries

Create a Directory Workspace from a URL

```
Directory directory = Directory.fromURL(  
    new URL  
    ("http://www.naturalearthdata.com/http://www.naturalearthdata.com/download/110m/cultural/ne_110m_admin_0_countries.zip"),  
    new File("naturalearth")  
)  
println directory.format  
directory.names.each { String name ->  
    println name  
}
```

Directory
ne_110m_admin_0_countries

Creating GeoPackage Workspaces

Create a GeoPackage Workspace from a file name

```
Workspace workspace = new GeoPackage("src/main/resources/data.gpkg")  
println workspace.format  
workspace.names.each { String name ->  
    println name  
}
```

GeoPackage
countries
ocean
places
rivers
states

Create a GeoPackage Workspace from a File

```
Workspace workspace = new GeoPackage(new File("src/main/resources/data.gpkg"))  
println workspace.format  
workspace.names.each { String name ->  
    println name  
}
```


GeoPackage
countries
ocean
places
rivers
states

Creating H2 Workspaces

Create a H2 Workspace from a File

```
Workspace workspace = new H2(new File("src/main/resources/h2/data.db"))
println workspace.format
workspace.names.each { String name ->
    println name
}
```

H2
countries
ocean
places
states

Creating Geobuf Workspaces

Create a Geobuf Workspace from a File

```
Workspace workspace = new Geobuf(new File("src/main/resources/geobuf"))
println workspace.format
workspace.names.each { String name ->
    println name
}
```

Geobuf
countries
ocean
places