

Workload Corpus — Families + the 13 Dwarfs

Two orthogonal divisions: 102 workloads by signature family, and the Berkeley 13 dwarfs · June 2026

The corpus has TWO orthogonal divisions of the SAME workloads. (1) The behaviour FAMILIES, organised by MEMORY SIGNATURE (what the write-signal actually clusters), kept as finalised: IDLE -- near-zero writes (CPU is its warm/active boundary); MEM -- working-set writes (CACHE is a footprint/locality sub-family); IO -- page-cache + metadata writes (cold reads count here); THREAD -- shared-line + allocator writes; BULK-REWRITE / encryptor -- high-entropy full rewrites (the ransomware cluster); ENUMERATION / metadata -- scanner-like; STEALTH / trickle -- low-rate, high-intensity; APP; and MIXED. This is the 'which behaviour' division -- designed by signature, validated by cohesion. (2) This document is a SECOND, CROSS-CUTTING division by the Berkeley 13 dwarfs (Colella's seven, 2004, + Berkeley's six, A View from Berkeley, 2006) -- the 'which computation motif' division. Every workload keeps its family label AND gets a dwarf label where one applies; the two taxonomies coexist, they do not replace each other. A dwarf is an algorithmic method that captures a pattern of computation and communication -- largely a MEMORY-ACCESS pattern, which is what the host memory signal sees.

We filter every dwarf by WRITE-visibility, because the signal only sees pages that are written. Visible / Visible++ = write-heavy, structured (a real signal). Irregular = visible writes with irregular access. Partial = part visible. Quiet = read/compute-bound -> near-idle (a CONTROL, the 'is this motif invisible to host introspection?' null). Threats are labelled motifs, not a separate family: ransomware = Combinational Logic (encryption), scanner = Graph Traversal / FSM.

Rules: a workload that already exists in another family is POINTED to (status 'exists', with its family), never duplicated. Each dwarf targets 4-5 distinct workloads. v1 pre-fills only the existing pointers and leaves the gaps; the new workloads are chosen together, dwarf by dwarf, in iterations (edit the WORKLOADS lists in the generator and re-run).

PREDICTED CONFUSION (the payoff of running both divisions together): the write-signal does not see 'which dwarf' -- it sees a WRITE SHAPE. So most dwarf kernels, though filed under the KERNEL family (a provenance bucket, not itself a signature), are PREDICTED to be CONFUSED WITH a small set of signature archetypes -- IDLE (near-zero), WORKING-SET (large regular rewrite ~ a memory sweep), SCATTER (random target ~ random-page writes), SEQUENTIAL-GROW (monotone append ~ a bulk sequential write), or FRONTIER-CHURN. The 'Predicted signal' column names that archetype per built kernel. It is a PROVISIONAL hypothesis: the capture measures the actual confusion matrix -- whether each kernel's feature vector really clusters with that archetype's non-compute occupants. Predicted distribution: WORKING-SET 33, SCATTER 12, SEQUENTIAL-GROW 11, IDLE 6, FRONTIER-CHURN 2 -- i.e. ~half of all compute is predicted to be indistinguishable, by writes alone, from a plain memory working-set sweep.

Part 1 — First division: behaviour families (102 workloads)

Every built workload by memory-signature family. The Dwarf column cross-references Part 2 (-- = access / IO / concurrency primitive, no motif).

S1 — IDLE (+ CPU boundary) (near-zero writes)

The no-write floor. CPU-bound workloads sit here as the warm/active boundary (pure compute is near-invisible to a write signal); matrix_mult drifts toward MEM via its output writes.

Workload	Status	Dwarf (Part 2)	Mechanism / note
run_idle	exists	--	sleep baseline
idle_long_baseline	exists	--	long uncontaminated idle (optional cache-drop)
idle_post_workload_recover y	exists	--	idle after a prior workload (writeback decay)

Workload	Status	Dwarf (Part 2)	Mechanism / note
cpu_hash_loop_v2	exists	Combinational Logic	register-resident hash; near-idle (CPU boundary)
cpu_branch_random_v2	exists	Finite State Machines	random branches; near-idle (CPU boundary)
cpu_matrix_mult_v2	exists	Dense Linear Algebra	matmul; writes output C -> drifts to MEM
kernel_spmv_v2	under-testing	Sparse Linear Algebra	SpMV quiet control: gather-dominated, read-only structure -> near-idle (kernel/D2_visible_sparse_linear_algebra/kernel_spmv_v2.c)
kernel_bfs_v2	under-testing	Graph Traversal	BFS quiet control: static graph traversed, only visited/frontier writes -> near-idle (kernel/D9_visible_graph_traversal/kernel_bfs_v2.c)
kernel_mc_pi_v2	exists	MapReduce / Monte Carlo	MC-pi quiet control: RNG sample + scalar/partials accumulate -> near-idle (kernel/D7_visible_mapreduce_montecarlo/kernel_mc_pi_v2.c)
kernel_nqueens_count_v2	exists	Backtrack / Branch-and-Bound	N-queens count quiet control: bitmask backtracking, scalar counter only -> near-idle despite exponential search (kernel/D11_visible_backtracking/kernel_nqueens_count_v2.c)
kernel_dfa_match_v2	exists	Finite State Machines	DFA recogniser quiet control: scan a read-only stream, write only a state word + match counter -> near-idle (kernel/D13_visible_finite_state_machines/kernel_dfa_match_v2.c)

S2 — MEM (+ CACHE sub-family) (working-set writes)

Anonymous working-set writes. CACHE workloads are a footprint/locality sub-family (small = quiet, large = loud). These are access primitives, not computational motifs (no dwarf).

Workload	Status	Dwarf (Part 2)	Mechanism / note
mem_workingset_sweep_v2	exists	--	page-strided writes, footprint sweep
mem_writemag_sweep_v2	exists	--	per-page write-magnitude sweep
mem_rmw_intensity_v2	exists	--	read-modify-write intensity
mem_pagefault_density_v2	exists	--	fault vs steady-state touch
mem_mmap_traversal_v2	exists	--	mmap file traversal
mem_random_write_pages_v2	exists	--	random page writes
mem_stride_sweep_large_v2	exists	--	large-buffer stride sweep
cache_hot_loop_v2	exists	--	L1-resident RMW (CACHE sub; quiet)
cache_cold_scan_v2	exists	--	> LLC linear scan (CACHE sub)
cache_stride_sweep_v2	exists	--	> LLC stride (CACHE sub)

S3 — IO (page-cache + metadata writes)

Writes through the page cache + file metadata. Cold reads (cache fills) count here; io_read_cache_hit is the weak (near-idle) member.

Workload	Status	Dwarf (Part 2)	Mechanism / note
io_read_cache_hit_v2	exists	--	cache-hot reads; near-idle (weak member)
io_direct_write_like_v2	exists	--	O_DIRECT writes, bypass page cache

S4 — THREAD (shared-line + allocator writes)

Concurrency write patterns: shared cache lines, futex/scheduler, allocator churn. Contention types are quiet in APF (visible via temporal/revisit features).

Workload	Status	Dwarf (Part 2)	Mechanism / note
thread_lock_contention_v2	exists	--	mutex + shared cacheline
thread_producer_consumer_v2	exists	--	ring buffer + condvar
thread_parallel_alloc_v2	exists	--	concurrent malloc/free churn

S5 — BULK-REWRITE / encryptor (high-entropy full rewrites)

The threat-shaped cluster: discover -> read -> transform -> write -> rename over many files, high-entropy output. Dwarf: Combinational Logic (encryption).

Workload	Status	Dwarf (Part 2)	Mechanism / note
sandbox_ransom_seq	exists	Combinational Logic	sequential 5-phase per file
sandbox_ransom_batched	exists	Combinational Logic	batched phases (all-at-once)
sandbox_ransom_slowburn	exists	Combinational Logic	paced: one file / interval
sandbox_ransom_selective	exists	Combinational Logic	selective subset (.dat only)

S6 — ENUMERATION / metadata (stat-heavy, few writes)

Directory / metadata enumeration (stat, readdir), little content write. Dwarf: Graph Traversal.

Workload	Status	Dwarf (Part 2)	Mechanism / note
sandbox_scanner_metadata	exists	Graph Traversal	directory enumeration via stat

S7 — STEALTH / trickle (low-rate, high-intensity writes)

Low page-count, high per-page intensity -- the low-APF / high-Hamming probe. A modulation of a write motif, not a dwarf of its own.

Workload	Status	Dwarf (Part 2)	Mechanism / note
sandbox_stealth_microwrite	exists	--	single-page micro-rewrites
sandbox_stealth_scattered	exists	--	scattered page rewrites
sandbox_stealth_paced	exists	--	time-jittered single-page writes

S8 — APP (real-application write mixes)

Whole real applications (not primitives). Each also carries a dwarf label: compression = Combinational Logic, parsing = FSM, DB = MapReduce.

Workload	Status	Dwarf (Part 2)	Mechanism / note
app_hashtable_intensive_v2	exists	Combinational Logic	open-addressing hash build/probe
app_sqlite_oltp_v2	exists	MapReduce / Monte Carlo	OLTP WAL append + checkpoint
app_sqlite_analytical_v2	exists	MapReduce / Monte Carlo	analytical aggregation / scan
app_compress_gzip_v2	exists	Combinational Logic	gzip compress (LZ77 + Huffman)

Workload	Status	Dwarf (Part 2)	Mechanism / note
app_decompress_gzip_v2	exists	Combinational Logic	gzip decompress
app_json_parse_v2	exists	Finite State Machines	streaming JSON parse

S9 — MIXED (blended write patterns)

Deliberate superpositions of other families; visible because their mem/io parts write. A blend by construction.

Workload	Status	Dwarf (Part 2)	Mechanism / note
mixed_mem_io_v2	exists	--	concurrent mem writes + file IO
mixed_cpu_mem_v2	exists	--	compute + mem pressure
mixed_cpu_io_v2	exists	--	cpu loop + file IO

S10 — KERNEL (compute motifs) (structured-compute writes)

Structured-compute writers -- the Berkeley dwarf kernels. Regular / periodic write patterns, distinct from MEM's amorphous sweeps. Each carries its dwarf label on axis 2. Built one at a time (see Status); the first is the D5 stencil.

Workload	Status	Dwarf (Part 2)	Mechanism / note
kernel_stencil_jacobi_v2	under-testing	Structured Grids	2D 5-point Jacobi; full-grid rewrite, double-buffer (kernel/D5_visible_structured_grids/kernel_stencil_jacobi_v2.c)
kernel_stencil_seidel_v2	under-testing	Structured Grids	Gauss-Seidel red-black, in-place; checkerboard writes (kernel/D5_visible_structured_grids/kernel_stencil_seidel_v2.c)
kernel_multigrid_v2	under-testing	Structured Grids	geometric multigrid V-cycle; multi-scale, time-varying footprint (kernel/D5_visible_structured_grids/kernel_multigrid_v2.c)
kernel_fft_v2	under-testing	Spectral Methods	in-place radix-2 FFT; stage-varying-stride butterfly + bit-reversal scatter (kernel/D3_visible_spectral_methods/kernel_fft_v2.c)
kernel_gemm_v2	under-testing	Dense Linear Algebra	blocked dense matmul $C=A*B$; large output-C rewrite (kernel/D1_visible_dense_linear_algebra/kernel_gemm_v2.c)
kernel_nbody_v2	under-testing	N-Body Methods	2D particle sim; four compact arrays rewritten per step, smooth evolution (kernel/D4_visible_nbody_methods/kernel_nbody_v2.c)
kernel_dp_v2	under-testing	Dynamic Programming	edit-distance DP table fill; row-major wavefront (kernel/D10_visible_dynamic_programming/kernel_dp_v2.c)
kernel_hmm_v2	under-testing	Graphical Models	scaled HMM forward; probability-trellis column fill + dense transition matvec (kernel/D12_visible_graphical_models/kernel_hmm_v2.c)
kernel_lu_v2	under-testing	Dense Linear Algebra	in-place LU factorisation; shrinking trailing-submatrix front (kernel/D1_visible_dense_linear_algebra/kernel_lu_v2.c)
kernel_qr_v2	under-testing	Dense Linear Algebra	modified Gram-Schmidt / QR; growing orthogonalised-column front (kernel/D1_visible_dense_linear_algebra/kernel_qr_v2.c)
kernel_attention_v2	under-testing	Dense Linear Algebra	scaled dot-product attention (QK^T , row softmax, $*V$); transformer core (kernel/D1_visible_dense_linear_algebra/kernel_attention_v2.c)

Workload	Status	Dwarf (Part 2)	Mechanism / note
kernel_conv_v2	under-testing	Dense Linear Algebra	2D convolution / CNN layer; overlapping-window MAC, feature-map rewrite (kernel/D1_visible_dense_linear_algebra/kernel_conv_v2.c)
kernel_ntt_v2	under-testing	Spectral Methods	multi-limb number-theoretic transform (modular butterfly); CKKS/lattice core, no crypto (kernel/D3_visible_spectral_methods/kernel_ntt_v2.c)
kernel_dct_v2	under-testing	Spectral Methods	blocked 8x8 2D DCT-II (JPEG transform); many small block rewrites (kernel/D3_visible_spectral_methods/kernel_dct_v2.c)
kernel_dwt_v2	under-testing	Spectral Methods	multi-level 2D Haar wavelet; shrinking multi-resolution pyramid (kernel/D3_visible_spectral_methods/kernel_dwt_v2.c)
kernel_fft2d_v2	under-testing	Spectral Methods	2D FFT (row FFTs, transpose, column FFTs); transpose scatter (kernel/D3_visible_spectral_methods/kernel_fft2d_v2.c)
kernel_barnes_hut_v2	under-testing	N-Body Methods	Barnes-Hut quadtree N-body; tree rebuilt each step + particle integrate (kernel/D4_visible_nbody_methods/kernel_barnes_hut_v2.c)
kernel_md_lj_v2	under-testing	N-Body Methods	Lennard-Jones molecular dynamics; cell list rebuilt each step + velocity-Verlet integrate (kernel/D4_visible_nbody_methods/kernel_md_lj_v2.c)
kernel_pic_v2	under-testing	N-Body Methods	electrostatic particle-in-cell; CIC scatter/gather + Jacobi Poisson solve on a grid (kernel/D4_visible_nbody_methods/kernel_pic_v2.c)
kernel_fmm_v2	under-testing	N-Body Methods	single-level fast multipole; per-box complex expansion coefficients + far eval (kernel/D4_visible_nbody_methods/kernel_fmm_v2.c)
kernel_sph_v2	under-testing	N-Body Methods	smoothed-particle hydrodynamics; two-pass neighbour sum with per-particle density/pressure fields (kernel/D4_visible_nbody_methods/kernel_sph_v2.c)
kernel_lbm_v2	under-testing	Structured Grids	Lattice-Boltzmann D2Q9; 9 distribution arrays streamed + BGK collide each step (kernel/D5_visible_structured_grids/kernel_lbm_v2.c)
kernel_fDTD_v2	under-testing	Structured Grids	2D FDTD electromagnetics; coupled E/H field grids in Yee leapfrog (kernel/D5_visible_structured_grids/kernel_fDTD_v2.c)
kernel_floyd_v2	under-testing	Dynamic Programming	Floyd-Warshall all-pairs shortest paths; whole matrix relaxed n times (kernel/D10_visible_dynamic_programming/kernel_floyd_v2.c)
kernel_matrixchain_v2	under-testing	Dynamic Programming	matrix-chain optimal parenthesisation; anti-diagonal fill, $O(n^3)$ (kernel/D10_visible_dynamic_programming/kernel_matrixchain_v2.c)
kernel_knapsack_v2	under-testing	Dynamic Programming	0/1 knapsack, space-optimised 1D rolling capacity array (kernel/D10_visible_dynamic_programming/kernel_knapsack_v2.c)
kernel_smithwaterman_v2	under-testing	Dynamic Programming	Smith-Waterman local alignment; wavefront fill + traceback (kernel/D10_visible_dynamic_programming/kernel_smithwaterman_v2.c)
kernel_beliefprop_v2	under-testing	Graphical Models	loopy sum-product belief propagation on a grid MRF; iterated message arrays (kernel/D12_visible_graphical_models/kernel_beliefprop_v2.c)
kernel_kalman_v2	under-testing	Graphical Models	ensemble of Kalman filters; small dense covariance matrices updated per step (kernel/D12_visible_graphical_models/kernel_kalman_v2.c)

Workload	Status	Dwarf (Part 2)	Mechanism / note
kernel_gibbs_v2	under-testing	Graphical Models	Gibbs sampling on a Potts/Ising grid; stochastic per-cell resample sweep (kernel/D12_visible_graphical_models/kernel_gibbs_v2.c)
kernel_ldpc_v2	under-testing	Graphical Models	LDPC min-sum decoder; bipartite Tanner-graph message passing (kernel/D12_visible_graphical_models/kernel_ldpc_v2.c)
kernel_spmv_v2	under-testing	Sparse Linear Algebra	SpMV: sparse x dense -> dense output; the GNN aggregation kernel (kernel/D2_visible_sparse_linear_algebra/kernel_spmv_v2.c)
kernel_sparse_cholesky_v2	under-testing	Sparse Linear Algebra	banded sparse Cholesky; factor fills in within the band (kernel/D2_visible_sparse_linear_algebra/kernel_sparse_cholesky_v2.c)
kernel_spgemm_v2	under-testing	Sparse Linear Algebra	SpGEMM: sparse x sparse -> new sparse matrix, fill-in (kernel/D2_visible_sparse_linear_algebra/kernel_spgemm_v2.c)
kernel_sddmm_v2	under-testing	Sparse Linear Algebra	SDDMM: sampled dense-dense -> sparse output at mask positions (kernel/D2_visible_sparse_linear_algebra/kernel_sddmm_v2.c)
kernel_moe_dispatch_v2	under-testing	Sparse Linear Algebra	MoE dispatch: token-permutation scatter into expert buffers + combine (kernel/D2_visible_sparse_linear_algebra/kernel_moe_dispatch_v2.c)
kernel_fem_assembly_v2	under-testing	Unstructured Grids	FEM stiffness assembly: scatter-add element matrices into a global matrix (kernel/D6_visible_unstructured_grids/kernel_fem_assembly_v2.c)
kernel_fem_matvec_v2	under-testing	Unstructured Grids	matrix-free FEM matvec: element gather-apply-scatter into a result vector (kernel/D6_visible_unstructured_grids/kernel_fem_matvec_v2.c)
kernel_dg_v2	under-testing	Unstructured Grids	discontinuous Galerkin step: per-element dense volume + face-flux coupling (kernel/D6_visible_unstructured_grids/kernel_dg_v2.c)
kernel_mesh_smooth_v2	under-testing	Unstructured Grids	unstructured Laplacian mesh smoothing over an adjacency list (kernel/D6_visible_unstructured_grids/kernel_mesh_smooth_v2.c)
kernel_unstructured_fv_v2	under-testing	Unstructured Grids	finite-volume: conservative face-flux scatter-add into cells (kernel/D6_visible_unstructured_grids/kernel_unstructured_fv_v2.c)
kernel_rmat_gen_v2	under-testing	Graph Traversal	R-MAT graph generation; writes the edge list (Graph500 construction) (kernel/D9_visible_graph_traversal/kernel_rmat_gen_v2.c)
kernel_graph_stream_v2	under-testing	Graph Traversal	streaming edge insertion; grows a dynamic adjacency structure (kernel/D9_visible_graph_traversal/kernel_graph_stream_v2.c)
kernel_label_prop_v2	under-testing	Graph Traversal	connected components by iterated min-label propagation (kernel/D9_visible_graph_traversal/kernel_label_prop_v2.c)
kernel_union_find_v2	under-testing	Graph Traversal	union-find with path compression; rewrites the parent-pointer array (kernel/D9_visible_graph_traversal/kernel_union_find_v2.c)
kernel_histogram_v2	exists	MapReduce / Monte Carlo	histogram / word-count reduce; scatter-increments into a large bins array (kernel/D7_visible_mapreduce_monte_carlo/kernel_histogram_v2.c)
kernel_mc_option_v2	exists	MapReduce / Monte Carlo	Monte-Carlo option pricing; stores all GBM price paths, then discounted-mean payoff (kernel/D7_visible_mapreduce_monte_carlo/kernel_mc_option_v2.c)

Workload	Status	Dwarf (Part 2)	Mechanism / note
kernel_path_trace_v2	exists	MapReduce / Monte Carlo	Monte-Carlo path tracer; accumulates random rays into an image buffer (kernel/D7_visible_mapreduce_monte_carlo/kernel_path_trace_v2.c)
kernel_diffusion_v2	exists	MapReduce / Monte Carlo	diffusion-model sampler; iterative whole-image denoise rewrite, ping-pong buffers (kernel/D7_visible_mapreduce_montecarlo/kernel_diffusion_v2.c)
kernel_nqueens_enum_v2	exists	Backtrack / Branch-and-Bound	N-queens enumerate: same search as the count control but stores every solution -> bulk append (kernel/D11_visible_backtracking/kernel_nqueens_enum_v2.c)
kernel_brackets_enum_v2	exists	Backtrack / Branch-and-Bound	balanced-parenthesis enumeration; append all Catalan(n) strings (kernel/D11_visible_backtracking/kernel_brackets_enum_v2.c)
kernel_maze_backtrack_v2	exists	Backtrack / Branch-and-Bound	maze DFS solver; marks a large visited/parent grid across the search (kernel/D11_visible_backtracking/kernel_maze_backtrack_v2.c)
kernel_graph_coloring_v2	exists	Backtrack / Branch-and-Bound	CSP m-colouring; forward-checking colour+domain table over a big graph, genuine backtracking (prune/RESTORE churn) at the default threshold-m (kernel/D11_visible_backtracking/kernel_graph_coloring_v2.c)
kernel_bnb_tsp_v2	exists	Backtrack / Branch-and-Bound	TSP best-first branch-and-bound; explicit partial-tour priority-queue frontier (kernel/D11_visible_backtracking/kernel_bnb_tsp_v2.c)
kernel_bnb_knapsack_v2	exists	Backtrack / Branch-and-Bound	0/1-knapsack best-first B&B; subset-node frontier heap, cross-checks D10 DP (kernel/D11_visible_backtracking/kernel_bnb_knapsack_v2.c)
kernel_lexer_v2	exists	Finite State Machines	character-class FSM emitting a token record per lexeme into a large token array (kernel/D13_visible_finite_state_machines/kernel_lexer_v2.c)
kernel_dfa_build_v2	exists	Finite State Machines	NFA->DFA subset construction; builds a dense transition table (~2 ^K (K-1) states) (kernel/D13_visible_finite_state_machines/kernel_dfa_build_v2.c)
kernel_aho_corasick_v2	exists	Finite State Machines	Aho-Corasick multi-pattern automaton build + match-position list append (kernel/D13_visible_finite_state_machines/kernel_aho_corasick_v2.c)
kernel_fsm_transduce_v2	exists	Finite State Machines	Mealy escape/framing transducer emitting an output stream ~ input size (kernel/D13_visible_finite_state_machines/kernel_fsm_transduce_v2.c)

First division total: 102 workloads across 10 signature families.

Part 2 — Second division: the Berkeley 13 dwarfs

Coverage summary

Dwarf	Origin	Visibility	Maps to	Have	Target
D1 Dense Linear Algebra	Colella-7	Visible	KERNEL	6	4-5
D2 Sparse Linear Algebra	Colella-7	Visible	split: IDLE (spmv control) + KERNEL (writers)	6	4-5
D3 Spectral Methods	Colella-7	Visible++	KERNEL	5	4-5
D4 N-Body Methods	Colella-7	Visible	KERNEL	6	4-5
D5 Structured Grids	Colella-7	Visible++	KERNEL	5	4-5

Dwarf	Origin	Visibility	Maps to	Have	Target
D6 Unstructured Grids	Colella-7	Visible	KERNEL (irregular access)	5	4-5
D7 MapReduce / Monte Carlo	Colella-7	Partial	split	6	4-5
D8 Combinational Logic	Berkeley+6	Quiet / Visible	control OR threat-labeled	4	4-5
D9 Graph Traversal	Berkeley+6	Visible	split: IDLE (bfs control) + KERNEL (graph writers)	6	4-5
D10 Dynamic Programming	Berkeley+6	Visible	KERNEL	5	4-5
D11 Backtrack / Branch-and-Bound	Berkeley+6	Quiet + Visible	count=quiet; store/state/frontier=visible	7	4-5
D12 Graphical Models	Berkeley+6	Visible	KERNEL	5	4-5
D13 Finite State Machines	Berkeley+6	Quiet + Visible	recognise=quiet; emit output=visible	7	4-5

D1 — Dense Linear Algebra [Visible]

Colella-7. Maps to: KERNEL. Example: GEMM, LU, QR, attention (transformers), convolution (CNNs), BLAS-3.

$O(n^3)$ compute on $O(n^2)$ data; regular, blocked access; rewrites the output / factorised matrix. Anchored on the kernels that dominate production: GEMM (every neural-net layer), LU/QR (linear solve, least-squares), plus attention + convolution (the transformer and CNN cores). Three distinct write fronts -- static full rewrite (GEMM), shrinking trailing front (LU), growing orthogonalised front (QR) -- with attention/conv added for real-world coverage (their write signature is ~GEMM).

Target 4-5 workloads — have 6.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_gemm_v2	KERNEL / D1	WORKING-S ET	under- testing	KERNEL family: blocked dense matmul (-> kernel/D1_visible_dense_linear_algebra/kernel_gemm_v2.c)	Visible (static full output-C rewrite)	Every neural-net layer; BLAS-3 (cuBLAS/MKL); scientific computing
cpu_matrix_mult_v2	CPU / D1	--	exists	CPU family: naive square matmul, writes output C	Visible (regular; small-scale GEMM)	Small-scale GEMM control
kernel_lu_v2	KERNEL / D1	WORKING-S ET	under- testing	KERNEL family: in-place LU factorisation (-> kernel/D1_visible_dense_linear_algebra/kernel_lu_v2.c)	Visible (shrinking trailing-submatrix front)	Linear solve: SPICE circuit sim, finite-element, optimisation (LAPACK dgetrf)
kernel_qr_v2	KERNEL / D1	SEQUENTIAL -GROW	under- testing	KERNEL family: Gram-Schmidt / QR orthogonalisation (-> kernel/D1_visible_dense_linear_algebra/kernel_qr_v2.c)	Visible (growing orthogonalised-column front)	Least-squares regression; GMRES/Arnoldi eigensolvers
kernel_attention_v2	KERNEL / D1	WORKING-S ET	under- testing	KERNEL family: scaled dot-product attention $QK^T/\text{softmax} * V$ (-> kernel/D1_visible_dense_linear_algebra/kernel_attention_v2.c)	Visible (transformer core; ~GEMM + row-softmax)	Every transformer / LLM (the per-token core)
kernel_conv_v2	KERNEL / D1	WORKING-S ET	under- testing	KERNEL family: 2D convolution / CNN layer, sliding-window MAC (-> kernel/D1_visible_dense_linear_algebra/kernel_conv_v2.c)	Visible (overlapping-window feature-map rewrite)	CNNs: image & video vision models

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
Cholesky factorisation	KERNEL / D1	--	candidate	KERNEL (candidate): in-place symmetric factorisation, triangular shrinking front	Visible (LU-like triangular front)	Kalman filters, finance covariance, normal-equation least-squares
Triangular solve (TRSM)	KERNEL / D1	--	candidate	KERNEL (candidate): forward/back substitution, column wavefront	Visible (column-wise solve front)	The solve step inside LU/Cholesky; preconditioners

D2 — Sparse Linear Algebra **[Visible]**

Colella-7. Maps to: split: IDLE (spmv control) + KERNEL (writers). Example: SpMV (quiet control), SpMM, sparse Cholesky, SpGEMM, SDDMM, MoE dispatch.

Sparse linear algebra is QUIET only when the OUTPUT is small: SpMV reads a big sparse matrix by indirect gather but writes just a vector, so it is near-idle -- the classic 'important but invisible' case (kept as kernel_spmv_v2, the control). But sparse work that produces a LARGE output IS write-visible, and that is most of modern practice: SpMM (a dense output, the graph-neural-network aggregation kernel), sparse Cholesky (fill-in factors), SpGEMM (a new sparse matrix, algebraic multigrid), SDDMM (a sampled sparse output, graph attention), and MoE dispatch (a token-permutation scatter, modern LLMs). So D2 spans a quiet half and a visible half.

Target 4-5 workloads — have 6.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_spmv_v2	IDLE / D2	IDLE	under-testing	IDLE family (QUIET control): CSR SpMV, gather-dominated, tiny vector write (-> kernel/D2_visible_sparse_linear_algebra/kernel_spmv_v2.c)	Quiet / near-idle (the invisible baseline)	Inner loop of CG/GMRES solvers; recommenders; graph-as-matrix
kernel_spmv_v2	KERNEL / D2	WORKING-SET	under-testing	KERNEL family (VISIBLE): sparse x dense -> dense output (-> kernel/D2_visible_sparse_linear_algebra/kernel_spmv_v2.c)	Visible (large dense output rewritten each pass)	Graph neural networks (the aggregation kernel; DGL/PyG)
kernel_sparse_cholesky_v2	KERNEL / D2	WORKING-SET	under-testing	KERNEL family (VISIBLE): banded sparse Cholesky, fill-in (-> kernel/D2_visible_sparse_linear_algebra/kernel_sparse_cholesky_v2.c)	Visible (factor fills in within the band; progressive write)	Direct solvers (CHOLMOD/MUMPS); FEM, circuits, optimisation
kernel_spgemm_v2	KERNEL / D2	SEQUENTIAL-GROW	under-testing	KERNEL family (VISIBLE): sparse x sparse -> new sparse matrix (-> kernel/D2_visible_sparse_linear_algebra/kernel_spgemm_v2.c)	Visible (writes a new sparse matrix with fill-in)	Algebraic multigrid setup; triangle counting; graph contraction
kernel_sddmm_v2	KERNEL / D2	SCATTER	under-testing	KERNEL family (VISIBLE): sampled dense-dense -> sparse output (-> kernel/D2_visible_sparse_linear_algebra/kernel_sddmm_v2.c)	Visible (scattered writes at the sparse mask positions)	Graph-attention networks; recommender systems

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_moe_dispatch_v2	KERNEL / D2	SCATTER	under-testing	KERNEL family (VISIBLE): MoE token dispatch/combine scatter-gather (-> kernel/D2_visible_sparse_linear_algebra/kernel_moe_dispatch_v2.c)	Visible (token-permutation scatter into expert buffers)	Mixture-of-Experts LLMs (Mixtral, DeepSeek); >60% of 2025-26 releases
PageRank	covered / D2	--	covered	covered by kernel_spmv_v2 (repeated SpMV; same quiet gather + small vector write)	same quiet gather	Google web ranking; centrality; link analysis
Conjugate Gradient (CG)	covered / D2	--	covered	covered by kernel_spmv_v2 (SpMV-bound iteration, small vector writes)	same quiet gather	FEM/CFD SPD iterative solver
Sparse triangular solve (SpTRSV)	covered / D2	--	covered	covered by kernel_spmv_v2 (dependency-ordered sparse solve, tiny writes)	same quiet gather	ILU preconditioners

D3 — Spectral Methods [Visible++]

Colella-7. Maps to: KERNEL. Example: FFT, NTT, DCT, DWT, 2D-FFT (covers DTFT, cepstrum, MFCC, STFT, wavelet scattering).

Butterfly / bit-reversed, strided, multi-pass; in-place rewrite of the whole array. FIVE distinct write-patterns cover the dwarf: 1D butterfly (FFT), multi-stream butterfly (NTT), blocked (DCT), halving pyramid (DWT), transpose + two-direction (2D-FFT). Famous transforms that reduce to these -- DTFT, cepstrum, MFCC, STFT, wavelet scattering, FFT-convolution -- are marked 'covered' and point to the built test whose signature already captures them (building them would be pseudoreplication).

Target 4-5 workloads — have 5.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_fft_v2	KERNEL / D3	SCATTER	under-testing	KERNEL family: in-place radix-2 FFT (-> kernel/D3_visible_spectral_methods/kernel_fft_v2.c)	Visible++ (1D butterfly; bit-reversal scatter)	All DSP: audio, radio/5G, MRI, image filtering
kernel_ntt_v2	KERNEL / D3	WORKING-SET	under-testing	KERNEL family: RNS multi-limb number-theoretic transform, CKKS/lattice core (-> kernel/D3_visible_spectral_methods/kernel_ntt_v2.c)	Visible++ (multi-stream modular butterfly; integer content)	Lattice crypto / CKKS homomorphic encryption; big-integer multiply
kernel_dct_v2	KERNEL / D3	WORKING-SET	under-testing	KERNEL family: blocked 8x8 discrete cosine transform (-> kernel/D3_visible_spectral_methods/kernel_dct_v2.c)	Visible (many small blocks; real content)	JPEG / MPEG / H.264 image & video compression
kernel_dwt_v2	KERNEL / D3	WORKING-SET	under-testing	KERNEL family: discrete wavelet transform, filter+downsample pyramid (-> kernel/D3_visible_spectral_methods/kernel_dwt_v2.c)	Visible (halving multi-resolution pyramid)	JPEG2000, denoising, audio/image compression
kernel_fft2d_v2	KERNEL / D3	SCATTER	under-testing	KERNEL family: 2D FFT (row FFTs, transpose, column FFTs) (-> kernel/D3_visible_spectral_methods/kernel_fft2d_v2.c)	Visible++ (transpose scatter + two-direction passes)	Image/optics spectral filtering, turbulence DNS, crystallography

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
DTFT / direct DFT	covered / D3	--	covered	covered by kernel_fft_v2 (computable DTFT = DFT = FFT; naive DFT = dense matvec)	same 1D-butterfly signature	Frequency analysis (textbook form of the FFT)
Cepstrum	covered / D3	--	covered	covered by kernel_fft_v2 (FFT -> log . -> inverse FFT)	two butterfly passes + pointwise	Pitch detection, echo / speaker analysis
MFCC	covered / D3	--	covered	covered by kernel_fft_v2 + kernel_dct_v2 (FFT -> mel filterbank -> log -> DCT)	butterfly + blocked cosine	The classic speech-recognition audio feature
STFT / spectrogram	covered / D3	--	covered	covered by kernel_fft_v2 (sliding windowed FFTs filling a spectrogram)	repeated 1D butterfly (sliding window)	Every audio ML front-end; speech, music
Wavelet scattering (WST)	covered / D3	--	covered	covered by kernel_dwt_v2 (cascade of wavelet transforms + modulus)	repeated pyramid	Audio / image classification features
FFT convolution	covered / D3	--	covered	covered by kernel_fft_v2 (forward FFT, pointwise multiply, inverse FFT)	two butterfly passes + pointwise	Large-kernel convolution; polynomial / big-integer multiply

D4 — N-Body Methods [Visible]

Colella-7. Maps to: KERNEL. Example: gravity nbody, Barnes-Hut, molecular dynamics, particle-in-cell, FMM, SPH.

N particles interacting pairwise; rewrites compact particle arrays (position/velocity) smoothly each timestep. Variants differ mostly in how they READ to compute forces (all-pairs, tree, neighbour lists) -- invisible to the write-signal -- so they are distinguished by the EXTRA structure they WRITE: Barnes-Hut a tree, FMM expansion arrays, MD cell/neighbour lists, PIC a grid (scatter-deposit). All-pairs adds no new write, so it is 'covered' by the baseline nbody.

Target 4-5 workloads — have 6.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_nbody_v2	KERNEL / D4	WORKING-S ET	under-testing	KERNEL family: 2D K-sampled gravity (-> kernel/D4_visible_nbody_methods/kernel_nbody_v2.c)	Visible (four compact arrays rewritten per step, smooth)	2D gravity model; astrophysics, particle effects
kernel_barnes_hut_v2	KERNEL / D4	SCATTER	under-testing	KERNEL family: quadtree build + traversal, O(n log n) (-> kernel/D4_visible_nbody_methods/kernel_barnes_hut_v2.c)	Visible/irregular (tree nodes rebuilt each step + particle rewrite)	Cosmology (GADGET), galaxy formation
kernel_md_lj_v2	KERNEL / D4	WORKING-S ET	under-testing	KERNEL family: Lennard-Jones MD with cell lists (-> kernel/D4_visible_nbody_methods/kernel_md_lj_v2.c)	Visible (periodic cell-list rebuild + position/velocity rewrite)	GROMACS / NAMD / AMBER: drug discovery, protein folding, materials
kernel_pic_v2	KERNEL / D4	SCATTER	under-testing	KERNEL family: particle-in-cell (scatter to grid, field solve, gather) (-> kernel/D4_visible_nbody_methods/kernel_pic_v2.c)	Visible (particle->grid scatter-deposit + grid rewrite)	Plasma physics, accelerators, semiconductor device sim

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_fmm_v2	KERNEL / D4	WORKING-S ET	under- testing	KERNEL family: fast multipole (multipole/local expansion arrays on a tree) (-> kernel/D4_visible_nbody_methods/kernel_fmm_v2.c)	Visible (expansion-coefficient arrays + particle rewrite)	Electrostatics, acoustics, fast O(n) far-field
kernel_sph_v2	KERNEL / D4	WORKING-S ET	under- testing	KERNEL family: smoothed-particle hydrodynamics (density/pressure fields) (-> kernel/D4_visible_nbody_methods/kernel_sph_v2.c)	Visible (extra per-particle fields + particle rewrite)	Fluid sim, film VFX (water/lava), astrophysics
All-pairs direct N-body	covered / D4	--	covered	covered by kernel_nbody_v2 (same particle-array writes; differs only in the force READS)	same smooth particle rewrite	Exact small-N molecular dynamics; reference force

D5 — Structured Grids [Visible++]

Colella-7. Maps to: KERNEL. Example: stencil, Jacobi/Gauss-Seidel, multigrid, Lattice-Boltzmann, FDTD.

Regular neighbour sweep over a grid, iterative; rewrites the grid each iteration. Covered by 3 genuinely-distinct members (double-buffer / in-place / multigrid); further stencil variants (9-point, 3D, separable) differ only in reads/content -> signal-redundant. LBM/FDTD listed as distinct candidates (multiple field arrays, leapfrog).

Target 4-5 workloads — have 5.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_stencil_jacobi_v2	KERNEL / D5	WORKING-S ET	under- testing	KERNEL family: 2D 5-point Jacobi, double-buffer (-> kernel/D5_visible_structured_grids/kernel_stencil_jacobi_v2.c)	Visible++ (periodic full rewrite, ~2x footprint)	Finite-difference PDE: heat / Poisson / diffusion solvers
kernel_stencil_seidel_v2	KERNEL / D5	WORKING-S ET	under- testing	KERNEL family: Gauss-Seidel red-black, in-place (-> kernel/D5_visible_structured_grids/kernel_stencil_seidel_v2.c)	Visible++ (checkerboard in-place, ~1x footprint)	PDE relaxation; smoother inside multigrid
kernel_multigrid_v2	KERNEL / D5	WORKING-S ET	under- testing	KERNEL family: multigrid V-cycle (-> kernel/D5_visible_structured_grids/kernel_multigrid_v2.c)	Visible++ (multi-scale, time-varying footprint)	The optimal PDE solver; CFD, electrostatics
kernel_lbm_v2	KERNEL / D5	WORKING-S ET	under- testing	KERNEL family: Lattice-Boltzmann D2Q9, stream + collide over 9 distribution arrays (-> kernel/D5_visible_structured_grids/kernel_lbm_v2.c)	Visible++ (nine distribution arrays streamed each step)	CFD: porous media, aerodynamics (OpenLB / Palabos)
kernel_fDTD_v2	KERNEL / D5	WORKING-S ET	under- testing	KERNEL family: 2D TM FDTD, leapfrog of coupled E/H field grids (-> kernel/D5_visible_structured_grids/kernel_fDTD_v2.c)	Visible++ (two coupled field grids, E<->H leapfrog)	Antenna / radar / photonics simulation (Meep)

D6 — Unstructured Grids [Visible]

Colella-7. Maps to: KERNEL (irregular access). Example: FEM assembly, matrix-free FEM matvec, discontinuous Galerkin, mesh smoothing, unstructured finite-volume.

The irregular cousin of D5: PDE computation on unstructured meshes, reaching neighbours through explicit connectivity / adjacency lists (indirect gather). It writes real mesh/matrix arrays, so it is visible -- but the honest nuance is that the irregular ACCESS is mostly reads (invisible), so a plain unstructured relaxation writes the same footprint as a structured stencil. The genuinely distinct write is the SCATTER-ACCUMULATE that structured grids do not do: assembling a global matrix, or scatter-adding fluxes into cells. FEM matvec is the quieter member (a vector output, the matrix-free analog of SpMV).

Target 4-5 workloads — have 5.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_fem_assembly_v2	KERNEL / D6	SCATTER	under-testing	KERNEL family: scatter-add element matrices into a global matrix (-> kernel/D6_visible_unstructured_grids/kernel_fem_assembly_v2.c)	Visible (indexed scatter-accumulate into a large matrix)	FEM assembly: ANSYS / Abaqus structural & crash; aerospace
kernel_fem_matvec_v2	KERNEL / D6	IDLE	under-testing	KERNEL family: matrix-free FEM matvec, element gather-apply-scatter (-> kernel/D6_visible_unstructured_grids/kernel_fem_matvec_v2.c)	Quieter (scatter-add into a result VECTOR; the matrix-free SpMV analog)	Large FEM/CFD iterative solvers (matrix-free)
kernel_dg_v2	KERNEL / D6	WORKING-SET	under-testing	KERNEL family: discontinuous Galerkin step, per-element dense + face flux (-> kernel/D6_visible_unstructured_grids/kernel_dg_v2.c)	Visible (per-element dense blocks rewritten + flux coupling)	High-order CFD & seismic wave propagation
kernel_mesh_smooth_v2	KERNEL / D6	WORKING-SET	under-testing	KERNEL family: unstructured Laplacian mesh smoothing (-> kernel/D6_visible_unstructured_grids/kernel_mesh_smooth_v2.c)	Visible (node-array rewrite; write ~ D5 stencil, distinct in access)	Graphics mesh processing; remeshing
kernel_unstructured_fv_v2	KERNEL / D6	SCATTER	under-testing	KERNEL family: finite-volume, conservative face-flux scatter-add into cells (-> kernel/D6_visible_unstructured_grids/kernel_unstructured_fv_v2.c)	Visible (face-list gather + conservative cell scatter-add)	OpenFOAM CFD; aerodynamics
Mesh partitioning (METIS)	KERNEL-irregular / D6	--	candidate	KERNEL-irregular (candidate): graph coarsen / partition / refine	Irregular (graph rewrite; closer to D9)	Parallel FEM domain decomposition

D7 — MapReduce / Monte Carlo [Partial]

Colella-7. Maps to: split. Example: Monte-Carlo integration, option pricing, MCMC, histogram/word-count, path tracing, diffusion sampling.

Embarrassingly parallel map (writes intermediates) + reduce (small); or RNG accumulate. sqlite_analytical is a loose proxy. Now built: a quiet MC-pi control + four visible writers (histogram scatter, MC-option bulk path store, path-trace image accumulate, diffusion whole-image rewrite).

Target 4-5 workloads — have 6.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
app_sqlite_analytical_v2	APP / D7	--	exists	APP family (loose): read-heavy aggregation/scan over a DB	Quiet-ish (read-dominated)	Analytical SQL scan / aggregate (OLAP)
kernel_mc_pi_v2	IDLE / D7	IDLE	under-testing	IDLE family (QUIET control): MC-pi/integration, RNG sample + scalar/partial accumulate (-> kernel/D7_visible_mapreduce_montecarlo/kernel_mc_pi_v2.c)	Quiet / near-idle (scalar accumulate; the invisible baseline)	Physics, finance, Bayesian; high-dimensional integrals
kernel_histogram_v2	KERNEL / D7	SCATTER	under-testing	KERNEL family (VISIBLE): scatter-increment N samples into a large bins array (-> kernel/D7_visible_mapreduce_montecarlo/kernel_histogram_v2.c)	Visible (random scatter across the whole bins array)	MapReduce / Spark ETL; analytics; the canonical reduce
kernel_mc_option_v2	KERNEL / D7	SEQUENTIAL-GROW	under-testing	KERNEL family (VISIBLE): Monte-Carlo option pricing, stores all E x T GBM paths then averages payoff (-> kernel/D7_visible_mapreduce_montecarlo/kernel_mc_option_v2.c)	Visible (bulk path-array storage rewritten each pass)	Quant finance: derivatives, VaR, risk
kernel_path_trace_v2	KERNEL / D7	WORKING-SET	under-testing	KERNEL family (VISIBLE): Monte-Carlo path tracer, accumulate random rays into an image buffer (-> kernel/D7_visible_mapreduce_montecarlo/kernel_path_trace_v2.c)	Visible (image-buffer accumulation; whole grid reswept each pass)	Film & game rendering (RenderMan, Blender Cycles)
kernel_diffusion_v2	KERNEL / D7	WORKING-SET	under-testing	KERNEL family (VISIBLE): diffusion-model sampler, iterative whole-image denoise rewrite (-> kernel/D7_visible_mapreduce_montecarlo/kernel_diffusion_v2.c)	Visible (whole image/latent rewritten every step)	Generative-AI image sampling (Stable Diffusion, DALL-E)
MCMC (Metropolis-Hastings)	covered / D7	--	covered	covered by kernel_gibbs_v2 (Gibbs sampling is an MCMC method; same propose + small-state resample write)	same quiet small-state rewrite	Bayesian inference (Stan / PyMC), statistical physics

D8 — Combinational Logic [Quiet / Visible]

Berkeley+6. Maps to: control OR threat-labeled. Example: compression, SHA-256, AES, CRC32, hashing.

Simple bit-level ops over large data. CRC/hash = quiet; ENCRYPTION = visible high-entropy rewrite.

Target 4-5 workloads — have 4.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
app_compress_gzip_v2	APP / D8	--	exists	APP family: LZ77+Huffman stream compress, writes output	Visible (entropy-changing)	Web (HTTP gzip), storage, backups (DEFLATE)
app_decompress_gzip_v2	APP / D8	--	exists	APP family: inverse, small read -> large write	Visible	Web / storage decompression

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
cpu_hash_loop_v2	CPU / D8	--	exists	CPU family: FNV hash over a stream	Quiet (register-resident)	Hash tables, checksums
sandbox_ransom_* (4 variants)	SECURITY / D8	--	exists	SECURITY family (THREAT-labeled): discover ->read->XOR->write->rename	Visible++ (high-entropy rewrite)	Benign XOR; encryption-shaped rewrite control
SHA-256	CPU/IDLE / D8	--	candidate	CPU/IDLE (candidate): streaming compression function, tiny digest	Quiet (stream read, 32-byte write)	git, blockchain, TLS certificates, dedup, integrity
AES block cipher	covered / D8	--	covered	covered by sandbox_ransom_* (same high-entropy full-rewrite signature)	Visible (high-entropy output rewrite)	HTTPS/TLS, disk encryption (BitLocker / FileVault), VPN
CRC32	CPU/IDLE / D8	--	candidate	CPU/IDLE (candidate): table-driven rolling checksum	Quiet (register-resident)	Ethernet, ZIP, storage error detection

D9 — Graph Traversal [Visible]

Berkeley+6. Maps to: split: IDLE (bfs control) + KERNEL (graph writers). Example: BFS (quiet control), R-MAT generation, streaming insertion, label propagation, union-find.

Traversal is QUIET only when the graph is STATIC: BFS/DFS/Dijkstra read the (read-only) adjacency by indirect gather and write just a small visited/frontier/distance array -- near-idle (kept as kernel_bfs_v2, the control, with the graph built once and only traversed). But a graph that CHANGES or is GENERATED writes the large object -- the graph structure itself: R-MAT generation writes the edge list (Graph500 construction), streaming insertion grows the adjacency, and label-propagation / union-find rewrite label / parent arrays. So D9 spans a quiet half and a visible half.

Target 4-5 workloads — have 6.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_bfs_v2	IDLE / D9	IDLE	under-testing	IDLE family (QUIET control): BFS on a STATIC graph, built once and only traversed (-> kernel/D9_visible_graph_traversal/kernel_bfs_v2.c)	Quiet / near-idle (read-only graph; only visited/frontier writes)	Graph500 traversal; shortest-hops; GC mark
kernel_rmat_gen_v2	KERNEL / D9	SEQUENTIAL-GROW	under-testing	KERNEL family (VISIBLE): R-MAT graph generation, writes the edge list (-> kernel/D9_visible_graph_traversal/kernel_rmat_gen_v2.c)	Visible (bulk edge-list write, the large object)	Graph500 construction; synthetic scale-free graphs
kernel_graph_stream_v2	KERNEL / D9	SEQUENTIAL-GROW	under-testing	KERNEL family (VISIBLE): streaming edge insertion into a growing adjacency (-> kernel/D9_visible_graph_traversal/kernel_graph_stream_v2.c)	Visible (the graph structure itself is written/grown)	Streaming / temporal graph analytics
kernel_label_prop_v2	KERNEL / D9	WORKING-SET	under-testing	KERNEL family (VISIBLE): connected-components by min-label propagation (-> kernel/D9_visible_graph_traversal/kernel_label_prop_v2.c)	Visible (iterated node-label array rewrite; a graph stencil)	Community detection; connected components

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_union_find_v2	KERNEL / D9	SCATTER	under-testing	KERNEL family (VISIBLE): union-find with path compression (-> kernel/D9_visible_graph_traversal/kernel_union_find_v2.c)	Visible (parent-pointer array rewritten by unions + path compression)	Connected components; Kruskal MST
sandbox_scanner_metadata	SECURITY / D9	--	exists	SECURITY family (loose): directory enumeration via stat -- a tree/graph walk proxy	Quiet / metadata	Directory-walk proxy
DFS / Dijkstra / A*	covered / D9	--	covered	covered by kernel_bfs_v2 (same quiet static-traversal write pattern: small visited/distance/heap state)	same quiet traversal	Topological sort, GPS routing, pathfinding

D10 — Dynamic Programming [Visible]

Berkeley+6. Maps to: KERNEL. Example: edit distance, Smith-Waterman, Viterbi, Floyd-Warshall, knapsack.

Fill a 1D/2D table, each cell from neighbours; regular monotone fill front (wavefront).

Target 4-5 workloads — have 5.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_dp_v2	KERNEL / D10	WORKING-SET	under-testing	KERNEL family: edit-distance table fill (-> kernel/D10_visible_dynamic_programming/kernel_dp_v2.c)	Visible (row-major wavefront; migrating band on a large table)	git diff, spell-check, fuzzy matching
kernel_floyd_v2	KERNEL / D10	WORKING-SET	under-testing	KERNEL family: Floyd-Warshall all-pairs shortest paths (-> kernel/D10_visible_dynamic_programming/kernel_floyd_v2.c)	Visible (whole n*n matrix rewritten n times per solve)	All-pairs shortest path; routing; transitive closure
kernel_matrixchain_v2	KERNEL / D10	WORKING-SET	under-testing	KERNEL family: matrix-chain optimal parenthesisation (-> kernel/D10_visible_dynamic_programming/kernel_matrixchain_v2.c)	Visible (anti-diagonal fill by chain length, O(n^3) inner)	Compiler / query-plan optimisation, NLP parsing
kernel_knapsack_v2	KERNEL / D10	WORKING-SET	under-testing	KERNEL family: 0/1 knapsack, space-optimised 1D rolling array (-> kernel/D10_visible_dynamic_programming/kernel_knapsack_v2.c)	Visible (single capacity vector repainted in reverse per item)	Resource allocation, scheduling, finance
kernel_smithwaterman_v2	KERNEL / D10	WORKING-SET	under-testing	KERNEL family: Smith-Waterman local alignment, fill + traceback (-> kernel/D10_visible_dynamic_programming/kernel_smithwaterman_v2.c)	Visible (row-major wavefront + backward traceback path)	Genomics local alignment (BLAST family)
Needleman-Wunsc h	covered / D10	--	covered	covered by kernel_dp_v2 (identical global-alignment row-major wavefront)	same row-major wavefront	Global DNA / protein sequence alignment

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
Viterbi decoding	covered / D10	--	covered	covered by kernel_hmm_v2 (same trellis column-fill, max-product instead of sum)	same column-fill front	Speech recognition, error-correction decode, POS tagging

D11 — Backtrack / Branch-and-Bound [Quiet + Visible]

Berkeley+6. Maps to: count=quiet; store/state/frontier=visible. Example: N-queens (count vs enumerate), balanced brackets, maze solving, graph colouring, TSP / knapsack B&B, DPLL SAT, MILP.

Explore + prune a search tree (place a choice, recurse, undo). QUIET when it only COUNTS or finds one solution -- a tiny working set, near-idle even over exponential compute. VISIBLE three ways: (a) MATERIALISE the whole solution set, (b) a LARGE WORKING STATE (a big grid, or a colour+domain table over a graph), (c) an explicit best-first FRONTIER. The count-vs-store return type is the quiet->visible switch.

Target 4-5 workloads — have 7.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_nqueens_count_v2	IDLE / D11	IDLE	under-testing	IDLE family (QUIET control): N-queens counter, three-bitmask backtracking, scalar reduce -> near-idle despite exponential compute (-> kernel/D11_visible_backtracking/kernel_nqueens_count_v2.c)	Quiet / near-idle (only a counter is written; no solutions stored)	Classic constraint-satisfaction benchmark
kernel_nqueens_enum_v2	KERNEL / D11	SEQUENTIAL-GROW	under-testing	KERNEL family (VISIBLE) source (a) materialise output: the SAME search as the count control but STORES every solution -> bulk append (-> kernel/D11_visible_backtracking/kernel_nqueens_enum_v2.c)	Visible (whole solution set appended; the return flips quiet->visible)	Enumerate all placements; the count-vs-store contrast
kernel_brackets_enum_v2	KERNEL / D11	SEQUENTIAL-GROW	under-testing	KERNEL family (VISIBLE) source (a) materialise output: enumerate all balanced-parenthesis strings, append each (-> kernel/D11_visible_backtracking/kernel_brackets_enum_v2.c)	Visible (Catalan(n) strings materialised)	Combinatorial generation; grammar / parser test corpora
kernel_maze_backtrack_v2	KERNEL / D11	SCATTER	under-testing	KERNEL family (VISIBLE) source (b) large working state: DFS solve marks a large visited/parent grid across the search (-> kernel/D11_visible_backtracking/kernel_maze_backtrack_v2.c)	Visible (large grid marked/unmarked ; ~58% of cells touched per solve)	Maze / route solving; robot path planning

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_graph_coloring_v2	KERNEL / D11	SCATTER	under-testing	KERNEL family (VISIBLE) source (b) large working state: CSP m-colouring, forward-checking prunes/restores a colour+domain table over a big graph; default m is near the chromatic threshold so it GENUINELY backtracks (-> kernel/D11_visible_backtracking/kernel_graph_coloring_v2.c)	Visible (colour+domain prune/RESTORE churn; the restore is the backtrack signature vs label_prop; best conflict-free partial under a budget)	Register allocation, scheduling, frequency assignment
kernel_bnb_tsp_v2	KERNEL / D11	FRONTIER-C HURN	under-testing	KERNEL family (VISIBLE) source (c) frontier: best-first branch-and-bound, explicit priority-queue of partial tours (-> kernel/D11_visible_backtracking/kernel_bnb_tsp_v2.c)	Visible (explicit best-first frontier churned; millions of push/pop)	Routing, VLSI, operations research
kernel_bnb_knapsack_v2	KERNEL / D11	FRONTIER-C HURN	under-testing	KERNEL family (VISIBLE) source (c) frontier: best-first B&B over include/exclude subsets; a strongly-correlated instance keeps a large live frontier (-> kernel/D11_visible_backtracking/kernel_bnb_knapsack_v2.c)	Visible (subset-node frontier heap; optimum cross-checks D10 DP knapsack)	Budget / resource allocation, cutting-stock
Sudoku solver	covered / D11	--	covered	covered by kernel_nqueens_count_v2 (same quiet place/undo backtracking over a tiny grid; scalar / near-idle writes)	same quiet place/undo	Constraint-propagation solvers / puzzles
DPLL / CDCL SAT	CPU/IDLE / D11	--	candidate	CPU/IDLE (candidate): unit-propagate, decide, learn clauses, backtrack	Quiet-ish (clause DB reads, learned-clause writes)	Hardware/chip verification, planning (MiniSat / Z3)
Branch-and-bound MILP	CPU/IDLE / D11	--	candidate	CPU/IDLE (candidate): LP-relaxation bound, branch, prune	Visible-ish (frontier + LP tableaux)	Logistics, scheduling, optimisation (Gurobi / CPLEX)

D12 — Graphical Models [Visible]

Berkeley+6. Maps to: KERNEL. Example: HMM, Kalman filter, LDPC belief propagation, loopy BP, Gibbs sampling. Probability ops over a graph; writes belief/message tables (matrix-like).

Target 4-5 workloads — have 5.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_hmm_v2	KERNEL / D12	WORKING-SET	under-testing	KERNEL family: scaled HMM forward, trellis fill (-> kernel/D12_visible_graphical_models/kernel_hmm_v2.c)	Visible (column-fill front + dense matvec; normalise d-probability content)	Speech recognition, gene finding, time-series

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_beliefprop_v2	KERNEL / D12	WORKING-S ET	under- testing	KERNEL family: loopy sum-product belief propagation on a grid MRF (-> kernel/D12_visible_graphical_models/kernel_beliefprop_v2.c)	Visible (iterated message arrays per grid cell)	Stereo vision, image denoising, MRF / CRF
kernel_kalman_v2	KERNEL / D12	WORKING-S ET	under- testing	KERNEL family: ensemble of Kalman filters, dense covariance updates (-> kernel/D12_visible_graphical_models/kernel_kalman_v2.c)	Visible (many small d*d covariance matrices rewritten per step)	GPS/INS navigation, object tracking, sensor fusion
kernel_gibbs_v2	KERNEL / D12	WORKING-S ET	under- testing	KERNEL family: Gibbs sampling on a Potts/Ising grid (-> kernel/D12_visible_graphical_models/kernel_gibbs_v2.c)	Visible (stochastic per-cell resample sweep of the grid)	Bayesian inference, topic models (LDA)
kernel_ldpc_v2	KERNEL / D12	WORKING-S ET	under- testing	KERNEL family: LDPC min-sum decoder, message passing on a Tanner graph (-> kernel/D12_visible_graphical_models/kernel_ldpc_v2.c)	Visible (bipartite edge-message arrays iterated)	5G / WiFi / SSD / satellite error correction

D13 — Finite State Machines [Quiet + Visible]

Berkeley+6. Maps to: recognise=quiet; emit output=visible. Example: regex/DFA match, JSON parse, lexer, NFA->DFA construction, Aho-Corasick, escape/transcode transducer.

Read a stream, transition through states via table lookup. QUIET when it only RECOGNISES (stream read + tiny state write -- the classic invisible FSM). VISIBLE when it EMITS a large output: a token stream (lexer), a transition TABLE built by subset construction (dfa_build), an automaton + match list (aho_corasick), or an output stream ~ input size (transducer).

Target 4-5 workloads — have 7.

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
app_json_parse_v2	APP / D13	--	exists	APP family: streaming JSON parse (the canonical quiet FSM)	Quiet (read + branch)	Every REST / JSON API; config parsing
kernel_dfa_match_v2	IDLE / D13	IDLE	under- testing	IDLE family (QUIET control): table-driven DFA recogniser scans a read-only stream, writes only a state word + match counter (-> kernel/D13_visible_finite_state_machines/kernel_dfa_match_v2.c)	Quiet / near-idle (stream READ + scalar; the invisible baseline)	grep, input validation, log processing
kernel_lexer_v2	KERNEL / D13	SEQUENTIAL -GROW	under- testing	KERNEL family (VISIBLE) emit output: character-class FSM emits one token record per lexeme into a large token array (-> kernel/D13_visible_finite_state_machines/kernel_lexer_v2.c)	Visible (token-array append; the tokens tile the input)	Every compiler / interpreter front-end

Workload / Algorithm	Family / Dwarf	Predicted signal	Status	Mechanism / points-to	Memory signature	Used in (real world)
kernel_dfa_build_v2	KERNEL / D13	SEQUENTIAL -GROW	under- testing	KERNEL family (VISIBLE) build the machine: NFA->DFA subset construction writes a dense transition table ($\sim 2^{(K-1)}$ states) (-> kernel/D13_visible_finite_state_machines/kernel_dfa_build_v2.c)	Visible (dense transition-table construction; the inverse of running a DFA)	regex compilation; lexer generators (flex); protocol codegen
kernel_aho_corasick_v2	KERNEL / D13	SEQUENTIAL -GROW	under- testing	KERNEL family (VISIBLE) build + match list: build goto/fail automaton over many patterns, scan text appending every match position (-> kernel/D13_visible_finite_state_machines/kernel_aho_corasick_v2.c)	Visible (automaton build + match-list append)	Multi-pattern scan: log processing, intrusion detection (Snort), bio sequence search
kernel_fsm_transduce_v2	KERNEL / D13	SEQUENTIAL -GROW	under- testing	KERNEL family (VISIBLE) output stream: Mealy escape/framing transducer emits an output stream ~ input size (-> kernel/D13_visible_finite_state_machines/kernel_fsm_transduce_v2.c)	Visible (output stream ~ input size; benign reversible framing, not crypto)	Serialisers, protocol framers, escaping / transcoding
HTTP / protocol parser	covered / D13	--	covered	covered by kernel_dfa_match_v2 (byte-by-byte protocol recogniser = same quiet stream-scan + tiny parse-state writes)	same quiet stream-scan	Web servers (nginx), TCP/IP stacks, deep-packet inspection
cpu_branch_random_v2	CPU / D13	--	exists	CPU family (loose): data-dependent random branches	Quiet	Branch-predictor control

Sources

[A View from Berkeley \(tech report\)](#)

[The 13 Motifs of Parallel Programming](#)

[Reprising the 13 Dwarfs of OpenCL \(HPCwire\)](#)