1 Interface overview

HTTPS with mandatory mutual TLS and JSON documents (bridge calls carry the target's media types). Management services need an identity token (`Bearer IDENTITY-TOKEN//<token>`) bound to the client certificate; bridges need `Bearer TRANSLATION-BRIDGE-TOKEN//<bridgeId>`. Errors contain errorMessage, errorCode, origin and timestamp. Request bodies are limited to 1 MiB.

1.1 HTTPS interface operations

Method	Path	Access
`POST`	`/testtranslation/interface-bridge/check-targets`	identity
`POST`	`/testtranslation/interface-bridge/initialize-bridge`	identity
`DELETE`	`/testtranslation/interface-bridge/abort-bridge/{bridgeId}`	identity
`POST`	`/testtranslation/data-model/init-translation`	identity
`GET`	`/testtranslation/data-model/get-translation-result/{translationId}`	identity
`DELETE`	`/testtranslation/data-model/abort-translation/{translationId}`	identity
any	`/testtranslation/bridge/{bridgeId}/{operationpath}`	bridge token
`GET`	`/testtranslation/monitor/echo`	certificate
`GET`	`/testtranslation/general/mgmt/get-config`	management
`POST`	`/testtranslation/general/mgmt/logs`	management

1.2 Bridge responses

Status codes of the target are passed through. 401: missing or wrong bridge token; 403: method or path outside the negotiated operation; 404: unknown or ended bridge; 502: target unreachable or translation failed.

1.3 Important delimitations

TestTranslation is a test application system for the TranslationManager, not a production translator.

- One bridge kind: `generic_https` to `generic_https`, one negotiated operation per bridge; targets with `CERT_AUTH` or `NONE` policies (authorization tokens for token-protected targets are not presented).
- Data models `simpleJson` and `senml` only; translations are synchronous (a task is `DONE` or `ERROR` when `init-translation` returns).
- Bridges are kept in the system's JSON state; translation tasks only in memory (latest 1000).