translationBridgeManagement HTTP/TLS/JSON

Interface Design Description

Service ID: *"translationBridgeManagement"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `translationBridgeManagement` service of the TranslationManager system.

Contents

1 Documentation edition and implementation scope **3**

2 Overview **3**
2.1 Interface registration . . . 3

3 Service Operations **4**
3.1 operation discovery . . . 4
3.2 operation negotiation . . . 5
3.3 operation abort . . . 6
3.4 operation query . . . 6

4 Data Models **9**
4.1 struct Address . . . 9
4.2 struct DeviceResponse . . . 9
4.3 struct ErrorMessage . . . 9
4.4 struct Page . . . 9
4.5 struct ServiceDefinitionResponse . . . 9
4.6 struct ServiceInstanceInterfaceResponse . . . 10
4.7 struct ServiceInstanceResponse . . . 10
4.8 struct SystemResponse . . . 10
4.9 struct TranslationAbortMgmtResponse . . . 11
4.10 struct TranslationBridgeCandidate . . . 11
4.11 struct TranslationDataModelTranslationDataDescriptor . . . 11
4.12 struct TranslationDiscoveryMgmtRequest . . . 11
4.13 struct TranslationDiscoveryResponse . . . 12
4.14 struct TranslationInterfaceTranslationDataDescriptor . . . 12
4.15 struct TranslationNegotiationMgmtRequest . . . 12
4.16 struct TranslationNegotiationResponse . . . 12
4.17 struct TranslationQueryListResponse . . . 13
4.18 struct TranslationQueryRequest . . . 13
4.19 struct TranslationQueryResponse . . . 13
4.20 Primitives . . . 14

5 Go and Rust implementation variants **16**
5.1 Go implementation . . . 16
5.2 Rust implementation . . . 16

6 References **17**

7 Revision History **18**
7.1 Amendments . . . 18
7.2 Quality Assurance . . . 18

1 Documentation edition and implementation scope

This is the 5.3.0 documentation edition, dated 2026-11-09. It carries forward the system and service contracts from the retained 5.2.2 documentation and identifies the current primary implementation sources. The former `documentation/v5.2.2` folder is retained unchanged.

Document version 5.3.0 is distinct from executable, dependency, registered system/service and wire-contract versions. Values still defined by the source (including 5.2.2 artefact versions, 1.0.0 service versions and `SysMonitor-AMQP-IDD-5.2.2` payload identifiers) are preserved. This documentation update does not change runtime behaviour or establish a new implementation release. Historical verification statements describe the tests recorded in the inherited baseline; this revision validates document compilation and references.

2 Overview

This document describes the `translationBridgeManagement` service interface of the TranslationManager system, which provides management of translation bridges on behalf of consumers: discovery, negotiation, abort and query.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `translationBridgeManagement` service interface

This document provides the Interface Design Description IDD to the *translationBridgeManagement – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `translationBridgeManagement` service interface in detail. Both in terms of its operations (Section 3) and its information model (Section 4).

2.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https`, policy `CERT_AUTH`, access address `translation-manager`, port 8465 and base path `/translation/bridge/mgmt`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`discovery`	POST	`/discovery`
`negotiation`	POST	`/negotiation`
`abort`	DELETE	`/abort`
`query`	POST	`/query`

3 Service Operations

The interfaces of the `translationBridgeManagement` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `translationBridgeManagement` SD document, as well as input and output types.

All operations require the requester's identity, presented according to the provider's authentication policy: the client certificate (mutual TLS) and, with the `outsourced` policy, `Authorization: Bearer IDENTITY-TOKEN//<token>`; systems holding the Authentication secret key send `Bearer AUTHENTICATOR-KEY//<system>//<hash>`, and with the `declared` policy `Bearer SYSTEM//<system>` is sent. Request and response bodies are `application/json` unless stated otherwise. Errors are answered with an ErrorMessage body and the status codes `400 Bad Request` (invalid parameter), `401 Unauthorized` (missing or invalid identity), `403 Forbidden` (not permitted, e.g. by the management, authorization or blacklist filter), `404 Not Found`, `408 Request Timeout`, `423 Locked`, `500 Internal Server Error` and `503 Service Unavailable` (a system it depends on failed).

3.1 POST /translation/bridge/mgmt/discovery

Operation: discovery
Input: TranslationDiscoveryMgmtRequest
Output: TranslationDiscoveryResponse

Discovers translation candidates on behalf of the named consumer, with discovery flags.

A successful call returns `200 OK` with the output in the body.

```
POST /translation/bridge/mgmt/discovery HTTP/1.1
Host: translation-manager:8465
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "candidates": [
    {
      "instanceId": "TemperatureSensor|temperatureReading|1.0.0",
      "provider": {
        "name": "TemperatureSensor",
        "metadata": {
          "location": "hall-1"
        },
        "version": "1.0.0",
        "addresses": [
          {}
        ],
        "device": {
          "name": "Raspberry1",
          "metadata": {
            "location": "hall-1"
          },
          "addresses": [
            {}
          ],
          "createdAt": "2026-10-22T12:00:00Z",
          "updatedAt": "2026-10-22T12:00:00Z"
        },
        "createdAt": "2026-10-22T12:00:00Z",
        "updatedAt": "2026-10-22T12:00:00Z"
      },
      "serviceDefinition": {
        "name": "temperatureReading",
        "createdAt": "2026-10-22T12:00:00Z",
        "updatedAt": "2026-10-22T12:00:00Z"
      },
      "version": "1.0.0",
```

```
      "expiresAt": "2026-10-22T12:00:00Z",
      "metadata": {
        "unit": "celsius"
      },
      "interfaces": [
        {
          "templateName": "generic_https",
          "protocol": "https",
          "policy": "CERT_AUTH",
          "properties": {
            "accessAddresses": [
              "192.168.0.10"
            ],
            "accessPort": 8080,
            "basePath": "/temperature",
            "operations": {
              "read": {
                "method": "GET",
                "path": "/read"
              }
            }
          }
        }
      ],
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "consumer": "TemperatureDisplay",
  "operation": "FILTER",
  "interfaceTemplateNames": [
    "string"
  ],
  "inputDataModelId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "outputDataModelId": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}
```

Listing 1: An discovery invocation.

```
{
  "bridgeId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "candidates": [
    {
      "serviceInstanceId": "TemperatureSensor|temperatureReading|1.0.0",
      "interfaceTemplateName": "string"
    }
  ]
}
```

Listing 2: An discovery response.

3.2 POST /translation/bridge/mgmt/negotiation

Operation: negotiation
Input: TranslationNegotiationMgmtRequest
Output: TranslationNegotiationResponse

Builds a discovered bridge to the chosen target instance on behalf of its consumer.
A successful call returns `201 Created` with the output in the body.

```
POST /translation/bridge/mgmt/negotiation HTTP/1.1
Host: translation-manager:8465
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json
```

```
5
6  {
7    "bridgeId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
8    "targetInstanceId": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
9  }
```

Listing 3: An negotiation invocation.

```
1  {
2    "bridgeId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
3    "bridgeInterface": {
4      "templateName": "generic_https",
5      "protocol": "https",
6      "policy": "CERT_AUTH",
7      "properties": {
8        "accessAddresses": [
9          "192.168.0.10"
10       ],
11       "accessPort": 8080,
12       "basePath": "/temperature",
13       "operations": {
14         "read": {
15           "method": "GET",
16           "path": "/read"
17         }
18       }
19     }
20   },
21   "tokenExpiresAt": "2026-10-22T12:00:00Z",
22   "tokenUsageLimit": 1
23 }
```

Listing 4: An negotiation response.

3.3 DELETE /translation/bridge/mgmt/abort?ids=*{ids}*

Operation: **abort**
Input: **Array<String>**
Output: **TranslationAbortMgmtResponse**

Aborts the listed bridges; returns the result per bridge.
Query parameters: *ids* (List<String>, required). List values are repeated or comma-separated.
A successful call returns `200 OK` with the output in the body.

```
1  DELETE /translation/bridge/mgmt/abort?ids=<ids> HTTP/1.1
2  Host: translation-manager:8465
3  Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 5: An abort invocation.

```
1  {
2    "results": {}
3  }
```

Listing 6: An abort response.

3.4 POST /translation/bridge/mgmt/query

Operation: query
Input: TranslationQueryRequest
Output: TranslationQueryListResponse

Returns a page of bridges matching the filter.
A successful call returns `200 OK` with the output in the body.

```
POST /translation/bridge/mgmt/query HTTP/1.1
Host: translation-manager:8465
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "bridgeIds": [
    "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  ],
  "creators": [
    "string"
  ],
  "statuses": [
    "string"
  ],
  "consumers": [
    "TemperatureDisplay"
  ],
  "providers": [
    "TemperatureSensor"
  ],
  "serviceDefinitions": [
    "temperatureReading"
  ],
  "interfaceTranslators": [
    "string"
  ],
  "dataModelTranslators": [
    "string"
  ],
  "creationFrom": "2026-10-22T12:00:00Z",
  "creationTo": "2026-10-22T12:00:00Z",
  "alivesFrom": "2026-10-22T12:00:00Z",
  "alivesTo": "2026-10-22T12:00:00Z",
  "minUsage": 1,
  "maxUsage": 1
}
```

Listing 7: An query invocation.

```
{
  "entries": [
    {
      "bridgeId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "status": "SUCCESS",
      "usageReportCount": 1,
      "alivesAt": "2026-10-22T12:00:00Z",
      "message": "1 local result: TemperatureSensor",
      "consumer": "TemperatureDisplay",
      "provider": "TemperatureSensor",
      "serviceDefinition": "temperatureReading",
```

```
      "operation": "FILTER",
      "interfaceTranslator": "string",
      "interfaceTranslatorData": {
        "fromInterfaceTemplate": "string",
        "toInterfaceTemplate": "string",
        "token": "<token>"
      },
      "inputDataModelTranslator": "string",
      "inputDataModelTranslatorData": {
        "fromModelId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
        "toModelId": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
      },
      "outputDataModelTranslator": "string",
      "outputDataModelTranslatorData": {
        "fromModelId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
        "toModelId": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
      },
      "createdBy": "Sysop",
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```


Listing 8: An query response.

4 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 4.20, which are used to represent things like hashes, identifiers and texts.

4.1 struct Address

A network address with its type.

Object Field	Value Type	Description
"type"	String	Address type: `HOSTNAME`, `IPV4`, `IPV6` or `MAC`.
"address"	String	One network address (host name, IPv4, IPv6 or MAC address).

4.2 struct DeviceResponse

A registered device.

Object Field	Value Type	Description
"name"	String	Device name.
"metadata"	Object	Free-form metadata (JSON object).
"addresses"	Array<Address>	Network addresses with their types.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

4.3 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	Error text, if the event is an error.
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

4.4 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

4.5 struct ServiceDefinitionResponse

A service definition.

Object Field	Value Type	Description
"name"	String	Service definition name.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

4.6 struct ServiceInstanceInterfaceResponse

One interface of a service instance.

Object Field	Value Type	Description
"templateName"	String	Name of the interface template, snake_case (e.g. `generic_https`).
"protocol"	String	Protocol of the interface, e.g. `http`, `https`, `mqtt`, `mqtts`.
"policy"	String	Security policy of the interface: `NONE`, `CERT_AUTH` or one of the token policies.
"properties"	Object	Interface properties defined by the template, e.g. `accessAddresses`, `accessPort`, `basePath`, `operations`.

4.7 struct ServiceInstanceResponse

A registered service instance.

Object Field	Value Type	Description
"instanceId"	String	Service instance identifier `<System>|<serviceDefinition>|<version>`, or policy instance identifier.
"provider"	SystemResponse	The provider system.
"serviceDefinition"	ServiceDefinitionResponse	The service definition.
"version"	Version	Version of the service instance.
"expiresAt"	DateTime	UTC expiry time; no value means no expiry.
"metadata"	Object	Free-form metadata (JSON object).
"interfaces"	Array<ServiceInstanceInterfaceResponse>	Service interfaces offered by the instance.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

4.8 struct SystemResponse

A registered system.

Object Field	Value Type	Description
"name"	String	System name.
"metadata"	Object	Free-form metadata (JSON object).
"version"	Version	Version of the system.
"addresses"	Array<Address>	Network addresses with their types.
"device"	DeviceResponse	The device hosting the system, if registered.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

4.9 struct TranslationAbortMgmtResponse

Results of aborting bridges.

Object Field	Value Type	Description
"results"	Object<Boolean>	Per bridge identifier, whether it was aborted.

4.10 struct TranslationBridgeCandidate

A candidate reachable through translation.

Object Field	Value Type	Description
"serviceInstanceId"	String	Service instance identifier `<System>|<serviceDefinition>|<version>`.
"interfaceTemplate Name"	String	Interface template of the candidate the bridge would translate to.

4.11 struct TranslationDataModelTranslationDataDescriptor

Settings of a data-model translation.

Object Field	Value Type	Description
"fromModelId"	String	Source data model.
"toModelId"	String	Target data model.
"interfaceProperties"	Object	Interface properties of the translator.
"configurationSettings"	Object	Configuration passed to the translator.

4.12 struct TranslationDiscoveryMgmtRequest

Discovery of translation bridges on behalf of a consumer.

Object Field	Value Type	Description
"candidates"	Array<ServiceInstanceResponse>	Candidate service instances (from service discovery).
"consumer"	String	Consumer on whose behalf the bridge is discovered.
"operation"	String	QoS operation: `FILTER` or `SORT`.
"interfaceTemplate Names"	Array<String>	Accepted interface templates, e.g. `generic_https`.
"inputDataModelId"	String	Data model of the operation input expected by the consumer.
"outputDataModelId"	String	Data model of the operation output expected by the consumer.
"flags"	Object<Boolean>	Discovery flags, e.g. `CANDIDATES_AUTH_CHECK`, `CONSUMER_BLACKLIST_CHECK`.

4.13 struct TranslationDiscoveryResponse

Candidates reachable through a translation bridge.

Object Field	Value Type	Description
"bridgeId"	String	Identifier (UUID) of the translation bridge.
"candidates"	Array<TranslationBridgeCandidate>	Store entries to create.

4.14 struct TranslationInterfaceTranslationDataDescriptor

Settings of an interface translation.

Object Field	Value Type	Description
"fromInterfaceTemplate"	String	Interface template of the consumer side.
"toInterfaceTemplate"	String	Interface template of the provider side.
"token"	String	The token.
"interfaceProperties"	Object	Interface properties of the translator.
"configurationSettings"	Object	Configuration passed to the translator.

4.15 struct TranslationNegotiationMgmtRequest

Builds a discovered bridge on behalf of a consumer.

Object Field	Value Type	Description
"bridgeId"	String	Identifier (UUID) of the translation bridge.
"targetInstanceId"	String	Service instance chosen from the discovery candidates.

4.16 struct TranslationNegotiationResponse

The established bridge.

Object Field	Value Type	Description
"bridgeId"	String	Identifier (UUID) of the translation bridge.
"bridgeInterface"	ServiceInstanceInterfaceResponse	Interface of the bridge the consumer calls instead of the provider.
"tokenExpiresAt"	DateTime	Expiry of the bridge token.
"tokenUsageLimit"	Number	Number of uses allowed with the bridge token.

4.17 struct TranslationQueryListResponse

List of translation bridges.

Object Field	Value Type	Description
"entries"	Array<TranslationQueryResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

4.18 struct TranslationQueryRequest

Paged filter for translation bridges.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"bridgeIds"	Array<String>	Bridge identifiers to match.
"creators"	Array<String>	Systems that created the bridges.
"statuses"	Array<String>	Bridge statuses to match.
"consumers"	Array<String>	Consumer systems to match.
"providers"	Array<String>	Provider system names to match.
"serviceDefinitions"	Array<String>	Service definition names to match.
"interfaceTranslators"	Array<String>	Interface translator systems to match.
"dataModelTranslators"	Array<String>	Data model translator systems to match.
"creationFrom"	DateTime	Lower bound of the creation time.
"creationTo"	DateTime	Upper bound of the creation time.
"alivesFrom"	DateTime	Lower bound of the bridge expiry.
"alivesTo"	DateTime	Upper bound of the bridge expiry.
"minUsage"	Number	Minimum number of usage reports.
"maxUsage"	Number	Maximum number of usage reports.

4.19 struct TranslationQueryResponse

A translation bridge.

Object Field	Value Type	Description
"bridgeId"	String	Identifier (UUID) of the translation bridge.
"status"	String	Bridge status: `NEW`, `DISCOVERED`, `PENDING`, `INITIALIZED`, `USED`, `ABORTED`, `CLOSED` or `ERROR`.
"usageReportCount"	Number	Number of usage reports received for the bridge.
"alivesAt"	DateTime	Expiry of the bridge.
"message"	String	Text of the log entry or status message of the job.
"consumer"	String	Name of the consumer system.
"provider"	String	Name of the provider system.
"serviceDefinition"	String	Service definition name.
"operation"	String	QoS operation: `FILTER` or `SORT`.
"interfaceTranslator"	String	System translating between the interfaces.
"interfaceTranslatorData"	TranslationInterfaceTranslationData Descriptor	Settings of the interface translation.
"inputDataModel Translator"	String	System translating the input data model.
"inputDataModel TranslatorData"	TranslationDataModelTranslationData Descriptor	Settings of the input data-model translation.
"outputDataModel Translator"	String	System translating the output data model.
"outputDataModel TranslatorData"	TranslationDataModelTranslationData Descriptor	Settings of the output data-model translation.
"createdBy"	String	Name of the system that created the record.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

4.20 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.
Version	JSON String, semantic version `major.minor.patch`.

5 Go and Rust implementation variants

5.1 Go implementation

Primary system folder: `Eclipse-Arrowhead-go/ah5-TranslationManager-go`.

The system owns its Go module, launcher and build configuration. Use the per-system `Makefile` and `go.mod`; the containing Go tree is the build source, not a historical Arrowhead copy. Ordinary native roles use independent identities and JSON snapshot state rather than the Java database. Do not assume Java SQL migration, clustering or identical transaction/retry semantics. The registry has its own configuration and optional native AMQP monitor; other roles must be checked against their own registrations.

Listening port. Built-in default 127.0.0.1:8465 (Arrowhead default). The shipped config.json, compose.yaml and Dockerfile use the same port on all interfaces ("listen": "0.0.0.0:8465"; 8540–8555 layout before 2026-11-09). Override with "listen" in the configuration file, SERVER_PORT=N or -server.port N; the port overrides keep the configured host.

Native behavior and outstanding work. Port of the Java TranslatorBridgeEngine (2026-10-24): registry discovery of interface translators (interfaceBridgeManagement), data model translators (dataModelTranslation) and factories (dataModelTranslatorFactoryControl); check-targets / initialize-bridge / abort-bridge; Java bridge statuses, transitions, reports, query and 8-hour cleanup; consumer and management APIs. Translators with TOKEN_AUTH interfaceBridgeManagement policies are not selected; custom translator configuration (TODO in Java) not sent; first-match matchmaking. These are the boundaries recorded by the native compatibility document; later implementation changes still require direct qualification. Native design/route evidence: `Eclipse-Arrowhead-go/ah5-TranslationManager-go/documentation/TranslationManager`.

For this Java interface, select only a native transport and operation explicitly implemented and advertised by that port. A matching method/path does not establish DTO, error, authorization, retry or persistence equivalence. Java MQTT/AMQP bindings are not automatically provided by a Go or Rust role. Differential contract and security checks remain necessary before substitution.

5.2 Rust implementation

Primary system folder: `Eclipse-Arrowhead-rust/ah5-TranslationManager-rust`.

The per-system entry point is declared as a binary of `arrowhead-support-rust` in `ah5-support-runtime-rust/Cargo.toml`. Build from the primary Rust workspace with the applicable package/binary selection. Documentation links can resolve into the shared core/support catalogue. Independent process identity and state remain required.

The ordinary native profile uses Tokio/Axum and rustls with peer-identity checks and independent locked JSON state. Network effects are not distributed database transactions. The precise trust, CRL reload and persistence guarantees are those of the native profile, not the Java implementation.

Listening port. Default 127.0.0.1:8465 (Arrowhead default, role translationmanager). Override with "listen": "host:port" in the configuration, SERVER_PORT=N or –server.port N; the port overrides keep the configured host.

Native behavior and outstanding work. Durable bridge lifecycle through pinned HTTPS InterfaceTranslator adapter. Java translator chaining/native conversion/discovery; absent adapter returns503; uncertain effects require reconciliation. These are the boundaries recorded by the native compatibility document; later implementation changes still require direct qualification. Native design/route evidence: `Eclipse-Arrowhead-rust/ah5-support-runtime-rust/documentation/TranslationManager`.

For this Java interface, select only a native transport and operation explicitly implemented and advertised by that port. A matching method/path does not establish DTO, error, authorization, retry or persistence equivalence. Java MQTT/AMQP bindings are not automatically provided by a Go or Rust role. Differential contract and security checks remain necessary before substitution.

6 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “translationBridgeManagement – Service Description (TranslationManager),” Eclipse Arrowhead, SD 5.3.0, 2026, translationManager-v5.3.0-translationBridgeManagement-SD.pdf.

7 Revision History

7.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)
3	2026-11-09	5.3.0	New documentation edition; primary-source references and Go/Rust implementation scope; 5.2.2 retained.	Documentation maintenance

7.2 Quality Assurance

No.	Date	Version	Approved by
1		5.3.0	