identityManagement HTTP/TLS/JSON

Interface Design Description

Service ID: *"identityManagement"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `identityManagement` service of the Authentication system.

Contents

1 Documentation edition and implementation scope **3**

2 Overview **3**
2.1 Interface registration . . . 3

3 Service Operations **4**
3.1 operation identity-mgmt-create . . . 4
3.2 operation identity-mgmt-update . . . 5
3.3 operation identity-mgmt-remove . . . 5
3.4 operation identity-mgmt-query . . . 5
3.5 operation identity-mgmt-session-close . . . 6
3.6 operation identity-mgmt-session-query . . . 7

4 Data Models **8**
4.1 struct ErrorMessage . . . 8
4.2 struct IdentityListMgmtCreateRequest . . . 8
4.3 struct IdentityListMgmtResponse . . . 8
4.4 struct IdentityListMgmtUpdateRequest . . . 8
4.5 struct IdentityMgmtRequest . . . 8
4.6 struct IdentityMgmtResponse . . . 8
4.7 struct IdentityQueryRequest . . . 9
4.8 struct IdentitySessionListMgmtResponse . . . 9
4.9 struct IdentitySessionQueryRequest . . . 9
4.10 struct IdentitySessionResponse . . . 9
4.11 struct Page . . . 10
4.12 Primitives . . . 10

5 Go and Rust implementation variants **11**
5.1 Go implementation . . . 11
5.2 Rust implementation . . . 11

6 References **11**

7 Revision History **12**
7.1 Amendments . . . 12
7.2 Quality Assurance . . . 12

1 Documentation edition and implementation scope

This is the 5.3.0 documentation edition, dated 2026-11-09. It carries forward the system and service contracts from the retained 5.2.2 documentation and identifies the current primary implementation sources. The former `documentation/v5.2.2` folder is retained unchanged.

Document version 5.3.0 is distinct from executable, dependency, registered system/service and wire-contract versions. Values still defined by the source (including 5.2.2 artefact versions, 1.0.0 service versions and `SysMonitor-AMQP-IDD-5.2.2` payload identifiers) are preserved. This documentation update does not change runtime behaviour or establish a new implementation release. Historical verification statements describe the tests recorded in the inherited baseline; this revision validates document compilation and references.

2 Overview

This document describes the `identityManagement` service interface of the Authentication system, which provides operator management of the identities known to Authentication (systems, their credentials and sysop flag) and of their active sessions.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `identityManagement` service interface

This document provides the Interface Design Description IDD to the *identityManagement – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `identityManagement` service interface in detail. Both in terms of its operations (Section 3) and its information model (Section 4).

2.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https` (`generic_http` when TLS is disabled), access port 8444 and base path `/authentication/mgmt`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`identity-mgmt-create`	POST	`/identities`
`identity-mgmt-update`	PUT	`/identities`
`identity-mgmt-remove`	DELETE	`/identities`
`identity-mgmt-query`	POST	`/identities/query`
`identity-mgmt-session-close`	DELETE	`/sessions`
`identity-mgmt-session-query`	POST	`/sessions`

3 Service Operations

The interfaces of the `identityManagement` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `identityManagement` SD document, as well as input and output types.

All operations require the requester's identity, presented according to the provider's authentication policy: the client certificate (mutual TLS) and, with the `outsourced` policy, `Authorization: Bearer IDENTITY-TOKEN//<token>`; systems holding the Authentication secret key send `Bearer AUTHENTICATOR-KEY//<system>//<hash>`, and with the `declared` policy `Bearer SYSTEM//<system>` is sent. Request and response bodies are `application/json`. Errors are answered with an ErrorMessage body and the status codes `400 Bad Request` (invalid parameter), `401 Unauthorized` (missing or invalid identity), `403 Forbidden` (not permitted, e.g. by the management or blacklist filter), `404 Not Found`, `408 Request Timeout`, `423 Locked`, `500 Internal Server Error` and `503 Service Unavailable` (a system it depends on failed).

3.1 POST /authentication/mgmt/identities

Operation: identity-mgmt-create
Input: IdentityListMgmtCreateRequest
Output: IdentityListMgmtResponse

Creates identities with credentials of the given authentication method.

A successful call returns `200 OK` with the output in the body.

```
POST /authentication/mgmt/identities HTTP/1.1
Host: authentication:8444
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "authenticationMethod": "PASSWORD",
  "identities": [
    {
      "systemName": "TemperatureDisplay",
      "credentials": {
        "password": "<password>"
      },
      "sysop": false
    }
  ]
}
```

Listing 1: An identity-mgmt-create invocation.

```
{
  "identities": [
    {
      "systemName": "TemperatureSensor",
      "authenticationMethod": "PASSWORD",
      "sysop": false,
      "createdBy": "Sysop",
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedBy": "Sysop",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 2: An identity-mgmt-create response.

3.2 PUT /authentication/mgmt/identities

Operation: identity-mgmt-update
Input: IdentityListMgmtUpdateRequest
Output: IdentityListMgmtResponse

Updates credentials and sysop flag of identities.
A successful call returns `200 OK` with the output in the body.

```
PUT /authentication/mgmt/identities HTTP/1.1
Host: authentication:8444
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "identities": [
    {
      "systemName": "TemperatureDisplay",
      "credentials": {
        "password": "<password>"
      },
      "sysop": false
    }
  ]
}
```

Listing 3: An identity-mgmt-update invocation.

```
{
  "identities": [
    {
      "systemName": "TemperatureSensor",
      "authenticationMethod": "PASSWORD",
      "sysop": false,
      "createdBy": "Sysop",
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedBy": "Sysop",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 4: An identity-mgmt-update response.

3.3 DELETE /authentication/mgmt/identities?names=*{names}*

Operation: identity-mgmt-remove
Input: Array<String>

Removes identities by system name, closing their sessions.
Query parameters: *names* (List<String>, required). List values are repeated or comma-separated.
A successful call returns `200 OK`.

```
DELETE /authentication/mgmt/identities?names=<names> HTTP/1.1
Host: authentication:8444
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 5: An identity-mgmt-remove invocation.

3.4 POST /authentication/mgmt/identities/query

Operation: identity-mgmt-query
Input: IdentityQueryRequest
Output: IdentityListMgmtResponse

Returns a page of identities matching the filter.
A successful call returns `200 OK` with the output in the body.

```
POST /authentication/mgmt/identities/query HTTP/1.1
Host: authentication:8444
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "namePart": "Temp",
  "isSysop": false,
  "createdBy": "Sysop",
  "creationFrom": "2026-10-22T12:00:00Z",
  "creationTo": "2026-10-22T12:00:00Z",
  "hasSession": true
}
```

Listing 6: An identity-mgmt-query invocation.

```
{
  "identities": [
    {
      "systemName": "TemperatureSensor",
      "authenticationMethod": "PASSWORD",
      "sysop": false,
      "createdBy": "Sysop",
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedBy": "Sysop",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 7: An identity-mgmt-query response.

3.5 DELETE /authentication/mgmt/sessions?names=*{names}*

Operation: identity-mgmt-session-close
Input: Array<String>

Closes the sessions of the named systems.
Query parameters: *names* (List<String>, required). List values are repeated or comma-separated.
A successful call returns `200 OK`.

```
DELETE /authentication/mgmt/sessions?names=<names> HTTP/1.1
Host: authentication:8444
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 8: An identity-mgmt-session-close invocation.

3.6 POST /authentication/mgmt/sessions

Operation: identity-mgmt-session-query
Input: IdentitySessionQueryRequest
Output: IdentitySessionListMgmtResponse

Returns a page of active sessions.

A successful call returns `200 OK` with the output in the body.

```
POST /authentication/mgmt/sessions HTTP/1.1
Host: authentication:8444
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "namePart": "Temp",
  "loginFrom": "2026-10-22T12:00:00Z",
  "loginTo": "2026-10-22T12:00:00Z"
}
```

Listing 9: An identity-mgmt-session-query invocation.

```
{
  "sessions": [
    {
      "systemName": "TemperatureSensor",
      "loginTime": "2026-10-22T12:00:00Z",
      "expirationTime": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 10: An identity-mgmt-session-query response.

4 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 4.12, which are used to represent things like hashes, identifiers and texts.

4.1 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

4.2 struct IdentityListMgmtCreateRequest

Identities to create.

Object Field	Value Type	Description
"authenticationMethod"	String	Authentication method of the identities; `PASSWORD` is the only implemented method.
"identities"	Array<IdentityMgmtRequest>	Identities to create, update or return.

4.3 struct IdentityListMgmtResponse

List of identities.

Object Field	Value Type	Description
"identities"	Array<IdentityMgmtResponse>	Identities to create, update or return.
"count"	Number	Total number of matching records (all pages).

4.4 struct IdentityListMgmtUpdateRequest

Identities to update.

Object Field	Value Type	Description
"identities"	Array<IdentityMgmtRequest>	Identities to create, update or return.

4.5 struct IdentityMgmtRequest

One identity.

Object Field	Value Type	Description
"systemName"	String	Name of the system, PascalCase (e.g. `TemperatureSensor`).
"credentials"	Object<String>	Credentials of the authentication method, for `PASSWORD` the key `password`.
"sysop"	Boolean	Whether the identity is a system operator (default false).

4.6 struct IdentityMgmtResponse

A stored identity (without credentials).

Object Field	Value Type	Description
"systemName"	String	Name of the system, PascalCase (e.g. `TemperatureSensor`).
"authenticationMethod"	String	Authentication method of the identities; `PASSWORD` is the only implemented method.
"sysop"	Boolean	Whether the identity is a system operator (bypasses the management filters).
"createdBy"	String	Name of the system that created the record.
"createdAt"	DateTime	UTC time of creation.
"updatedBy"	String	Name of the system that changed the record last.
"updatedAt"	DateTime	UTC time of the last change.

4.7 struct IdentityQueryRequest

Paged filter for identities.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"namePart"	String	Part of the system name to match.
"isSysop"	Boolean	Only sysop (true) or non-sysop (false) identities.
"createdBy"	String	Name of the system that created the record.
"creationFrom"	DateTime	Lower bound of the creation time.
"creationTo"	DateTime	Upper bound of the creation time.
"hasSession"	Boolean	Only identities with (true) or without (false) an active session.

4.8 struct IdentitySessionListMgmtResponse

List of active sessions.

Object Field	Value Type	Description
"sessions"	Array<IdentitySessionResponse>	Active sessions.
"count"	Number	Total number of matching records (all pages).

4.9 struct IdentitySessionQueryRequest

Paged filter for active sessions.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"namePart"	String	Part of the system name to match.
"loginFrom"	DateTime	Lower bound of the login time.
"loginTo"	DateTime	Upper bound of the login time.

4.10 struct IdentitySessionResponse

An active session.

Object Field	Value Type	Description
"systemName"	String	Name of the system, PascalCase (e.g. `TemperatureSensor`).
"loginTime"	DateTime	UTC time of the login.
"expirationTime"	DateTime	UTC time when the identity token expires.

4.11 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

4.12 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

5 Go and Rust implementation variants

5.1 Go implementation

Primary system folder: `Eclipse-Arrowhead-go/ah5-core-go/authentication`.

The system owns its Go module, launcher and build configuration. Use the per-system `Makefile` and `go.mod`; the containing Go tree is the build source, not a historical Arrowhead copy. Ordinary native roles use independent identities and JSON snapshot state rather than the Java database. Do not assume Java SQL migration, clustering or identical transaction/retry semantics. The registry has its own configuration and optional native AMQP monitor; other roles must be checked against their own registrations.

Listening port. Built-in default 127.0.0.1:8444 (Arrowhead default). The shipped config.json sets "listen": "0.0.0.0:8444". Override with "listen" in the configuration file, SERVER_PORT=N or -server.port N; the port overrides keep the configured host. Native design/route evidence: `Eclipse-Arrowhead-go/ah5-core-go/authentication/documentation`.

For this Java interface, select only a native transport and operation explicitly implemented and advertised by that port. A matching method/path does not establish DTO, error, authorization, retry or persistence equivalence. Java MQTT/AMQP bindings are not automatically provided by a Go or Rust role. Differential contract and security checks remain necessary before substitution.

5.2 Rust implementation

Primary system folder: `Eclipse-Arrowhead-rust/ah5-core-rust/authentication`.

The per-system entry point is built by the `arrowhead-core-rust` crate. Build from the primary Rust workspace with the applicable package/binary selection. Documentation links can resolve into the shared core/support catalogue. Independent process identity and state remain required.

The ordinary native profile uses Tokio/Axum and rustls with peer-identity checks and independent locked JSON state. Network effects are not distributed database transactions. The precise trust, CRL reload and persistence guarantees are those of the native profile, not the Java implementation.

Native design/route evidence: `Eclipse-Arrowhead-rust/ah5-core-rust/documentation/Authentication`.

For this Java interface, select only a native transport and operation explicitly implemented and advertised by that port. A matching method/path does not establish DTO, error, authorization, retry or persistence equivalence. Java MQTT/AMQP bindings are not automatically provided by a Go or Rust role. Differential contract and security checks remain necessary before substitution.

6 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “identityManagement – Service Description (Authentication),” Eclipse Arrowhead, SD 5.3.0, 2026, authentication-v5.3.0-identityManagement-SD.pdf.

7 Revision History

7.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-11-09	5.3.0	New documentation edition; primary-source references and Go/Rust implementation scope; 5.2.2 retained.	Documentation maintenance

7.2 Quality Assurance

No.	Date	Version	Approved by
1		5.3.0	