translationBridgeManagement MQTT/TLS/JSON

Interface Design Description

Service ID: *"translationBridgeManagement"*

Abstract
This document describes the MQTT protocol with TLS payload security and JSON payload encoding variant of the `translationBridgeManagement` service of the TranslationManager system.

Contents

1 Overview **3**

2 Service Operations **4**
2.1 operation discovery . . . 4
2.2 operation negotiation . . . 5
2.3 operation abort . . . 6
2.4 operation query . . . 6

3 Data Models **8**
3.1 struct MqttRequestTemplate . . . 8
3.2 struct MqttResponseTemplate . . . 8
3.3 struct ErrorMessage . . . 8
3.4 struct Address . . . 8
3.5 struct DeviceResponse . . . 8
3.6 struct Page . . . 9
3.7 struct ServiceDefinitionResponse . . . 9
3.8 struct ServiceInstanceInterfaceResponse . . . 9
3.9 struct ServiceInstanceResponse . . . 9
3.10 struct SystemResponse . . . 10
3.11 struct TranslationAbortMgmtResponse . . . 10
3.12 struct TranslationBridgeCandidate . . . 10
3.13 struct TranslationDataModelTranslationDataDescriptor . . . 10
3.14 struct TranslationDiscoveryMgmtRequest . . . 11
3.15 struct TranslationDiscoveryResponse . . . 11
3.16 struct TranslationInterfaceTranslationDataDescriptor . . . 11
3.17 struct TranslationNegotiationMgmtRequest . . . 11
3.18 struct TranslationNegotiationResponse . . . 12
3.19 struct TranslationQueryListResponse . . . 12
3.20 struct TranslationQueryRequest . . . 12
3.21 struct TranslationQueryResponse . . . 12
3.22 Primitives . . . 13

4 References **14**

5 Revision History **15**
5.1 Amendments . . . 15
5.2 Quality Assurance . . . 15

1 Overview

This document describes the `translationBridgeManagement` service interface of the TranslationManager system over MQTT, which provides management of translation bridges on behalf of consumers: discovery, negotiation, abort and query.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	MQTT	3.1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `translationBridgeManagement` service interface

This document provides the Interface Design Description IDD to the *translationBridgeManagement – Service Description* document [5]. The operations, their semantics and the data models are the same as in the HTTP/TLS/JSON IDD [6]; this document specifies the MQTT binding.

The MQTT interface is offered only when the system runs with `mqtt.api.enabled=true`; it is then registered with the interface template `generic_mqtts` (`generic_mqtt` without TLS), the broker address and port (`mqtt.broker.address`, `mqtt.broker.port`) and the base topic `arrowhead/translation/bridge/management/`. The standalone deployment sets `mqtt.api.enabled=false`, so the MQTT interfaces are not registered there.

2 Service Operations

The provider subscribes to one topic per operation, the base topic followed by the operation name:

Operation	Request topic
`discovery`	`arrowhead/translation/bridge/management/discovery`
`negotiation`	`arrowhead/translation/bridge/management/negotiation`
`abort`	`arrowhead/translation/bridge/management/abort`
`query`	`arrowhead/translation/bridge/management/query`

A consumer publishes a request envelope (MqttRequestTemplate) to the topic and receives the answer (MqttResponseTemplate) on its own `responseTopic`. The `authentication` field carries the requester's identity according to the provider's authentication policy: `IDENTITY-TOKEN//<token>` (outsourced or internal policy), `SYSTEM//<name>` (declared policy) or the requester's X.509 certificate (certificate policy). The `status` of the response uses the HTTP status code numbers (200, 201, 204, 400, 401, 403, 404, 408, 423, 500, 503); on error the payload is an ErrorMessage.

```
{
  "traceId": "a1b2c3",
  "authentication": "IDENTITY-TOKEN//<token>",
  "responseTopic": "arrowhead/response/TemperatureDisplay/a1b2c3",
  "qosRequirement": 1,
  "params": {},
  "payload": {}
}
```

Listing 1: Request envelope.

```
{
  "status": 200,
  "traceId": "a1b2c3",
  "receiver": "TemperatureDisplay",
  "payload": {}
}
```

Listing 2: Response envelope.

2.1 PUBLISH `arrowhead/translation/bridge/management/discovery`

Operation: discovery
Input: TranslationDiscoveryMgmtRequest
Output: TranslationDiscoveryResponse

Discovers translation candidates on behalf of the named consumer, with discovery flags.

```
{
  "candidates": [
    {
      "instanceId": "TemperatureSensor|temperatureReading|1.0.0",
      "provider": {
        "name": "TemperatureSensor",
        "metadata": {
          "location": "hall-1"
        },
        "version": "1.0.0",
        "addresses": [
```

```
          {}
        ],
        "device": {
          "name": "Raspberry1",
          "metadata": {
            "location": "hall-1"
          },
          "addresses": [
            {}
          ],
          "createdAt": "2026-10-22T12:00:00Z",
          "updatedAt": "2026-10-22T12:00:00Z"
        },
        "createdAt": "2026-10-22T12:00:00Z",
        "updatedAt": "2026-10-22T12:00:00Z"
      },
      "serviceDefinition": {
        "name": "temperatureReading",
        "createdAt": "2026-10-22T12:00:00Z",
        "updatedAt": "2026-10-22T12:00:00Z"
      },
      "version": "1.0.0",
      "expiresAt": "2026-10-22T12:00:00Z",
      "metadata": {
        "unit": "celsius"
      },
      "interfaces": [
        {
          "templateName": "generic_https",
          "protocol": "https",
          "policy": "CERT_AUTH",
          "properties": {
            "accessAddresses": [
              "192.168.0.10"
            ],
            "accessPort": 8080,
            "basePath": "/temperature",
            "operations": {
              "read": {
                "method": "GET",
                "path": "/read"
              }
            }
          }
        }
      ],
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "consumer": "TemperatureDisplay",
  "operation": "FILTER",
  "interfaceTemplateNames": [
    "string"
  ],
  "inputDataModelId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "outputDataModelId": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}
```


Listing 3: Payload of an discovery request.

2.2 PUBLISH arrowhead/translation/bridge/management/negotiation

Operation: negotiation
Input: TranslationNegotiationMgmtRequest
Output: TranslationNegotiationResponse

Builds a discovered bridge to the chosen target instance on behalf of its consumer.

```
{
  "bridgeId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "targetInstanceId": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}
```

Listing 4: Payload of an negotiation request.

2.3 PUBLISH arrowhead/translation/bridge/management/abort

Operation: abort
Input: Array<String>
Output: TranslationAbortMgmtResponse

Aborts the listed bridges; returns the result per bridge.

```
[
  "3fa85f64-5717-4562-b3fc-2c963f66afa6"
]
```

Listing 5: Payload of an abort request.

2.4 PUBLISH arrowhead/translation/bridge/management/query

Operation: query
Input: TranslationQueryRequest
Output: TranslationQueryListResponse

Returns a page of bridges matching the filter.

```
{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "bridgeIds": [
    "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  ],
  "creators": [
    "string"
  ],
  "statuses": [
    "string"
  ],
  "consumers": [
    "TemperatureDisplay"
  ],
  "providers": [
    "TemperatureSensor"
  ],
  "serviceDefinitions": [
    "temperatureReading"
```

```
  ],
  "interfaceTranslators": [
    "string"
  ],
  "dataModelTranslators": [
    "string"
  ],
  "creationFrom": "2026-10-22T12:00:00Z",
  "creationTo": "2026-10-22T12:00:00Z",
  "alivesFrom": "2026-10-22T12:00:00Z",
  "alivesTo": "2026-10-22T12:00:00Z",
  "minUsage": 1,
  "maxUsage": 1
}
```

Listing 6: Payload of an query request.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Each *struct* denotes a JSON Object with the named fields; fields that are not needed may be omitted.

3.1 struct MqttRequestTemplate

The request envelope.

Object Field	Value Type	Description
"traceId"	String	Identifier chosen by the requester, returned in the response.
"authentication"	String	Identity of the requester (see Section 2).
"responseTopic"	String	Topic on which the response is published.
"qosRequirement"	Number	MQTT QoS of the response (0, 1 or 2).
"params"	Object<String>	Optional parameters (the query parameters of the HTTP binding).
"payload"	Object	The operation input.

3.2 struct MqttResponseTemplate

The response envelope.

Object Field	Value Type	Description
"status"	Number	Status code.
"traceId"	String	The trace identifier of the request.
"receiver"	String	Name of the requester.
"payload"	Object	The operation output, or an ErrorMessage.

3.3 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	Error text, if the event is an error.
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.4 struct Address

A network address with its type.

Object Field	Value Type	Description
"type"	String	Address type: `HOSTNAME`, `IPV4`, `IPV6` or `MAC`.
"address"	String	One network address (host name, IPv4, IPv6 or MAC address).

3.5 struct DeviceResponse

A registered device.

Object Field	Value Type	Description
"name"	String	Device name.
"metadata"	Object	Free-form metadata (JSON object).
"addresses"	Array<Address>	Network addresses with their types.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.6 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.7 struct ServiceDefinitionResponse

A service definition.

Object Field	Value Type	Description
"name"	String	Service definition name.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.8 struct ServiceInstanceInterfaceResponse

One interface of a service instance.

Object Field	Value Type	Description
"templateName"	String	Name of the interface template, snake_case (e.g. `generic_https`).
"protocol"	String	Protocol of the interface, e.g. `http`, `https`, `mqtt`, `mqtts`.
"policy"	String	Security policy of the interface: `NONE`, `CERT_AUTH` or one of the token policies.
"properties"	Object	Interface properties defined by the template, e.g. `accessAddresses`, `accessPort`, `basePath`, `operations`.

3.9 struct ServiceInstanceResponse

A registered service instance.

Object Field	Value Type	Description
"instanceId"	String	Service instance identifier `<System>|<serviceDefinition>|<version>`, or policy instance identifier.
"provider"	SystemResponse	The provider system.
"serviceDefinition"	ServiceDefinitionResponse	The service definition.
"version"	Version	Version of the service instance.
"expiresAt"	DateTime	UTC expiry time; no value means no expiry.
"metadata"	Object	Free-form metadata (JSON object).
"interfaces"	Array<ServiceInstanceInterface Response>	Service interfaces offered by the instance.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.10 struct SystemResponse

A registered system.

Object Field	Value Type	Description
"name"	String	System name.
"metadata"	Object	Free-form metadata (JSON object).
"version"	Version	Version of the system.
"addresses"	Array<Address>	Network addresses with their types.
"device"	DeviceResponse	The device hosting the system, if registered.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.11 struct TranslationAbortMgmtResponse

Results of aborting bridges.

Object Field	Value Type	Description
"results"	Object<Boolean>	Per bridge identifier, whether it was aborted.

3.12 struct TranslationBridgeCandidate

A candidate reachable through translation.

Object Field	Value Type	Description
"serviceInstanceId"	String	Service instance identifier `<System>|<serviceDefinition>|<version>`.
"interfaceTemplate Name"	String	Interface template of the candidate the bridge would translate to.

3.13 struct TranslationDataModelTranslationDataDescriptor

Settings of a data-model translation.

Object Field	Value Type	Description
"fromModelId"	String	Source data model.
"toModelId"	String	Target data model.
"interfaceProperties"	Object	Interface properties of the translator.
"configurationSettings"	Object	Configuration passed to the translator.

3.14 struct TranslationDiscoveryMgmtRequest

Discovery of translation bridges on behalf of a consumer.

Object Field	Value Type	Description
"candidates"	Array<ServiceInstanceResponse>	Candidate service instances (from service discovery).
"consumer"	String	Consumer on whose behalf the bridge is discovered.
"operation"	String	QoS operation: `FILTER` or `SORT`.
"interfaceTemplate Names"	Array<String>	Accepted interface templates, e.g. `generic_https`.
"inputDataModelId"	String	Data model of the operation input expected by the consumer.
"outputDataModelId"	String	Data model of the operation output expected by the consumer.
"flags"	Object<Boolean>	Discovery flags, e.g. `CANDIDATES_AUTH_CHECK`, `CONSUMER_BLACKLIST_CHECK`.

3.15 struct TranslationDiscoveryResponse

Candidates reachable through a translation bridge.

Object Field	Value Type	Description
"bridgeId"	String	Identifier (UUID) of the translation bridge.
"candidates"	Array<TranslationBridgeCandidate>	Store entries to create.

3.16 struct TranslationInterfaceTranslationDataDescriptor

Settings of an interface translation.

Object Field	Value Type	Description
"fromInterfaceTemplate"	String	Interface template of the consumer side.
"toInterfaceTemplate"	String	Interface template of the provider side.
"token"	String	The token.
"interfaceProperties"	Object	Interface properties of the translator.
"configurationSettings"	Object	Configuration passed to the translator.

3.17 struct TranslationNegotiationMgmtRequest

Builds a discovered bridge on behalf of a consumer.

Object Field	Value Type	Description
"bridgeId"	String	Identifier (UUID) of the translation bridge.
"targetInstanceId"	String	Service instance chosen from the discovery candidates.

3.18 struct TranslationNegotiationResponse

The established bridge.

Object Field	Value Type	Description
"bridgeId"	String	Identifier (UUID) of the translation bridge.
"bridgeInterface"	ServiceInstanceInterfaceResponse	Interface of the bridge the consumer calls instead of the provider.
"tokenExpiresAt"	DateTime	Expiry of the bridge token.
"tokenUsageLimit"	Number	Number of uses allowed with the bridge token.

3.19 struct TranslationQueryListResponse

List of translation bridges.

Object Field	Value Type	Description
"entries"	Array<TranslationQueryResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.20 struct TranslationQueryRequest

Paged filter for translation bridges.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"bridgeIds"	Array<String>	Bridge identifiers to match.
"creators"	Array<String>	Systems that created the bridges.
"statuses"	Array<String>	Bridge statuses to match.
"consumers"	Array<String>	Consumer systems to match.
"providers"	Array<String>	Provider system names to match.
"serviceDefinitions"	Array<String>	Service definition names to match.
"interfaceTranslators"	Array<String>	Interface translator systems to match.
"dataModelTranslators"	Array<String>	Data model translator systems to match.
"creationFrom"	DateTime	Lower bound of the creation time.
"creationTo"	DateTime	Upper bound of the creation time.
"alivesFrom"	DateTime	Lower bound of the bridge expiry.
"alivesTo"	DateTime	Upper bound of the bridge expiry.
"minUsage"	Number	Minimum number of usage reports.
"maxUsage"	Number	Maximum number of usage reports.

3.21 struct TranslationQueryResponse

A translation bridge.

Object Field	Value Type	Description
"bridgeId"	String	Identifier (UUID) of the translation bridge.
"status"	String	Bridge status: `NEW`, `DISCOVERED`, `PENDING`, `INITIALIZED`, `USED`, `ABORTED`, `CLOSED` or `ERROR`.
"usageReportCount"	Number	Number of usage reports received for the bridge.
"alivesAt"	DateTime	Expiry of the bridge.
"message"	String	Text of the log entry or status message of the job.
"consumer"	String	Name of the consumer system.
"provider"	String	Name of the provider system.
"serviceDefinition"	String	Service definition name.
"operation"	String	QoS operation: `FILTER` or `SORT`.
"interfaceTranslator"	String	System translating between the interfaces.
"interfaceTranslatorData"	TranslationInterfaceTranslationDataDescriptor	Settings of the interface translation.
"inputDataModelTranslator"	String	System translating the input data model.
"inputDataModelTranslatorData"	TranslationDataModelTranslationDataDescriptor	Settings of the input data-model translation.
"outputDataModelTranslator"	String	System translating the output data model.
"outputDataModelTranslatorData"	TranslationDataModelTranslationDataDescriptor	Settings of the output data-model translation.
"createdBy"	String	Name of the system that created the record.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.22 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.
Version	JSON String, semantic version `major.minor.patch`.

4 References

[1] A. Banks and R. Gupta, “Mqtt version 3.1.1,” OASIS, Standard, 2014.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “translationBridgeManagement – Service Description (TranslationManager),” Eclipse Arrowhead, SD 5.2.2, 2026, translationManager-v5.2.2-translationBridgeManagement-SD.pdf.

[6] ——, “translationBridgeManagement HTTP/TLS/JSON – Interface Design Description (TranslationManager),” Eclipse Arrowhead, IDD 5.2.2, 2026, translationManager-v5.2.2-translationBridgeManagement-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): standalone deployment, configuration and security statements updated; missing primitive definitions added.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	