identityManagement MQTT/TLS/JSON

Interface Design Description

Service ID: *"identityManagement"*

Abstract
This document describes the MQTT protocol with TLS payload security and JSON payload encoding variant of the `identityManagement` service of the Authentication system.

Contents

1 Overview **3**

2 Service Operations **4**
2.1 operation identity-mgmt-create . . . 4
2.2 operation identity-mgmt-update . . . 5
2.3 operation identity-mgmt-remove . . . 5
2.4 operation identity-mgmt-query . . . 5
2.5 operation identity-mgmt-session-close . . . 6
2.6 operation identity-mgmt-session-query . . . 6

3 Data Models **7**
3.1 struct MqttRequestTemplate . . . 7
3.2 struct MqttResponseTemplate . . . 7
3.3 struct ErrorMessage . . . 7
3.4 struct IdentityListMgmtCreateRequest . . . 7
3.5 struct IdentityListMgmtResponse . . . 7
3.6 struct IdentityListMgmtUpdateRequest . . . 8
3.7 struct IdentityMgmtRequest . . . 8
3.8 struct IdentityMgmtResponse . . . 8
3.9 struct IdentityQueryRequest . . . 8
3.10 struct IdentitySessionListMgmtResponse . . . 9
3.11 struct IdentitySessionQueryRequest . . . 9
3.12 struct IdentitySessionResponse . . . 9
3.13 struct Page . . . 9
3.14 Primitives . . . 10

4 References **11**

5 Revision History **12**
5.1 Amendments . . . 12
5.2 Quality Assurance . . . 12

1 Overview

This document describes the `identityManagement` service interface of the Authentication system over MQTT, which provides operator management of the identities known to Authentication (systems, their credentials and sysop flag) and of their active sessions.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	MQTT	3.1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `identityManagement` service interface

This document provides the Interface Design Description IDD to the *identityManagement – Service Description* document [5]. The operations, their semantics and the data models are the same as in the HTTP/TLS/JSON IDD [6]; this document specifies the MQTT binding.

The MQTT interface is offered only when the system runs with `mqtt.api.enabled=true`; it is then registered with the interface template `generic_mqtts` (`generic_mqtt` without TLS), the broker address and port (`mqtt.broker.address`, `mqtt.broker.port`) and the base topic `arrowhead/authentication/identity/management/`. In the Arrowhead-test-cloud-java deployment the MQTT interfaces of the core systems are disabled.

2 Service Operations

The provider subscribes to one topic per operation, the base topic followed by the operation name:

Operation	Request topic
`identity-mgmt-create`	`arrowhead/authentication/identity/management/identity-mgmt-create`
`identity-mgmt-update`	`arrowhead/authentication/identity/management/identity-mgmt-update`
`identity-mgmt-remove`	`arrowhead/authentication/identity/management/identity-mgmt-remove`
`identity-mgmt-query`	`arrowhead/authentication/identity/management/identity-mgmt-query`
`identity-mgmt-session-close`	`arrowhead/authentication/identity/management/identity-mgmt-session-close`
`identity-mgmt-session-query`	`arrowhead/authentication/identity/management/identity-mgmt-session-query`

A consumer publishes a request envelope (MqttRequestTemplate) to the topic and receives the answer (MqttResponseTemplate) on its own `responseTopic`. The `authentication` field carries the requester's identity according to the provider's authentication policy: `IDENTITY-TOKEN//<token>` (outsourced or internal policy), `SYSTEM//<name>` (declared policy) or the requester's X.509 certificate (certificate policy). The `status` of the response uses the HTTP status code numbers (200, 201, 204, 400, 401, 403, 404, 408, 423, 500, 503); on error the payload is an ErrorMessage.

```
{
  "traceId": "a1b2c3",
  "authentication": "IDENTITY-TOKEN//<token>",
  "responseTopic": "arrowhead/response/TemperatureDisplay/a1b2c3",
  "qosRequirement": 1,
  "params": {},
  "payload": {}
}
```

Listing 1: Request envelope.

```
{
  "status": 200,
  "traceId": "a1b2c3",
  "receiver": "TemperatureDisplay",
  "payload": {}
}
```

Listing 2: Response envelope.

2.1 PUBLISH `arrowhead/authentication/identity/management/identity-mgmt-create`

Operation: identity-mgmt-create
Input: IdentityListMgmtCreateRequest
Output: IdentityListMgmtResponse

Creates identities with credentials of the given authentication method.

```
{
  "authenticationMethod": "PASSWORD",
```

```
  "identities": [
    {
      "systemName": "TemperatureDisplay",
      "credentials": {
        "password": "<password>"
      },
      "sysop": false
    }
  ]
}
```

Listing 3: Payload of an identity-mgmt-create request.

2.2 PUBLISH arrowhead/authentication/identity/management/identity-mgmt-update

Operation: identity-mgmt-update
Input: IdentityListMgmtUpdateRequest
Output: IdentityListMgmtResponse

Updates credentials and sysop flag of identities.

```
{
  "identities": [
    {
      "systemName": "TemperatureDisplay",
      "credentials": {
        "password": "<password>"
      },
      "sysop": false
    }
  ]
}
```

Listing 4: Payload of an identity-mgmt-update request.

2.3 PUBLISH arrowhead/authentication/identity/management/identity-mgmt-remove

Operation: identity-mgmt-remove
Input: Array<String>

Removes identities by system name, closing their sessions.

```
[
  "TemperatureSensor"
]
```

Listing 5: Payload of an identity-mgmt-remove request.

2.4 PUBLISH arrowhead/authentication/identity/management/identity-mgmt-query

Operation: identity-mgmt-query
Input: IdentityQueryRequest
Output: IdentityListMgmtResponse

Returns a page of identities matching the filter.

```
{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "namePart": "Temp",
  "isSysop": false,
  "createdBy": "Sysop",
  "creationFrom": "2026-10-22T12:00:00Z",
  "creationTo": "2026-10-22T12:00:00Z",
  "hasSession": true
}
```

Listing 6: Payload of an identity-mgmt-query request.

2.5 PUBLISH arrowhead/authentication/identity/management/identity-mgmt-session-close

Operation: identity-mgmt-session-close
Input: Array<String>

Closes the sessions of the named systems.

```
[
  "TemperatureSensor"
]
```

Listing 7: Payload of an identity-mgmt-session-close request.

2.6 PUBLISH arrowhead/authentication/identity/management/identity-mgmt-session-query

Operation: identity-mgmt-session-query
Input: IdentitySessionQueryRequest
Output: IdentitySessionListMgmtResponse

Returns a page of active sessions.

```
{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "namePart": "Temp",
  "loginFrom": "2026-10-22T12:00:00Z",
  "loginTo": "2026-10-22T12:00:00Z"
}
```

Listing 8: Payload of an identity-mgmt-session-query request.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Each *struct* denotes a JSON Object with the named fields; fields that are not needed may be omitted.

3.1 struct MqttRequestTemplate

The request envelope.

Object Field	Value Type	Description
"traceId"	String	Identifier chosen by the requester, returned in the response.
"authentication"	String	Identity of the requester (see Section 2).
"responseTopic"	String	Topic on which the response is published.
"qosRequirement"	Number	MQTT QoS of the response (0, 1 or 2).
"params"	Object<String>	Optional parameters (the query parameters of the HTTP binding).
"payload"	Object	The operation input.

3.2 struct MqttResponseTemplate

The response envelope.

Object Field	Value Type	Description
"status"	Number	Status code.
"traceId"	String	The trace identifier of the request.
"receiver"	String	Name of the requester.
"payload"	Object	The operation output, or an ErrorMessage.

3.3 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.4 struct IdentityListMgmtCreateRequest

Identities to create.

Object Field	Value Type	Description
"authenticationMethod"	String	Authentication method of the identities; `PASSWORD` is the only implemented method.
"identities"	Array<IdentityMgmtRequest>	Identities to create, update or return.

3.5 struct IdentityListMgmtResponse

List of identities.

Object Field	Value Type	Description
"identities"	Array<IdentityMgmtResponse>	Identities to create, update or return.
"count"	Number	Total number of matching records (all pages).

3.6 struct IdentityListMgmtUpdateRequest

Identities to update.

Object Field	Value Type	Description
"identities"	Array<IdentityMgmtRequest>	Identities to create, update or return.

3.7 struct IdentityMgmtRequest

One identity.

Object Field	Value Type	Description
"systemName"	String	Name of the system, PascalCase (e.g. `TemperatureSensor`).
"credentials"	Object<String>	Credentials of the authentication method, for `PASSWORD` the key `password`.
"sysop"	Boolean	Whether the identity is a system operator (default false).

3.8 struct IdentityMgmtResponse

A stored identity (without credentials).

Object Field	Value Type	Description
"systemName"	String	Name of the system, PascalCase (e.g. `TemperatureSensor`).
"authenticationMethod"	String	Authentication method of the identities; `PASSWORD` is the only implemented method.
"sysop"	Boolean	Whether the identity is a system operator (bypasses the management filters).
"createdBy"	String	Name of the system that created the record.
"createdAt"	DateTime	UTC time of creation.
"updatedBy"	String	Name of the system that changed the record last.
"updatedAt"	DateTime	UTC time of the last change.

3.9 struct IdentityQueryRequest

Paged filter for identities.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"namePart"	String	Part of the system name to match.
"isSysop"	Boolean	Only sysop (true) or non-sysop (false) identities.
"createdBy"	String	Name of the system that created the record.
"creationFrom"	DateTime	Lower bound of the creation time.
"creationTo"	DateTime	Upper bound of the creation time.
"hasSession"	Boolean	Only identities with (true) or without (false) an active session.

3.10 struct IdentitySessionListMgmtResponse

List of active sessions.

Object Field	Value Type	Description
"sessions"	Array<IdentitySessionResponse>	Active sessions.
"count"	Number	Total number of matching records (all pages).

3.11 struct IdentitySessionQueryRequest

Paged filter for active sessions.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"namePart"	String	Part of the system name to match.
"loginFrom"	DateTime	Lower bound of the login time.
"loginTo"	DateTime	Upper bound of the login time.

3.12 struct IdentitySessionResponse

An active session.

Object Field	Value Type	Description
"systemName"	String	Name of the system, PascalCase (e.g. `TemperatureSensor`).
"loginTime"	DateTime	UTC time of the login.
"expirationTime"	DateTime	UTC time when the identity token expires.

3.13 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.14 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] A. Banks and R. Gupta, “Mqtt version 3.1.1,” OASIS, Standard, 2014.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “identityManagement – Service Description (Authentication),” Eclipse Arrowhead, SD 5.2.2, 2026, authentication-v5.2.2-identityManagement-SD.pdf.

[6] ——, “identityManagement HTTP/TLS/JSON – Interface Design Description (Authentication),” Eclipse Arrowhead, IDD 5.2.2, 2026, authentication-v5.2.2-identityManagement-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	