serviceOrchestrationHistoryManagement MQTT/TLS/JSON

Interface Design Description

Service ID: *"serviceOrchestrationHistoryManagement"*

Abstract
This document describes the MQTT protocol with TLS payload security and JSON payload encoding variant of the `serviceOrchestrationHistoryManagement` service of the SimpleStoreServiceOrchestration system.

Contents

1 Overview **3**

2 Service Operations **4**
2.1 operation query . . . 4

3 Data Models **6**
3.1 struct MqttRequestTemplate . . . 6
3.2 struct MqttResponseTemplate . . . 6
3.3 struct ErrorMessage . . . 6
3.4 struct OrchestrationHistoryQueryRequest . . . 6
3.5 struct OrchestrationHistoryResponse . . . 7
3.6 struct OrchestrationJob . . . 7
3.7 struct Page . . . 7
3.8 Primitives . . . 8

4 References **9**

5 Revision History **10**
5.1 Amendments . . . 10
5.2 Quality Assurance . . . 10

1 Overview

This document describes the `serviceOrchestrationHistoryManagement` service interface of the SimpleStoreServiceOrchestration system over MQTT, which provides query of the orchestration history: the pull and push orchestration jobs, their status and outcome.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	MQTT	3.1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `serviceOrchestrationHistoryManagement` service interface

This document provides the Interface Design Description IDD to the *serviceOrchestrationHistoryManagement – Service Description* document [5]. The operations, their semantics and the data models are the same as in the HTTP/TLS/JSON IDD [6]; this document specifies the MQTT binding.

The MQTT interface is offered only when the system runs with `mqtt.api.enabled=true`; it is then registered with the interface template `generic_mqtts` (`generic_mqtt` without TLS), the broker address and port (`mqtt.broker.address`, `mqtt.broker.port`) and the base topic `arrowhead/serviceorchestration/orchestration/management/history/`. In the Arrowhead-test-cloud-java deployment the MQTT interfaces of the core systems are disabled.

2 Service Operations

The provider subscribes to one topic per operation, the base topic followed by the operation name:

Operation	Request topic
`query`	`arrowhead/serviceorchestration/orchestration/management/history/query`

A consumer publishes a request envelope (MqttRequestTemplate) to the topic and receives the answer (MqttResponseTemplate) on its own `responseTopic`. The `authentication` field carries the requester's identity according to the provider's authentication policy: `IDENTITY-TOKEN//<token>` (outsourced or internal policy), `SYSTEM//<name>` (declared policy) or the requester's X.509 certificate (certificate policy). The `status` of the response uses the HTTP status code numbers (200, 201, 204, 400, 401, 403, 404, 408, 423, 500, 503); on error the payload is an ErrorMessage.

```
{
  "traceId": "a1b2c3",
  "authentication": "IDENTITY-TOKEN//<token>",
  "responseTopic": "arrowhead/response/TemperatureDisplay/a1b2c3",
  "qosRequirement": 1,
  "params": {},
  "payload": {}
}
```

Listing 1: Request envelope.

```
{
  "status": 200,
  "traceId": "a1b2c3",
  "receiver": "TemperatureDisplay",
  "payload": {}
}
```

Listing 2: Response envelope.

2.1 PUBLISH `arrowhead/serviceorchestration/orchestration/management/history/query`

Operation: query
Input: OrchestrationHistoryQueryRequest
Output: OrchestrationHistoryResponse

Returns a page of orchestration jobs matching the filter.

```
{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "ids": [
    "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  ],
  "statuses": [
    "string"
  ],
  "type": "IPV4",
  "requesterSystems": [
```

```
    "TemperatureDisplay"
  ],
  "targetSystems": [
    "TemperatureDisplay"
  ],
  "serviceDefinitions": [
    "temperatureReading"
  ],
  "subscriptionIds": [
    "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  ]
}
```

Listing 3: Payload of an query request.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Each *struct* denotes a JSON Object with the named fields; fields that are not needed may be omitted.

3.1 struct MqttRequestTemplate

The request envelope.

Object Field	Value Type	Description
"traceId"	String	Identifier chosen by the requester, returned in the response.
"authentication"	String	Identity of the requester (see Section 2).
"responseTopic"	String	Topic on which the response is published.
"qosRequirement"	Number	MQTT QoS of the response (0, 1 or 2).
"params"	Object<String>	Optional parameters (the query parameters of the HTTP binding).
"payload"	Object	The operation input.

3.2 struct MqttResponseTemplate

The response envelope.

Object Field	Value Type	Description
"status"	Number	Status code.
"traceId"	String	The trace identifier of the request.
"receiver"	String	Name of the requester.
"payload"	Object	The operation output, or an ErrorMessage.

3.3 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.4 struct OrchestrationHistoryQueryRequest

Paged filter for orchestration jobs.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"ids"	Array<String>	Job identifiers (UUID) to match.
"statuses"	Array<String>	Job statuses to match.
"type"	String	Orchestration type to match: `PULL` or `PUSH`.
"requesterSystems"	Array<String>	Requester system names to match.
"targetSystems"	Array<String>	Target system names.
"serviceDefinitions"	Array<String>	Service definition names to match.
"subscriptionIds"	Array<String>	Subscription identifiers.

3.5 struct OrchestrationHistoryResponse

List of orchestration jobs.

Object Field	Value Type	Description
"entries"	Array<OrchestrationJob>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.6 struct OrchestrationJob

One orchestration job (pull or push).

Object Field	Value Type	Description
"id"	String	Identifier (UUID) of the orchestration job.
"status"	String	Status of the job: `PENDING`, `IN_PROGRESS`, `DONE` or `ERROR`.
"type"	String	Orchestration type: `PULL` or `PUSH`.
"requesterSystem"	String	Name of the system that requested the orchestration.
"targetSystem"	String	Name of the consumer system the orchestration was made for.
"serviceDefinition"	String	Service definition name.
"subscriptionId"	String	Subscription that started the push job.
"message"	String	Status message, e.g. `1 local result: DataManager`.
"createdAt"	DateTime	UTC time of creation.
"startedAt"	DateTime	UTC time when the job started.
"finishedAt"	DateTime	UTC time when the job finished.

3.7 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.8 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] A. Banks and R. Gupta, “Mqtt version 3.1.1,” OASIS, Standard, 2014.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “serviceOrchestrationHistoryManagement – Service Description (SimpleStoreService-Orchestration),” Eclipse Arrowhead, SD 5.2.2, 2026, simpleStoreServiceOrchestration-v5.2.2-serviceOrchestrationHistoryManagement-SD.pdf.

[6] ——, “serviceOrchestrationHistoryManagement HTTP/TLS/JSON – Interface Design Description (SimpleStoreServiceOrchestration),” Eclipse Arrowhead, IDD 5.2.2, 2026, simpleStoreServiceOrchestration-v5.2.2-serviceOrchestrationHistoryManagement-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	