# 1 Interface overview

Mandatory mutual TLS, Arrowhead token/certificate binding, JSON request and response documents. Echo responses, orchestration subscription IDs, authorization public keys and encryption IV responses are text. Certificate-only operations and management are distinguished in the table.

## 1.1 HTTPS interface operations

HTTPS uses JSON unless an operation specifies text. Request bodies are limited to 1 MiB; upstream responses to 8 MiB. Identity-token format: `Bearer IDENTITY-TOKEN//token`. Certificate-only identity operations still require verified mutual TLS and apply credential/certificate binding.

| Method | Path | Access |
|---|---|---|
| GET | /authentication/general/mgmt/get-config | management |
| POST | /authentication/general/mgmt/logs | management |
| GET | /authentication/monitor/echo | certificate |
| POST | /authentication/identity/login | certificate |
| POST | /authentication/identity/logout | certificate |
| POST | /authentication/identity/change | certificate |
| GET | /authentication/identity/verify/{token} | identity |
| POST | /authentication/mgmt/identities | management |
| PUT | /authentication/mgmt/identities | management |
| DELETE | /authentication/mgmt/identities | management |
| POST | /authentication/mgmt/identities/query | management |
| DELETE | /authentication/mgmt/sessions | management |
| POST | /authentication/mgmt/sessions | management |

Errors contain errorMessage, errorCode, exceptionType, origin and timestamp. Exact validation/error parity and all Java security-policy settings remain release gates. Unknown routes return 404; unavailable authorities fail closed.

# 2 Limitations

PASSWORD identities use bcrypt and single active opaque sessions. Java SQL/session import, complete query/time normalization and alternative framework transports require further work. No stored plaintext password or raw identity token is used.