1 Interface overview

Mandatory mutual TLS, Arrowhead token/certificate binding, JSON request and response documents. Echo responses, orchestration subscription IDs, authorization public keys and encryption IV responses are text. Certificate-only operations and management are distinguished in the table.

1.1 HTTPS interface operations

HTTPS uses JSON unless an operation specifies text. Request bodies are limited to 1 MiB; upstream responses to 8 MiB. Identity-token format: `Bearer IDENTITY-TOKEN//token`. Certificate-only identity operations still require verified mutual TLS and apply credential/certificate binding.

Method	Path	Access
GET	/consumerauthorization/general/mgmt/get-config	management
POST	/consumerauthorization/general/mgmt/logs	management
GET	/consumerauthorization/monitor/echo	certificate
POST	/consumerauthorization/authorization/grant	identity
DELETE	/consumerauthorization/authorization/revoke/{instanceId}	identity
POST	/consumerauthorization/authorization/lookup	identity
POST	/consumerauthorization/authorization/verify	identity
POST	/consumerauthorization/authorization/mgmt/grant	management
DELETE	/consumerauthorization/authorization/mgmt/revoke	management
POST	/consumerauthorization/authorization/mgmt/query	management
POST	/consumerauthorization/authorization/mgmt/check	management
POST	/consumerauthorization/authorization-token/generate	identity
GET	/consumerauthorization/authorization-token/token/verify/{token}	identity
GET	/consumerauthorization/authorization-token/public-key	identity
POST	/consumerauthorization/authorization-token/encryption-key	identity
DELETE	/consumerauthorization/authorization-token/encryption-key	identity
POST	/consumerauthorization/authorization/mgmt/token/generate	management
POST	/consumerauthorization/authorization/mgmt/token/query	management
DELETE	/consumerauthorization/authorization/mgmt/token/revoke	management
POST	/consumerauthorization/authorization/mgmt/token/encryption-key	management
DELETE	/consumerauthorization/authorization/mgmt/token/encryption-key	management

Errors contain errorMessage, errorCode, exceptionType, origin and timestamp. Exact validation/error parity and

all Java security-policy settings remain release gates. Unknown routes return 404; unavailable authorities fail closed.

2 Limitations

Management-over-provider policy precedence, scoped policies, metadata checks, usage/time-limited tokens, Base64 and RSA JWT tokens, AES wire encryption and authenticated key wrapping are implemented. Foreign-consumer/federation token generation, Java database import, complete DTO/error parity and broad cryptographic interoperability fixtures remain incomplete. AES ECB/CBC are legacy Java wire formats, not recommendations for new protocols.