choreographerManagement HTTP/TLS/JSON

Interface Design Description

Service ID: *"choreographerManagement"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `choreographerManagement` service of the Choreographer system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation query-plans . . . 4
2.2 operation get-plan . . . 5
2.3 operation create-plan . . . 5
2.4 operation remove-plan . . . 7
2.5 operation check-plan . . . 7
2.6 operation start-sessions . . . 7
2.7 operation abort-session . . . 8
2.8 operation query-sessions . . . 9
2.9 operation query-session-steps . . . 9
2.10 operation query-worklog . . . 10
2.11 operation query-executors . . . 10
2.12 operation get-executor . . . 11
2.13 operation create-executor . . . 12
2.14 operation remove-executor . . . 12

3 Data Models **14**
3.1 struct ActionRequest . . . 14
3.2 struct ActionResponse . . . 14
3.3 struct CheckPlanResponse . . . 14
3.4 struct ErrorMessage . . . 14
3.5 struct ExecutorCreateRequest . . . 14
3.6 struct ExecutorListResponse . . . 15
3.7 struct ExecutorResponse . . . 15
3.8 struct ExecutorServiceDefinitionResponse . . . 15
3.9 struct MetadataRequirement . . . 15
3.10 struct OrchestrationServiceRequirement . . . 16
3.11 struct PlanListResponse . . . 16
3.12 struct PlanRequest . . . 16
3.13 struct PlanResponse . . . 16
3.14 struct RunPlanListRequest . . . 17
3.15 struct RunPlanListResponse . . . 17
3.16 struct RunPlanRequest . . . 17
3.17 struct RunPlanResponse . . . 17
3.18 struct SessionListResponse . . . 17
3.19 struct SessionResponse . . . 18
3.20 struct SessionStepListResponse . . . 18
3.21 struct SessionStepResponse . . . 18
3.22 struct StepRequest . . . 19
3.23 struct StepResponse . . . 19
3.24 struct WorklogListResponse . . . 19
3.25 struct WorklogResponse . . . 20
3.26 Primitives . . . 20

4 References **21**

5 Revision History **22**
5.1 Amendments . . . 22
5.2 Quality Assurance . . . 22

1 Overview

This document describes the `choreographerManagement` service interface of the Choreographer system, which provides operator management of plans, sessions, session steps, the worklog and executors.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `choreographerManagement` service interface

This document provides the Interface Design Description IDD to the *choreographerManagement – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `choreographerManagement` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https`, policy `CERT_AUTH`, access address `choreographer`, port 8457 (`server.port`; the standalone deployment registers 8454) and base path `/choreographer/mgmt`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`query-plans`	GET	`/plans`
`get-plan`	GET	`/plans/{id}`
`create-plan`	POST	`/plans`
`remove-plan`	DELETE	`/plans/{id}`
`check-plan`	GET	`/plans/{id}/check`
`start-sessions`	POST	`/sessions/start`
`abort-session`	DELETE	`/sessions/{id}`
`query-sessions`	GET	`/sessions`
`query-session-steps`	GET	`/session-steps`
`query-worklog`	GET	`/worklog`
`query-executors`	GET	`/executors`
`get-executor`	GET	`/executors/{id}`
`create-executor`	POST	`/executors`
`remove-executor`	DELETE	`/executors/{id}`

2 Service Operations

The interfaces of the `choreographerManagement` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `choreographerManagement` SD document, as well as input and output types.

All operations require the requester's identity, presented according to the provider's authentication policy: the client certificate (mutual TLS) and, with the `outsourced` policy, `Authorization: Bearer IDENTITY-TOKEN//<token>`; systems holding the Authentication secret key send `Bearer AUTHENTICATOR-KEY//<system>//<hash>`, and with the `declared` policy `Bearer SYSTEM//<system>` is sent. Request and response bodies are `application/json` unless stated otherwise. Errors are answered with an ErrorMessage body and the status codes `400 Bad Request` (invalid parameter), `401 Unauthorized` (missing or invalid identity), `403 Forbidden` (not permitted, e.g. by the management, authorization or blacklist filter), `404 Not Found`, `408 Request Timeout`, `423 Locked`, `500 Internal Server Error` and `503 Service Unavailable` (a system it depends on failed).

2.1 GET /choreographer/mgmt/plans?page={page}&size={size}&direction={direction}&sortField={sortField}

Operation: query-plans
Output: PlanListResponse

Returns a page of plans.

Query parameters: *page* (Integer, optional); *size* (Integer, optional); *direction* (String, optional); *sortField* (String, optional). List values are repeated or comma-separated.

A successful call returns `200 OK` with the output in the body.

```
GET /choreographer/mgmt/plans?page=<page>&size=<size>&direction=<direction>&sortField=<sortField>
    HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 1: An query-plans invocation.

```
{
  "entries": [
    {
      "id": 42,
      "name": "TemperatureSensor",
      "firstActionName": "string",
      "actions": [
        {
          "id": 42,
          "name": "TemperatureSensor",
          "firstAction": true,
          "nextActionName": "string",
          "firstStepNames": [
            "string"
          ],
          "steps": [
            {}
          ],
          "createdAt": "2026-10-22T12:00:00Z",
          "updatedAt": "2026-10-22T12:00:00Z"
        }
      ],
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
```

```
}
```

Listing 2: An query-plans response.

2.2 GET /choreographer/mgmt/plans/*{id}*

Operation: get-plan
Input: String
Output: PlanResponse

Returns a plan.

Path parameter: *id*.

A successful call returns `200 OK` with the output in the body.

```
GET /choreographer/mgmt/plans/<id> HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 3: An get-plan invocation.


```
{
  "id": 42,
  "name": "TemperatureSensor",
  "firstActionName": "string",
  "actions": [
    {
      "id": 42,
      "name": "TemperatureSensor",
      "firstAction": true,
      "nextActionName": "string",
      "firstStepNames": [
        "string"
      ],
      "steps": [
        {
          "id": 42,
          "name": "TemperatureSensor",
          "serviceDefinition": "temperatureReading",
          "minVersion": 1,
          "maxVersion": 1,
          "quantity": 1,
          "localCloudOnly": true,
          "nextStepNames": [
            "string"
          ],
          "createdAt": "2026-10-22T12:00:00Z",
          "updatedAt": "2026-10-22T12:00:00Z"
        }
      ],
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "createdAt": "2026-10-22T12:00:00Z",
  "updatedAt": "2026-10-22T12:00:00Z"
}
```


Listing 4: An get-plan response.

2.3 POST /choreographer/mgmt/plans

Operation: create-plan
Input: PlanRequest
Output: PlanResponse

Validates and stores a plan (cycles, reachability, transitive reduction).
A successful call returns `201 Created` with the output in the body.

```
POST /choreographer/mgmt/plans HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "name": "TemperatureSensor",
  "firstActionName": "string",
  "actions": [
    {
      "name": "TemperatureSensor",
      "nextActionName": "string",
      "firstStepNames": [
        "string"
      ],
      "steps": [
        {
          "name": "TemperatureSensor",
          "quantity": 1,
          "localCloudOnly": true,
          "nextStepNames": [
            "string"
          ]
        }
      ]
    }
  ]
}
```

Listing 5: An create-plan invocation.

```
{
  "id": 42,
  "name": "TemperatureSensor",
  "firstActionName": "string",
  "actions": [
    {
      "id": 42,
      "name": "TemperatureSensor",
      "firstAction": true,
      "nextActionName": "string",
      "firstStepNames": [
        "string"
      ],
      "steps": [
        {
          "id": 42,
          "name": "TemperatureSensor",
          "serviceDefinition": "temperatureReading",
          "minVersion": 1,
          "maxVersion": 1,
          "quantity": 1,
          "localCloudOnly": true,
          "nextStepNames": [
            "string"
          ],
          "createdAt": "2026-10-22T12:00:00Z",
```

```
          "updatedAt": "2026-10-22T12:00:00Z"
        }
      ],
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "createdAt": "2026-10-22T12:00:00Z",
  "updatedAt": "2026-10-22T12:00:00Z"
}
```

Listing 6: An create-plan response.

2.4 DELETE /choreographer/mgmt/plans/*{id}*

Operation: remove-plan
Input: String

Removes a plan.
Path parameter: *id*.
A successful call returns `200 OK`.

```
DELETE /choreographer/mgmt/plans/<id> HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 7: An remove-plan invocation.

2.5 GET /choreographer/mgmt/plans/*{id}*/check?allowInterCloud=*{allowInterCloud}*

Operation: check-plan
Input: String
Output: CheckPlanResponse

Checks whether providers and executors exist for every step.
Path parameter: *id*.
Query parameters: *allowInterCloud* (boolean, optional, default `false`). List values are repeated or comma-separated.
A successful call returns `200 OK` with the output in the body.

```
GET /choreographer/mgmt/plans/<id>/check?allowInterCloud=<allowInterCloud> HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 8: An check-plan invocation.

```
{
  "planId": 1,
  "errorMessages": [
    "string"
  ],
  "needInterCloud": true
}
```

Listing 9: An check-plan response.

2.6 POST /choreographer/mgmt/sessions/start

Operation: start-sessions
Input: RunPlanListRequest
Output: RunPlanListResponse

Starts sessions of plans by identifier.
A successful call returns `201 Created` with the output in the body.

```
POST /choreographer/mgmt/sessions/start HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "sessions": [
    {
      "planId": 1,
      "quantity": 1,
      "allowInterCloud": true,
      "chooseOptimalExecutor": true,
      "notifyProtocol": "HTTPS",
      "notifyAddress": "192.168.0.20",
      "notifyPort": 8080,
      "notifyPath": "/notify"
    }
  ]
}
```

Listing 10: An start-sessions invocation.

```
{
  "entries": [
    {
      "planId": 1,
      "sessionId": 1,
      "quantity": 1,
      "status": "INITIATED",
      "errorMessages": [
        "string"
      ],
      "needInterCloud": true
    }
  ]
}
```

Listing 11: An start-sessions response.

2.7 DELETE /choreographer/mgmt/sessions/*{id}*

Operation: abort-session
Input: String

Aborts a session.
Path parameter: *id*.
A successful call returns `200 OK`.

```
DELETE /choreographer/mgmt/sessions/<id> HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 12: An abort-session invocation.

2.8 GET /choreographer/mgmt/sessions?page={page}&size={size}&direction={direction}&sortField={sortField}&planId={planId}&status={status}

Operation: query-sessions
Output: SessionListResponse

Returns a page of sessions.

Query parameters: *page* (Integer, optional); *size* (Integer, optional); *direction* (String, optional); *sortField* (String, optional); *planId* (Long, optional); *status* (String, optional). List values are repeated or comma-separated.

A successful call returns `200 OK` with the output in the body.

```
GET /choreographer/mgmt/sessions?page=<page>&size=<size>&direction=<direction>&sortField=<sortField
    >&planId=<planId>&status=<status> HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 13: An query-sessions invocation.


```
{
  "entries": [
    {
      "id": 42,
      "planId": 1,
      "planName": "fillTank",
      "status": "INITIATED",
      "quantityDone": 1,
      "quantityGoal": 1,
      "executionNumber": 1,
      "owner": "TemperatureDisplay",
      "notifyUri": "https://display:8080/events",
      "startedAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```


Listing 14: An query-sessions response.

2.9 GET /choreographer/mgmt/session-steps?page={page}&size={size}&direction={direction}&sortField={sortField}&sessionId={sessionId}&status={status}

Operation: query-session-steps
Output: SessionStepListResponse

Returns a page of session steps.

Query parameters: *page* (Integer, optional); *size* (Integer, optional); *direction* (String, optional); *sortField* (String, optional); *sessionId* (Long, optional); *status* (String, optional). List values are repeated or comma-separated.

A successful call returns `200 OK` with the output in the body.

```
GET /choreographer/mgmt/session-steps?page=<page>&size=<size>&direction=<direction>&sortField=<
    sortField>&sessionId=<sessionId>&status=<status> HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 15: An query-session-steps invocation.

```
{
  "entries": [
    {
      "id": 42,
      "sessionId": 1,
      "stepId": 1,
      "planName": "fillTank",
      "actionName": "string",
      "stepName": "string",
      "executorName": "string",
      "status": "WAITING",
      "executionNumber": 1,
      "message": "1 local result: TemperatureSensor",
      "startedAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 16: An query-session-steps response.

2.10 GET /choreographer/mgmt/worklog?page={page}&size={size} &direction={direction}&sortField={sortField}&sessionId={sessionId} &planName={planName}&actionName={actionName}&stepName={stepName}

Operation: query-worklog
Output: WorklogListResponse

Returns a page of worklog entries.

Query parameters: *page* (Integer, optional); *size* (Integer, optional); *direction* (String, optional); *sortField* (String, optional); *sessionId* (Long, optional); *planName* (String, optional); *actionName* (String, optional); *stepName* (String, optional). List values are repeated or comma-separated.

A successful call returns `200 OK` with the output in the body.

```
GET /choreographer/mgmt/worklog?page=<page>&size=<size>&direction=<direction>&sortField=<sortField>&
    sessionId=<sessionId>&planName=<planName>&actionName=<actionName>&stepName=<stepName> HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 17: An query-worklog invocation.

```
{
  "entries": [
    {
      "id": 42,
      "entryDate": "2026-10-22T12:00:00Z",
      "planName": "fillTank",
      "actionName": "string",
      "stepName": "string",
      "sessionId": 1,
      "executionNumber": 1,
      "message": "1 local result: TemperatureSensor"
    }
  ],
  "count": 1
}
```

Listing 18: An query-worklog response.

2.11 GET /choreographer/mgmt/executors?page={page}&size={size}&direction={direction}&sortField={sortField}

Operation: query-executors
Output: ExecutorListResponse

Returns a page of executors.

Query parameters: *page* (Integer, optional); *size* (Integer, optional); *direction* (String, optional); *sortField* (String, optional). List values are repeated or comma-separated.

A successful call returns `200 OK` with the output in the body.

```
GET /choreographer/mgmt/executors?page=<page>&size=<size>&direction=<direction>&sortField=<sortField
    > HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 19: An query-executors invocation.

```
{
  "entries": [
    {
      "id": 42,
      "name": "TemperatureSensor",
      "address": "192.168.0.10",
      "port": 8080,
      "basePath": "/executor",
      "serviceDefinitions": [
        {
          "serviceDefinitionName": "temperatureReading",
          "minVersion": 1,
          "maxVersion": 1
        }
      ],
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 20: An query-executors response.

2.12 GET /choreographer/mgmt/executors/{id}

Operation: get-executor
Input: String
Output: ExecutorResponse

Returns an executor.

Path parameter: *id*.

A successful call returns `200 OK` with the output in the body.

```
GET /choreographer/mgmt/executors/<id> HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 21: An get-executor invocation.

```
{
  "id": 42,
```

```
  "name": "TemperatureSensor",
  "address": "192.168.0.10",
  "port": 8080,
  "basePath": "/executor",
  "serviceDefinitions": [
    {
      "serviceDefinitionName": "temperatureReading",
      "minVersion": 1,
      "maxVersion": 1
    }
  ],
  "createdAt": "2026-10-22T12:00:00Z",
  "updatedAt": "2026-10-22T12:00:00Z"
}
```

Listing 22: An get-executor response.

2.13 POST /choreographer/mgmt/executors

Operation: create-executor
Input: ExecutorCreateRequest
Output: ExecutorResponse

Registers an executor on behalf of a system.

A successful call returns `201 Created` with the output in the body.

```
POST /choreographer/mgmt/executors HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "systemName": "TemperatureSensor",
  "address": "192.168.0.10",
  "port": 8080,
  "basePath": "/executor",
  "serviceDefinitionName": "temperatureReading",
  "minVersion": 1,
  "maxVersion": 1
}
```

Listing 23: An create-executor invocation.

```
{
  "id": 42,
  "name": "TemperatureSensor",
  "address": "192.168.0.10",
  "port": 8080,
  "basePath": "/executor",
  "serviceDefinitions": [
    {
      "serviceDefinitionName": "temperatureReading",
      "minVersion": 1,
      "maxVersion": 1
    }
  ],
  "createdAt": "2026-10-22T12:00:00Z",
  "updatedAt": "2026-10-22T12:00:00Z"
}
```

Listing 24: An create-executor response.

2.14 DELETE /choreographer/mgmt/executors/*{id}*

Operation: remove-executor
Input: String

Removes an executor.
Path parameter: *id*.
A successful call returns `200 OK`.

```
DELETE /choreographer/mgmt/executors/<id> HTTP/1.1
Host: choreographer:8457
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 25: An remove-executor invocation.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.26, which are used to represent things like hashes, identifiers and texts.

3.1 struct ActionRequest

An action of a plan.

Object Field	Value Type	Description
"name"	String	Name of the action within the plan.
"nextActionName"	String	Action executed after this one.
"firstStepNames"	Array<String>	Steps that start the action.
"steps"	Array<StepRequest>	The steps of the action.

3.2 struct ActionResponse

An action of a plan.

Object Field	Value Type	Description
"id"	Number	Identifier of the action.
"name"	String	Name of the action within the plan.
"firstAction"	Boolean	Whether this is the plan's first action.
"nextActionName"	String	Action executed after this one.
"firstStepNames"	Array<String>	Steps that start the action.
"steps"	Array<StepResponse>	The steps of the action.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.3 struct CheckPlanResponse

Result of checking a plan against the current cloud.

Object Field	Value Type	Description
"planId"	Number	The checked plan.
"errorMessages"	Array<String>	Problems found in the plan.
"needInterCloud"	Boolean	Whether the plan needs providers in other clouds.

3.4 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	Error text, if the event is an error.
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.5 struct ExecutorCreateRequest

An executor to create on behalf of a system.

Object Field	Value Type	Description
"systemName"	String	Executor system.
"address"	String	One network address (host name, IPv4, IPv6 or MAC address).
"port"	Number	Port of the executor interface.
"basePath"	String	Base path of the executor interface.
"serviceDefinitionName"	String	Service definition the executor can execute steps for.
"minVersion"	Number	Lowest accepted major version.
"maxVersion"	Number	Highest accepted major version.

3.6 struct ExecutorListResponse

List of executors.

Object Field	Value Type	Description
"entries"	Array<ExecutorResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.7 struct ExecutorResponse

A registered executor.

Object Field	Value Type	Description
"id"	Number	Identifier of the executor.
"name"	String	Executor system.
"address"	String	Address of the executor interface.
"port"	Number	Port of the executor interface.
"basePath"	String	Base path of the executor interface.
"serviceDefinitions"	Array<ExecutorServiceDefinitionResponse>	Service definitions the executor serves.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.8 struct ExecutorServiceDefinitionResponse

A service definition an executor serves.

Object Field	Value Type	Description
"serviceDefinitionName"	String	Service definition name, camelCase (e.g. `temperatureReading`).
"minVersion"	Number	Lowest accepted major version.
"maxVersion"	Number	Highest accepted major version.

3.9 struct MetadataRequirement

A JSON object of metadata requirements: each key is a metadata path (dot notation), each value the required value or an operator object such as `{"op": "LESS_THAN", "value": 10}`.

3.10 struct OrchestrationServiceRequirement

Requirements on the requested service.

Object Field	Value Type	Description
"serviceDefinition"	String	Service definition name.
"operations"	Array<String>	Service operations the consumer wants to use.
"versions"	Array<Version>	Accepted service versions.
"alivesAt"	DateTime	Only instances that are still registered (not expired) at this UTC time are matched.
"metadata Requirements"	Array<MetadataRequirement>	Requirements on the service instance metadata; each map is one alternative.
"interfaceTemplate Names"	Array<String>	Accepted interface templates, e.g. `generic_https`.
"interfaceAddressTypes"	Array<String>	Address types the provider interface must offer.
"interfaceProperty Requirements"	Array<MetadataRequirement>	Requirements on the interface properties; each map is one alternative.
"securityPolicies"	Array<String>	Accepted interface security policies.
"preferredProviders"	Array<String>	Provider systems to prefer.

3.11 struct PlanListResponse

List of plans.

Object Field	Value Type	Description
"entries"	Array<PlanResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.12 struct PlanRequest

A plan to create.

Object Field	Value Type	Description
"name"	String	Unique plan name.
"firstActionName"	String	Action the plan starts with.
"actions"	Array<ActionRequest>	The actions of the plan.

3.13 struct PlanResponse

A stored plan.

Object Field	Value Type	Description
"id"	Number	Identifier of the plan.
"name"	String	Unique plan name.
"firstActionName"	String	Action the plan starts with.
"actions"	Array<ActionResponse>	The actions of the plan.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.14 struct RunPlanListRequest

Sessions to start by plan identifier.

Object Field	Value Type	Description
"sessions"	Array<RunPlanRequest>	Sessions to start or return.

3.15 struct RunPlanListResponse

Started sessions.

Object Field	Value Type	Description
"entries"	Array<RunPlanResponse>	Matching records of the current page.

3.16 struct RunPlanRequest

Start of a session of a plan.

Object Field	Value Type	Description
"planId"	Number	Identifier of the plan.
"quantity"	Number	Number of times the plan (or step) is executed.
"allowInterCloud"	Boolean	Allow inter-cloud orchestration for the steps.
"chooseOptimal Executor"	Boolean	Rank the local executors and choose the best one.
"notifyProtocol"	String	Protocol of session notifications, e.g. `HTTPS`.
"notifyAddress"	String	Address of session notifications.
"notifyPort"	Number	Port of session notifications.
"notifyPath"	String	Path of session notifications.

3.17 struct RunPlanResponse

A started (or refused) session.

Object Field	Value Type	Description
"planId"	Number	Identifier of the plan.
"sessionId"	Number	Identifier of the session.
"quantity"	Number	Requested executions.
"status"	SessionStatus	Status of the session.
"errorMessages"	Array<String>	Problems found in the plan.
"needInterCloud"	Boolean	Whether the plan needs providers in other clouds.

3.18 struct SessionListResponse

List of sessions.

Object Field	Value Type	Description
"entries"	Array<SessionResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.19 struct SessionResponse

A session.

Object Field	Value Type	Description
"id"	Number	Identifier of the session.
"planId"	Number	Identifier of the plan.
"planName"	String	Name of the plan.
"status"	SessionStatus	Session status.
"quantityDone"	Number	Executions finished so far.
"quantityGoal"	Number	Executions requested.
"executionNumber"	Number	Number of the current execution.
"owner"	String	System that started the session.
"notifyUri"	String	Where session notifications are sent.
"startedAt"	DateTime	UTC time when the job started.
"updatedAt"	DateTime	UTC time of the last change.

3.20 struct SessionStepListResponse

List of session steps.

Object Field	Value Type	Description
"entries"	Array<SessionStepResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.21 struct SessionStepResponse

A step execution of a session.

Object Field	Value Type	Description
"id"	Number	Identifier of the session step.
"sessionId"	Number	Identifier of the session.
"stepId"	Number	Identifier of the plan step.
"planName"	String	Name of the plan.
"actionName"	String	Name of the action.
"stepName"	String	Name of the step.
"executorName"	String	Executor system running the step.
"status"	SessionStepStatus	Status of the session step.
"executionNumber"	Number	Number of the current execution.
"message"	String	Text of the log entry or status message of the job.
"startedAt"	DateTime	UTC time when the job started.
"updatedAt"	DateTime	UTC time of the last change.

3.22 struct StepRequest

A step of an action.

Object Field	Value Type	Description
"name"	String	Name of the step within the action.
"quantity"	Number	Number of times the plan (or step) is executed.
"serviceRequirement"	OrchestrationServiceRequirement	Orchestration requirement the executor's provider must meet.
"localCloudOnly"	Boolean	Use only providers of the local cloud.
"staticParameters"	Object<String>	Parameters passed to the executor unchanged.
"nextStepNames"	Array<String>	Steps that start when this one has finished.

3.23 struct StepResponse

A step of an action.

Object Field	Value Type	Description
"id"	Number	Identifier of the step.
"name"	String	Name of the step within the action.
"serviceDefinition"	String	Service definition of the step's requirement.
"minVersion"	Number	Lowest major version derived from `versions`.
"maxVersion"	Number	Highest major version derived from `versions`.
"quantity"	Number	Number of times the plan (or step) is executed.
"serviceRequirement"	OrchestrationServiceRequirement	Orchestration requirement the executor's provider must meet.
"localCloudOnly"	Boolean	Use only providers of the local cloud.
"staticParameters"	Object<String>	Parameters passed to the executor unchanged.
"nextStepNames"	Array<String>	Steps that start when this one has finished.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.24 struct WorklogListResponse

List of worklog entries.

Object Field	Value Type	Description
"entries"	Array<WorklogResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.25 struct WorklogResponse

A worklog entry.

Object Field	Value Type	Description
"id"	Number	Identifier of the worklog entry.
"entryDate"	DateTime	UTC time of the log entry.
"planName"	String	Name of the plan.
"actionName"	String	Name of the action.
"stepName"	String	Name of the step.
"sessionId"	Number	Identifier of the session.
"executionNumber"	Number	Number of the current execution.
"message"	String	Worklog text.
"exception"	String	Stack trace or exception text of the log entry, if any.

3.26 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
SessionStatus	One of `INITIATED`, `RUNNING`, `ABORTED`, `DONE` (JSON String).
SessionStepStatus	One of `WAITING`, `RUNNING`, `ABORTED`, `DONE` (JSON String).
String	JSON String.
Version	JSON String, semantic version `major.minor.patch`.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “choreographerManagement – Service Description (Choreographer),” Eclipse Arrowhead, SD 5.2.2, 2026, choreographer-v5.2.2-choreographerManagement-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): standalone deployment, configuration and security statements updated.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	