sysMonitor AMQP/TLS/JSON

Interface Design Description

Service ID: *"sysMonitor"*

Abstract
This document describes the AMQP 0-9-1 protocol with TLS payload security and JSON payload encoding variant of the `sysMonitor` service of the GraphDBManager system (SysMonitor-AMQP-IDD-5.2.2).

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation echo . . . 4
2.2 operation power . . . 4
2.3 operation status . . . 4

3 Data Models **6**
3.1 struct Observation . . . 6
3.2 Primitives . . . 6

4 References **7**

5 Revision History **8**
5.1 Amendments . . . 8
5.2 Quality Assurance . . . 8

1 Overview

This document describes the AMQP binding of the native `sysMonitor` service of GraphDBManager.
It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	AMQP	0-9-1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `sysMonitor` service interface

This document provides the Interface Design Description IDD to the *sysMonitor – Service Description* document [5].

1.1 Interface registration

With `sysmonitor.enabled=true`, GraphDBManager registers the service at start-up with interface template `generic_amqps` (protocol `amqps`, policy `CERT_AUTH`; `generic_amqp` without TLS) and the following properties and metadata:

```
{
  "serviceDefinitionName": "sysMonitor",
  "version": "1.0.0",
  "metadata": {
    "contract": "SysMonitor-AMQP-IDD-5.2.2",
    "schemaVersion": "1.0",
    "publisherMode": "native",
    "observationTypes": [
      "echo",
      "power",
      "status"
    ],
    "delivery": "persistent, publisher-confirmed"
  },
  "interfaces": [
    {
      "templateName": "generic_amqps",
      "protocol": "amqps",
      "policy": "CERT_AUTH",
      "properties": {
        "accessAddresses": [
          "amqp-broker"
        ],
        "accessPort": 5671,
        "exchange": "arrowhead",
        "baseRoutingKey": "TestCloud.sysmonitor.GraphDBManager.GraphDBManager",
        "operations": [
          "echo",
          "power",
          "status"
        ]
      }
    }
  ]
}
```

Listing 1: Registered service instance (TestCloud).

2 Service Operations

The publisher is the `SysMonitorPublisher` of the common library, configured with `sysmonitor.broker.address`, `sysmonitor.broker.port`, `sysmonitor.local.cloud` (default: from the system certificate), `sysmonitor.publish.interval` and `sysmonitor.ssl.*` (default: the `server.ssl` stores). The publisher connects to the broker (default `amqp-broker`, port 5671) with TLS, verifies the broker host name and authenticates with its X.509 system certificate (SASL `EXTERNAL`; the certificate CN is the broker user name). Every publication interval it publishes each observation to the topic exchange `arrowhead` with the routing key `<baseRoutingKey>.<operation>`, where the base routing key is `<Cloud>.sysmonitor.<System>.<serviceInstance>`. Messages are persistent (delivery mode 2), `application/json`, carry the observation identifier as message id, and are publisher-confirmed (timeout 5 s); a failed cycle is retried with a new connection at the next interval. The broker's topic permissions allow the system to publish only below its own base routing key.

2.1 PUBLISH `<Cloud>.sysmonitor.DataManager.DataManager.echo`

Operation: echo
Output: Observation

Liveness: `status` (`alive` or `degraded`), `uptimeSeconds` and a `detail` text; quality `good` or `uncertain`.

2.2 PUBLISH `<Cloud>.sysmonitor.DataManager.DataManager.power`

Operation: power
Output: Observation

Power supply: `supplyType=line`, `state=available`; unit `1`.

2.3 PUBLISH `<Cloud>.sysmonitor.DataManager.DataManager.status`

Operation: status
Output: Observation

Process state: `state=running`, `health` (`healthy`/`degraded`) and `serviceCount`, the number of registered services.

```
{
  "schemaVersion": "1.0",
  "observationId": "GraphDBManager-echo-1792670400000-42",
  "providerSystem": "GraphDBManager",
  "serviceInstance": "GraphDBManager",
  "observationType": "echo",
  "sourceTime": "2026-10-22T12:00:00.000Z",
  "sequence": 42,
  "value": {
    "status": "alive",
    "uptimeSeconds": 3600,
    "detail": "GraphDBManager is running"
  },
  "quality": "good",
  "metadata": {
    "publisherMode": "native"
  }
}
```

Listing 2: An echo observation.

3 Data Models

3.1 struct Observation

Object Field	Value Type	Description
"schemaVersion"	String	`1.0`.
"observationId"	String	`<System>-<type>-<epoch ms>-<sequence>`.
"providerSystem"	String	The publishing system.
"serviceInstance"	String	Service instance, default the system name.
"observationType"	String	`echo`, `power`, `status`.
"sourceTime"	String	ISO 8601 UTC time with milliseconds.
"sequence"	Number	Sequence number per publisher.
"value"	Object	Observed value, see the operations.
"unit"	String	`1` for `power` and `status`; absent for `echo`.
"quality"	String	`good` or `uncertain`.
"metadata"	Object	`{"publisherMode": "native"}`.

3.2 Primitives

Type	Description
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] AMQP Working Group, “Amqp 0-9-1 specification,” AMQP Working Group, Tech. Rep., 2008.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “sysMonitor – Service Description (GraphDBManager),” Eclipse Arrowhead, SD 5.2.2, 2026, graphDBManager-v5.2.2-sysMonitor-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-28	5.2.2	Document created from the corresponding DataManager document for the GraphDB-backed copy GraphDBManager.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	