serviceOrchestrationPushManagement MQTT/TLS/JSON

Interface Design Description

Service ID: *"serviceOrchestrationPushManagement"*

Abstract
This document describes the MQTT protocol with TLS payload security and JSON payload encoding variant of the `serviceOrchestrationPushManagement` service of the DynamicServiceOrchestration system.

Contents

1 Overview **3**

2 Service Operations **4**
2.1 operation subscribe . . . 4
2.2 operation trigger . . . 5
2.3 operation unsubscribe . . . 6
2.4 operation query . . . 6

3 Data Models **7**
3.1 struct MqttRequestTemplate . . . 7
3.2 struct MqttResponseTemplate . . . 7
3.3 struct ErrorMessage . . . 7
3.4 struct MetadataRequirement . . . 7
3.5 struct OrchestrationJob . . . 7
3.6 struct OrchestrationNotifyInterface . . . 8
3.7 struct OrchestrationPushJobListResponse . . . 8
3.8 struct OrchestrationPushTrigger . . . 8
3.9 struct OrchestrationRequest . . . 8
3.10 struct OrchestrationServiceRequirement . . . 9
3.11 struct OrchestrationSubscriptionListRequest . . . 9
3.12 struct OrchestrationSubscriptionListResponse . . . 9
3.13 struct OrchestrationSubscriptionQueryRequest . . . 9
3.14 struct OrchestrationSubscriptionRequest . . . 10
3.15 struct OrchestrationSubscriptionResponse . . . 10
3.16 struct Page . . . 10
3.17 struct QoSRequirement . . . 10
3.18 Primitives . . . 11

4 References **12**

5 Revision History **13**
5.1 Amendments . . . 13
5.2 Quality Assurance . . . 13

1 Overview

This document describes the `serviceOrchestrationPushManagement` service interface of the Dynamic-ServiceOrchestration system over MQTT, which provides operator management of push orchestration: subscriptions made on behalf of consumers, and triggering of push orchestration.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	MQTT	3.1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `serviceOrchestrationPushManagement` service interface

This document provides the Interface Design Description IDD to the *serviceOrchestrationPushManagement – Service Description* document [5]. The operations, their semantics and the data models are the same as in the HTTP/TLS/JSON IDD [6]; this document specifies the MQTT binding.

The MQTT interface is offered only when the system runs with `mqtt.api.enabled=true`; it is then registered with the interface template `generic_mqtts` (`generic_mqtt` without TLS), the broker address and port (`mqtt.broker.address`, `mqtt.broker.port`) and the base topic `arrowhead/serviceorchestration/orchestration/management/push/`. In the Arrowhead-test-cloud-java deployment the MQTT interfaces of the core systems are disabled.

2 Service Operations

The provider subscribes to one topic per operation, the base topic followed by the operation name:

Operation	Request topic
`subscribe`	`arrowhead/serviceorchestration/orchestration/management/push/subscribe`
`trigger`	`arrowhead/serviceorchestration/orchestration/management/push/trigger`
`unsubscribe`	`arrowhead/serviceorchestration/orchestration/management/push/unsubscribe`
`query`	`arrowhead/serviceorchestration/orchestration/management/push/query`

A consumer publishes a request envelope (MqttRequestTemplate) to the topic and receives the answer (MqttResponseTemplate) on its own `responseTopic`. The `authentication` field carries the requester's identity according to the provider's authentication policy: `IDENTITY-TOKEN//<token>` (outsourced or internal policy), `SYSTEM//<name>` (declared policy) or the requester's X.509 certificate (certificate policy). The `status` of the response uses the HTTP status code numbers (200, 201, 204, 400, 401, 403, 404, 408, 423, 500, 503); on error the payload is an ErrorMessage.

```
{
  "traceId": "a1b2c3",
  "authentication": "IDENTITY-TOKEN//<token>",
  "responseTopic": "arrowhead/response/TemperatureDisplay/a1b2c3",
  "qosRequirement": 1,
  "params": {},
  "payload": {}
}
```

Listing 1: Request envelope.

```
{
  "status": 200,
  "traceId": "a1b2c3",
  "receiver": "TemperatureDisplay",
  "payload": {}
}
```

Listing 2: Response envelope.

2.1 PUBLISH `arrowhead/serviceorchestration/orchestration/management/push/subscribe`

Operation: subscribe
Input: OrchestrationSubscriptionListRequest
Output: OrchestrationSubscriptionListResponse

Creates subscriptions on behalf of target systems.

```
{
  "subscriptions": [
    {
      "targetSystemName": "TemperatureDisplay",
      "orchestrationRequest": {
        "serviceRequirement": {
          "serviceDefinition": "temperatureReading",
```

```
          "operations": [
            "FILTER"
          ],
          "versions": [
            "1.0.0"
          ],
          "alivesAt": "2026-10-22T12:00:00Z",
          "metadataRequirements": [
            {}
          ],
          "interfaceTemplateNames": [
            "string"
          ],
          "interfaceAddressTypes": [
            "string"
          ],
          "interfacePropertyRequirements": [
            {}
          ],
          "securityPolicies": [
            "string"
          ],
          "preferredProviders": [
            "string"
          ]
        },
        "orchestrationFlags": {
          "MATCHMAKING": true
        },
        "qualityRequirements": [
          {}
        ],
        "exclusivityDuration": 60
      },
      "notifyInterface": {
        "protocol": "HTTPS",
        "properties": {
          "address": "192.168.0.20",
          "port": "8080",
          "method": "POST",
          "path": "/orchestration/notify"
        }
      },
      "duration": 3600
    }
  ]
}
```

Listing 3: Payload of an subscribe request.

2.2 PUBLISH arrowhead/serviceorchestration/orchestration/management/push/trigger

Operation: trigger
Input: OrchestrationPushTrigger
Output: OrchestrationPushJobListResponse

Starts push orchestration for the selected subscriptions (by target system or identifier); returns the started jobs.

```
{
  "targetSystems": [
    "TemperatureDisplay"
  ],
  "subscriptionIds": [
    "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  ]
```

```
}
```

Listing 4: Payload of an trigger request.

2.3 PUBLISH arrowhead/serviceorchestration/orchestration/management/push/unsubscribe

Operation: unsubscribe
Input: Array<String>

Removes subscriptions by identifier.

```
[
  "3fa85f64-5717-4562-b3fc-2c963f66afa6"
]
```

Listing 5: Payload of an unsubscribe request.

2.4 PUBLISH arrowhead/serviceorchestration/orchestration/management/push/query

Operation: query
Input: OrchestrationSubscriptionQueryRequest
Output: OrchestrationSubscriptionListResponse

Returns a page of subscriptions matching the filter.

```
{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "ownerSystems": [
    "string"
  ],
  "targetSystems": [
    "TemperatureDisplay"
  ],
  "serviceDefinitions": [
    "temperatureReading"
  ]
}
```

Listing 6: Payload of an query request.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Each *struct* denotes a JSON Object with the named fields; fields that are not needed may be omitted.

3.1 struct MqttRequestTemplate

The request envelope.

Object Field	Value Type	Description
"traceId"	String	Identifier chosen by the requester, returned in the response.
"authentication"	String	Identity of the requester (see Section 2).
"responseTopic"	String	Topic on which the response is published.
"qosRequirement"	Number	MQTT QoS of the response (0, 1 or 2).
"params"	Object<String>	Optional parameters (the query parameters of the HTTP binding).
"payload"	Object	The operation input.

3.2 struct MqttResponseTemplate

The response envelope.

Object Field	Value Type	Description
"status"	Number	Status code.
"traceId"	String	The trace identifier of the request.
"receiver"	String	Name of the requester.
"payload"	Object	The operation output, or an ErrorMessage.

3.3 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.4 struct MetadataRequirement

A JSON object of metadata requirements: each key is a metadata path (dot notation), each value the required value or an operator object such as `{"op": "LESS_THAN", "value": 10}`.

3.5 struct OrchestrationJob

One orchestration job (pull or push).

Object Field	Value Type	Description
"id"	String	Identifier (UUID) of the orchestration job.
"status"	String	Status of the job: `PENDING`, `IN_PROGRESS`, `DONE` or `ERROR`.
"type"	String	Orchestration type: `PULL` or `PUSH`.
"requesterSystem"	String	Name of the system that requested the orchestration.
"targetSystem"	String	Name of the consumer system the orchestration was made for.
"serviceDefinition"	String	Service definition name.
"subscriptionId"	String	Subscription that started the push job.
"message"	String	Status message, e.g. `1 local result: DataManager`.
"createdAt"	DateTime	UTC time of creation.
"startedAt"	DateTime	UTC time when the job started.
"finishedAt"	DateTime	UTC time when the job finished.

3.6 struct OrchestrationNotifyInterface

Notification endpoint of push orchestration.

Object Field	Value Type	Description
"protocol"	String	Protocol of the notification: `HTTP`, `HTTPS`, `MQTT` or `MQTTS`.
"properties"	Object<String>	For HTTP(S) `address`, `port`, `method`, `path`; for MQTT(S) `topic` (and broker `address`, `port`).

3.7 struct OrchestrationPushJobListResponse

Push jobs started by a trigger.

Object Field	Value Type	Description
"jobs"	Array<OrchestrationJob>	Orchestration jobs started by the trigger.

3.8 struct OrchestrationPushTrigger

Selects the subscriptions to execute now.

Object Field	Value Type	Description
"targetSystems"	Array<String>	Consumers whose subscriptions are executed.
"subscriptionIds"	Array<String>	Subscriptions to execute.

3.9 struct OrchestrationRequest

An orchestration request.

Object Field	Value Type	Description
"serviceRequirement"	OrchestrationServiceRequirement	Requirements on the service the consumer wants to use.
"orchestrationFlags"	Object<Boolean>	Orchestration flags, e.g. `MATCHMAKING`, `ONLY_PREFERRED`, `ALLOW_INTERCLOUD`.
"qualityRequirements"	Array<QoSRequirement>	Quality-of-service requirements (evaluated by DeviceQoSEvaluator).
"exclusivityDuration"	Number	Requested exclusive reservation of the provider in seconds.

3.10 struct OrchestrationServiceRequirement

Requirements on the requested service.

Object Field	Value Type	Description
"serviceDefinition"	String	Service definition name.
"operations"	Array<String>	Service operations the consumer wants to use.
"versions"	Array<Version>	Accepted service versions.
"alivesAt"	DateTime	Only instances that are still registered (not expired) at this UTC time are matched.
"metadata Requirements"	Array<MetadataRequirement>	Requirements on the service instance metadata; each map is one alternative.
"interfaceTemplate Names"	Array<String>	Accepted interface templates, e.g. `generic_https`.
"interfaceAddressTypes"	Array<String>	Address types the provider interface must offer.
"interfaceProperty Requirements"	Array<MetadataRequirement>	Requirements on the interface properties; each map is one alternative.
"securityPolicies"	Array<String>	Accepted interface security policies.
"preferredProviders"	Array<String>	Provider systems to prefer.

3.11 struct OrchestrationSubscriptionListRequest

Subscriptions to create on behalf of consumers.

Object Field	Value Type	Description
"subscriptions"	Array<OrchestrationSubscription Request>	Subscriptions to create.

3.12 struct OrchestrationSubscriptionListResponse

List of subscriptions.

Object Field	Value Type	Description
"entries"	Array<OrchestrationSubscription Response>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.13 struct OrchestrationSubscriptionQueryRequest

Paged filter for subscriptions.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"ownerSystems"	Array<String>	Subscription owner names to match.
"targetSystems"	Array<String>	Target system names.
"serviceDefinitions"	Array<String>	Service definition names to match.

3.14 struct OrchestrationSubscriptionRequest

A push orchestration subscription.

Object Field	Value Type	Description
"targetSystemName"	String	Consumer system; default the requester.
"orchestrationRequest"	OrchestrationRequest	The orchestration request executed for the subscription.
"notifyInterface"	OrchestrationNotifyInterface	Where and how the orchestration result is pushed to the target system.
"duration"	Number	Requested lifetime of the subscription in seconds; no value means unlimited.

3.15 struct OrchestrationSubscriptionResponse

A stored subscription.

Object Field	Value Type	Description
"id"	String	Identifier (UUID) of the subscription.
"ownerSystemName"	String	Name of the system that created the subscription.
"targetSystemName"	String	Name of the consumer system the push orchestration is made for.
"orchestrationRequest"	OrchestrationRequest	The orchestration request executed for the subscription.
"notifyInterface"	OrchestrationNotifyInterface	Where and how the orchestration result is pushed to the target system.
"expiredAt"	DateTime	UTC time when the subscription expires.
"createdAt"	DateTime	UTC time of creation.

3.16 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.17 struct QoSRequirement

One quality-of-service requirement.

Object Field	Value Type	Description
"type"	String	Type of the QoS evaluation, as known by DeviceQoSEvaluator.
"operation"	String	QoS operation: `FILTER` or `SORT`.
"requirements"	Object	Parameters of the QoS requirement.

3.18 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.
Version	JSON String, semantic version `major.minor.patch`.

4 References

[1] A. Banks and R. Gupta, “Mqtt version 3.1.1,” OASIS, Standard, 2014.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “serviceOrchestrationPushManagement – Service Description (DynamicServiceOrchestration),” Eclipse Arrowhead, SD 5.2.2, 2026, dynamicServiceOrchestration-v5.2.2-serviceOrchestrationPushManagement-SD.pdf.

[6] ——, “serviceOrchestrationPushManagement HTTP/TLS/JSON – Interface Design Description (DynamicServiceOrchestration),” Eclipse Arrowhead, IDD 5.2.2, 2026, dynamicServiceOrchestration-v5.2.2-serviceOrchestrationPushManagement-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	