dataProxy

Service Description

Service ID: *"dataProxy"*

Abstract
This document describes the `dataProxy` service, version 1.0.0, produced by the DataManager support system of Arrowhead 5.2.2.

Contents

1 Overview **3**
1.1 Significant Prior Art . . . 3
1.2 How This Service Is Meant to Be Used . . . 3
1.3 Important Delimitations and Dependencies . . . 3

2 Service Interface **4**
2.1 operation list-systems . . . 4
2.2 operation list-services . . . 4
2.3 operation get-data . . . 4
2.4 operation put-data . . . 4

3 Information Model **5**
3.1 struct SenMLRecord . . . 5
3.2 struct ServiceListResponse . . . 5
3.3 struct SystemListResponse . . . 5
3.4 Primitives . . . 5

4 References **7**

5 Revision History **8**
5.1 Amendments . . . 8
5.2 Quality Assurance . . . 8

1 Overview

This document describes the `dataProxy` service, which provides a cache of the latest SenML message per system and service, for consumers that cannot reach the producer directly. It is produced by the DataManager system [1] in service version 1.0.0.

The rest of this document is organized as follows. In Section 2, we describe the abstract message operations provided by the service. In Section 3, we end the document by presenting the data types used by the mentioned operations. The concrete interface is specified in the HTTP/TLS/JSON IDD [2].

1.1 Significant Prior Art

Successor of the Arrowhead 4.6 DataManager proxy service.

1.2 How This Service Is Meant to Be Used

A producer stores its latest measurement with `put-data`; consumers read it with `get-data` and browse with `list-systems` and `list-services`.

1.3 Important Delimitations and Dependencies

Only the last message per system and service is kept, in memory. With `service.authorization.enabled=true` every call is checked with ConsumerAuthorization.

2 Service Interface

This section describes the interfaces to the `dataProxy` service. In particular, each subsection names an abstract operation, an input type and an output type, in that order. The input type is named inside parentheses, while the output type is preceded by a colon. Input and output types are only denoted when accepted or returned, respectively, by the interface in question.

All abstract data types named in this section are defined in Section 3.




Figure 1: SysML-style block of the `dataProxy` service and its operations.

The following interface operations are available.

2.1 operation list-systems () : SystemListResponse

Returns the systems with cached data.

2.2 operation list-services (Name) : ServiceListResponse

Returns the services of a system with cached data.

2.3 operation get-data (Name) : List<SenMLRecord>

Returns the cached SenML message of the system and service.

2.4 operation put-data (List<SenMLRecord>)

Replaces the cached message of the system and service.

3 Information Model

Here, all data objects that can be part of the `dataProxy` service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is used to denote a collection of named fields, each with its own data type. As a complement to the explicitly defined types in this section, there is also a list of implicit primitive types in Section 3.4, which are used to represent things like hashes and identifiers.

3.1 struct SenMLRecord

A SenML record (RFC 8428); a message is a JSON array of records.

Field	Type	Description
bn	String	SenML base name.
bt	String	SenML base time (seconds).
bu	String	SenML base unit.
bv	String	SenML base value.
bs	String	SenML base sum.
bver	String	SenML base version.
n	String	SenML name.
u	String	SenML unit.
v	String	SenML numeric value.
vs	String	SenML string value.
vb	Boolean	SenML Boolean value.
vd	String	SenML data value (Base64).
s	String	SenML sum.
t	String	SenML time (seconds, relative to the base time).
ut	String	SenML update time (seconds).

3.2 struct ServiceListResponse

Service names with data of a system.

Field	Type	Description
services	List<String>	Service names with stored data.

3.3 struct SystemListResponse

List of systems.

Field	Type	Description
systems	List<String>	System names with stored data.

3.4 Primitives

Types and structures mentioned throughout this document that are assumed to be available to implementations of this service. The concrete interpretations of each of these types and structures must be provided by any IDD document claiming to implement this service.

Type	Description
Boolean	One out of `true` or `false`.
List	An *array* of a known number of items, each having type A.
Name	A string identifier that is intended to be both human and machine-readable.
String	A chain of characters.

4 References

[1] J. Delsing, “DataManager – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-support-java-spring/DataManager/documentation/v5.2.2/DataManager-v5.2.2-SysD.pdf.

[2] ——, “dataProxy HTTP/TLS/JSON – Interface Design Description (DataManager),” Eclipse Arrowhead, IDD 5.2.2, 2026, dataManager-v5.2.2-dataProxy-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	