eventHandlerManagement

Service Description

Service ID: *"eventHandlerManagement"*

Abstract
This document describes the `eventHandlerManagement` service, version 1.0.0, produced by the EventHandler support system of Arrowhead 5.2.2.

Contents

1 Overview **3**
1.1 Significant Prior Art . . . 3
1.2 How This Service Is Meant to Be Used . . . 3
1.3 Important Delimitations and Dependencies . . . 3

2 Service Interface **4**
2.1 operation query-subscriptions . . . 4
2.2 operation update-subscription . . . 4
2.3 operation remove-subscription . . . 4

3 Information Model **5**
3.1 struct SubscriptionListResponse . . . 5
3.2 struct SubscriptionRequest . . . 5
3.3 struct SubscriptionResponse . . . 5
3.4 Primitives . . . 6

4 References **7**

5 Revision History **8**
5.1 Amendments . . . 8
5.2 Quality Assurance . . . 8

1 Overview

This document describes the `eventHandlerManagement` service, which provides operator management of all event subscriptions. It is produced by the EventHandler system [1] in service version 1.0.0.

The rest of this document is organized as follows. In Section 2, we describe the abstract message operations provided by the service. In Section 3, we end the document by presenting the data types used by the mentioned operations. The concrete interface is specified in the HTTP/TLS/JSON IDD [2].

1.1 Significant Prior Art

Successor of the Arrowhead 4.6 EventHandler management endpoints.

1.2 How This Service Is Meant to Be Used

Operators page through subscriptions, change and remove them.

1.3 Important Delimitations and Dependencies

Access follows the management policy (standalone deployment: `sysop-only`).

2 Service Interface

This section describes the interfaces to the `eventHandlerManagement` service. In particular, each subsection names an abstract operation, an input type and an output type, in that order. The input type is named inside parentheses, while the output type is preceded by a colon. Input and output types are only denoted when accepted or returned, respectively, by the interface in question.

All abstract data types named in this section are defined in Section 3.



Figure 1: SysML-style block of the `eventHandlerManagement` service and its operations.

The following interface operations are available.

2.1 operation query-subscriptions () : SubscriptionListResponse

Returns a page of all subscriptions.

2.2 operation update-subscription (SubscriptionRequest) : SubscriptionResponse

Replaces a subscription.

2.3 operation remove-subscription (Identifier)

Removes a subscription.

3 Information Model

Here, all data objects that can be part of the `eventHandlerManagement` service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is used to denote a collection of named fields, each with its own data type. As a complement to the explicitly defined types in this section, there is also a list of implicit primitive types in Section 3.4, which are used to represent things like hashes and identifiers.

3.1 struct SubscriptionListResponse

List of subscriptions.

Field	Type	Description
entries	List<SubscriptionResponse>	Matching records of the current page.
count	Number	Total number of matching records (all pages).

3.2 struct SubscriptionRequest

A subscription to an event type.

Field	Type	Description
eventType	String	Event type, camelCase.
notifyUri	String	HTTPS endpoint to which matching events are posted.
matchMetadata	Boolean	Whether only events whose metadata contain `metadataFilter` are delivered.
metadataFilter	Map<String, String>	Metadata an event must contain to be delivered.
startsAt	String	Start of the subscription's validity window.
expiresAt	String	End of the validity window.

3.3 struct SubscriptionResponse

A stored subscription.

Field	Type	Description
id	Number	Identifier of the subscription.
subscriberSystemName	String	System that owns the subscription.
eventType	String	Event type, camelCase.
notifyUri	String	HTTPS endpoint to which matching events are posted.
matchMetadata	Boolean	Whether only events whose metadata contain `metadataFilter` are delivered.
metadataFilter	Map<String, String>	Metadata an event must contain to be delivered.
startsAt	String	Start of the subscription's validity window.
expiresAt	String	End of the validity window.
createdAt	String	UTC time of creation.
updatedAt	String	UTC time of the last change.

3.4 Primitives

Types and structures mentioned throughout this document that are assumed to be available to implementations of this service. The concrete interpretations of each of these types and structures must be provided by any IDD document claiming to implement this service.

Type	Description
Boolean	One out of `true` or `false`.
Identifier	A string that identifies a record, e.g. a UUID or a composite identifier.
List	An *array* of a known number of items, each having type A.
Map	A set of key-value pairs.
Number	An integer number.
String	A chain of characters.

4 References

[1] J. Delsing, “EventHandler – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-support-java-spring/EventHandler/documentation/v5.2.2/EventHandler-v5.2.2-SysD.pdf.

[2] ——, “eventHandlerManagement HTTP/TLS/JSON – Interface Design Description (EventHandler),” Eclipse Arrowhead, IDD 5.2.2, 2026, eventHandler-v5.2.2-eventHandlerManagement-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): standalone deployment, configuration and security statements updated.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	