gatekeeperManagement

Service Description

Service ID: *"gatekeeperManagement"*

Abstract
This document describes the `gatekeeperManagement` service, version 5.2.2, produced by the Gatekeeper support system of Arrowhead 5.2.2.

Contents

1 Overview **3**
1.1 Significant Prior Art . . . 3
1.2 How This Service Is Meant to Be Used . . . 3
1.3 Important Delimitations and Dependencies . . . 3

2 Service Interface **4**
2.1 operation clouds . . . 4
2.2 operation relays . . . 4
2.3 operation status . . . 4

3 Information Model **5**
3.1 struct CloudList . . . 5
3.2 struct RelayList . . . 5
3.3 struct Status . . . 5
3.4 Primitives . . . 5

4 References **6**

5 Revision History **7**
5.1 Amendments . . . 7
5.2 Quality Assurance . . . 7

1 Overview

This document describes the `gatekeeperManagement` service, which provides read access to the neighbour clouds and relays the Gatekeeper knows and to its status. It is produced by the Gatekeeper system [1] in service version 5.2.2.

The rest of this document is organized as follows. In Section 2, we describe the abstract message operations provided by the service. In Section 3, we end the document by presenting the data types used by the mentioned operations. The concrete interface is specified in the HTTP/TLS/JSON IDD [2].

1.1 Significant Prior Art

Successor of the Arrowhead 4.6 Gatekeeper management endpoints.

1.2 How This Service Is Meant to Be Used

LocalCloudManager shows the relay connection and the configured clouds.

1.3 Important Delimitations and Dependencies

Only LocalCloudManager and Sysop. The unregistered endpoints `POST /gatekeeper/mgmt/clouds`, `POST /gatekeeper/mgmt/relays` and `DELETE /gatekeeper/mgmt/clouds/{operator}/{name}` edit the configuration.

2 Service Interface

This section describes the interfaces to the `gatekeeperManagement` service. In particular, each subsection names an abstract operation, an input type and an output type, in that order. The input type is named inside parentheses, while the output type is preceded by a colon. Input and output types are only denoted when accepted or returned, respectively, by the interface in question.

All abstract data types named in this section are defined in Section 3.




Figure 1: SysML-style block of the `gatekeeperManagement` service and its operations.

The following interface operations are available.

2.1 operation clouds () : CloudList

Returns the configured neighbour clouds.

2.2 operation relays () : RelayList

Returns the configured relays.

2.3 operation status () : Status

Returns the Gatekeeper status with the relay connection.

3 Information Model

Here, all data objects that can be part of the `gatekeeperManagement` service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is used to denote a collection of named fields, each with its own data type. As a complement to the explicitly defined types in this section, there is also a list of implicit primitive types in Section 3.4, which are used to represent things like hashes and identifiers.

3.1 struct CloudList

Field	Type	Description
entries	List<Map<String, Object>>	Configured neighbour clouds (`name`, `operator`, `gatekeeperAddress`, `gatekeeperPort`, `metadata`).
count	Number	Number of entries.

3.2 struct RelayList

Field	Type	Description
entries	List<Map<String, Object>>	Configured relays (`name`, `address`, `port`, `type`, `secure`, `metadata`).
count	Number	Number of entries.

3.3 struct Status

Field	Type	Description
status	String	`ok`.
system	String	`Gatekeeper`.
version	Version	`5.2.2`.
implementation	String	`java`.
x509	Boolean	Mutual TLS in use.
registration	Map<String, Object>	Registration state in the ServiceRegistry.
relay	Map<String, Object>	Connection state of the inter-cloud relay.

3.4 Primitives

Types and structures mentioned throughout this document that are assumed to be available to implementations of this service. The concrete interpretations of each of these types and structures must be provided by any IDD document claiming to implement this service.

Type	Description
Boolean	One out of `true` or `false`.
List	An *array* of a known number of items, each having type A.
Map	A set of key-value pairs.
Number	An integer number.
Object	Any structured value.
String	A chain of characters.
Version	Specifies a version, semantic versioning `major.minor.patch`.

4 References

[1] J. Delsing, “Gatekeeper – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-Gatekeeper-java-spring/documentation/v5.2.2/Gatekeeper-v5.2.2-SysD.pdf.

[2] ——, “gatekeeperManagement HTTP/TLS/JSON – Interface Design Description (Gatekeeper),” Eclipse Arrowhead, IDD 5.2.2, 2026, gatekeeper-v5.2.2-gatekeeperManagement-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	