translationReport

Service Description

Service ID: *"translationReport"*

Abstract
This document describes the `translationReport` service, version 1.0.0, produced by the TranslationManager support system of Arrowhead 5.2.2.

Contents

1 Overview **3**
1.1 Significant Prior Art . . . 3
1.2 How This Service Is Meant to Be Used . . . 3
1.3 Important Delimitations and Dependencies . . . 3

2 Service Interface **4**
2.1 operation report . . . 4

3 Information Model **5**
3.1 struct TranslationReportRequest . . . 5
3.2 Primitives . . . 5

4 References **6**

5 Revision History **7**
5.1 Amendments . . . 7
5.2 Quality Assurance . . . 7

1 Overview

This document describes the `translationReport` service, which provides event reports of translators about the bridges they serve (use, internal close, errors). It is produced by the TranslationManager system [1] in service version 1.0.0.

The rest of this document is organized as follows. In Section 2, we describe the abstract message operations provided by the service. In Section 3, we end the document by presenting the data types used by the mentioned operations. The concrete interfaces are specified in the HTTP/TLS/JSON IDD [2] and the MQTT/TLS/JSON IDD [3].

1.1 Significant Prior Art

New in Arrowhead 5.

1.2 How This Service Is Meant to Be Used

Interface and data-model translators call `report` when a bridge is used, closed or fails; the TranslationManager updates the bridge status and usage counters.

1.3 Important Delimitations and Dependencies

Only the translators of a bridge should report about it.

2 Service Interface

This section describes the interfaces to the `translationReport` service. In particular, each subsection names an abstract operation, an input type and an output type, in that order. The input type is named inside parentheses, while the output type is preceded by a colon. Input and output types are only denoted when accepted or returned, respectively, by the interface in question.

All abstract data types named in this section are defined in Section 3.

Figure 1: SysML-style block of the `translationReport` service and its operations.

The following interface operations are available.

2.1 operation report (TranslationReportRequest)

Reports an event of a bridge (`USED`, `INTERNAL_CLOSED`, `INTERNAL_ERROR`, `EXTERNAL_ERROR`).

3 Information Model

Here, all data objects that can be part of the `translationReport` service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is used to denote a collection of named fields, each with its own data type. As a complement to the explicitly defined types in this section, there is also a list of implicit primitive types in Section 3.2, which are used to represent things like hashes and identifiers.

3.1 struct TranslationReportRequest

Event reported by a translator about a bridge.

Field	Type	Description
bridgeId	Identifier	Identifier (UUID) of the translation bridge.
timestamp	String	Time of the event, ISO 8601 UTC.
state	String	Event: `USED`, `INTERNAL_CLOSED`, `INTERNAL_ERROR` or `EXTERNAL_ERROR`.
errorMessage	String	Error text, if the event is an error.

3.2 Primitives

Types and structures mentioned throughout this document that are assumed to be available to implementations of this service. The concrete interpretations of each of these types and structures must be provided by any IDD document claiming to implement this service.

Type	Description
Identifier	A string that identifies a record, e.g. a UUID or a composite identifier.
String	A chain of characters.

4 References

[1] J. Delsing, “TranslationManager – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-support-java-spring/TranslationManager/documentation/v5.2.2/TranslationManager-v5.2.2-SysD.pdf.

[2] ——, “translationReport HTTP/TLS/JSON – Interface Design Description (TranslationManager),” Eclipse Arrowhead, IDD 5.2.2, 2026, translationManager-v5.2.2-translationReport-HTTP-IDD.pdf.

[3] ——, “translationReport MQTT/TLS/JSON – Interface Design Description (TranslationManager),” Eclipse Arrowhead, IDD 5.2.2, 2026, translationManager-v5.2.2-translationReport-MQTT-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	