1 Interface overview

HTTPS, mandatory mutual TLS, Arrowhead identity-token header and JSON request/response documents. General management is sysop/whitelist protected; enrollment endpoints use approved certificate fingerprints and profile/serial checks instead of ordinary identity tokens. Error responses contain errorMessage, errorCode, origin and timestamp. Exact DTO and status/error parity is not certified.

1.1 HTTPS interface operations

The listener is HTTPS with JSON by default; raw configuration and CRL responses use their declared media types. A request body is capped at 1 MiB. The table records implemented routes, not a claim of complete behavioral conformance.

Method	Path	Access
GET	/gatetunnel/echo	identity
GET	/gatetunnel/publickey	identity
POST	/gatetunnel/connect_provider	identity
POST	/gatetunnel/connect_consumer	identity
POST	/gatetunnel/close_sessions	identity
GET	/gatetunnel/mgmt/sessions	management
POST	/gatetunnel/mgmt/sessions/close	management
POST	/gatetunnel/intercloud/provider	identity
POST	/gatetunnel/intercloud/consumer	identity
GET	/gatetunnel/mgmt/status	management
GET	/gatetunnel/monitor/echo	certificate
GET	/gatetunnel/general/mgmt/get-config	management
POST	/gatetunnel/general/mgmt/logs	management

1.2 Important delimitations

This implementation is a development profile, not a certified interchangeable Java replacement. All systems use private JSON snapshots rather than the Java databases. MQTT application APIs, exhaustive DTO normalization and error parity, automatic data migration and production qualification remain outstanding.

- Legacy-mTLS relay sessions are supported; control-session records are not a second AMQP tunnel data plane. AH-GT-1 encrypted requests are rejected. Consumer listeners are volatile and renegotiated after restart.
- The source reference uses a shared non-Spring HTTP dispatcher. Its route coverage is not inferred from Go route presence; manual JavaSupportRuntime review is required.