1 Interface overview

HTTPS, mandatory mutual TLS, Arrowhead identity-token header and JSON request/response documents. General management is sysop/whitelist protected; enrollment endpoints use approved certificate fingerprints and profile/serial checks instead of ordinary identity tokens. Error responses contain errorMessage, errorCode, origin and timestamp. Exact DTO and status/error parity is not certified.

1.1 HTTPS interface operations

The listener is HTTPS with JSON by default; raw configuration and CRL responses use their declared media types. A request body is capped at 1 MiB. The table records implemented routes, not a claim of complete behavioral conformance.

Method	Path	Access
GET	/gatekeeper/echo	identity
POST	/gatekeeper/init_gsd	identity
POST	/gatekeeper/init_multi_gsd	identity
POST	/gatekeeper/init_icn	identity
GET	/gatekeeper/mgmt/clouds	management
POST	/gatekeeper/mgmt/clouds	management
DELETE	/gatekeeper/mgmt/clouds/{operator}/{name}	management
GET	/gatekeeper/mgmt/relays	management
POST	/gatekeeper/mgmt/relays	management
GET	/gatekeeper/mgmt/status	management
GET	/gatekeeper/monitor/echo	certificate
GET	/gatekeeper/general/mgmt/get-config	management
POST	/gatekeeper/general/mgmt/logs	management

1.2 Important delimitations

This implementation is a development profile, not a certified interchangeable Java replacement. All systems use private JSON snapshots rather than the Java databases. MQTT application APIs, exhaustive DTO normalization and error parity, automatic data migration and production qualification remain outstanding.

- Reuses the existing native Go legacy-mTLS relay engine, adapted to pinned clients. AH-GT-1 end-to-end encryption is absent. Broker ACLs and trusted neighbour provisioning remain required; no live federation is exercised by this delivery.
- The source reference uses a shared non-Spring HTTP dispatcher. Its route coverage is not inferred from Go route presence; manual JavaSupportRuntime review is required.